




STREX MODULE

48V SYSTEM



1.0 DOT

LED 10W | 48V | PCB 3-step
aluminium powder coated
PC cover

0.11kg IP20 $\pm 0.3^\circ$ \odot $\triangle 26^\circ$

non dim

| | CODE |
|--|---------|
| | 171142W |
| | 171142B |

DALI dim

| | CODE |
|--|---------|
| | 171145W |
| | 171145B |

| LIGHT COLOUR | LUMEN | CRI | CODE |
|--------------|-------|-----|------|
| 2700K | 900 | >90 | 3 |
| 3000K | 1000 | >90 | 5 |

dim options on page 341

1.0 OPAL

LED 8W | 48V | PCB 3-step
aluminium powder coated
PC cover

0.16kg IP20 $\pm 0.3^\circ$ \odot

non dim

| | CODE |
|--|---------|
| | 171182W |
| | 171182B |

DALI dim

| | CODE |
|--|---------|
| | 171185W |
| | 171185B |

| LIGHT COLOUR | LUMEN | CRI | CODE |
|--------------|-------|-----|------|
| 2700K | 540 | >90 | 3 |
| 3000K | 600 | >90 | 5 |

dim options on page 341

2.0 OPAL

LED 16W | 48V | PCB 3-step
aluminium powder coated
PC cover

0.32kg IP20 $\pm 0.3^\circ$ \odot

non dim


| | CODE |
|--|---------|
| | 171282W |
| | 171282B |

DALI dim

| | CODE |
|--|---------|
| | 171285W |
| | 171285B |

| LIGHT COLOUR | LUMEN | CRI | CODE |
|--------------|-------|-----|------|
| 2700K | 1080 | >90 | 3 |
| 3000K | 1200 | >90 | 5 |

dim options on page 341



available from autumn 2020