



# PALOS ROUND


OUTDOOR  
FLOOR SURFACE




p. 667




available from summer 2021



1.0



2.0




1.0

LED 9.5W | 100-240VAC  
50-60Hz | COB 3-step | incl. PS  
phase-cut dim | aluminium  
powder coated | 1.3m cable

0.73kg IP65

|  | CODE    |
|--|---------|
|  | 416674A |
|  | 416674Q |
|  | 416674B |

| LIGHT COLOUR | LUMEN | CRI | CODE |
|--------------|-------|-----|------|
| 2700K        | 540   | >80 | 2    |
| 3000K        | 580   | >80 | 4    |




2.0

2x LED 9.5W | 100-240VAC  
50-60Hz | COB 3-step | incl. PS  
phase-cut dim | aluminium  
powder coated | 1.3m cable

1.01kg IP65

|  | CODE    |
|--|---------|
|  | 416774A |
|  | 416774Q |
|  | 416774B |

| LIGHT COLOUR | LUMEN | CRI | CODE |
|--------------|-------|-----|------|
| 2700K        | 2x550 | >80 | 2    |
| 3000K        | 2x590 | >80 | 4    |




ALWAYS USE

base with fixation plate

|          | CODE     |
|----------|----------|
| base 170 | 910013_0 |
| base 270 | 910014_0 |
| base 470 | 910016_0 |
| base 670 | 910018_0 |
| base 870 | 910010_0 |

base colour

|  | CODE |
|--|------|
|  | A    |
|  | Q    |
|  | B    |



ALWAYS USE

base with concrete fixation

|          | CODE     |
|----------|----------|
| base 170 | 910073_0 |
| base 270 | 910074_0 |
| base 470 | 910076_0 |
| base 670 | 910078_0 |
| base 870 | 910070_0 |

base colour

|  | CODE |
|--|------|
|  | A    |
|  | Q    |
|  | B    |