




IC rated

MATCH

TRIMLESS | CEILING RECESSED



1.0 TRIMLESS

LED COB 6W | 350mA | 18V
excl. driver
aluminium powder coated

IP20 0°-90°|360° 30° SDCM2 L80|50K 0.15kg

45-47 85 4-26

CODE	
190851W	
190851B	

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	535	>90	3
3000K	600	>90	5

ALWAYS USE

driver | 350mA | revision opening
required

CODE	
10W dim	90223402
10W DALI	90243401

more options and specs on page 724

1.0

LED COB 6W | 350mA | 18V
excl. driver
aluminium powder coated

IP20 0°-90°|350° 30° SDCM2 L80|50K 0.14kg

wire springs 45-47 85 4-26

CODE	
190151W	
190151H	
190151B	

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	535	>90	3
3000K	600	>90	5

ALWAYS USE

driver | 350mA

CODE	
10W dim	90223402
10W DALI	90243401

more options and specs on page 724

2.0

2x LED COB 6W | 700mA | 18V
excl. driver
aluminium powder coated

IP20 0°-90°|350° 30° SDCM2 L80|50K 0.27kg

wire springs 105x30 60 4-26

CODE	
190251W	
190251B	

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x535	>90	3
3000K	2x600	>90	5

ALWAYS USE

driver | 700mA | only 1x needed

CODE	
15W dim	90225502
28W DALI	90245801

more options and specs on page 727