

XS-IPD843-4EW

X-Security IP 4 Megapixel Camera
1/3" CMOS 4 Megapixel
Wifi IEEE 802.11b/g/n
2.8 mm Lens
IR LEDs Range 30 m
WEB, DSS/PSS, Smartphone and
NVR



X-Security
IP Dome Camera
ECO Range
1/3" Progressive CMOS
4 Megapixel (2304x1296)
2.8 mm Lens
0 Lux
IR LED Range 30 m
DWDR
3DNR
MicroSD card recording
H.265+
RJ-45 10/100 BaseT
Wi-Fi
PoE IEEE802.3af
WEB, CMS (SPSS/DMSS), Smartphone and NVR interface
ONVIF Compatible
Weatherproof IP67
Vandal proof IK10

Specifications

Brand	X-Security
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2304x1296)
Main Stream rate	2560x1440 (1~25/30 FPS)
Extra Stream rate	640x480 (1~25/30 FPS)
Compression	H.265+ / H.265 / H264+ / H.264 / MJPEG
Bitrate	H265: 9 kbps–4096 kbps H264: 24 kbps–4096 kbps CBR/VBR
Lens	2.8 mm (H: 100°)
Infrared lighting	0 Lux / IR LEDs (30 m)
Image improvements	DWDR, BLC, HLC, AWB, AGC, 3D-NR, Privacy Masking, Motion Detection, ROI, Flip/Mirror
Day / Night	Auto ICR Removable Filter
Network interface	Ethernet 10/100 BaseT and WiFi 802.11b/g/n
Internal memory	Micro SD Max slot 256GB
Alarm	Event by alarm
Remote access	WEB, CMS (DSS/PSS), Smartphone and NVR interface
Interoperability	ONVIF
Power	DC 12 V / 408 mA
Degree of protection	Weatherproof IP67, Anti-vandal IK10
Temp. operation	-40° C ~ +60° C
Dimensions	88.7 (D) x 110 (Ø) mm
Weight	414 g