

# XS-IPSD4604WH-4

4 MP Motorised IP Camera  
1/3" Progressive CMOS  
Compression H.265/H.264/MJPEG  
4X (2.7~11 mm) Varifocal lens  
Intelligent detection, Auto Iris,  
Autofocus  
WEB, Software, Smartphone and  
NVR



Brand	X-Security
Image sensor	1/3" Progressive CMOS
Maximum resolution	4 Megapixel (2592x1520)
Main Stream rate	4M/3M/1080P/1.3M/720P (1~25/30fps)
Extra Stream rate	D1/CIF(1 ~ 25/30fps)
Compression	H.265/H.264/MJPEG
Bitrate	448 Kbps ~ 8192 Kbps
Lens	2.7~ 11mm Motorised vari-focal (4X) Optical Zoom, Auto Iris, Auto-focus
Digital Zoom	16X
Minimum illumination	0.05 Lux / F1.6 (Colour); 0.005 Lux / F1.6 (B/W)
Image improvements	WDR, BLC, HLC, AWB, AGC, 2D/3D-NR, Privacy Masking
Day / Night	Mechanical ICR filter
Network interface	Ethernet 10/100 BaseT
Internal memory	Slot for Micro SD card (Max 128 GB)
Pan/Tilt Range	Horizontal: 0°~355°, Vertical: 0°~90° auto flip 180°
Manual speed	Horizontal: 0.1°~100° /s, Vertical: 0.1°~60° /s
Speed between Presets	Horizontal: 100° /s, Vertical: 60° /s
Preset positions	300, 8 Tour, Auto Scan
Intelligent detection	Face detection, tripwire, area intrusion, scene changes, abandoned/lost objects
Remote access	Web browser, CMS Software (DSS/PSS), Smartphone (DMSS) and NVR
Interoperability	ONVIF
Power	DC 12 V / 850 mA, PoE IEEE802.3af
Degree of protection	Weatherproof IP66, Anti-vandal IK10
Temp. operation	-30° C ~ +60° C
Dimensions	89 mm (H) x 122 (Ø) mm



# Specifications

---