

# MS-UR35-L04EU-G-P-W

Milesight

Industrial Router 4G WiFi GPS PoE

5 ports 10/100 (4 PoE ports)

PoE 802.3 af/at | microSD slot

Dual SIM card slot 4G/3G

WiFi 802.11 b/g/n | GPS Positioning



Milesight

Industrial Router 4G with WiFi, GPS and PoE

5 Ethernet ports RJ45 10/100

4 PoE ports (ports 1-4) 802.3 af/at

Dual SIM card slot 4G/3G (not included)

LTE 4G CAT4

WiFi access point 802.11 b/g/n

I/O ports, Serial RS232 and RS485

GPS and GLONASS positioning

MicroSD slot

WiFi, LTE and GPS antennas included

DIN rail, wall or tabletop installation

DC power 9 to 48V (power 48V included)

Status LEDs

# Specifications

<b>Brand</b>	Milesight
<b>Device</b>	Industrial Router 4G PoE
<b>WiFi</b>	IEEE 802.11 b/g/n 2.4 GHz Access Point
<b>Ethernet</b>	5 Ethernet RJ45 10/100 ports Mbps
<b>PoE</b>	1~4 IEEE 802.3af/at POE ports
<b>SIM</b>	2 microSIM card slots 4G / 3G (not included)
<b>LTE Frequencies</b>	Bands 1/3/5/7/8/20/38/40/41
<b>Positioning</b>	GPS + GLONASS
<b>Antenna connectors</b>	LTE (Length 23 cm), GPS and WiFi (Length 17 cm) (including antennas)
<b>CPU</b>	528 MHZ, 32-bit ARM Cortex-A7
<b>RAM</b>	128 MB DDR3
<b>Flash</b>	128 MB
<b>Network Protocols</b>	PPP, PPPoE, SNMP v1/v2c/v3, TCP, UDP, DHCP, RIP v1/v2, OSPF, DDNS, VRRP, HTTP, HTTPS, DNS, ARP, QoS, SNTP, Telnet, VLAN, SSH
<b>Ports</b>	I/O, series RS232 and RS485
<b>Power</b>	DC 9~48V (48V power supply required for PoE included)
<b>Material</b>	Metallic
<b>Temp. operation</b>	-40° C ~ +70° C (reduced LTE functions > 60° C)
<b>Operating humidity</b>	0 ~ 95 % (non-condensing) to 25° C
<b>Installation</b>	DIN rail, wall or desktop
<b>Dimensions</b>	26 (A) x 108 (W) x 90 (D) mm
<b>Weight</b>	271 g
<b>Region</b>	EU version for EMEA and Asia-Pacific