## MS-UR35-L04EU-P

## Milesight

Industrial Router 4G PoE

5 ports 10/100 (4 PoE ports)

PoE 802.3 af/at | microSD slot

Dual SIM card slot 4G/3G

DIN, wall or desktop installation



## Milesight

Industrial Router 4G PoE

5 Ethernet ports RJ45 10/100

4 PoE ports (ports 1~4) 802.3 af/at

Dual SIM card slot 4G/3G (not included)

LTE 4G CAT4

I/O ports, Serial RS232 and RS485

MicroSD slot

LTE antenna included

DIN rail, wall or tabletop installation

DC power 9 to 48V (power 48V included)

Status LEDs

## Specifications

| Brand              | Milesight  |
|--------------------|--|
| Device             | Industrial Router 4G PoE   |
| WiFi               | IEEE 802.11 b/g/n 2.4 GHz Access Point   |
| Ethernet           | 5 Ethernet RJ45 10/100 ports Mbps  |
| РоЕ                | 1~4 IEEE 802.3af/at PoE ports  |
| SIM                | 2 microSIM card slots 4G / 3G (not included)   |
| LTE Frequencies    | Bands 1/3/5/7/8/20/38/40/41  |
| Antenna connectors | LTE (Length 23 cm) (antenna included)  |
| CPU                | 528 MHZ, 32-bit ARM Cortex-A7  |
| RAM                | 128 MB DDR3  |
| Flash              | 128 MB   |
| Network Protocols  | PPP, PPPoE, SNMP v1/v2c/v3, TCP, UDP, DHCP, RIP v1/v2, OSPF, DDNS, VRRP, HTTP, HTTPS, DNS, ARP, QoS, SNTP, Telnet, VLAN, SSH |
| Ports              | I/O, series RS232 and RS485  |
| Power              | DC 9~48V (48V power supply required for PoE included)  |
| Material           | Metallic   |
| Temp. operation    | -40° C $\sim$ +70° C (reduced LTE functions > 60° C)   |
| Operating humidity | 0 ~ 95 % (non-condensing) to 25° C   |
| Installation       | DIN rail, wall or desktop  |
| Dimensions         | 26 (Al) × 108 (W) × 90 (D) mm  |
| Weight             | 271 g  |
| Region             | EU version for EMEA and Asia-Pacific   |