

MS-WS156-868M

LoRaWAN scene panel

Up to 15Km range with direct vision

User-customizable display

Configuration via NFC and APP

Degree of Protection IP30

Long-lasting battery



Milesight

LoRaWan IoT Smart Scene Panel

6 pushbuttons

3 years of battery (20 keystrokes / day)

User-customizable display

Frequency 868MHz

Communication range up to 15Km with direct view

Easy configuration via NFC and smartphone APP

You can activate different predefined scenes

Compatible with LoRaWAN Milesight products

Specifications

| | |
|------------------------|---------------------------------------|
| Frequency Band | 868 MHz |
| Sensitivity | -137dBm@300bps |
| Power Output | 16dBm Max. |
| Protocol | OTAA/ABP Class A |
| Scope of communication | Up to 15Km range with direct vision |
| Display | 2.9" E-Ink 128x296 |
| Other functions | User-customizable display |
| Interface | 1 External pushbutton + 1 LED display |
| Configuration | NFC via smartphone APP |
| Scene pushbuttons | 6 |
| Power | 2x Battery 590 mAh CR2450 |
| Battery Life | 3 years (20 beats/day) |
| Operating temperature | -10°C to 50°C (Relative humidity) |
| Grado de Protección | IP30 |
| Dimensiones | 14 (Fo) x 86 (Al) x 86 (An) mm |
| Material | PC+ABS |
| Color | Blanco |
| Certificados | CE, FCC |