

HWI-T240H

4 Megapixel Hikvision IP Camera
1/3" Progressive Scan CMOS
Compression H.265+ / WDR
2.8 mm Lens
EXIR IR LEDs range 30 m
WEB, CMS Software, Smartphone
and NVR



Hikvision
IP camera
1/3" Progressive Scan CMOS
4 Megapixel (2560x1440)
2.8 mm Lens
0 Lux
IR Range 30 m
H.265+/H.265/H.264+/H.264
Dual stream
RJ-45 10/100M BaseT
PoE IEEE802.3af
IR Cut
3D-DNR
WDR 120 dB
Weatherproof IP67
WEB, CMS, Smartphone and NVR interface
ONVIF Compatible

Specifications

Brand	Hikvision
Range	HiWatch Series
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Main Stream rate	4Mpx (20 FPS) / 1080p / 720p (25 FPS)
Extra Stream rate	D1 / CIF (1 ~ 25 FPS)
Compression	H.265+/H.265/H.264+/H.264
Bitrate	32 Kbps ~ 8 Mbps
Lens	2.8 mm
Minimum illumination	Colour 0.01 Lux @ F1.2 Colour 0.028 Lux @ F2.0
Infrared lighting	0 Lux / EXIR LEDs IR (30 m)
Image improvements	WDR 120dB, BLC, 3D-NR, AGC, Motion detection
Day / Night	Removable mechanical ICR filter
Alarms	No
Audio	No
Network interface	Ethernet 10/100 BaseT
Internal memory	No
Remote access	Web Browser, Smartphone App IVMS 4500 and PC Software IVMS 4200
Interoperability	ONVIF, PSIA, CGI, ISAPI
Power	DC 12 V / 500 mA, PoE IEEE802.3af
Degree of protection	Weatherproof IP67, Vandal-proof IK10
Material	Metal and Plastic
Temp. operation	-30° C ~ +50° C
Dimensions	93.2 mm (D) x 110 (Ø) mm
Weight	360 g