

SF-IPPT470CWA-4US-AI

IP Camera PT 4 Megapixel Night
Color
1/1.8" Progressive Scan CMOS
Fixed lens 4 mm | PAN & TILT
Audio | Alarm | MicroSD Slot
Built-in microphone and speaker
TrueSense and Face Capture



Saffire
IP Camera PT- ULTRA Range
1/1.8" Progressive Scan CMOS
4 Megapixel (2560x1440)
4 mm Lens
Night Color, color image 24h
WDR
Compression H.265+/H.264+
IR Cut
0 Lux
White back-up light up to 30 m
TrueSense, false alarm filter for vehicles and people
Face Capture: Compatible with facial recognition recorders
Alarm
Built-in speaker
RJ-45 10/100M BaseT
WEB, CMS, Smartphone and NVR interface
ONVIF Compatible
Micro SD card recording
PoE+ IEEE802.3at
Weatherproof IP66

Specifications

Brand	SAFIRE
Image sensor	1/1.8" Progressive Scan CMOS Night Color
Maximum resolution	4 Megapixel (2560x1440)
Minimum illumination	0.0005 Lux / Color 24/7
White Ligth	White light Range 30m
Main Stream coding	4 Mpx (2560x1440) 25 fps (2560 x 1440, 1920 x 1080, 1280 x 960, 1280 x 720)
Sub-Stream Encoding	25 fps (704 x 576, 640 x 480, 352 x 288)
Compression	H.265+/ H.265 / H.264+/ H.264
Lens	4 mm
Digital zoom	16X
Electronic shutter	1/1s-1/30,000s
Manual Speed	Horizontal: 60°/s Vertical: 50°/s
Day / Night	Removable mechanical ICR filter
Image improvements	BLC, HLC, 120dB WDR, 3D-NR, AGC, AWB, MD, Privacy Masking, ROI
Advanced functions	TrueSense for vehicles and people detection with false alarm filter: Line crossing, Intrusion, Region entry, Region exit, Removed object and Abandoned object Face Capture. Automatic selection of the best photo. Capable of capturing up to 5 faces at a time. * TrueSense and Face Capture cannot be enabled at the same time.
FOV	Horizontal: 88.7°, Vertical: 46.5°, Diagonal: 105.
Internal memory	MicroSD card, Max 256 GB
Audio	Microphone and speaker incorporated 1 input (Line In) / 1 output (Line Out)
Alarms	1 input / 1 output + Audible and visual alarm
PTZ Control	Through network access
Network interface	Ethernet 10 / 100M BaseT
Remote access	Web browser, Safire Control Center Smartphone App and PC Software
Interoperability	ONVIF, PSIA, CGI
Power	DC 12 V, 3.33 A / 14W, PoE (802.3af)
Temp. operation	-10° C ~ +55° C
Degree of protection	IP66 / Surges 6000V
Dimensions (without bracket)	182 (H) x 120 (Ø) mm
Weight (without bracket)	1125 g