



## BAUWERK GLUE SCALE

Format	MS 40 <sup>*</sup>	MS 35 <sup>*</sup>	Quantum	F5 <sup>**</sup>	Adhesive Trowel type
Unicopark			✓		4 (B12–B13)
Villapark   Studiopark	✓	✓	✓		2 (B8–B10)
Casapark	✓	✓	✓		4 (B12–B13)
Formpark 780 & 520   Formpark Mini 570 & 380   Formpark Quadrato   Formpark Rombico	✓	✓	✓		2 (B8–B10)
Trendpark   Cleverpark	✓	✓	✓		2 (B8–B10)
Unopark   Solopark   Monopark   Monopark Comfort	✓	✓	✓	✓	1 (B6)
Multipark 10   Multipark 9.5	✓	✓	✓		2 (B8–B10)
Solid parquet   On-edge	✓ <sup>1</sup>	✓ <sup>1</sup>	✓ <sup>1</sup>	✓	1 (B6)
Prepark   Prepark Comfort	✓	✓	✓	✓	1 (B6)
Cleverpark Silente   Multipark Silente	✓		✓		2 (B8–B10)
Triopark	✓	✓	✓		4 (B12–B13)
Bauwerk Silente mat			✓		1 (B6)

✓ Recommended by Bauwerk    ✓ Possible alternative

**Note:**

- \* for cement screeds with an increased moisture content of up to max. 5% apply first Bona R590 moisture barrier
- \*\* when applying F5 on calcium sulphate flowing screed, apply first Bona D515
- \*\*\* Please use Bauwerk MS40 if Cradle to Cradle® certification is desired.
- <sup>1</sup> Plies to oiled surfaces, for lacquered surfaces only use Bona lacquer.

**General Information**

- › this table is applicable for examined, suitable subfloors for parquet such as cement-, calcium sulphate- and calcium sulphate flowing screed, chipboards and fibreboards.
- › all types of glue listed in this overview are suitable for underfloor heating
- › for any further information please address to your Bauwerk contact person