

INSTALLATION AND ACTIVATION GUIDE

Carefully follow these instructions to guarantee a safe and proper component installation.

1. Remove the battery from the carrier

- **Insert the specific key** into the battery lock.
- **Turn the key** to unlock the safety mechanism.
- **Carefully slide the battery out** from the carrier and set it aside temporarily.

2. Carrier Installation

- **Locate the 4 pre-installed screws** on the steering head (head tube).
- **Unscrew the bolts**, position the carrier over the holes, and fasten it securely to the frame using the same screws.



3. Electrical Connection

To ensure proper operation, connect the cables following the color code.

Cable	Color	Notes
Display	Green	Align the arrows
Pedal Assist Sensor	Blue	Align the arrows
Motor	Black	Align the arrows

⚠ PLEASE NOTE: Connector Alignment

When connecting the cables (Display, Sensor, and Motor), pay close attention:

- **Locate the arrows** printed on the ends of the connectors.
- **Perfectly align the two arrows** (arrow to arrow) before pushing them together.
- *Incorrect or forced insertion can damage the internal pins.*



4. System Activation

Once the wiring is complete, proceed as follows:

1. **Slide the battery** into its dedicated housing on the carrier.
2. **Turn on the battery** using the power switch.
3. **Turn on the bicycle** by pressing the power button on the handlebar display.

For further information, please refer to the **USER MANUAL**.