

QuickTask™ Mop

Looped Polyester Microfiber Mop, (TASK0300)

The QuickTask range consists of a variety of flat mop heads that can be easily attached to a choice of flat mop head frames and handle assemblies. The flat mop heads are compatible with the QuickTask hinged mop frames 2749 (stainless steel) and 2740 (autoclavable polypropylene).

The split Microfiber terry cloth construction of the TASK0300 mop head provides exceptional performance in removing soil, residues and other contaminants from nearly any surface, including polymeric flooring. The Microfiber loops are very sorbent, and the mop can be used for application of a wide range of solutions and to mop-dry already wet surfaces.



Features & Benefits

- Exceptional sorbency and mop to dry performance on wet surfaces.
- Autoclavable (suggested cycle 121° C for 30 minutes)
- Highly effective at the removal of liquids, soils, residues and other contaminants
- Especially effective on polymeric flooring

Performance Characteristics

Product Information

Mop head component materials (cleaning surface first)	Polyester split microfiber blue; woven polyester backing; Woven polyester hemmed edge
Construction	Multi-layer sewn lamination/sealed border
Chemical compatibility	Compatible with a wide range of chemicals and disinfectants including hypochlorite solutions (bleach).
ISO Class cGMP Grade	6-8 B/C/D
Compatible Mop Frames	2749 (stainless steel) and 2740 (autoclavable polypropylene).

Technical Data

Attribute (units)	Typical Value*	Test Method**
Mop weight, dry; (g)	84	CTM004-03
Sorbent capacity; (mL/mop)	254	CTM004-03
Mop Coverage ft ² (m ²) ***		CTM037-01
S-Curve	246 (23)	
Place and Pull	202 (19)	

*Notes

- a) The data shown are typical values and should not be used as product specifications.
- b) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
- c) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

**Test Methods:

- 1) CTM – Refers to Contec Test Method
- 2) IEST-RP-CC004.3, Evaluating Wiping Materials Used in Cleanroom and Other Controlled Environments, Institute of environmental Sciences and Technology, Rolling Meadows IL.

***Mop coverage

Note that solution coverage depends on many variables including room airflow, temperature, surface type and texture, solution used, and mop application protocols and technique. Because of these variables, coverage data provided may not correspond to visibly-wet surfaces for contact time required for a particular solution. Coverage data is based on mop head applying solution such that the mopped surface is visibly wetted across the full mop path with no dry streaking observed, under controlled conditions. It is the responsibility of the user to determine appropriate coverage to ensure surfaces are visibly wet for the contact time required for their specific solution.

Products

Part Number	Description	EA/OB1	OB1/CS	EA/CS
TASK0300	QuickTask Mop Head, looped polyester microfiber, 16.5" x 4.5" (42 x 11.5cm)	10	4	40

