

Nitrile gloves 240 mm - blue

About

Nitrile Gloves are latex-free, powder-free and resistant to a range of chemicals*. The ambidextrous, blue 240 mm (9") long cleanroom gloves are antistatic, flexible and comfortable offering the wearer good dexterity for prolonged use.

FLEXIBLE & COMFORTABLE

CHEMICAL RESISTANT*

ANTISTATIC

Specifications

COMPATIBILITY:

ISO Class 5

LENGTH:

240mm (9")

MATERIAL:

Nitrile

PROTEIN LEVEL:

Nitrile contains no natural latex proteins

SURFACE:

Finger-textured

SHAPE:

Ambidextrous

COLOUR:

Blue

Features

- Resistant to a range of chemicals*
- Antistatic
- Latex & powder-free
- Comfortable

Meeting international standaards

- ISO 2859
- EN455: part 1-4
- EN374: part 1-3
- EN420
- EN455
- ASTM D6319



Nitrile gloves 240 mm - blue

Product Name: Clean Room Class 100

White Nitrile Gloves,

9"(240mm), Finger Textured.

Made and packed in South East Manufacture:

Surface: Finger Textured

Length:

9 inches (240mm)

Tensile Strength: min 18 mpa

Packaging: 100pieces/ Per-Double Poly Bag &

10Bags Per-Carton poly liner/ per-Outer Carton @1000 pices

Material:

100% Nitrile Butadiene Rubber

Quality Systems:

Manufactured in a facility holding Industry Std. Clean room Plant with ISO 9001:2015/ISO 13485:2016

MIL STD - 105E

Sampling:

Non-Volatile Residue:

<30.0 µg/cm²

No Silicone Oil , detected Organics:

by FTIR Spectroscopy

In accordance with ISO 2859 Inspection:

Ionic Burden: **Fluoride** <0. <0.800 $(\mu g/cm^2)$ <1.500 Sodium Chloride < 0.050 (as determined **Potassium** <0.050 **Bromide** <0.050

by IEST-RP-CC005.4) Nitrate <1.500 Lithium < 0.0004 Phosphate <0.800 Magnesium <0.004

• Meeting International Standards: กู ISO 2859

ii) EN455: Part 1-4

Su

ii) EN374: Part 1-3

iv) EN 420 v) EN 455

vi) ASTM D6319

Brand: **ProCleanroom**

Four (4) years from Shelf Life:

date of manufacture

Colour: blue

Design:

Ambidextrous, Beaded cuff

Thickness: 6mils(± 1)

Physical: AQL 1.5 tor Major /

AQL 2.5 for Minor ASTM D6319

Store in a cool dry place (5"C-30"C) **Storage Instructions:**

away from direct sunlight and

heat

Individual bags of 100pcs/Bag · Traceability:

marked with traceability

numbers

Liquid Particle Counts: <1600 particle counts

(as determined

by IEST-RP-CC005.4)

cumulative at 0.5micron

Dimension Criteria:

| Size | Palm/Width | |
|---------|------------|--|
| X-Small | _(75+5mm) | |
| Small | (85+5mm) | |
| Medium | _ (95+5mm) | |
| Large | (105+5mm) | |
| X-Large | (115_±5mm | |

Length: 240 ±10mm

Single Wall thickness (x0.01mm) Finger thickness: 0.16±0.03mm Palm thickness : 0.12±0.03mm Cuff thickness : 0.09±0.03mm



Material safety data sheet 1/3

| Section I: | Identification | | | |
|---|---|----------------------------------|-----------------------------|--|
| Product Name: Clean Roon | n Class 100 White/Blue N Finger or Palm Textured | | | |
| | Raw Materials: | | Nitrile Latex: Chemical: | 95.50% 4.50% |
| Section II: | Hazardous Ingred | ients / Identity Infor | mation | |
| The chemicals are: 1. Carboxyla 2. Zinc dibut | ited Butadiene Acrylonitrile hyl dithiocarbamate aptobenzothiazole n Hydroxide | | | (NBR) (ZDBC) (ZMBT) (KOH) (\$8) (ZnO) (TiO2) |
| Section III: | Physical Data | | | |
| Physica | ıl Appearance | Beading Colour Surface Fir | nishina | : Beaded at cuff : White : Finger Textured, |
| Powder Coating | | Nil | lior lirig | . i ingor rextured, |
| Boiling Point | | N/A | | |
| Vapour Pressure (n | | N/A | | |
| Vapour Density (air | | N/A | | |
| Specific Gravity (wa | ater = 1) | N/A | | |
| Solubility in Water | | Insoluble | | |
| % Volatile by Volum | ne | N/A | | |
| Evaporation Rate | | N/A | | |
| Viscosity | | N/A | | |
| | | | | |
| | | | | |



Material safety data sheet 2/3

| | The Nitrile Devider Free C40 Claves are preduced | | |
|---|--|--|--|
| | The Nitrile Powder Free, C10 Gloves are produced | | |
| Conformity: | conforming to FDA's 1000ml Watertight Test. ASTM D5151 and ASTM D3578 and conforms | | |
| Comornity. | to customer specified standard accordingly. | | |
| | to customer specified standard accordingly. | | |
| Section V: Fire and Explosion Haz | zard Data | | |
| • | | | |
| Flashpoint | N/A | | |
| Autoignition Temperature | N/A | | |
| Flammable Limits | N/A | | |
| | Water, Carbondioxide, Chemical Foam, | | |
| Extinguishing Media | Dry Powder and Fire Extinguishing | | |
| | media may be used. | | |
| | Use of standard procedure for combustion | | |
| Fire fighting procedures and Personal Protection | material fires including approved | | |
| | self contained breathing apparatus. | | |
| Fire and Free last on Harris | No fire of explosion hazards are associated | | |
| Fire and Explosion Hazards | with these products. | | |
| | They will melt at relavent temperature. | | |
| | | | |
| Section VI: Health Hazards Data | | | |
| | The chemical formulation of the gloves and | | |
| | surface lubricating materials do not | | |
| Bio-Compatibility: | contain any substances normally known to | | |
| | be harmful to the user or to any person with | | |
| | whom the gloves comes in contact. | | |
| | | | |
| Section VII: Reactivity Data | | | |
| Stability | Stable | | |
| Condition To Avoid | Does not apply | | |
| Incompatibility | Gloves easily contaminated while in contact | | |
| (Material to Avoid) | with copper content material | | |
| Hazardous Decomposition Products | In a fire, these product may produce a black smoke | | |
| | Will not occur | | |
| Hazardous Polymerization | | | |
| Hazardous Polymerization | · | | |
| • | al Procedures | | |
| Section VIII: Spill, Leak and Disposa | al Procedures These products are solid articles and are | | |
| Section VIII: Spill, Leak and Disposa Steps to be taken in case | These products are solid articles and are not subjects to leak or spill. | | |
| • | These products are solid articles and are | | |



Material safety data sheet 3/3

| Section IX: | Personal Protect | ion Information |
|---|---|---|
| Eye, Skin, Respirato | ory Protection | Not necessary under condition of intended use |
| Ventilation | | Not necessary under condition of intended use |
| | | |
| Section X: | Special Precaution | ons |
| Caution to be take | n in handling and stora | ge |
| Glove should be ke Avoid storing under | pt in cool and dry place to direct sunlight. | prolong its shelf life. |
| * TLV - Threshold Limit \ | Value established by Occupation | d contain Silicon Oil and the final product is Silicon Oil free. nal Safety and Health Administration (OSHA) American Conference of Industrial Hygienist, 87-88 |
| | | |