### PROSAT<sup>®</sup> Polynit Heatseal Wipes

## 100% no-run interlock knit polyester wipes presaturated with 70% Semi Grade IPA and 30% DI water

PROSAT® Polynit Heatseal Wipes are manufactured from 100% knitted textured polyester with laser-cut sealed edges for very low levels of particles and fibers. Polyester wipes are chemically resistant and exceptionally low in particles and fibers. An interlock knit creates a durable fabric, the addition of a periodic additional stitch of a no-run interlock knit prevents the fabric unraveling creating an even more durable fabric with strong edges.

Through years of continuous improvement, we have created processes that minimize nonvolatile residues (NVRs) and particles, yet result in a sorbent wipe with excellent functionality.

Presaturated wipes ensure consistent saturation of each wipe independent of operator. Presaturated wipes can increase solvent control and accountability as well as reduce VOC emissions. The wipes are provided in convenient, easy to use peel and reseal pouches or refilable tubs.



Features	Benefits
Laundered knitted 100% polyester fabric	• Extremely low levels of particles and fibers
Heat sealed edges	Allows full utilization of wipe surface
Resealable pouch	Preserves cleanliness and solvent saturation levels
Presaturated wipes	Reduces VOC emissions and solvent use

Part No.	Description	Size	Packaging
PS-HS9-7030	PROSAT Polynit Heatseal Wipes,	9" x 9"	30/pouch;
	Presaturated with 70% Semi Grade IPA/30% DI water	(230 x 230 mm)	30 pouches/case
PSPS0008	PROSAT Polynit Heatseal Wipes,	9" x 9"	150/bag; 1 bag/bucket;
	Presaturated with 70% Semi Grade IPA/30% DI water	(230 x 230 mm)	2 buckets/case
PSPS0087	PROSAT Polynit Heatseal Wipes,	4" x 4"	200/pouch;
	Presaturated with 70% Semi Grade IPA/30% DI water	(102 x 102 mm)	12 pouches/case
PSPS0094	PROSAT Polynit Heatseal Wipes,	9" x 9"	10/pouch;
	Presaturated with 70% Semi Grade IPA/30% DI water	(230 x 230 mm)	60 pouches/case

PDSW073 | 041323

Copyright © 2022 Contec, Inc. All rights reserved.



Product Information			
Material	• 100% polyester		
Construction	• No-run pique knit		
Packaging materials	<ul> <li>Outer bags (OB1), low density polyethylene (LDPE)</li> <li>Case (CS), corrugated fiberboard (PAP)</li> </ul>		
Environment	• ISO 3-8 Grade C/D		



Recycle	Recycle Symbols				
PET					
HDPE					
LDPE					
PP					
PAP	201				

Technical Data					
Attribute (units)	Typical Value	Test Method			
Basis weight, nominal; (g/m²)	140	Contec Method			
Specific ions		IEST-RP-CC004.3, Sec. 7.2.2			
Sodium; (ppm)	0.18				
Chloride; (ppm)	0.003				
Particles, readily releasable					
Particles $\geq 0.5 \mu m$ ; (x10 <sup>6</sup> /m <sup>2</sup> )	2.6	IEST-RP-CC004.2, Sec. 5.1			
Fibers ≥ 100µm; (x 10³/m²)	0.142	IEST-RP-CC004.2, Sec. 5.2			

Packaging	EA/PCH	PCH/OB1	OB1/CS	EA/CS
PS-HS9-7030	30	10	3	900
PSPS0008	150	1	2	300
PSPS0087	200	4	3	2,400
PSPS0094	10	30	2	600

EA = each; PCH = pouch; OB = outer bag; CS = case

#### Notes

a) The data shown are typical values and should not be used as product specifications.

b) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.

c) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

#### Test Methods:

1. CTM = Contec Test Method

2. IEST-RP-CC004.3 = Evaluating Wiping Materials Used in Cleanroom and Other Controlled Environments, Institute of environmental Sciences and Technology, Rolling Meadows IL

PDSW073 | 101122

Copyright © 2022 Contec, Inc. All rights reserved.

Contact us: info@contecinc.com contecinc.com Contec, Inc. Spartanburg, SC 29303 USA tel: +1-864-503-8333



# Contact Details



### ProCleanroom

T: +31 (0)40 209 40 24

E: shop@procleanroom.com