D300F_230V // wood lathe



highlights

- spindle M33 DIN800
- grey cast iron machine bed, tail stock, tool rest and head stock made of grey cast iron
- MT2 tail stock with quick lock system
- extremely quiet drive with POLY-V-belt
- extended tool rest with quick lock system
- quick adjustment for tail stock
- large face plate Ø145mm, rubber feet to minimize vibrations
- spindle/tail stock bore 10mm
- with overload protection
- the product counts to electric filter class B and has to be EMV protected if used in urban areas

included in delivery: 4-side grab chuck, life centre, face plate, 2x hand rest, several tools





Technical modifications and errors excepted. RRP in Euro incl. VAT.

D300F_230V // wood lathe



technical details

| voltage | 230V |
|-------------------------|---------|
| center height in mm | 105 |
| tailstock sleeve travel | 35 |
| tailstock cone | MK1/MT1 |
| gross weight in kg | 20 |
| packaging width in mm | 335 |
| packaging height in mm | 190 |

| motor power s1 in W | 250 |
|--------------------------------|---------------|
| distance between centers in mm | 305 |
| lathe spindle speed in min-1 | 750-3200 |
| head stock spindle | M33 DIN800 |
| net weight in kg | 19 |
| packaging length in mm | 710 |
| EAN code | 9120058371813 |