

**Article** Coloured, white or transparent self-adhesive vinyl films, on one-side silicon paper liner.

**Main uses** Industrial labels and signs, graphic decorations

**Employment conditions** Between 10°C and 28°C – between 30% and 70% RH

### Safety Informations

In compliance with art. 33 – Tit. IV of Regulation CE n° 1907/2006 REACH

Substances list under application of art. 57 and 59 par. 1 regulation CE n° 1907/2006 "Reach"

#### List of ST700 series articles free of substances listed in the Candidate List of SVHC ed. 16/01/2020

<b>ARTICLES</b>
<b>Gloss films</b>
ST700 Premium Vinyl

#### List of ST700 series articles containing substances listed in the Candidate List of SVHC ed. 16/01/2020, in a percentage of 0.1 % w/w or greater

<b>SUBSTANCE</b>	<b>ARTICLES</b>
Lead sulfochromate yellow (C.I. Pigment Yellow 34) N° CAS 1344-37-2 N° EINECS 215-693-7	ST700 Premium Vinyl

Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) as modified by Reg. 2019/957 and by all previous regulations.

**All the products of ST700 series do not contain any substances identified in the above mentioned Annex**

Annex I, II and III to REGULATION (EU) 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants (POPs).

**All the products of ST700 series do not contain any substances identified in the above mentioned Annex**



# Safety Informations

## ST700 Premium Vinyl

### SAFETY USE INSTRUCTIONS

- Do not burn the material: vinyl films are self-extinguishable by nature (see "CLASSIFICATION OF REACTION TO FIRE"), but paper liner and adhesive could burn if triggered by an ignition source. The combustion could cause, especially in conditions of oxygen-shortage, the emission of smoke and other potentially dangerous substances, toxic and irritating for inhalation or contact with mucous. The chemical nature of such substances made by combustion cannot be foreseen.
- Keep children under surveillance : self-adhesive material can cause suffocation if applied on mouth, nose or swallowed
- Do not inhale the air in the closed polythene bags containing self-adhesive material: after long storage-time, some volatile substances in the plastic films could be in a concentration that reaches or exceeds the limit set for professional exposure.
- During unrolling the material could accumulate or discharge electrostatic sparks. Take care in all situations where such discharges might cause the start of a fire.
- The material, under certain conditions, could cause cuts or abrasions: if possible use protective gloves during handling.
- Self-adhesive materials are non conceived for the (partial) wrapping or packing of food or drinks. Please avoid contact with food and beverages.
- During the use of self-adhesive products respect all the hygiene rules in professional working conditions.

### CLASSIFICATION OF REACTION TO FIRE (EN 13501-1 : 2007 + A1)

All the ST700 range vinyl has obtained the following classification of reaction to fire:

**B – S2 – D0**

The test report, is attached file with the TDS or can be available on request in .PDF format.  
Please check the suitability of European classification of fire reaction with the laws and regulations in your country.

Gloss films
ST700 Premium Vinyl



# Safety Informations

## ST700 Premium Vinyl

---

### Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Rebo believes are reliable, but the accuracy or completeness of such information is not guaranteed.

---

### Product Use

Many factors beyond Rebo's control and uniquely within user's knowledge and control can affect the use and performance of a Rebo product in a particular application. Given the variety of factors that can affect the use and performance of a Rebo product, user is solely responsible for evaluating the Rebo product and determining whether it is fit for a particular purpose and suitable for user's method of application.

---

### Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable Rebo product packaging or product literature, Rebo warrants that each Rebo product meets the applicable REBO product specification at the time REBO ships the product. REBO MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.

If the Rebo product does not conform to this warranty, then the sole and exclusive remedy is, at Rebo's option, replacement of the Rebo product or refund of the purchase price.

---

### Limitation of Liability

Except where prohibited by law, Rebo will not be liable for any loss or damage arising from the Rebo product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

---

ISO 9001 : 2008

This Industrial Identification product was manufactured under a Rebo quality system registered to ISO 9001:2008 standards.



#### Rebo B.V.

Beckerijnghstraat 21  
PO. box 125 | 3760 AC Soest  
The Netherlands

T. +31 (0)35 - 601 69 41  
[www.rebosystems.com](http://www.rebosystems.com)