Connecting the TS Controller to a WiFi Network (this step is done with the Phone and the TS Controller only)

1) Connect your mobile phone to the same WiFi network you want to connect the TS Controller to:

Network: Heater..WiFi 2.4GHz

Password: Elecro123

2) Open the Elecro WiFi app

Check the correct network is displayed in the network box and then enter the network password in the password field. Do not click 'CONFIRM' yet, please move on to step 3.



3) On the TS controller, press the "M" button four times, until the word "INSTALLATION" appears at the top of the

display and press OK



- 4) Now use the RED/BLUE directional arrows until "WiFi/BMS" appears at the top of the display, press OK
- 5) Now use the RED/BLUE directional arrows until "SET PORT" appears at the top of the display, press OK. Make a note of the 5 digit port number displayed and press OK.

6) Use the RED/BLUE directional arrows until "CONNECT WIFI" appears at the top of the display, press OK. When the word "CONTINUE?" appears at the top of the display, press OK and then immediately press the **CONFIRM** button on the phone app



After approximately 30 seconds you should get confirmation on the phone that the connection was successful. If connected successfully the TS Controller will return to 'NORMAL'. If the connection failed then it will return to the 'CONNECT WiFi' option. Please try to connect again if this happens.



Connecting the App to the TS Controller (this step is done with the Phone only)

1) In the app select the 'Local' button. Enter the 'Address' as 16 and insert the 5 digit port number you made a note of earlier. Click 'CONNECT'. You should now see the TS Controller display.

