

## Geled Helder 230mm (\*250-280mm)



### Productspecificaties

Art.nr.	W	IP	Input	Kleur temp.	Lichtbundel	Kleur	Led chip	Afmeting	Gatmaat	Dim	
GE-W-230-3		IP44		3000K	60 graden	wit	Cob	230x72mm	195-200mm	OPTIE	
GE-W-230-4		IP44		4000K	60 graden	wit	Cob	230x72mm	195-200mm	OPTIE	
Op verzoek		IP44		3000K 4000K	60 graden	wit	Cob	250x120mm	230mm	OPTIE	
		IP44		3000K 4000K	60 graden	wit	Cob	280x140mm	260mm	OPTIE	
<b>Geschikte driver</b>								<b>Lumen</b>			
GE-8W-D	8W		AC230V					893lm			
GE-12W-D	12W		AC230V					1340lm			
GE-16W-D	16W		AC230V					1840lm			
GE-20W-D	20W		AC230V					2300lm			
GE-25W-D	25w		AC230V					2875lm			
GE-30W-D	30W		AC230V					3450lm			
GE-35W-D	35W		AC230V					4025lm			

### Technische specificaties

CRI	85
Macadam	3 SDCM
Efficiency	115lm/w
Product life minimum	39.000h L80 B10/55.000h L70 B10
Chip	Toyoda
Driver	Lifud
Diffuser	N.v.t
TA	-20C TA/max
Powerfactor	0,96
UGR	22
Certificaten	CE/ROHS /Enec(driver)

