

## Glare Downlight 145mm



### Productspecificaties

Artikel nummer	<b>LL-GL-145-3</b>
Artikel nummer	<b>LL-GL-145-4</b>
IP-Waarde	<b>IP 44</b>
Input	<b>AC230V</b>
Kleur temperatuur	<b>3000k, 4000K</b>
Bundel	<b>60 graden</b>
Driver	<b>Lifud</b>
Chip	<b>COB</b>
Lumen	<b>8W &gt; 893lm (driver)</b> <b>12W &gt; 1340lm (driver)</b>
Afmeting	<b>145x63mm</b>
Gatmaat	<b>125mm</b>
Dimbaar	<b>Optioneel</b>

**\*Standaard geleverd met Lifud driver incl. 30cm kabel en 3-polig GST**

### Technische specificaties

CRI	<b>85</b>
Macadam	<b>3 SDCM</b>
Efficiency	<b>115lm/w</b>
Product life minimum	<b>39.000h L80 B10/55.000h L70 B10</b>
Chip	<b>COB</b>
Driver	<b>Lifud</b>
Diffuser	<b>N.v.t</b>
TA	<b>-20C TA/max</b>
Powerfactor	<b>0,96</b>
UGR	<b>19</b>
Certificaten	<b>CE/ROHS /EneC(driver)</b>