

LED Plafonniere IK10 ROLO 12W



Productspecificaties

| | |
|---------------------------|-----------------------|
| Artikel nummer | LL-ROLO-12W |
| Wattage | 12W |
| IP-Waarde | IP65 |
| Input | AC230V 50/60Hz |
| Kleur temperatuur | 3000k, 4000k |
| Bundel | 180 graden |
| Driver | Lifud |
| Chip | LED SMD2835 |
| Lumen | 1200 lm |
| Afmeting | 290x105mm |
| * Polycarbonaat behuizing | |

Optioneel:

Nood unit t.b.v. led paneel

| | |
|----------------|--------------------|
| Artikel nummer | LL-NU-LP-1H |
|----------------|--------------------|

Technische specificaties

| | |
|----------------------|--|
| CRI | 80 |
| Macadam | 3 SDCM |
| Efficiency | 100lm/w |
| Product life minimum | 50.000h L80 B10 |
| Chip | Epistar |
| Driver | Lifud |
| Diffuser | Opaal |
| TA | -20C TA/ 40C |
| Powerfactor | 0,96 |
| UGR | N.V.T. |
| Extra opties | Nood unit |
| Aansluitwaardes | 18stuks B-groep 22stuks C-groep |
| Uitval percentage | 0,3% |
| Certificaten | CE/SAA/Intertek/FCC/RoHS |
| Garantie | 3 jaar |