

## MULTI + 30PC led plafonniere 4000k 16w



### Productspecificaties

|                            |                            |
|----------------------------|----------------------------|
| Artikel nummer             | <b>304161 (wit)</b>        |
| Artikel nummer             | <b>30416190101 (zwart)</b> |
| Wattage                    | <b>16W</b>                 |
| IP-Waarde                  | <b>IP65</b>                |
| Input                      | <b>AC230V</b>              |
| Kleur                      | <b>Wit of zwart</b>        |
| Kleur temperatuur          | <b>4000k</b>               |
| Bundel                     | <b>120 graden</b>          |
| Driver                     | <b>Lifud</b>               |
| Chip                       | <b>SMD</b>                 |
| Lumen                      | <b>2000 lm</b>             |
| Afmeting                   | <b>320x84,5mm</b>          |
| * Technopolymeer behuizing |                            |

### Technische specificaties

|                      |  |
|----------------------|--|
| CRI                  | <b>80</b>                              |
| Macadam              | <b>3 SDCM</b>                          |
| Efficiency           | <b>125lm/w</b>                         |
| Product life minimum | <b>50.000h L80 B10</b>                 |
| Chip                 | <b>Citizen</b>                         |
| Driver               | <b>Lifud</b>                           |
| Diffuser             | <b>Opaal</b>                           |
| TA                   | <b>-20C TA/ 40C</b>                    |
| Powerfactor          | <b>0,96</b>                            |
| UGR                  | <b>N.V.T.</b>                          |
| Aansluitwaardes      | <b>18stuks B-groep 22stuks C-groep</b> |
| Uitval percentage    | <b>0,3%</b>                            |
| Certificaten         | <b>CE/SAA/Intertek/FCC/RoHS</b>        |
| Garantie             | <b>3 jaar</b>                          |