RG 214 U-ZH

DOUBLE SCREENED 50 OHM RF COAXIAL CABLE
MANUFACTURED IN COMPLIANCE WITH MIL-C-17F STANDARDS
COMPLIANCE IEC 60754-1 IEC 60754-2 IEC 61034-2

Class CPR E_{ca}

CA	PE	CA	CA	Pet	LSZH
7 x 0,75 mm	ø 7,25 mm	ø 7,90 mm	ø 8,60 mm	h. 27 mm	ø 10,8 mm

A	B	C	D	E	F

MECHANICAL DATA

A	**INNER CONDUCTOR**	SILVERED COPPER	**7 x 0,75 mm**
B	**DIELECTRIC**	LOW DENSITY POLYETHYLENE	**ø 7,25 ± 0,18 mm**
C	**1° BRAID**	SILVERED COPPER	**144 x 0,16 mm**
		- COVERAGE	**96%**
D	**2° BRAID**	SILVERED COPPER	**168 x 0,16 mm**
		- COVERAGE	**98%**
E	**NON-MIGRATING**	POLYESTER TAPE	**h. 27 mm**
F	**SHEATH**	FLAME RETARDANT NON-CORROSIVE THERMOPLASTIC FREE OF HALOGENS	**ø 10,8 ± 0,18 mm**
	- COLOUR	**BLACK - RAL 9004**	
	- PRINTING	**M17/75-RG214 MIL-C-17G RG 214 U-ZH 50 Ohm LSZH**	
		MADE IN ITALY CE 56 WEEK/YEAR EN 50575:2014 + A1:2016 Eca	

MINIMUM BENDING RADIUS (mm)
- **SINGLE** ø EXTERNAL X 5
- **REPEATED** ø EXTERNAL X 10

TEMPERATURE RANGE -30 °C / +70 °C

CABLE WEIGHT (Kg/Km)
- **COPPER** 119,7
- **PLASTIC** 89,4
- **TOTAL** 209,6

ELECTRICAL PROPERTIES at 20°C

IMPEDANCE 50 ± 2 Ohm

CAPACITANCE 100 pF/m

VELOCITY RATIO 66%

RESISTANCE
- **INNER CONDUCT.** 6 Ohm/Km
- **BRAID** 4,2 Ohm/Km

TENSION
- **SHEATH SPARK TESTING** 5,5 kV

ATTENUATIONS dB/100 m.

		dB	W
5	MHz	1,3	
10	MHz	1,9	
50	MHz	4,5	
100	MHz	6,7	
200	MHz	9,9	
400	MHz	14,3	

MAX. POWER RATING W

		dB	W
500	MHz	16,1	
600	MHz	17,8	
800	MHz	21,3	
1000	MHz	24,3	
1350	MHz	29,7	
1500	MHz	31,7	

		dB	W
1750	MHz	35,2	
2150	MHz	40,5	
2250	MHz	41,5	
2500	MHz	44,7	
2750	MHz	47,9	
3000	MHz	51,3	

STRUCTURAL RETURN LOSS dB

30 ÷ 300	MHz	>28	1000 ÷ 2000	MHz	>22
300 ÷ 600	MHz	>26	2000 ÷ 3000	MHz	>20
600 ÷ 1000	MHz	>25	….. ÷ …..	MHz	-

SCREENING EFFECTIVENESS dB

100 ÷ 900	MHz	>78
900 ÷ 2000	MHz	-
2000 ÷ 3000	MHz	-

The producer reserves himself to make modification on the item without any notice.

Deltron Trading B.V. - Morsestraat 9 - 7903 BK Hoogeveen
t. 0528 268816 - e. info@deltron.nl - w. www.deltron.nl