

WELDAS[®]

The Professional's Choice



2022

Europe Catalog No. 0722

The professional's choice world wide

Weldas® on going product development and quality control supported by field testing has earned a world wide reputation for the highest quality and most innovative products.

Weldas® products are marked with appropriate EN marking standards and are manufactured in our own, by TÜV, ISO certified factory. Most of the Weldas products are certified according to the applicable European Norms which can be found on www.weldas-ce.com. For the Russian market, EAC certificates are also available.

The pH, CHROMIUM (VI) and PCP levels of all materials in Weldas® products have been tested and meet CE health standards. Colouring is done by natural materials.

Weldas® also offers a custom designed product line for special application and marketing needs in models, packaging, barcode etc.. For more information on this contact Weldas®.

Weldas® products are warranted against manufacturing defects. Because of applications vary, it is the user's responsibility to select the right product for each application.

Weldas® is active in the following markets:

- Welding market.
- Personal protection market.
- General industrial market.

www.weldas.com



*“Global specialist
in the protection
of the welder”*




COMFOflex®

WELDING GLOVES




Cotton lining



Foam lining



COMFOflex® lining



COMFOflex®

10-2000



S, L, XL, XXL
LH
L/18"

- A-grade cow split leather
- Hand COMFOflex® lined
- Cuff cotton lined
- Wide body model
- Size L also available in Left Hand only pairs (LH) and 18" (46 cm.)



95%

KEVLAR® 4 ply + 5 ply

COMFOflex®

EN 12477 (2001+A1:2005) TYPE A
TÜV BP 60153044 0001
TÜV 60399937 003



Ω ELECTROSTATIC TESTED Ω

10-2178



L

- Same features like the 10-2000 glove
- One finger model



95%

KEVLAR® 4 ply

COMFOflex®

EN 12477 (2001+A1:2005) TYPE A
TÜV BP 60153044 0002
TÜV 60399937 003



Ω ELECTROSTATIC TESTED Ω

10-2087



L, XL

- A-grade cow shoulder split leather
- Hand full COMFOflex® lined
- Cuff cotton lined
- Wide body model



95%

KEVLAR® 4 ply + 5 ply

COMFOflex®

EN 12477 (2001+A1:2005) TYPE A
TÜV BP 60152704 0001
TÜV 60400422 002



Ω ELECTROSTATIC TESTED Ω

COMFOflex® WELDING GLOVES

10-2900-A




L, XL

- A-grade cow split leather
- Hand COMFOflex® and wool lined
- Cuff flame retardant lined
- Wide body model



70%

KEVLAR® 4 ply + 5 ply



STEERSOtuff®

EN 12477 (2001+A1:2005) TYPE A
TÜV BP 60152711 0001
TÜV 60400498 002



10-2655



M, L, XL, XXL

- Hand bison leather
- Cuff split cowhide
- Inner back of the hand COMFOflex® lined
- Cuff flame retardant lined
- **CHROMIUM < 2 mg./kg.**



30%

KEVLAR® 4 ply + 5 ply



ThunderingBison™

EN 12477 (2001+A1:2005) TYPE A
TÜV BP 60152714 0001
TÜV 60403193 003



10-2850



L, XL

- Grain and split deerskin
- Backhand COMFOflex® lined and inner cuff flame retardant lined
- Highest comfort level



30%

KEVLAR® 4 ply + 5 ply



DEERSOsoft®


EN 12477 (2001+A1:2005) TYPE A
TÜV BP 60152709 0001
TÜV 60400523 002



10-2050



S, M, L,
XL, XXL



34 cm.

- Hand made of white grain cowhide and black split cowhide
- COMFOflex® lining at the back of the glove
- Flame retardant fabric 520 gr./m² for the cuff
- This glove is sewn with 3 ply Dupont™ KEVLAR®



20%

KEVLAR® 3 ply



Arc Knight®

EN 12477 (2001+A1:2005) TYPE A
TÜV BP 60152673 0001
TÜV 60403196 002



NEW

COMFOflex® WELDING GLOVES

10-2750



L, XL, XXL

- A-grade cow grain leather
- Backhand **COMFOflex**® lined and cuff cotton lined
- Back palm reversed grain (suede)
- Oil and water resistant
- Excellent quality and comfortable to wear



30%

KEVLAR® 4 ply + 5 ply



STEERSOstuff®

EN 12477 (2001+A1:2005) TYPE A
TÜV BP 60152710 0001
TÜV 60400759 002



Ω ELECTROSTATIC TESTED Ω

10-2755




L, XL

- Combined features:
- on the back of our 10-2385
- and the innerhand of the 10-2750 with extra comfort padges
- Oil and water resistant
- Excellent quality and comfortable to wear



30%

KEVLAR® 4 ply + 5 ply



COMFOflex®

EN 12477 (2001+A1:2005) TYPE A
TÜV BP 60152707 0001
TÜV 60403152 003



10-2385




L, XL, XXL

- A-grade cow side split leather
- Hand full **COMFOflex**® lined and cuff full flame retardant lined
- Wide body model
- Aluminized back is designed to reflect radiant heat and has a layer of split deerskin in between the back and **COMFOflex**® lining



35%

KEVLAR® 4 ply



COMFOflex®

EN 12477 (2001+A1:2005) TYPE A
TÜV BP 60152705 0001
TÜV 60400780 002



+



=



44-3006LB, 44-3008LB, 44-3009BF:
see page 39

COTTON LINED WELDING GLOVES

10-2392



S, L, XL, XXL,
XXXL, LH/L,
LH/XL
L/18"

- Cow shoulder split leather
- Full cotton lined
- Straight thumb helps the user to handle a mig gun a lot better
- Size L also available in 18" (46 cm.)
- Size L and XL also available in Left Hand only pairs (LH)



95%

KEVLAR® 3 ply ✓

EN 12477 (2001+A1:2005) TYPE A
TÜV BP 60153042 0001
TÜV 60400826 002



Ω ELECTROSTATIC TESTED Ω

10-2392 MIT



L

- One finger model of glove 10-2392
- Cow shoulder split leather
- Full cotton lined



95%

KEVLAR® 3 ply ✓

EN 12477 (2001+A1:2005) TYPE A
TÜV BP 60153042 0001
TÜV 60400826 002



Ω ELECTROSTATIC TESTED Ω

10-2392GB



L, XL

- Same as glove 10-2392, but *Golden Brown™* model
- Cow shoulder split leather
- Full cotton lined
- Straight thumb helps the user to handle a mig gun a lot better



95%

KEVLAR® 3 ply ✓

EN 12477 (2001+A1:2005) TYPE A
TÜV BP 60153042 0001
TÜV 60400826 002



Ω ELECTROSTATIC TESTED Ω

10-2150



L, XL

- Innerhand is made of cow grain leather to make it oil and water resistant
- All other parts of the glove are made of cow split leather
- Full cotton lined



95%

EN 12477 (2001+A1:2005) TYPE A
TÜV BP 60152708 0001
TÜV 60403114 003



COTTON LINED WELDING GLOVES

10-2101



S, L, XL, XXL
LH/L, LH/XL

- The 10-2101 is our general purpose glove of the range
- Cow shoulder split leather
- Full cotton lined
- Size L and XL also available in Left Hand only pairs (LH)



90%

EN 12477 (2001+A1:2005) TYPE A
TÜV BP 60152715 0001
TÜV 60400835 002



10-2101GB



L, XL

- Same as glove 10-2101, but *Golden Brown™* model
- Cow shoulder split leather
- Full cotton lined



90%

EN 12477 (2001+A1:2005) TYPE A
TÜV BP 60152715 0001
TÜV 60400835 002






Weldas sizing incorporates EN 420 size standards, the lining and the intended use

(EN 420)

GLOVE AND HAND SIZE REFERENCE

| Hand Size Index | 7½ | 8½ | 9 | 9½ | 10½ | 11½ |
|----------------------|-----|-----|-----|-----|-----|------|
| Weldas Size Label | S | M | L | XL | XXL | XXXL |
| Measurement mm | 190 | 216 | 229 | 241 | 267 | 293 |
| Minimum length in mm | 310 | 320 | 330 | 340 | 350 | 360 |



WWW.WELDAS-CE.COM

SOFTouch™ TIG WELDING GLOVES

10-1003




M, L, XL, XXL

- Oil and abrasion resistant
- Reversed (suede) grain pig leather
- Seamless index finger

KEVLAR® 3 ply

SOFTouch™

EN 12477 (2001 + A1 : 2005)
TYPE B
TÜV BP 60161565 0001
TÜV DE2153T4 002



10-1004




S, M, L, XL, XXL
RH/XL

- Hand made of goatskin
- Double leather in the palm
- Very soft and excellent feeling
- Cuff made of grey flame retardant fabric
- Size XL also available in Right Hand only pairs (RH)

KEVLAR® 3 ply

SOFTouch™

EN 12477 (2001 + A1 : 2005)
TYPE B
TÜV BP 60161747 0001
TÜV DE21Z111 002



10-1005




S, M, L, XL, XXL

- Very smooth and pliable
- Calfskin grain leather
- Seamless index finger

KEVLAR® 3 ply

SOFTouch™

EN 12477 (2001 + A1 : 2005)
TYPE B
TÜV BP 60161507 0001
TÜV DE2145GU 002



Ω ELECTROSTATIC TESTED Ω

10-1007



M, L, XL

- Goatskin palm
- Cow split leather back and cuff

KEVLAR® 3 ply

SOFTouch™

EN 12477 (2001 + A1 : 2005)
TYPE B
TÜV BP 60162388 0001
TÜV DE21NF0S 002



SOFTouch™

TIG WELDING GLOVES

10-1009



M, L, XL, XXL

- Hand made of goatskin
- Very soft and excellent feeling
- Cuff made of split cow leather
- Seamless index finger

KEVLAR® 3 ply

SOFTouch™

EN 12477 (2001 + A1 : 2005)
TYPE B
TÜV BP 60161802 0001
TÜV DE21CMVU 002



Ω ELECTROSTATIC TESTED Ω

10-1050



M, L, XL, XXL

- Outer hand made of soft black grain cow leather
- White grain goat leather spacers on the sides of the fingers
- Curved cuff made of supple split cow leather trimmed at the edge with white grain goat leather
- Thin fleecy, flame retardant lining at the back of the hand
- Seamless index finger

KEVLAR® 4 ply

SOFTouch™

EN 12477 (2001 + A1 : 2005)
TYPE A
TÜV BP 60163685 0001
TÜV DE21QIQJ 003



10-2304



M, L, XL, XXL

- Hand made of deerskin
- Very soft feeling
- Cuff made of split cow leather

KEVLAR® 3 ply



DEERSOsoft®

EN 12477 (2001+A1:2005) TYPE A
TÜV BP 60161805 0001
TÜV DE215FIB 002



10-2644



M, L, XL, XXL

- Hand bison leather
- Cuff split cowhide
- **CHROMIUM < 2 mg./kg.**



KEVLAR® 3 ply



ThunderingBison™

EN 12477 (2001 + A1 : 2005)
TYPE B
TÜV BP 60162726 0001
TÜV DE21PY9M 002



WORKING GLOVES

10-2670



M, L, XL, XXL

- Work glove designed for general purpose applications
- Grain goat leather with stretchy spandex glove back
- Wrist closable with a hook and loop closure for good fit of the glove

EN 388:2016/A1:2018
UE-000115/00



10-1206



L


- Cow split leather
- Cotton lined
- Rubberized safety cuff

EN 388:2016/A1:2018
UE-000107/00



WORKING GLOVES

10-2806



L

- Cow split leather
- Double leather in the palm
- Cotton lined
- Rubberized safety cuff

EN 388:2016/A1:2018
UE-000103/00



10-2209



S, M, L, XL, XXL

- A-grade cow split leather
- Cotton lined
- Rubberized safety cuff

EN 388:2016/A1:2018
UE-000104/00



10-2209LB



L, XL

- A-grade cow split leather
- Cotton lined
- Rubberized safety cuff
- *Lava Brown™* model

EN 388:2016/A1:2018
UE-000105/00



10-2207



L, XL

- Cow split leather
- Cotton lined
- Safety cuff

EN 388:2016/A1:2018
UE-000106/00



DRIVER GLOVES

10-2064



L, XL

- Durable split cow leather

EN 388:2016/A1:2018
UE-000108/00



10-2336



M, L, XL

- Palm made of cow grain side leather
- Back made of split cow leather
- Extra fingertip sensitivity

KEVLAR® 3 ply



EN 388:2016/A1:2018
UE-000109/00



10-2633



M, L, XL, XXL

- Innerhand made of grain bison leather
- Back made of split cow leather
- **CHROMIUM < 2 mg./kg.**

KEVLAR® 3 ply



EN 388:2016/A1:2018
UE-0000110/00



10-2700



S, M, L, XL, XXL

- Cow grain side leather of the highest quality
- Oil and water resistant



EN 388:2016/A1:2018
UE-000111/00



DRIVER GLOVES

10-9334



XL

- Palm made of cow grain side leather
- Back made of split cow leather



EN 388:2016/A1:2018
UE-000112/00




(EN 420)

GLOVE AND HAND SIZE REFERENCE

| Hand Size Index | 7½ | 8½ | 9 | 9½ | 10½ | 11½ |
|----------------------|-----|-----|-----|-----|-----|------|
| Weldas Size Label | S | M | L | XL | XXL | XXXL |
| Measurement mm | 190 | 216 | 229 | 241 | 267 | 293 |
| Minimum length in mm | 310 | 320 | 330 | 340 | 350 | 360 |



Lava Brown™ CLOTHING



Lava Brown™ products are made of high quality A-grade side split cow leather

44-7300 Jacket full leather



- A-grade side split cow leather
- KEVLAR® 5 ply
- Leather thickness: min. 1 mm.



EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60126846 0001
TÜV 21285003 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

| | | |
|--------------|--------|---------|
| | ↕ | |
| 44-7300M | 76 cm. | 100 cm. |
| 44-7300L | 81 cm. | 112 cm. |
| 44-7300XL | 86 cm. | 124 cm. |
| 44-7300XXL | 91 cm. | 136 cm. |
| 44-7300XXXL | 96 cm. | 148 cm. |
| 44-7300XXXXL | 96 cm. | 160 cm. |

44-7300/P Jacket with flame retardant back



- A-grade side split cow leather
- KEVLAR® 5 ply
- Leather thickness: min. 1 mm.
- Back: flame retardant cotton 315 gr/m²



EN ISO 11611:2015
CLASS 1/A1+A2
TÜV BP 60127076 0001
TÜV 21280500 001



**EN ISO 11611:2015
CLASS 1/A1+A2**

| | | |
|---------------|--------|---------|
| | ↕ | |
| 44-7300M/P | 76 cm. | 100 cm. |
| 44-7300L/P | 81 cm. | 112 cm. |
| 44-7300XL/P | 86 cm. | 124 cm. |
| 44-7300XXL/P | 91 cm. | 136 cm. |
| 44-7300XXXL/P | 96 cm. | 148 cm. |

Lava Brown™ CLOTHING

44-7300/P-AQ Ladies jacket with flame retardant back



- A-grade side split cow leather
- KEVLAR® 5 ply
- Leather thickness: min. 1 mm.
- Back: flame retardant cotton 315 gr./m²



EN ISO 11611:2015
CLASS 1/A1+A2
TÜV BP 60127076 0001
TÜV 21280500 001



**EN ISO 11611:2015
CLASS 1/A1+A2**

| | | |
|----------------|--------|---------|
| | ↕ | |
| 44-7300S/P-AQ | 76 cm. | 98 cm. |
| 44-7300M/P-AQ | 76 cm. | 110 cm. |
| 44-7300L/P-AQ | 81 cm. | 120 cm. |
| 44-7300XL/P-AQ | 86 cm. | 130 cm. |

44-7800 Cape sleeve



- A-grade side split cow leather
- KEVLAR® 5 ply
- Leather thickness: min. 1 mm.



EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60126846 0001
TÜV 21285003 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

| | | |
|-------------|---------|--|
| | ↕ | |
| 44-7800M | 100 cm. | |
| 44-7800L | 112 cm. | |
| 44-7800XL | 124 cm. | |
| 44-7800XXL | 136 cm. | |
| 44-7800XXXL | 148 cm. | |

44-78.. Apron for cape sleeves



- A-grade side split cow leather
- KEVLAR® 5 ply
- Leather thickness: min. 1 mm.



EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60126846 0001
TÜV 21285003 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

| | | |
|-----------|---------|--------|
| | ↕ | ↔ |
| 44-7820 | 51 cm. | 56 cm. |
| 44-7828 | 71 cm. | 56 cm. |
| 44-7836 | 91 cm. | 56 cm. |
| 44-7836XL | 120 cm. | 80 cm. |



Lava Brown™ CLOTHING

44-7248

Pants with breast protection and open back

44-7440

Pants with open back



122 cm.

- A-grade side split cow leather
- KEVLAR® 5 ply
- Leather thickness: min. 1 mm.



102 cm.



STEERSOstuff®

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60126846 0001
TÜV 21285003 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

44-7440/7600

Pants with closed back



- A-grade side split cow leather
- KEVLAR® 5 ply
- Leather thickness: min. 1 mm.

44-7440/7600M
44-7440/7600L
44-7440/7600XL
44-7440/7600XXL
44-7440/7600XXXL

110 cm.
112 cm.
116 cm.
122 cm.
128 cm.



STEERSOstuff®

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60126846 0001
TÜV 21285003 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

44-7440/7648

Pants with breast protection and closed back, bib and brace



- A-grade side split cow leather
- KEVLAR® 5 ply
- Leather thickness: min. 1 mm.

44-7440/7648M
44-7440/7648L
44-7440/7648XL
44-7440/7648XXL
44-7440/7648XXXL
44-7440/7648XXXXL

136 cm.
140 cm.
144 cm.
148 cm.
152 cm.
156 cm.



STEERSOstuff®

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60126846 0001
TÜV 21285003 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

Lava Brown™ CLOTHING

44-71.. Apron



- A-grade side split cow leather
- KEVLAR® 5 ply
- Leather thickness: min. 1 mm.
- Self-balancing strap system

| | | |
|-----------|---------|--------|
| | ↕ | ↔ |
| 44-7124 | 60 cm. | 60 cm. |
| 44-7136 | 91 cm. | 60 cm. |
| 44-7142 | 107 cm. | 60 cm. |
| 44-7142 W | 107 cm. | 80 cm. |
| 44-7148 | 122 cm. | 60 cm. |
| 44-7148 W | 122 cm. | 80 cm. |

COMFORT



44-7124
60x60 cm.



STEERSOtuff®

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60126846 0001
TÜV 21285003 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

44-7023 Sleeves



- A-grade side split cow leather
- KEVLAR® 5 ply
- Leather thickness: min. 1 mm.
- Balancing strap system

44-7023

↕
58 cm.



STEERSOtuff®

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60126846 0001
TÜV 21285003 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

44-7028 Heavy duty arm guard (piece)



- Heavy duty
- A-grade side split cow leather
- KEVLAR® 5 ply
- Leather thickness: min. 1 mm.
- COMFOflex® lining used
- Hook and loop closure
- Inside 520 gr./m² flame retardant fabric
- See for extension 44-7114EXT (page 18)

44-7028 35 cm. 32-41 cm. 35-45 cm.



STEERSOtuff®

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60126846 0001
TÜV 21285003 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

Lava Brown™ CLOTHING

44-7106 Spats for shoe protection



- A-grade side split cow leather
- KEVLAR® 5 ply
- Leather thickness: min. 1 mm.
- With under the shoe an elastic strap to secure shoe top cover

44-7106

33-43 cm. 15 cm.



EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60126846 0001
TÜV 21285003 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

44-7114 Spats for leg and shoe protection



- A-grade side split cow leather
- KEVLAR® 5 ply
- Leather thickness: min. 1 mm.
- With bendable insert at shin and shoe top to allow shape formation
- See for extension 44-7114EXT

44-7114

37-47 cm. 36 cm.



EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60126846 0001
TÜV 21285003 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

44-7114EXT Diameter extension for 44-7114 and 44-7028



- A-grade side split cow leather
- KEVLAR® 5 ply
- Leather thickness: min. 1 mm.
- 15 cm. wide extension for 44-7114 and 44-7028

44-7114EXT

15 cm.



EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60126846 0001
TÜV 21285003 001



**EN ISO 11611:2015
CLASS 2/A1+A2**



COMFOflex[®]

SOFTouch[™]

DEERSOsoft[®]

ThunderingBison[™]

TURMOflex[®]

Lava Brown[™]

STEERSOtuff[®]

Arc Knight[®]

Arc Queen[™]

Golden Brown[™]

Fire Fox[™]

Yellowjacket[®]

SWEATSOpad[®]

COMBOframe[™]

LAVAshield[®]

PYTHONrap[™]

Glove Medic[™]

Golden Brown™ CLOTHING



KEVLAR® 3 ply √



Min. 1 mm.

2 x Min. 1 mm.



1 x

Golden Brown™ products are made of high quality side split or grain cow leather
Golden Brown™ split leather products: pages 20, 21, 22, 23. Grain leather products: page 24.

44-2530/P Jacket with flame retardant back



- Side split cow leather
- KEVLAR® 3 ply √
- Leather thickness: min. 1 mm.
- Back: flame retardant cotton 305 gr/m²

44-2530M/P
 44-2530L/P
 44-2530XL/P
 44-2530XXL/P
 44-2530XXXL/P

| | | |
|--------|---------|---|
| ↑↓ | ↑ | ↑ |
| 76 cm. | 100 cm. | |
| 81 cm. | 112 cm. | |
| 86 cm. | 124 cm. | |
| 91 cm. | 136 cm. | |
| 96 cm. | 148 cm. | |



Golden Brown™

EN ISO 11611:2015
 CLASS 1/A1+A2
 TÜV BP 60132808 0001
 TÜV 60141016 001



**EN ISO 11611:2015
 CLASS 1/A1+A2**

44-2847 Shoulder apron



- Side split cow leather
- KEVLAR® 3 ply √
- Leather thickness: min. 1 mm.

44-2847M
 44-2847L
 44-2847XL

| | |
|--------|--------|
| ↑↓ | ↔ |
| 92 cm. | 53 cm. |
| 92 cm. | 58 cm. |
| 92 cm. | 63 cm. |



Golden Brown™

EN ISO 11611:2015
 CLASS 2/A1+A2
 TÜV BP 60132827 0001
 TÜV 60150123 001



**EN ISO 11611:2015
 CLASS 2/A1+A2**

Golden Brown™ CLOTHING

44-2800 Cape sleeve



- Side split cow leather
- KEVLAR® 3 ply
- Leather thickness: min. 1 mm.

44-2800L
44-2800XL
44-2800XXL



112 cm.
124 cm.
136 cm.



Golden Brown™

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60132827 0001
TÜV 60150123 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

44-28.. Apron for cape sleeves



- Side split cow leather
- KEVLAR® 3 ply
- Leather thickness: min. 1 mm.

44-2828
44-2836

71 cm. 56 cm.
91 cm. 56 cm.



Golden Brown™

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60132827 0001
TÜV 60150123 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

44-21.. Apron



- Side split cow leather
- KEVLAR® 3 ply
- Leather thickness: min. 1 mm.
- Self-balancing strap system

44-2136
44-2142
44-2142 W

91 cm. 60 cm.
107 cm. 60 cm.
107 cm. 80 cm.



Golden Brown™

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60132827 0001
TÜV 60150123 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

Golden Brown™ CLOTHING

44-2600 Pants



- Side split cow leather
- KEVLAR® 3 ply
- Leather thickness: min. 1 mm.

| | |
|-----------|---------|
| 44-2600M | 110 cm. |
| 44-2600L | 112 cm. |
| 44-2600XL | 116 cm. |



Golden Brown™

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60132808 0001
TÜV 60141016 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

44-2648 Pants with breast protection, bib and brace



- Side split cow leather
- KEVLAR® 3 ply
- Leather thickness: min. 1 mm.

| | |
|------------|---------|
| 44-2648M | 136 cm. |
| 44-2648L | 140 cm. |
| 44-2648XL | 144 cm. |
| 44-2648XXL | 148 cm. |



Golden Brown™

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60132808 0001
TÜV 60141016 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

44-2321, 44-2321XL Sleeves



- Side split cow leather
- KEVLAR® 3 ply
- Leather thickness: min. 1 mm.
- Hook and loop closure at the top
- Wrist-end with elastic band included

| | | | |
|-----------|--------|-----------|-----------|
| 44-2321 | 52 cm. | 21-31 cm. | 34-47 cm. |
| 44-2321XL | 52 cm. | 21-31 cm. | 45-60 cm. |



Golden Brown™

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60132827 0001
TÜV 60150123 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

Golden Brown™ CLOTHING

44-2106 Spats for shoe protection



- Side split cow leather
- KEVLAR® 3 ply
- Leather thickness: min. 1 mm.
- With under the shoe an elastic strap to secure shoe top cover

44-2106

33-43 cm. 15 cm.



Golden Brown™

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60132827 0001
TÜV 60150123 001



**EN ISO 11611:2015
CLASS 2/A1+A2**

44-2114 Spats for leg and shoe protection



- Side split cow leather
- KEVLAR® 3 ply
- Leather thickness: min. 1 mm.
- With bendable insert at shin and shoe top to allow shape formation

44-2114

37-47 cm. 36 cm.



Golden Brown™

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60132827 0001
TÜV 60150123 001



**EN ISO 11611:2015
CLASS 2/A1+A2**



Golden Brown™ CLOTHING



KEVLAR® 3 ply √

Min. 1 mm.

2 x Min. 1 mm.

1 x

Golden Brown™ products are made of high quality side split or grain cow leather
Golden Brown™ split leather products: pages 20, 21, 22, 23. Grain leather products: page 24.

44-5530 Jacket full leather



- Grain cow leather
- KEVLAR® 3 ply √
- Leather thickness: min. 1 mm.



Golden Brown™

EN ISO 11611:2015
 CLASS 2/A1+A2
 TÜV BP 60132801 0001
 TÜV 60140939 001



**EN ISO 11611:2015
 CLASS 2/A1+A2**

- 44-5530L
- 44-5530XL
- 44-5530XXL
- 44-5530XXXL

| | | |
|---|--------|---------|
| ↑ | 81 cm. | 112 cm. |
| | 86 cm. | 124 cm. |
| | 91 cm. | 136 cm. |
| | 96 cm. | 148 cm. |

44-5600 Pants with breast protection, bib and brace



- Grain cow leather
- KEVLAR® 3 ply √
- Leather thickness: min. 1 mm.



Golden Brown™

EN ISO 11611:2015
 CLASS 2/A1+A2
 TÜV BP 60132801 0001
 TÜV 60140939 001



**EN ISO 11611:2015
 CLASS 2/A1+A2**

- 44-5600L
- 44-5600XL
- 44-5600XXL
- 44-5600XXXL

| | |
|---|---------|
| ↑ | 140 cm. |
| | 144 cm. |
| | 148 cm. |
| | 152 cm. |
| | |

Yellowjacket® CLOTHING



KEVLAR® 3 ply ✓



Min. 1 mm.

305 gr./m²



1 x

Yellowjacket® product is made of 305 gr./m² flame retardant cotton body and split cow leather sleeves

33-3060 Jacket, flame retardant cotton with leather sleeves



- 305 gr./m² flame retardant cotton body
- split cow leather sleeves
- KEVLAR® 3 ply ✓

Yellowjacket®

EN ISO 11611:2015
CLASS 1/A1+A2
TÜV BP 60132808 0001
TÜV 60141016 001

| | | |
|--------------|--------|---------|
| | ↕ | |
| 33-3060S | 76 cm. | 108 cm. |
| 33-3060M | 76 cm. | 116 cm. |
| 33-3060L | 81 cm. | 127 cm. |
| 33-3060XL | 86 cm. | 138 cm. |
| 33-3060XXL | 91 cm. | 147 cm. |
| 33-3060XXXL | 96 cm. | 158 cm. |
| 33-3060XXXXL | 96 cm. | 168 cm. |



**EN ISO 11611:2015
CLASS 1/A1+A2**



Arc Knight® CLOTHING



KEVLAR® 3 ply √



520 gr./m²



Double material



1 x

Arc Knight® 38-4350, 38-4355, 38-44.. and 38-4340 are made of heavy duty 520 gr./m² FR cotton with split cow leather reinforcement.

Arc Knight® 38-4330, 38-4335, 38-4375, 38-4328, 38-43.., 38-4360 and 38-4321XL are made of heavy duty 520 gr./m² FR cotton.

38-4350 Jacket with leather reinforcement



- High comfort and flexibility
- Heavy duty 520 gr./m² FR cotton with black split cow leather reinforcement
- KEVLAR® 3 ply √
- Sleeve with double closure



Arc Knight®

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60122567 0001
TÜV 21260757 003



EN ISO 11611:2015
CLASS 2/A1+A2

| | | |
|------------|--------|---------|
| | 76 cm. | 96 cm. |
| 38-4350M | 81 cm. | 104 cm. |
| 38-4350L | 86 cm. | 112 cm. |
| 38-4350XL | 91 cm. | 120 cm. |
| 38-4350XXL | 96 cm. | 128 cm. |


38-4330 Jacket



44-7820
44-7828
44-7836
44-7836XL
(see page 15)



38-4320
(see page 28)



44-2828
44-2836
(see page 21)

- High comfort and flexibility
- Heavy duty 520 gr./m² FR cotton
- KEVLAR® 3 ply √
- Possibility to add a *Lava Brown™* or *Golden Brown™* apron to this jacket



Arc Knight®

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60122567 0001
TÜV 21260757 003



EN ISO 11611:2015
CLASS 2/A1+A2

| | | |
|------------|--------|---------|
| | 76 cm. | 96 cm. |
| 38-4330M | 81 cm. | 104 cm. |
| 38-4330L | 86 cm. | 112 cm. |
| 38-4330XL | 91 cm. | 120 cm. |
| 38-4330XXL | 96 cm. | 128 cm. |

Arc Knight® CLOTHING

38-4335 Jacket, high visibility



- High visibility
- High comfort and flexibility
- Heavy duty 520 gr./m² FR cotton
- KEVLAR® 3 ply √
- Available in size: M, L, XL, XXL, XXXL

38-4355 Jacket, high visibility



Arc Knight®


**EN ISO 11611:2015
CLASS 2/A1+A2
EN ISO 20471:2013
+ A1:2016 clause 6
TÜV BP 60122567 0003
TÜV 21260757 003**

38-4375 Lab coat



- High comfort and flexibility
- Heavy duty 520 gr./m² FR cotton
- KEVLAR® 3 ply √

- | | | |
|------------|---------|---------|
| 38-4375M | 114 cm. | 96 cm. |
| 38-4375L | 114 cm. | 104 cm. |
| 38-4375XL | 114 cm. | 112 cm. |
| 38-4375XXL | 114 cm. | 120 cm. |



Arc Knight®

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60122567 0001
TÜV 21260757 003

**EN ISO 11611:2015
CLASS 2/A1+A2**

38-4328 Cape sleeve



- High comfort and flexibility
- Heavy duty 520 gr./m² FR cotton
- KEVLAR® 3 ply √

- | | |
|-------------|---------|
| 38-4328M | 96 cm. |
| 38-4328L | 104 cm. |
| 38-4328XL | 112 cm. |
| 38-4328XXL | 120 cm. |
| 38-4328XXXL | 128 cm. |



Arc Knight®

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60122567 0001
TÜV 21260757 003

**EN ISO 11611:2015
CLASS 2/A1+A2**

Arc Knight® CLOTHING

38-4320 Apron for cape sleeve



- High comfort and flexibility
- Black split cow leather
- KEVLAR® 3 ply

38-4320

51 cm.

56 cm.



Arc Knight®

EN ISO 11611:2015
CLASS 2/A1+A2

TÜV BP 60122567 0001
TÜV 21260757 003



**EN ISO 11611:2015
CLASS 2/A1+A2**

38-43.. Apron



- High comfort and flexibility
- Heavy duty 520 gr./m² FR cotton
- KEVLAR® 3 ply
- Self-balancing strap system

38-4336
38-4342
38-4342 W

91 cm.
107 cm.
107 cm.

60 cm.
60 cm.
80 cm.



Arc Knight®

EN ISO 11611:2015
CLASS 2/A1+A2

TÜV BP 60122567 0001
TÜV 21260757 003



**EN ISO 11611:2015
CLASS 2/A1+A2**

38-44.. Apron with leather reinforcement



- High comfort and flexibility
- Heavy duty 520 gr./m² FR cotton with black split cow leather reinforcement
- KEVLAR® 3 ply
- Self-balancing strap system

38-4436
38-4442
38-4442 W

91 cm.
107 cm.
107 cm.

60 cm.
60 cm.
80 cm.



Arc Knight®

EN ISO 11611:2015
CLASS 2/A1+A2

TÜV BP 60122567 0001
TÜV 21260757 003



**EN ISO 11611:2015
CLASS 2/A1+A2**

Arc Knight® CLOTHING

38-4360 Pants



- High comfort and flexibility
- Heavy duty 520 gr./m² FR cotton
- KEVLAR® 3 ply

| | |
|------------|--------|
| 38-4360M | 79 cm. |
| 38-4360L | 81 cm. |
| 38-4360XL | 83 cm. |
| 38-4360XXL | 85 cm. |

- Possibility to add knee pads

| | |
|-------------|---------|
| 38-4380M | 136 cm. |
| 38-4380L | 140 cm. |
| 38-4380XL | 144 cm. |
| 38-4380XXL | 148 cm. |
| 38-4380XXXL | 152 cm. |

38-4380 Pants, breast protection, bib and brace



Arc Knight®

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60122567 0001
TÜV 21260757 003



**EN ISO 11611:2015
CLASS 2/A1+A2**

38-4340 Pants with leather reinforcement, breast protection, bib and brace



- High comfort and flexibility
- Heavy duty 520 gr./m² FR cotton with black split cow leather reinforcement
- KEVLAR® 3 ply

| | |
|-------------|---------|
| 38-4340M | 136 cm. |
| 38-4340L | 140 cm. |
| 38-4340XL | 144 cm. |
| 38-4340XXL | 148 cm. |
| 38-4340XXXL | 152 cm. |



Arc Knight®

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60122567 0001
TÜV 21260757 003



**EN ISO 11611:2015
CLASS 2/A1+A2**

38-4321XL Sleeves



- High comfort and flexibility
- Heavy duty 520 gr./m² FR cotton
- KEVLAR® 3 ply

| | | | |
|-----------|--------|-----------|-----------|
| 38-4321XL | 52 cm. | 21-31 cm. | 45-60 cm. |
|-----------|--------|-----------|-----------|



Arc Knight®

EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60122567 0001
TÜV 21260757 003



**EN ISO 11611:2015
CLASS 2/A1+A2**

Fire Fox™ CLOTHING

⚡ KEVLAR® 3 ply √ 305 gr./m² Double material 1 x

Fire Fox™ clothing is made of 305 gr./m² flame retardant cotton

33-2300 Jacket



- 305 gr./m² flame retardant cotton
- KEVLAR® 3 ply √
- Possibility to add a *Lava Brown™* or *Golden Brown™* apron to this jacket



Fire Fox™

EN ISO 11611:2015
CLASS 1/A1+A2
TÜV BP 60148715 0001
TÜV 60332344 001



**EN ISO 11611:2015
CLASS 1/A1+A2**

- 44-7820
- 44-7828
- 44-7836
- 44-7836XL (see page 15)
- 44-2828
- 44-2836 (see page 21)

38-4320 (see page 28)

| | | |
|-------------|--------|---------|
| 33-2300M | 76 cm. | 96 cm. |
| 33-2300L | 81 cm. | 104 cm. |
| 33-2300XL | 86 cm. | 112 cm. |
| 33-2300XXL | 91 cm. | 120 cm. |
| 33-2300XXXL | 96 cm. | 128 cm. |

33-2600 Pants



- 305 gr./m² flame retardant cotton
- KEVLAR® 3 ply √
- Possibility to add knee pads



Fire Fox™

EN ISO 11611:2015
CLASS 1/A1+A2
TÜV BP 60148715 0001
TÜV 60332344 001



**EN ISO 11611:2015
CLASS 1/A1+A2**

| | |
|-------------|--------|
| 33-2600M | 79 cm. |
| 33-2600L | 81 cm. |
| 33-2600XL | 83 cm. |
| 33-2600XXL | 85 cm. |
| 33-2600XXXL | 87 cm. |

Fire Fox™ CLOTHING

33-2700 Pants with breast protection, bib and brace



- 305 gr./m² flame retardant cotton
- KEVLAR® 3 ply
- Possibility to add knee pads

33-2700M
33-2700L
33-2700XL
33-2700XXL
33-2700XXXL



79 cm.
81 cm.
83 cm.
85 cm.
87 cm.



Fire Fox™

EN ISO 11611:2015
CLASS 1/A1+A2
TÜV BP 60148715 0001
TÜV 60332344 001



**EN ISO 11611:2015
CLASS 1/A1+A2**

33-2800 Coverall



- 305 gr./m² flame retardant cotton
- KEVLAR® 3 ply
- Possibility to add knee pads

33-2800M
33-2800L
33-2800XL
33-2800XXL
33-2800XXXL



176 cm.
180 cm.
184 cm.
188 cm.
196 cm.




Fire Fox™

EN ISO 11611:2015
CLASS 1/A1+A2
TÜV BP 60148715 0001
TÜV 60332344 001



**EN ISO 11611:2015
CLASS 1/A1+A2**

33-2320 Sleeves



- 305 gr./m² flame retardant cotton
- KEVLAR® 3 ply

33-2320 52 cm. 19-32 cm. 36-47 cm.



Fire Fox™

EN ISO 11611:2015
CLASS 1/A1+A2
TÜV BP 60148740 0001
TÜV 60343261 001



**EN ISO 11611:2015
CLASS 1/A1+A2**

Fire Fox™

FR COTTON CAPS

23-*514 FR Cap



Fire Fox™

EN ISO 11611:2015
CLASS 1/A1+A2
TÜV BP 60148742 0001
TÜV 60341060 001



**EN ISO 11611:2015
CLASS 1/A1+A2**

23-*515 FR Cap



COMFORT



**Choose the best size for all caps:
* = 1, 2, 3, 4, 5, 6, 7**

| Size | Articlenumber | |
|-------|---------------|--------|
| 7 | 23-1xxx | 56 cm. |
| 7 1/8 | 23-2xxx | 57 cm. |
| 7 1/4 | 23-3xxx | 58 cm. |
| 7 3/8 | 23-4xxx | 59 cm. |
| 7 1/2 | 23-5xxx | 60 cm. |
| 7 5/8 | 23-6xxx | 61 cm. |
| 7 3/4 | 23-7xxx | 62 cm. |

COTTON CAPS

23-*503 Camouflage



23-*507 USA flag



23-*524 Wild



Fire Fox™

FR BEANIE

23-8000 FR Beanie



- Often used in combination with helmet
- High comfort and flexibility
- 305 gr./m² flame retardant cotton




Fire Fox™

EN ISO 11611:2015
CLASS 1/A1+A2
TÜV BP 60148742 0001
TÜV 60341060 001



**EN ISO 11611:2015
CLASS 1/A1+A2**

23-8000L 56-59 cm. 
23-8000XL 59-62 cm.

Fire Fox™

FR COTTON DOO-RAGS

23-3612 FR Doo-Rag



23-3613 FR Doo-Rag



Fire Fox™

EN ISO 11611:2015
CLASS 1/A1+A2
TÜV BP 60148742 0001
TÜV 60341060 001



**EN ISO 11611:2015
CLASS 1/A1+A2**

23-3611 FR Doo-Rag



23-3615 FR Doo-Rag



- Often used in combination with helmet
- High comfort and flexibility
- Sweatband integrated in the front of the Doo-Rag
- 305 gr./m² flame retardant cotton

All Doo-Rags, one size fits all:

46-68 cm.

COTTON DOO-RAGS

23-3601 Camouflage



23-3602 Wild



23-3604 USA flag



23-3606 Happy Hour



23-3607 Paradise



23-3609 European flag



Fire Fox™

FR HELMET HOODS

23-6680, 23-6680XL

23-6680/LV

23-6690



- Connectable to helmet gear
- Hook and loop closure
- 305 gr./m² flame retardant cotton




Fire Fox™

EN ISO 11611:2015
CLASS 1/A1+A2
TÜV BP 60148742 0001
TÜV 60341060 001



**EN ISO 11611:2015
CLASS 1/A1+A2**

23-6680 / 23-6680LV / 23-6690: 64 cm.
23-6680XL: 68 cm.



23-6680: 41 cm.
23-6690: 41 cm.
23-6680XL: 44 cm.
23-6680/LV: 62 cm.

23-6680 / 23-6680LV / 23-6690: 42 - 53 cm.
23-6680XL: 52 - 65 cm.

Multiple sizes and lengths

Arc Knight®

LEATHER HELMET HOOD

23-6630



- Hook and loop closure
- Black split cow leather with 520 gr./m² flame retardant cotton
- Available in size L and XL
- KEVLAR® 3 ply



EN ISO 11611:2015
CLASS 2/A1+A2
TÜV BP 60133477 0001
TÜV 60142905 001



**EN ISO 11611:2015
CLASS 2/A1+A2**



TURMOflex®

WINTER HELMET LINERS

23-7766



- Connectable to helmet gear
- Hook and loop closure
- 305 gr./m² flame retardant cotton
- COMFOflex® lining



TURMOflex®

EN ISO 11611:2015
CLASS 1/A1+A2
TÜV BP 60148742 0001
TÜV 60341060 001



**EN ISO 11611:2015
CLASS 1/A1+A2**

23-7702



23-7733



23-7711



before
washed



“Most comfortable sweatband in the world”

AIR CUSHIONED
SWEATSpad[®]


SWEATSpad[®]



SWEATSOpad®

HELMET COMFORTER

- Helmet pad and sweatband combined in one piece air cushioned *SWEATSOpad*®
- Flame retardant
- No more "helmet head"!
- No more slippage!
- No more sweat!



20-3100V, 20-3100V/17



20-3100V
20-3100V/17

22 cm.
17 cm.

SWEATSOpad®

EN ISO 11611:2003
CLAUSE 6.6
TÜV AK 60013119 0001
TÜV 21120493 001



20-3200V



20-3200V

25 cm.

SWEATSOpad®

EN ISO 11611:2003
CLAUSE 6.6
TÜV AK 60013119 0001
TÜV 21120493 001



20-3300V



20-3300V

14 cm.

SWEATSOpad®

EN ISO 11611:2003
CLAUSE 6.6
TÜV AK 60013119 0001
TÜV 21120493 001



LEATHER HELMET CAPS AND BIBS

44-7180




- Grain leather helmet cap
- Black grain cowhide
- Will fit over the helmet gear and can be attached with hook and loop to the top of the helmet gear.

44-7181



- Grain leather back neck protection
- Black grain cowhide
- Made to be attached with hook and loop to the cap (= art.nr. 44-7180)

- Dimensions:




44-7182



- Grain leather front neck protection
- Black grain cowhide
- Can be attached with hook and loop to the helmet inside or outside

- Dimensions:




44-7184



- Split leather Front neck protection
- Black split cowhide
- Can be attached with hook and loop to the helmet inside or outside

- Dimensions:



ACCESSORIES

44-7111



- Foldable inspector mask
- Fits glass: 110 x 50 mm.
- Glass not included

KEVLAR® 3 ply √




44-7110



- Electrode bag with hanging system
- To be filled with max. 2 kg. electrodes
- Double leather construction

KEVLAR® 3 ply √



ACCESSORIES

44-3006LB, 44-3006LB/PR



- High heat reflective handshield
- Split cowhide leather back with **aluminized PFR front**
- Also available in pairs (44-3006LB/PR)

KEVLAR® 5 ply

15 cm. 20 cm.

All handshields:
EN ISO 11611:2015
TÜV 60353593-002



44-3008LB



- High heat reflective handshield
- Split cowhide leather back with **fiber glass front**
- Extra heat resistant

15 cm. 20 cm.

KEVLAR® 5 ply

44-3009BF



- High heat reflective handshield
- **Black coated fiber glass back with fiber glass front**
- Heavy duty handshield for the toughest applications

15 cm. 20 cm.

KEVLAR® 5 ply

10-1099



- TIG finger
- For extra protection
- For extra stability in position welding
- Silica fabric
- With hook and loop

KEVLAR® 3 ply

3,5 cm. 16 cm.

10-1911/UL



- **10-1911/UL**
Repair & reinforcement kit for unlined gloves such as TIG welding, drivers and mechanic gloves.

Caution: For certified gloves, check ratings before operation. For non-certified gloves, owner is responsible to ensure proper protection before operation.

10-2911/LI



- **10-2911/LI**
Repair & reinforcement kit for lined gloves such as stick or MIG welders, heavy duty work, heat resistant gloves.



WELDING PILLOWS



44-7900



- 50 x 50 x 8 cm.
- KEVLAR® 3 ply



44-7905



- 39 x 33 x 3 cm.
- KEVLAR® 3 ply

44-7910



- 50 x 50 x 8 cm.
- KEVLAR® 3 ply



44-7915



- 39 x 33 x 3 cm.
- KEVLAR® 3 ply

44-7920



- 50 x 50 x 8 cm.
- KEVLAR® 3 ply



44-7925



- 39 x 33 x 3 cm.
- KEVLAR® 3 ply

PYTHONrap™ CABLE COVERS

T = Tube



44-xxxxT

| | | |
|----------|-----------|---|
| 44-1022T | 22 mm dia | 1 m length lightbrown leather cable cover |
| 44-1027T | 27 mm dia | 1 m length lightbrown leather cable cover |

V = Hook and loop



44-xxxxV

| | | |
|----------|-----------|--|
| 44-0550V | 50 mm dia | 5 m length lightbrown leather cable cover |
| 44-1050V | 50 mm dia | 10 m length lightbrown leather cable cover |

| | | |
|--------------|-----------|--|
| 44-5030V/MTR | 30 mm dia | Lightbrown leather cable cover PER METER |
| | | 1 roll = 50 mtr. |
| 44-5050V/MTR | 50 mm dia | Lightbrown leather cable cover PER METER |
| | | 1 roll = 50 mtr. |

Z = Zipper



44-xxxxZ

| | | |
|----------|-----------|---|
| 44-3001Z | 22 mm dia | 1 m length lightbrown leather cable cover |
| 44-3010Z | 22 mm dia | 3 m length lightbrown leather cable cover |
| 44-3022Z | 22 mm dia | 6,7 m length lightbrown leather cable cover |
| 44-3922Z | 22 mm dia | 3,9 m length lightbrown leather cable cover |
| 44-3928Z | 28 mm dia | 3,9 m length lightbrown leather cable cover |
| 44-7922Z | 22 mm dia | 7,9 m length lightbrown leather cable cover |
| 44-7928Z | 28 mm dia | 7,9 m length lightbrown leather cable cover |
| 44-4001Z | 32 mm dia | 1 m length lightbrown leather cable cover |
| 44-4525Z | 37 mm dia | 2,5 m length lightbrown leather cable cover |
| 44-4535Z | 37 mm dia | 3,5 m length lightbrown leather cable cover |



44-xxxxZ

| | | |
|----------|-----------|--|
| 44-3601Z | 22 mm dia | 1 m length black grain leather cable cover |
| 44-3628Z | 28 mm dia | 1 m length black grain leather cable cover |



44-xxxxZ

| | | |
|----------|-----------|--|
| 44-4023Z | 23 mm dia | 4 m length black flame retardant nylon cable cover |
| 44-4028Z | 28 mm dia | 4 m length black flame retardant nylon cable cover |
| 44-8023Z | 23 mm dia | 8 m length black flame retardant nylon cable cover |
| 44-8028Z | 28 mm dia | 8 m length black flame retardant nylon cable cover |

KEVLAR® 3 ply



Other length / diameter combinations on request

LAVAsield® WELDING BLANKETS

50-1866

50-2368/2468

50-3068



- Silica fabric
- 174 x 174 cm.
- ± 1000°C
- ± 600 gr./m²
- KEVLAR® 3 ply ↓

- Black fiberglass
- Neoprene / neoprene coating
- 174 x 234 cm.
- ± 550°C
- ± 800 gr./m²
- KEVLAR® 3 ply ↓

- Gold fiberglass
- Acryl / neoprene coating
- 174 x 234 cm.
- ± 550°C
- ± 1000 gr./m²
- KEVLAR® 3 ply ↓

50-2472 Per meter



- Black fiberglass
- Neoprene / neoprene coating
- Not locked stitched
- Without grommets
- Width ± 183 cm.
- Total roll length ± 45 mtr.
- ± 550°C
- ± 800 gr./m²

50-3072 Per meter




- Gold fiberglass
- Acryl / neoprene coating
- Not locked stitched
- Without grommets
- Width ± 183 cm.
- Total roll length ± 45 mtr.
- ± 550°C
- ± 1000 gr./m²

LAVAsield®

ISO 9150:1988-12

TÜV 21278287 001




LAVAsield® WELDING SCREENS

55-6166 Orange/Red 1.74 x 1.74 mtr.



Fits within frame 1.8 x 1.8 mtr.

- Heat sealed seams and grommets
- Nylon ties are furnished for convenience and secure fastening to the quick connection Weldas® *COMBOframe*™: 55-8668



LAVAsield®

DIN EN ISO 25980:2015-01
13821-PZA-17




55-6168 Orange/Red 1.74 x 2.34 mtr.



Fits within frame 1.8 x 2.4 mtr.

- Heat sealed seams and grommets
- Nylon ties are furnished for convenience and secure fastening to the quick connection Weldas® *COMBOframe*™: 55-8668



LAVAsield®

DIN EN ISO 25980:2015-01
13821-PZA-17




55-7166 Green 1.74 x 1.74 mtr.



Fits within frame 1.8 x 1.8 mtr.

- Heat sealed seams and grommets
- Nylon ties are furnished for convenience and secure fastening to the quick connection Weldas® *COMBOframe*™: 55-8668



LAVAsield®

DIN EN ISO 25980:2015-01
13822-PZA-17



55-7168 Green 1.74 x 2.34 mtr.




Fits within frame 1.8 x 2.4 mtr.

- Heat sealed seams and grommets
- Nylon ties are furnished for convenience and secure fastening to the quick connection Weldas® *COMBOframe*™: 55-8668





LAVAsield®

DIN EN ISO 25980:2015-01
13822-PZA-17



COMBOframe™ MODULAR FRAME

55-8668



55-8668

1.8 x 1.8 mtr. / 1.8 x 2.4 mtr.

- Weldas® COMBOframe™ suitable for the welding screens: 55-6166, 55-6168, 55-7166, 55-7168
- Will be delivered as only frame (incl. swivelset), without screens

COMBOframe™



LAVashield® WELDING SCREENS PER METER

55-6166/MTR Orange/Red



- Heat sealed seam and grommets at one side
- Distance between grommets ± 20 cm.
- Will be delivered together with rings Ø 50 mm.
- Height ± 1.78 mtr.
- Total roll length ± 27 mtr.

LAVashield®

DIN EN ISO 25980:2015-01
13821-PZA-17



55-7166/MTR Green



- Heat sealed seam and grommets at one side
- Distance between grommets ± 20 cm.
- Will be delivered together with rings Ø 50 mm.
- Height ± 1.78 mtr.
- Total roll length ± 27 mtr.

LAVashield®

DIN EN ISO 25980:2015-01
13822-PZA-17



LAVAshield®

ECONO STRIP SCREENS

55-6166/Strip Orange/Red



0.68 x 1.8 mtr.

- Will be delivered together with 5 rings Ø 50 mm.



LAVAshield®

DIN EN ISO 25980:2015-01
13821-PZA-17



55-7166/Strip Green



0.68 x 1.8 mtr.

- Will be delivered together with 5 rings Ø 50 mm.



LAVAshield®

DIN EN ISO 25980:2015-01
13822-PZA-17



LAVAshield®

CONNECTABLE WELDING SCREENS

55-6218 Orange/Red




1.37 x 1.8 mtr.

- Connectable welding screen
- Heat sealed seams
- Will be delivered together with 9 rings Ø 50 mm.



LAVAshield®

DIN EN ISO 25980:2015-01
13821-PZA-17



55-7218 Green



1.37 x 1.8 mtr.

- Connectable welding screen
- Heat sealed seams
- Will be delivered together with 9 rings Ø 50 mm.



LAVAshield®

DIN EN ISO 25980:2015-01
13822-PZA-17



SELECTION CRITERIA

In order to make the right choice in a type and/or model of a personal protection product the user should make for himself selection criteria in order to come up with the best choice for his/her situation.

Weldas wants to help with that by giving you a number of selection criteria to start by making the right choice. Please read for that the 2 following pages carefully.

General selection criteria for leather products such as welding gloves and welding clothing

Choosing the right product is always important to make the workplace productive but also safe.

The factors to consider include one or more of the following arguments:



- Protection arguments: resistant to heat, flame, molten splashes, UV, electricity and punctures.
- Health arguments: values of pH, Chromium, PCP or other substances that needs to be within limits.
- Durability arguments: values of abrasion resistance, tensile strength, tear resistance, heat related dimensional change resistance, reinforced seams and stress points as well as thread strength and flame resistance.
- Comfort arguments: the right sizing and fit, dexterity, fingertip sensitivity, weight, sweat vapor transmission and absorption and climate and oil resistant.

Type of leather selection criteria for leather products such as welding gloves and welding clothing:

| Type of leather | Features |
|------------------------------|--|
| Split cow leather | Heat & flame resistant, material breaths because of open structure, also low priced |
| Grain cow leather | Pliable and strong, water and oil resistant |
| Suede (reversed) pig leather | Soft and comfortable and mostly lower priced than other leathers |
| Grain deer leather | Fit and dexterity and, with that, very good comfort as well as water and oil resistant |
| Grain goat leather | Fit and dexterity, light weight and very good comfort as well as water and oil resistant |
| Grain bison leather | Fit and dexterity, very good comfort, high mechanical value as well as water and oil resistant |

Leather grades and terminology:

Different portions of the hide of an animal have different characteristics: the side offers the best strength and most constant quality, the shoulder offers good strength and pliability, the belly is the lowest in quality but also the most economical.



Choice of thumb design:

| Straight thumb | Wing thumb | Keystone thumb |
|---|------------------------------|---------------------|
| | | |
| For extra sensitivity and/or extra welding gun grip | For seamless palm durability | For comfortable fit |

Note on thumb/palm design: extra durability and/or cut resistance can be achieved by adding an extra reinforcement around thumb and/or on palm of the glove.

Remark: the choice of materials and design for welding gloves and clothing but also for other products out of the Weldas product program always depend on what the applicable European norm desires. For that reason our products are tested and certified by a, by the European Union approved, test and certification laboratory. All test reports and certificates can be found on our special CE website:

www.weldas-ce.com

Weldas offers a lot of information through its catalog, website and other means of publication in order to help the user to make the right choice of product for its personal protection but it is and will always be the responsibility of the user what product he/she does choose.

INFORMATION ON EUROPEAN NORMS

In 1989 the council of the European community agreed on the directive 89/686/EEC which requires employers to use the appropriate personal protective equipment (PPE). As of April 21, 2018 the Regulation (EU) 2016/425 repealed the directive 89/686/EEC. All products used for personal protection must be marked with the appropriate basic CE marking and extended if the applicable norm does ask for it and according to it's intended use. The regulation recognizes 3 levels of protection and the products to go with these levels:

Category I

Category I includes exclusively the following minimal risks:

- (a) superficial mechanical injury;
- (b) contact with cleaning materials of weak action or prolonged contact with water;
- (c) contact with hot surfaces not exceeding 50 °C;
- (d) damage to the eyes due to exposure to sunlight (other than during observation of the sun);
- (e) atmospheric conditions that are not of an extreme nature.

Category II


Category II includes risks other than those listed in Categories I and III;

Category III

Category III includes exclusively the risks that may cause very serious consequences such as death or irreversible damage to health relating to the following:

- (a) substances and mixtures which are hazardous to health;
- (b) atmospheres with oxygen deficiency;
- (c) harmful biological agents;
- (d) ionising radiation;
- (e) high-temperature environments the effects of which are comparable to those of an air temperature of at least 100 °C;
- (f) low-temperature environments the effects of which are comparable to those of an air temperature of – 50 °C or less;
- (g) falling from a height;
- (h) electric shock and live working;
- (i) drowning;
- (j) cuts by hand-held chainsaws;
- (k) high-pressure jets;
- (l) bullet wounds or knife stabs;
- (m) harmful noise.

Example of imprint of a Weldas® certified glove:



Basic norms and pictograms used for personal protection:

EN 420 norm on sizing of gloves: see page 9 of this catalogue.

EN 388 norm on mechanical risks for gloves:

| Digit | Test Resistance | Level 1 | Level 2 | Level 3 | Level 4 | Level 5 | |
|-------|-----------------------------|---------|---------|---------|---------|---------|----|
| 1st | Abrasion (# cycles) | 100 | 500 | 2000 | 8000 | - | |
| 2nd | Blade Cut (index) | 1,2 | 2,5 | 5,0 | 10,0 | 20,0 | |
| 3rd | Tear (Newton) | 10 | 25 | 50 | 75 | - | |
| 4th | Puncture (Newton) | 20 | 60 | 100 | 150 | - | |
| 5th | TDM Cut resistance (Newton) | A | B | C | D | E | F |
| | | 2 | 5 | 10 | 15 | 22 | 30 |

EN 407 norm thermal risks for gloves:

| Digit | Test Resistance | Digit | Test Resistance |
|-------|-------------------|-------|----------------------------------|
| 1st | Burning behaviour | 5th | Small splashes of molten metal |
| 2nd | Contact heat | | |
| 3rd | Convective heat | 6th | Large quantities of molten metal |
| 4th | Radiant heat | | |

EN 12477 norm on welding gloves and allied processes:

| Minimum requirements | according to EN... | Type A Minimum Rating | Type B Minimum Rating |
|---------------------------------|--------------------|-----------------------------------|-----------------------------------|
| Electrical Insulation | pr1149-2 | R _z ≥10 ⁶ Ω | R _z ≥10 ⁵ Ω |
| Abrasion Resistance | EN 388 2 | 500 cycles | 100 cycles |
| Blade Cut Resistance | EN 388 1 | Index 1,2 | Index 1,2 |
| Tear Resistance | EN 388 2 | 25 N | 10 N |
| Puncture Resistance | EN 388 2 | 60 N | 20 N |
| Burning Behaviour | EN 407 3 | | 2 |
| Contact Heat Resistance | EN 407 1 | 100° C | 100° C |
| Convective Heat Resistance | EN 407 2 | HTI≥7 | 0 |
| Small Molten Splash Resistance | EN 407 3 | 25 Droplets | 15 Droplets |
| Dexterity (pick up of rod dia.) | EN 420 1 | ≤11mm | ≤6,5mm |

EN 11611 norm on welding clothing and allied processes:

| Requirement(s) | Class 1 | Class 2 |
|--|--|--------------------|
| Tensile strength — woven outer textile material — leather | | 400 N 80 N |
| Tear strength | | 20 N |
| Dimensional change of woven textile materials Dimensional change of knitted textile materials | | ≤ ± 3 % ≤ ± 5 % |
| Flame spread * : For ISO 15025:2000, Procedure B, this requirement is not applicable. | ISO 15025:2000, Procedure A, (surface ignition) ; ISO 15025:2000, Procedure B, (edge ignition) No flaming to the top or either side edge; No hole formation a; No flaming or molten debris Mean afterflame ≤ 2 s; Mean afterglow ≤ 2 s | |
| Impact of spatter | 15 drops | 25 drops |
| Heat transfer (radiation) | RHTI 24 W 7 | RHTI 24 W 16 |
| Burst strength | 200kPa | |
| Seam strength — textile material — leather | 225 N 110 N | |
| Electrical resistance | >10 ⁵ Ω | |
| Innocuousness | See 6.11 | |
| Leather | Fat content: ≤ 15 % | |



Weldas® Europe B.V.
Blankenweg 18
NL-4612 RC Bergen op Zoom
Holland

Tel.: +31 164 27 46 50
Fax: +31 164 27 46 55
europa@weldas.eu
www.weldas.com



WWW.WELDAS-CE.COM

KEVLAR® is a registered trademark of E.I. DuPont Co.
Weldas® is a registered trademark of Weldas® Company.
Arc Knight® is a registered trademark of Weldas® Co.
COMFOflex® is a registered trademark of Weldas® Co.
DEERSOsoft® is a registered trademark of Weldas® Co.
LAVAshield® is a registered trademark of Weldas® Co.
STEERSOuff® is a registered trademark of Weldas® Co.
SWEATSOpad® is a registered trademark of Weldas® Co.
TURMOflex® is a registered trademark of Weldas® Co.
Yellowjacket® is a registered trademark of Weldas® Co.
Arc Queen™ is a trademark of Weldas® Co.
COMBOframe™ is a trademark of Weldas® Co.
Fire Fox™ is a trademark of Weldas® Co.
Glove Medic™ is a trademark of Weldas® Co.
Golden Brown™ is a trademark of Weldas® Co.
Lava Brown™ is a trademark of Weldas® Co.
PYTHONrap™ is a trademark of Weldas® Co.
SOFTouch™ is a trademark of Weldas® Co.
ThunderingBison™ is a trademark of Weldas® Co.

©0722 Weldas® Europe B.V.
Printing and typesetting errors reserved.

YOUR DISTRIBUTOR:

