

Poolican + Tankkd stock tank

Connections, functions and water care

IMPORTANT WITH A TANKKD STOCK TANK

Do NOT use the Poolican salt / electrolysis function. Add NO salt and NO chlorine to the water. Use Microbe-Lift as instructed by Tankkd: one capful (a small splash) per week.

What is the Poolican 4-in-1?

- | | |
|-------------------------------|---|
| 1. Circulation | The built-in pump moves water through the system. |
| 2. Filtration | A washable cartridge filter traps debris. |
| 3. Heating and cooling | Reversible 5 kW Full Inverter heat pump. |
| 4. Salt electrolysis | Built into the unit, but always switched off with Tankkd. |

Connecting to the Tankkd

WATER FROM THE TANK

Tankkd outlet Ø 38 mm → Intex adapter 38 → 32 mm → Poolican IN

WATER RETURNING TO THE TANK

Poolican OUT → Intex adapter 32 → 38 mm → Tankkd inlet Ø 38 mm

- Connect both lines using suitable hoses and hose clamps; follow the IN/OUT markings on the unit.
- Place the Poolican on a level, stable surface and keep its air vents unobstructed.
- Fill the tank above the connections, open the valves, prime as directed in the Poolican manual and check all joints for leaks.
- Only then switch on circulation and heating/cooling. Keep the salt function switched off.

Technical details at a glance

Brand / unit	Poollex Poolican, integrated 4-in-1 unit
Maximum pool volume	Up to 25 m ³ , according to the manufacturer
Heat pump	Reversible, Full Inverter, 5 kW
Circulation pump	Flow rate 5 m ³ /h; electrical power 140 W
Filtration	Washable cartridge filter
Hose connections	Ø 32/38 mm; Tankkd adapter 38 → 32 mm
Controls	On the unit and via Wi-Fi/app

Care: keep the water circulating, clean the filter regularly and follow the manual for your supplied Poolican model on electrical safety, frost protection and servicing.