

PPF MAIN TEN ANCE BOOKLET



GYEON®

PPF MAIN 10ANCE RULES


1. After the PPF installation, allow the film to settle for 48h to 72h - during this period do not expose your vehicle to chemicals or harsh weather conditions. Try to keep the vehicle in stable environment.

2. Do not wash your car with use of chemicals within the first 14 days after PPF application.

3. Do not use automatic car washes and while using hand wash, only rely on a trusted place.

4. Do not let contaminants, like bird droppings, remain on any surface. Remove safely as soon as possible.

5. Do not expose and let dry acid, caustic chemicals and any other contaminants you are aware of on your PPF.



6. You drive = you care. Each car is subject to a unique life. The harsher the life, the more maintenance it requires.

7. If any damage occurs, please contact your GYEON Installer, do not try to fix it on your own.

8. Always wash and dry your car once it is cool and out of direct sunlight, never when the car is hot.

9. Use GYEON Q²M PPF Wash and Q²M PPF Maintain products at least once a month.

10. Use GYEON Q²M PPF Wash and Q²M PPF Maintain products at least once a month.





HOW TO MAINTAIN YOUR PPF'ED VEHICLE?

Wash your vehicle with a traditional 2 bucket methods and GYEON PPF Maintenance products.

To wash GYEON PPF you can use Q²M PPF Wash, a super slick and foamy shampoo designed to remove mild iron contamination on the film.

This shampoo can be used on the entire exterior surface of your vehicle too.

Poor 20/30ML in 12 liters bucket, and wash your vehicle from top to bottom with Q²M Smoothie in straight motion a panel at the time. Rinse heavily.





To dry your vehicle, use Q²M SilkDryer - use it in straight motion. Do not apply pressure while drying your paintwork. Use separate dedicated towels for your paintwork, wheels and lower parts of your vehicle for an efficient and safe drying procedure.

Once washed, we recommend to apply Q²M PPF Maintain to boost hydrophobicity, gloss and slickness. Q²M PPF Maintain can be apply on dry or on wet vehicle, it will act as drying aid.





For films older than 2 years, we recommend the use of Q²M PPF Renew, a dedicated cleanser for glossy protection film and wrap.



To boost hydrophobicity after the use of Q²M PPF Renew, coat the film with Q²PPF, a flexible coating for PPF and wraps, with great UV resistance and slickness.



WWW.GYEONSERVICES.COM