According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

Printing date:6/5/2011 Revision date: 6/5/2011

1 Identification of the substance and of the company/undertaking

1.1 Product identifier:

Identification on the label/Trade name: Citric acid

Additional identification: 2-hydroxy-1,2,3-propanetricarboxylic acid

Identification of the product: CAS#77-92-9; EC#201-069-1

Index Number: Not available

REACH registration No.: 01-2119457026-42-0004

1.2 Relevant identified uses of the substance and uses advised against:

1.2.1 Identified uses:

Use as an intermediate in the production of other organic chemicals.

Formulation into preparations.

Use in personal care products.

Use in detergent/cleaning and other household products.

Use in paper making.

Use in construction products

Use in polymers and plastics products.

Use in the oil industry.

Use in the textile industry.

Use in paints and coatings.

Use in photography products.

Use in laboratory reagents.

Use in water treatment.

Use in the treatment of metal surfaces.

Use in agricultural applications.

Use in medical devices

1.2.2 Uses advised against:

Not available.

1.3 Details of the supplier of the safety data sheet:

Supplier(Only representative): Chemical Inspection & Regulation Service Limited

Supplier(Manufacturer): COFCO BIOCHEMICAL(ANHUI)CO.,LTD

Address: NO.73 Daqing Road, Bengbu City, Anhui, China 233010

 Contact person(E-mail):
 sly469@163.com

 Telephone:
 +86-552-4928078

 Fax:
 +86-552-4928460

1.4 Emergency telephone Number:

+353 41 980 6916

Available outside office hours? YES NO X

2 Hazards Identification

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

Printing date:6/5/2011 Revision date: 6/5/2011

2.1 Classification of the substance

2.1.1 Classification:

The substance is classified as following according to 67/548/EEC and REGULATION (EC) No 1272/2008:

EU CLP 1272/2008	
Hazard classes/Hazard categories	Hazard statement
Eye Irrit. 2	H319

For full text of H- phrases: see section 2.2.

67/548/EEC	
Hazards characteristics	R-Phrases
Xi	R36

For full text of R- phrases: see section 16.

2.1.2 The most important adverse effects

2.1.2.1 The most important adverse physicochemical effects:

Not available

2.1.2.2 The most important adverse human health effects:

Causes serious eye irritation.

2.1.2.3 The most important adverse environmental effects:

Not applicable.

2.2 label elements

Hazard Pictograms:



Signal Word(S): Warnin

Hazard Statement: H319: Causes serious eye irritation

Precautionary Statement: P264: Wash...thoroughly after handling. (with soap and water)

P280: Wear protective gloves/protective clothing/eye protection/face protection

P305+ P351 +P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P337+P313: If eye irritation persists: Get medical advice/attention.

2.3 Other hazards

Not available(PBT,vPvB, Substance is an endocrine disruptor etc.)

3 Composition/information on ingredients

Substance/Mixture: Substance

Ingredient(s):

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

Printing date: 6/5/2011 Revision date: 6/5/2011

Chemical Name	Registration No.	CAS No.	EC No.	Concentration
2-hydroxy-1,2,3-propanetricarboxylic acid	01-2119457026-42-0004	77-92-9	201-069-1	>99%

4 First aid measures

4.1 Description of first aid measures:

In all cases of doubt, or when symptoms persist, seek medical attention.

4.1.1 In case of inhalation:

Get medical aid immediately. Remove from exposure to fresh air immediately.

4.1.2 In case of skin contact:

Wash off with soap and water. If skin irritation persists: Get medical advice/attention.

4.1.3 In case of eyes contact:

Rinse cautiously with water for several minutes as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

4.1.4 In case of ingestion:

Drink plenty of water. Do not induce vomiting. Consult a physician if necessary.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

If skin irritation or rash occurs, get medical advice/attention.

5 Fire-Fighting measures

5.1 Extinguishing media:

Suitable extinguishing media: Use Water, water spray, dry powder, foam, carbon dioxide (CO2).

Unsuitable extinguishing media: Not available.

5.2 Special hazards arising from the substance or mixture

Carbon oxides.

5.3 Advice for fire-fighters:

Firefighters must wear fire resistant protective equipment. Wear self contained breathing apparatus and protective gloves.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

6.1.1 For non-emergency personnel:

Remove all sources of ignition. Ventilate area of leak or spill.

6.1.2 For emergency responders:

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

Printing date:6/5/2011 Revision date: 6/5/2011

Wear appropriate personal protective equipment as specified in section 8.

6.2 Environmental Precautions:

Prevent further leakage or spillage if safe to do so. No special environmental precautions required.

6.3 Methods for Containment and Cleaning up:

Pick up and transfer to properly labelled containers. After cleaning, flush away traces with water.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

6.5 Additional information:

Hold for waste disposal.

Ventilate area and wash spill site after material pickup is complete.

7 Handling and storage

7.1 Precautions for safe handling:

7.1.1 Protective measures:

No technical protective measures are required. Take precautionary measures against static discharges.

7.1.2 Advice on general occupational hygiene:

Do not eat, drink and smoke in work areas. Wash hands after use.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions: Keep tightly closed in a dry and cool place.

Incompatible products: Strong oxidizing agents, strong bases.

Packaging material: Polyethylene coated paper bags, Polyvinyl or Polyethylene/propylene big bags

7.3 Specific end use(s):

Not applicable.

8 Exposure control/personal protection

8.1 Control parameters:

- 8.1.1 Occupational exposure limits: Not listed.
- 8.1.2 Additional exposure limits under the conditions of use: Not available.
- 8.1.3 DNEL/DMEL and PNEC-Values: Not available.

8.2 Exposure controls

8.2.1 Appropriate engineering controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

8.2.2 Individual protection measures, such as personal protective equipment:

Eye/face protection Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's

eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Hand protection Wear appropriate protective rubber gloves to prevent skin exposure.

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

Printing date:6/5/2011 Revision date: 6/5/2011

Body protection Wear protective gloves and clean body-covering clothing.

Respiratory protection A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2

requirements or European Standard EN 149 must be followed whenever workplace conditions

warrant respirator use.

Thermal hazards Wear suitable protective clothing to prevent heat.

8.2.3 Environmental exposure controls:

Handling according to local regulations, Federal and official regulations.

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Crystalline
Colour: White
Odour: Odorless
Odour threshold: Not available
pH: 1.8(25°C)

Melting point/range (°C): 426 K at 101 325 Pa

Boiling point/range (°C):

Flash point (°C):

State 101.3 kPa

Evaporation rate:

Not applicable

Flammability (solid, gas);

Ignition temperature (°C):

Upper/lower flammability/explosive limits:

Not determined

Vapour pressure (20°C): 2.21 x 10⁻⁶ Pa at 25°C

Vapour density: Not applicable Relative Density (25°C): 1.665 at 20°C. Bulk density (kg/m³): Not determined Water solubility (g/l) at 20°C: 592 g/l at 20°C n-Octanol/Water (log Po/w): Not available Auto-ignition temperature: Not available Not available Decomposition temperature: Not available Viscosity, dynamic (mPa s): Explosive properties: Non explosive Oxidising properties: No oxidising

9.2. Other information:

Fat solubility(solvent– oil to be specified) etc:

Bulk density:

No data available

No data available

No data available

Dissociation constant in water(pKa):

No data available

No data available

No data available

10 Stability and reactivity

10.1 Reactivity:

The substance is stable under normal storage and handling conditions.

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

Printing date:6/5/2011 Revision date: 6/5/2011

10.2 Chemical stability:

Under normal conditions, the product is stable. No hazardous reaction when handled and stored according to provisions.

Hazardous reactions are not known.

10.3 Possibility of hazardous reactions:

Under normal conditions, not hazardous reactions will occur.

10.4 Conditions to avoid:

Heat, ignition sources, incompatible materials.

10.5 Incompatible materials:

Reactive with oxidizing agents, reducing agents, alkalis.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide.

11 Toxicological information

11.1 Toxicokinetics, metabolism and distribution

Non-human toxikological data

Citric acid is ubiquitous in the animal kingdom. No study which meets current OECD guidelines is available. However, sufficient information exists on the substance as it is part of the metabolic processed in animals and plants. Therefore pathways for adsorption, distribution and excretion as well as its metabolism are well established, and even essential to all living organisms. The same conclusion may be applied to the citrate salts as discussed at the beginning of chapter 5.

11.2 Information on toxicological effects

Acute toxicity:

LD50(Oral, mouse): 5400 mg/kg bw
LD50(Dermal, rat): 2000mg/kg bw
LC50(Inhalation): No data available

Skin corrosion/Irritation: Not irritating

Serious eye damage/irritation: irritating

Respiratory or skin sensitization:Not sensitisingGerm cell mutagenicity:NegativeCarcinogenicity:Not classifiedreproductive toxicity:Not classifiedSTOT- single exposure:Not classifiedSTOT-repeated exposure:Not classified

Aspiration hazard: Not classified

12 Ecological information

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

Printing date: 6/5/2011 Revision date: 6/5/2011

Toxicity:

Acute	toxicity	Time	Species	Method	Evaluation	Remarks
LC50	440mg/l	48h	Fish	OECD 203	N/A	N/A
EC50	1535mg/l	24h	Daphnia	OECD 202	N/A	N/A
EC50	425 mg/l	8d	Algae	Not available	N/A	N/A

Persistence and degradability:

Abiotic degradation Citric acid and the metal salts do not possess any functional group that is susceptible to

hydrolysis and the substance is expected to be stable in aqueous solution. In addition,

the biodegradability of the substance dominates the understanding of stability.

Biotic degradation
Available data suggest that citric acid and the metal salts are rapidly degradable in

surface water, soils and sediment. Therefore, based on available data, the substances

in this category are not expected to present a hazard to the environment.

Bioaccumulative potential: Low potential for bioaccumulation.

Mobility in soil:

Not available.

Not applicable.

Results of PBT&vPvB assessment:

The substance does not meet the criteria for PBT or vPvB.

Other adverse effects:

13 Disposal considerations

13.1 Waste treatment methods

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing use or contamination of this product may change the waste management options. According to local regulations, Federal and official regulations.

13.2 Product / Packaging disposal:

If empty container retains product residues, all label precautions must be observed. Return for reuse or dispose according to national or local regulations.

14 Transport information

	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO/IATA)	
UN-Number:	Not regulated	Not regulated	Not regulated	
UN Proper shipping name:	Not regulated		Not regulated	
Transport hazard Class:	Not regulated	Not regulated	Not regulated	
Packaging group:	Not regulated	Not regulated	Not regulated	
Environmental hazards:	Not regulated	Not regulated	Not regulated	
Special precautions for user:	See section 2.2	See section 2.2	See section 2.2	
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not regulated	Not regulated	Not regulated	

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

Printing date:6/5/2011 Revision date: 6/5/2011

15 Regulation information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant information regarding authorization: Not applicable. **Relevant information regarding restriction:** Not applicable.

Other EU regulations: Employment restrictions concerning young person must be observed. For

use only by technically qualified individuals.

Other National regulations:

Not applicable

Chemical Safety Assessment has been carried out? YES X NO

16 Other information

16.1 Indication of changes Version 1.1 Amended by EU No 453/2010

Version 2.0 Placed exposure scenarios in the Annex (eSDS)

16.2 Relevant R- phrases (number and full text):

R36 Irritating to eyes.

16.3 Training instructions:

Not applicable.

16.4 Further information:

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

16.5 Notice to reader:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgment of suitability of this information to ensure proper use and protect the health and safety of employees.

This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Printing date:6/5/2011 Revision date: 6/5/2011 Version 2.0

Annex to extended safety data sheet (eSDS) Exposure scenario

	Exposure section to						
	Substance / User identity						
	Registration number(s)	01-2119457026-42-0004					
	Substance identity	CAS#77-92-9; EC#201-06	9-1				
1	Short title of the exposure scenario	1. Production of citric acid	I				
	Processes and activities covered by	PROC 1, PROC 2, PROC	3, PROC 4, P	ROC 8b,			
	the exposure scenario	SU 3,SU 8,					
2	Operational conditions and risk manage	ment measures					
	Duration an frequency of use						
	Worker						
	All applicable PROCs	>4h					
	Physical form of substance:	Solid.					
	Concentration of substance in preparation or article	90%					
	Other relevant operational conditions	No measured data are ava	ilable for relea	ases of citric acid to air and waste water for			
	of use	the generic production site	. Releases are	e therefore estimated on the basis of other			
		information.					
		Releases to air:					
		Due to the very low vapour	pressure of the	he key intermediates and of citric acid			
		itself, losses to air are cons	sidered to be 2	zero.			
		Releases to waste water:					
		The key production stage is	s the precipita	tion of calcium citrate. This substance is of			
		low solubility, although a sr	mall quantity o	of citric acid could remain dissolved, a			
		fraction of 0.0001, or 2.86	kg/d over 350	days.			
		There could be losses duri	ng handling a	nd packaging processes, but when around			
		30 tonnes per day are han-	dled these pro	cesses are highly automated. It can be			
		anticipated that occasional	spillages can	occur due to small levels of leakage,			
		amounting to at most 1 kg	per day passi	ng to aqueous waste.			
		The total passing to aqueo	us waste wate	er is 3.86 kg/d.			
	Risk management measures:						
2.1	Control of worker exposure						
	Operational conditions related to respiration and skin contact	Information type	Data field	Explanation			
		Respiration volume	10 m ³ /d	Default for workers, light activity			
		under conditions of use					
		Area of skin contact		ECETOC TRA default:			
		with the substance	2				
		under conditions of use	240 cm^2	PROC 1: palm of one hand			
			_				
			480 cm^2	PROC 2: palms of both hands			

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	D. I I.	240 cm ² 480 cm ² 480 cm ²	PROC 3: palm of one hand PROC4: palms of both hands PROC8b: palms of both hands	
	Body weight	70 kg	Default	
Technical fate of substance and losses from process/use to waste, waste water and air			Explanation See text	
	amount lost f	lied 0.0001 rom kg/kg	See text	
Engineering controls:				
Personal protective equipment (PPE)	Information type	Data field	Explanation	
	Containment plus good work practice required	Yes		
	Local exhaust ventilation required plus good work practise	Yes	Typical practice of chemical industry. Not applicable for PROC1.	
	Skin protection	Protective gloves		
	Eye protection	Safety glasses		
	Respiratory protection	Dust mask. In case of open handling of large quantities of accidental release particle mask of respirator with independent air supply	n r r :	
	Clothing	Working clothing worn.		

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

Risk management measures related to	Information type	Data field	Explanation	
environmental emissions from industrial sites	Onsite pre-treatment of waste water	Yes	Neutralisation	
	Resulting fraction of initially applied amount in waste water released from site to the external sewage system		On-site biological waste treatment is expected to remove a high proportion of citric acid, as the substance is highly biodegradable.	
	Air emission abatement	No measured data		
	Resulting fraction of applied amount in waste gas released to environment	No measured data		
	Onsite waste treatment	No measured data	Secondary biological treatment	
	Fraction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment.	No measured data		
	Municipal or other type of external waste water treatment	None	None	
	Effluent (of the waste water treatment plant) discharge rate	1 x 10 ⁷ l/d	Default for a large industrial site	
	Recovery of sludge for agriculture or horticulture	Yes	Dried sludge may be sold as an approved agricultural fertiliser	
Frequency and duration of use				_

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Revision date. 0/3/2011							
		Information	on type		Data field		Explanation	
		Used amou	nt of substance pe	r day	30 tonnes			
			of exposure per [for one worker]	day at	>4 hours (all	PROCs)	REACH default used exposure times	as a w
		Frequency [for one wo	of exposure at worker]	orkplace	Once per day	7		
		Annual am	ount used per site		10,000 tonne	·S		
	Use per site Duration of emission Waste water flow Dilution factor	Emission d	ays per site		350			
	Information on estimated exposure and D	ownstream-u	ser guidance					
3	Exposure estimation and reference to its	source:						
	Dermal exposure estimates (based on ECETOC TRA model)	Process category	Description	LEV present?	Predicte d exposure (µg/cm²/ day)	Exposed skin surface area (cm ²)	exposure	
		PROC1	Use in closed process, no likelihood of exposure	Nob	100	240	0.3	
		PROC2	Use in closed, continuous process with occasional controlled exposure (e.g. sampling)	Yes	20	480	0.14	
		PROC3	Use in closed batch process (synthesis or formulation)	Yes	10	240	0.03	
		PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises	Yes	100	480	0.69	
		PROC8b	Transfer from/to large vessels	Yes	100	480	0.69	

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155 Version 2.0

			(dedicated)				
		,	ulated assuming a e ECETOC TRA			Ū	
	Inhalation exposure estimates (based on ECETOC TRA model)	Process category	Description	LEV present?	Predicte d exposure (ppm)	Predicte d exposure (mg/m³) ^c	Inhalatio n exposure (mg/kg/da y) ^d
	PROC1	Use in closed process, no likelihood of exposure	No ^b	0.001	0.01	0.001	
		PROC2	Use in closed, continuous process with occasional controlled exposure (e.g. sampling)	Yes	0.01	0.1	0.01
		PROC3	Use in closed batch process (synthesis or formulation)	Yes	0.01	0.1	0.01
	PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises	Yes	0.31	2.5	0.36	
		PROC8b	Transfer from/to large vessels(dedica ted)	Yes	0.16	1.25	0.18
		c) Results are d) Calculated	TOC TRA model calculated as mg assuming a defau plume of 10 m3, li	/m3 for solic alt bodyweig	ls and ppm fo ht of 70 kg f	or non-solids or workers a	3

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155 Version 2.0

	Summary of long-term exposure concentration to workers	Routes of exposure	Concentrations	Justification		
	Concentration to Workers	Dermal local exposure (in µg/cm2)	0.6	ECETOC TRA prediction for PROC8b, multiplied by an uptake factor of 0.006.		
		Dermal systemic exposure (in mg/kg bw/d)	0.004	ECETOC TRA prediction for PROC8b, multiplied by an uptake factor of 0.006.		
		Inhalation exposure (in mg/m3)/8h workday	2.5	ECETOC TRA prediction for PROC8b		
		Inhalation exposure (in mg/kg/d)/8h workday	0.36	ECETOC TRA prediction for PROC8b		
4	Environmental releases	-L				
	Predicted environmental release	Predicted environmental release estimates have been used for releases during production. I measured data are available for the concentration of citric acid in any environment compartment. The releases have been estimated using the exposure scenario for producti (section 9.1.1.2 and 9.1.1.6) and Predicted Environmental Concentrations have be determined using EUSES 2.1.1. The EUSES program implements the environment exposure models described in REACH Technical Guidance Chapter R16. Default more parameters have been used unless stated below. The basis of local and regional production tonnages is to consider the sizes of the largest sit in the EU relative to the total tonnage as follows: Production volume in EU: 100 000 tonnes Regional tonnage: 10 000 tonnes Fraction of main local source: 1 Local tonnage: 29 tonnes per day Number of days: 350 The contribution of local releases to the regional concentration has been considered using the same and the s				
	Summary of Predicted Exposure Concentrations	AIR Annual average local PEC in air (total) WATER, SEDIMENT Local PEC in surface water during emission episode (dissolved) Annual average local PEC in surface water (dissolved) Local PEC in fresh-water sediment during emission episode	9.0153 0.0153 0.261	[mg m ⁻³] [mg l ⁻¹] [mg kg wwt ⁻¹]		

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155 Version 2.0

Local PEC in seawater during emission episode (dissolved)	1.80 x 10 ⁻³	[mg l ⁻¹]
Annual average local PEC in seawater (dissolved)	1.78 x 10 ⁻³	[mg l ⁻¹]
Local PEC in marine sediment during emission episode	0.0307	[mg kg wwt ⁻¹]
SOIL, GROUNDWATER		
Local PEC in agric. soil (total) averaged over 30	0.000	e a sala
days	0.0227	[mg kg wwt ⁻¹]
Local PEC in agric. soil (total) averaged over 180 days	7.43 x 10 ⁻³	[mg kg wwt ⁻¹]
Local PEC in grassland (total) averaged over 180 days	2.97 x 10 ⁻³	[mg kg wwt ⁻¹]
Local PEC in pore water of agricultural soil	1.12 x 10 ⁻⁴	[mg l ⁻¹]
Local PEC in pore water of grassland	4.48 x 10 ⁻⁵	[mg l ⁻¹]
Local PEC in groundwater under agricultural soil	1.12 x 10 ⁻⁴	[mg l ⁻¹]

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Substance / User identity								
	Registration number(s)	01-2119457026-42-0004							
	Substance identity	CAS#77-92-9; EC#201-							
1	Short title of the exposure scenario	2. Use of citric acid as							
	Processes and activities covered by	SU3 (Industrial uses), S							
	the exposure scenario	,	OC 3, PROC 4, PROC 8b,						
2	Operational conditions and risk manager		,						
_	Duration an frequency of use	THORIC HIDAGGICO							
	Worker								
	All applicable PROCs	>4h							
	Physical form of substance:	solid	solid						
	Concentration of substance in								
	or preparation or article Other relevant operational conditions of use								
	Risk management measures:								
2.1	Control of worker exposure								
	Containment and local exhaust ventilation	Information type	Data field	Explanation					
	Vertulation	Containment plus good work practice required	Yes						
		Local exhaust	Yes	Typical practice of chemical					
		ventilation required		industry. Not applicable for					
		plus good work							
		practise		PROC1.					
	Personal protective equipment (PPE)	Information type	Data field	Explanation					
		Skin protection	Protective gloves						
		Eye protection	Safety glasses						
		Respiratory	Dust mask.						
		protection	In case of open						
			In case of open handling of larger						
			quantities or						
			accidental release:						
			particle mask or						
			respirator with						
			independent air supply						
		Clothing	Working clothing worn.						

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

Onsite pre-treatment of waste water Ves Neutralisation		Risk management measures related to	Information type	Data field	Explanation
of waste water Resulting fraction of initially applied amount in waste water relatment Resulting fraction of site to the external sewage system Air emission abatement Resulting fraction of applied amount in waste gas released to environment Onsite waste treatment Onsite waste treatment Fraction of initially applied amount in waste gas released to environment Onsite to the external waste treatment Fraction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste and the residues from onsite waste water and waste gas treatment. Municipal or other type of external waste water water treatment plant) discharge rate Effluent (of the waste water treatment) plant) discharge rate Recovery of sludge for agriculture or horticulture Control of environmental exposure Frequency and duration of use Intervation tree. Date field. Explanation.		environmental emissions from	Onsite mus treatment	Voc	Nontrolication
initially applied amount in waste water released from site to the external sewage system Air emission abatement Air emission applied amount in waste gas released to environment Air emission abatement Air emission		industrial sites:		ies	Neutransation
amount in waste water released from site to the external sewage system Air emission abdement Resulting fraction of applied amount in waste gas released to environment					On-site biological waste
water released from site to the external sewage system Air emission abatement Resulting fraction of applied amount in waste gas released to environment Onsite waste treatment Fraction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water usate waste verament. This is the sum of direct losses from processes to waste water and waste gas released. Municipal or other type of external waste water treatment Municipal or other type of external waste water treatment Effluent (of the waste water treatment) Effluent (of the waste water treatment) Recovery of sludge for agriculture or horticulture Frequency and duration of use Information type. Data field Explanation Frequency and duration of use					treatment is expected to
sewage system Air emission abatement Resulting fraction of applied amount in waste gas released to environment Onsite waste treatment Praction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment. Municipal or other type of external waste water treatment waste water treatment plant) discharge rate Recovery of sludge for agriculture or horticulture Praction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment. Municipal or other type of external waste water treatment plant) discharge rate Recovery of sludge for agriculture or horticulture Recovery of sludge for agriculture or horticulture Praction of initially applied amount sent to external waste water treatment and waste gas treatment. No measured data No measured data No measured data Praction of initially applied and treatment No measured data Treatment Treatment No measured data Treatment No measured data Treatment No measured data Treatment No measured data Treatment Treatment Treatment No measured data Treatment Treatment Treatment No measured data Treatment Treatment Treatment Treatment No measured data Treatment Treatment Treatment Treatment No measured data Treatment Treatment Treatment Treatment Treatment Treatment No measured data Treatment Tre			water released from		remove a high proportion of
Air emission abatement					citric acid, as the substance
Resulting fraction of applied amount in waste gas released to environment Onsite waste treatment Fraction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment. Municipal or other type of external waste water treatment Municipal or other type of external waste water treatment plant) discharge rate Recovery of sludge for agriculture or horticulture Prequency and duration of use Information type. Pate field No measured data Secondary biological treatment No measured data No measured data Population No measured data Population Secondary biological treatment Preatment Default for a large industrial site Default for a large industrial site Dried sludge may be sold as an approved agricultural fertiliser					is highly biodegradable.
applied amount in waste gas released to environment Onsite waste treatment No measured data Fraction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment. Municipal or other type of external waste water treatment waste water treatment. Municipal or other type of external waste water treatment waste water treatment losses water water treatment. Effluent (of the waste water treatment plant) discharge rate Recovery of sludge for agriculture or horticulture 2.2 Control of environmental exposure Frequency and duration of use Information type Date field Explanation Information typ				No measured data	
treatment No measured data treatment Fraction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment. Municipal or other type of external waste water treatment (of the waste water treatment plant) discharge rate treatment plant) discharge rate Recovery of sludge for agriculture or horticulture President of the processor of the plant of the waste water treatment pl			applied amount in waste gas released to	No measured data	
applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment. Municipal or other type of external waste water treatment waste water treatment waste water treatment plant) discharge rate Recovery of sludge for agriculture or horticulture Effluent (of the waste water treatment plant) discharge rate and plant waste water treatment plant) discharge rate reatment plant) discharge rate reatment. None Default for a large industrial site provided as an approved agricultural fertiliser 2.2 Control of environmental exposure Frequency and duration of use				No measured data	
type of external waste water treatment None None Effluent (of the waste water treatment plant) discharge rate Recovery of sludge for agriculture or horticulture Yes Control of environmental exposure Frequency and duration of use Information type Dota field Fxplanation Fxplanation Fxplanation Fxplanation Fxplanation			applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and	No measured data	
waste water treatment plant) discharge rate			type of external waste water	None	None
for agriculture or horticulture Yes Control of environmental exposure Frequency and duration of use Information type Data field Explanation Explanation			waste water treatment plant)	1x 10 ⁷ l/d	
Frequency and duration of use Information type Data field Evaluation			for agriculture or	Yes	as an approved agricultural
Information type Data field Evaluation	2.2	Control of environmental exposure		.	
Duration, frequency and amount Information type Data field Explanation		Frequency and duration of use	_		
		Duration, frequency and amount	Information type	Data field	Explanation

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155 Version 2.0

110110111111111111111111111111111111111					
	Used amount of substance per day	10,000 kg/d	Generic information		
	Duration of exposure	>4 hours (all PF	OCs) REACH default used as a		
	per day at workplace [for one worker]		worst case; actually		
	[ror one worker]		exposure times may be		
			significantly less		
	Frequency of	Once per day	In situations where the		
	exposure at workplace [for one		duration of exposure is lower,		
	worker]		frequency of exposure may		
			be higher		
	Annual amount used per site	3,000 tpa	Generic information		
	Emission days per	300 d/y	REACH default number of		
	site		days for high volumes		
Other operational conditions of use					
Releases to air	Due to the very low va itself, losses to air are co		the key intermediates and of citric acid ero.		
Releases to water	The REACH ERC 6A (I waste water is 2%.	ndustrial use of i	ntermediate) release default estimates to		
Technical conditions and measures at process level (source) to prevent release	No specific measures ar	e considered			
Technical onsite conditions and measures to reduce or limit discharges, air emissions	intermediate is 0.7% by process. Processing of	weight for a we citric acid is a we	elease rate from processing of synthetic t process and 0% for a dry (water-free) t-process. On-site waste water treatment bitation and so on) is already included in		
	citric acid is not conside	red to be realistic	6 default) from the processing of 30 t/d of . Realistic losses to waste water from the rial site are expected to come from:		
	 Substance washout from ventilation systems Minor routine spillages Occasional equipment loss/leakages Given that a solid is precipitated efficiently it is considered that 7 kg/d is a more realistic estimate. 				
	Given that a solid is pre		tly it is considered that 7 kg/d is a more		
	Given that a solid is pro- realistic estimate. Citric acid is highly deg	ecipitated efficien	ite waste water treatment is expected to ed to the wider environment.		
	Given that a solid is pre realistic estimate. Citric acid is highly deg mean that little of the su It can be assumed that the	ecipitated efficien radable and on-s bstance is release his process will be	ite waste water treatment is expected to		
Technical fate of substance and losses	Given that a solid is pre realistic estimate. Citric acid is highly deg mean that little of the su It can be assumed that the wastern waster passing	ecipitated efficien radable and on-s bstance is release his process will be to a larger-than	ite waste water treatment is expected to ed to the wider environment.		

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	water and air Information on estimated exposure and I	Fraction of amount lo process/use gas Fraction of amount lo process/use water	f applied ost from to waste) kg/kg).007 kg/kg	See to				
3	Exposure estimation and reference to its		garaaria e						
	Dermal	Process	Description		Derm	Predicted	Exposed	Dermal	
		category			al expos	exposure (µg/cm²/d	skin surface	exposure	
					ure?	ay)	area (cm²)	(mg/kg/ day) ^a	
		PROC1	Use in clos process, no likelihood of exposure	1	Yes	100	240	0.3	
		PROC2	Use in clos continuous with occasi controlled o	process	Yes	20	480	0.14	
		PROC3	Use in clos process (sy formulation	nthesis or	Yes	10	240	0.03	
		PROC4	Use in batcother proces (synthesis) opportunity exposure as	where for	Yes	100	480	0.69	
		PROC8b	Transfer fro large vesse (dedicated)	ls	Yes	100	480	0.69	
		a) Calculated b) In the ECE	_	•	_	•		DC1.	

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155 Version 2.0

Inhalation	Process	Description		LEV	Predicte	ed Predicted	Inhalation
	category			prese	exposui		Exposure
				nt?	(ppm)	(mg/m ³) ^c	(mg/kg/
							day) ^d
	PROC1	Use in close	ed	No ^b	0.001	0.01	0.001
		process, no					
		likelihood o	f				
		exposure					
	PROC2	Use in close		Yes	0.01	0.1	0.01
		continuous	_				
		with occasion					
	PROC3	Use in close		Yes	0.01	0.1	0.01
	PROCS	process (syr		168	0.01	0.1	0.01
		formulation					
	PROC4	Use in batch	,	Yes	0.31	2.5	0.36
		other proces			0.51	2.3	0.50
		(synthesis)					
		opportunity	for				
		exposure ar	ises				
	PROC8b	Transfer fro		Yes	0.16	1.25	0.18
		large vessel	S				
		(dedicated)					
						relevant for PRO	DC1.
		e calculated as	-				
	d) Calculated	l assuming a	default boo	lyweight	of 70 kg	for workers an	d a default
		olume of 10 m					
long-term exposure concentration to	Routes of e	exposure	Cone	centratio		Justification ECETOC	TRA
workers		_				prediction for 1	
	Dermal loca	-	0.6			multiplied by a	
	(in µg/cm2)					factor of 0.006.	
						ECETOC	TDA
	Dermal syst	temic				prediction for 1	TRA PROC8b
	exposure		0.004			multiplied by a	
	(in mg/kg b	w/d)				factor of 0.006.	
						EGETO G	TTD 4
	Inhalation e	exposure	2.5			ECETOC prediction for F	TRA
	(in mg/m3)/	/8h workday				prediction for F	KOC80
	Inhalation e	xposure	0.26			ECETOC	TRA
	(in mg/kg/d)/8h	0.36			prediction for F	ROC8b
	workday						

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155 Version 2.0

Predicted Environmental		PEC	unit				
Concentrations	AIR						
	Annual average local PEC in air (total)	5.45 x 10 ⁻¹⁶	[mg m ⁻³]				
	WATER, SEDIMENT	WATER, SEDIMENT					
	Local PEC in surface water during emission episode (dissolved)	0.0154	[mg l ⁻¹]				
	Annual average local PEC in surface water (dissolved)	0.0154	[mg l ⁻¹]				
	Local PEC in fresh-water sediment during emission episode	0.263	[mg kg wwt ⁻¹]				
	Local PEC in seawater during emission episode (dissolved)	0.0084	[mg l ⁻¹]				
	Annual average local PEC in seawater (dissolved)	0.00716	[mg l ⁻¹]				
	Local PEC in marine sediment during emission episode	0.144	[mg kg wwt ⁻¹]				
	SOIL, GROUNDWATER						
	Local PEC in agric. soil (total) averaged over 30 days	0.0411	[mg kg wwt ⁻¹]				
	Local PEC in agric. soil (total) averaged over 180 days	0.0135	[mg kg wwt ⁻¹]				
	Local PEC in grassland (total) averaged over 180 days	0.00539	[mg kg wwt ⁻¹]				
	Local PEC in pore water of agricultural soil	0.000203	[mg l ⁻¹]				
	Local PEC in pore water of grassland	0.0000813	[mg l ⁻¹]				
	Local PEC in groundwater under agricultural soil	0.000203	[mg l ⁻¹]				

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Substance / User identity						
	Registration number(s)	01-2119457026-42-0004					
	Substance identity	CAS#77-92-9; EC#201-069) -1				
1	Short title of the exposure scenario	3. Formulation of citric acid	d into preparations				
	Processes and activities covered by the exposure scenario	SU3, 10, SU5, SU13, 20 PROC2, PROC3, PROC4 PROC13, PROC14, PRO	, PROC5, PROC7, PROC8 C15, PROC19	a, PROC8b, PROC9,			
2	Operational conditions and risk manager						
	Duration an frequency of use						
	Worker						
	All applicable PROCs	>4h					
	Physical form of substance:	solid					
	Concentration of substance in preparation or article						
	Other relevant operational conditions of use	The citrates used in the formulation of products are generally solids which may be mixed with other solids or dissolved in aqueous solution. There is some potential for airborne release of citric acid (or citrate) particulates on charging (transfer dosing) to the process equipment used, especially if containment is not good However, the most likely release will be to waste water via clean out or spillage. Taking the HERA figure of approx. 100 000 tpa [HERA, 2005] for total use of citrates in detergents, and realistic values of 10% formulated in a single region, and 60% of that at a single location, gives a volume of 6,000 tpa citrates formulated at a single location. For this generic site, the daily loss rate to waste water is 6000 t x 1000 kg/t x 0.0009 / 300 d = 18 kg/d. The tonnage to be covered is now 150 000 tpa, but the site size is retained. The loss rate is considered to be a reasonable worst case for a large site. At smalle formulation sites the amount handled per day would be lower and the controls could be less, but overall rates per day would be similar.					
	Risk management measures:						
2.1	Control of worker exposure						
	Containment and local exhaust	Information type	Data field	Explanation			
	ventilation	Containment plus good work practice required	Yes	General good hygiene and housekeeping			
		Local exhaust ventilation required plus good work practice.	Yes	Typical practice of chemical industry.			
	Personal protective equipment (PPE)	Information type	Data field	Explanation			
		Skin protection	Protective gloves				
		Eye protection Safety glasses Clothing Working clothing worn.					
	Risk management measures related to	Information type	Data field	Explanation			
	environmental emissions from	Onsite pre-treatment of	Yes	Removal of solids in			
	industrial sites:	waste water		settling tanks			
		Resulting fraction of	No measured data				
		initially applied amount	mododiod data				
		I miliany applied amount					

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155 Version 2.0

		in waste water released		
		from site to the external		
		sewage system		
			No measured data	
		Air emission abatement		
		Resulting fraction of	No measured data	See text
		applied amount in waste		
		gas released to		
		environment		
		Onsite waste treatment	No	Worst-case assumption
				as no specific
				information available.
		Fraction of initially	No measured data	
		applied amount sent to		
		external waste		
		treatment. This is the		
		sum of direct losses		
		from processes to		
		waste, and the residues		
		from onsite waste water		
		and waste gas		
		treatment.		
		Municipal or other type	Yes	Typical practise in the
		-	100	chemical industry
		of external waste water		
		treatment	$1 * 10^7 \text{ L/d}$	Default for a large
		Effluent (of the waste	1 * 10 L/u	industrial site.
		water treatment plant)		
		discharge rate		100
		Recovery of sludge for	Yes	Worst-case assumption as no specific
		agriculture or		information available.
		horticulture		intermation available.
2.2	Control of environmental exposure			
	Frequency and duration of use			
	Duration, frequency and amount	Information type	Data field	Explanation
		Used amount of	6000 tonnes	
		substance per day		
		Duration of exposure per	>4 hours (all PROCs)	For some
		day at workplace [for		applications/setting
		one worker]		exposure times may be
				significantly less
		Frequency of exposure	Once per day	For some
		at workplace [for one	Choo por day	applications/settings
		worker]		with shorter duration
		WOLKEL		exposures, multiple
				exposures may occur in

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155 Version 2.0

T	Revision date: 6/5/2011			1		-	-	1
						a sin	igle day	
		Annual amo	ount used per	20 tonnes				
		Emission da	ave nor sito	300 days				
				ooo days				
	Information on estimated exposure and D		ser guidance					
3	Exposure estimation and reference to its	source:						
	Occupational exposure:	_	1		1			
	Dermal	Process	Description		Dermal	Predict	Expose	Dermal
		category			exposu re?	ed exposu	d skin surface	exposure
						re (µg/cm² /day)	area (cm²)	(mg/kg/ day) ^a
		PROC1	Use in close no likelihood exposure	d process, I of	Yes	100	240	0.3
		PROC2	Use in close continuous with occasio controlled ex (e.g. samplin	process nal kposure	Yes	20	480	0.14
		PROC3	Use in close process (syr formulation)	nthesis or	Yes	10	240	0.034
		PROC4	Use in batch process (syr where oppo- exposure ar	nthesis) rtunity for	Yes	100	480	0.69
		PROC5	Mixing or ble batch proces (multistage a significant co	sses and/or	Yes	200	480	1.37
		PROC7	Industrial sp	raying	Yes	200	1500	4.29
		PROC8a	Transfer from vessels (non-dedical		Yes	100	960	1.37
		PROC8b	Transfer from vessels (dec		Yes	100	480	0.69
		PROC9	Transfer to s containers	small	Yes	100	480	0.69
		PROC13	Treatment o		Yes	100	480	0.69

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

PROC14	<u>:</u>	101101011 010101 07072011						
PROC19			PROC14	preparations or articles by tabletting, compression,	Yes	50	480	0.34
Inhalation			PROC15	reagents in small scale	Yes	10	240	0.034
PROC1 Use in closed process, no likelihood of exposure			PROC19	intimate contact (only	Yes	500	1980	14.1
PROC1 Use in closed process, no likelihood of exposure PROC2 Use in closed, continuous process with occasional controlled exposure (e.g. sampling) PROC3 Use in closed batch process (synthesis or formulation) PROC4 Use in batch and other process (synthesis) where opportunity for exposure arises PROC5 Mixing or blending in batch processes (multistage and/or significant contact) PROC7 Industrial spraying Yes 1.25 10 1.43 PROC8a Transfer from/to large vessels (non-dedicated) PROC8b Transfer from/to large vessels (dedicated) Yes 0.31 2.5 0.36 0.014 0.014 0.014 0.014 0.014 0.014 0.014 0.014 0.015 0.1 0.014 0.014 0.014 0.015 0.1 0.014 0.014 0.015 0.1 0.014 0.014 0.015 0.1 0.014 0.014 0.015 0.1 0.014 0.014 0.015 0.1 0.014 0.014 0.015 0.1 0.014 0.014 0.015 0.1 0.014 0.014 0.015 0.1 0.014 0.014 0.014 0.015 0.1 0.014 0.014 0.014 0.015 0.1 0.014 0.014	Inha	ılation		Description	present	ed exposu re	ed exposu re (mg/m ³	on Exposu re (mg/kg/
continuous process with occasional controlled exposure (e.g. sampling) PROC3 Use in closed batch process (synthesis or formulation) PROC4 Use in batch and other process (synthesis) where opportunity for exposure arises PROC5 Mixing or blending in batch processes (multistage and/or significant contact) PROC7 Industrial spraying Yes 1.25 10 1.43 PROC8a Transfer from/to large vessels (non-dedicated) PROC8b Transfer from/to large vessels (dedicated) Yes 0.31 2.5 0.36 0.36 0.31 0.36 0.36 0.36 0.36 0.36 0.36 0.36 0.36			PROC1	no likelihood of	No ^b	0.0013	0.01	0.0014
process (synthesis or formulation) PROC4 Use in batch and other process (synthesis) where opportunity for exposure arises PROC5 Mixing or blending in batch processes (multistage and/or significant contact) PROC7 Industrial spraying PROC8a Transfer from/to large vessels (non-dedicated) PROC8b Transfer from/to large vessels (dedicated) Transfer from/to large vessels (dedicated) PROC8b Transfer from/to large vessels (dedicated) PROC8c Drace Yes O.31 2.5 O.36 O.36 O.31 D.36 O.36 O.31 D.36 O.36 O.36 O.36 O.36 O.36 O.36			PROC2	continuous process with occasional controlled exposure	Yes	0.0125	0.1	0.014
process (synthesis) where opportunity for exposure arises PROC5 Mixing or blending in batch processes (multistage and/or significant contact) PROC7 Industrial spraying Yes 1.25 10 1.43 PROC8a Transfer from/to large vessels (non-dedicated) PROC8b Transfer from/to large vessels (dedicated) Yes 0.31 2.5 0.36 O.71			PROC3	process (synthesis or	Yes	0.0125	0.1	0.014
batch processes (multistage and/or significant contact) PROC7 Industrial spraying Yes 1.25 10 1.43 PROC8a Transfer from/to large vessels (non-dedicated) PROC8b Transfer from/to large vessels (dedicated) Yes 0.63 5 0.71 PROC8b Transfer from/to large vessels (dedicated)			PROC4	process (synthesis) where opportunity for	Yes	0.31	2.5	0.36
PROC8a Transfer from/to large vessels (non-dedicated) PROC8b Transfer from/to large vessels (dedicated) Yes 0.63 5 0.71 PROC8b Transfer from/to large vessels (dedicated)			PROC5	batch processes (multistage and/or	Yes	0.31	2.5	0.36
vessels (non-dedicated) PROC8b Transfer from/to large vessels (dedicated) Yes 0.31 2.5 0.36			PROC7	Industrial spraying	Yes	1.25	10	1.43
vessels (dedicated)			PROC8a		Yes	0.63	5	0.71
PROC9 Transfer to small Yes 0.25 2 0.29			PROC8b	vessels (dedicated)	Yes	0.31	2.5	0.36
			PROC9	Transfer to small	Yes	0.25	2	0.29

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

		containers						
	PROC13	Treatment of by dipping a		Yes	0.	0013	0.01	0.0014
	preparations or articles by tabletting, compression, extrusion, pelletisation		Yes	0.	13	1	0.14	
			Yes	0.9	063	0.5	0.071	
	PROC19	PROC19 Hand-mixing with intimate contact (only PPE available		Yes	0.	0063	0.05	0.0071
	b) Results are calculated as mg/m3 for solic) Calculated assuming a default bodywerespiratory volume of 10 m3, light activity, for		weigh y, for a	t of 70 k an 8 hou	g for v r work	workers ar	nd a default	
long-term exposure concentration to workers	Dermal loca (in µg/cm2)	al exposure	3 ECET PROC		PROC1	TOC TRA prediction for C19, multiplied by an uptake of 0.006.		
	Dermal systemic exposure (in mg/kg bw/d)		0.08 PRC facto		PROC1	CETOC TRA prediction for ROC19, multiplied by an uptake actor of 0.006.		an uptake
	Inhalation e mg/m3)/8h				ECETO PROC7			ction for
	Inhalation e mg/kg/d)/8h		1.43 ECETO PROC7		OC TRA prediction for		ction for	
Predicted Exposure Concentrations			PEC			unit		
(PEC)	AIR							
	Annual average local PEC in air (total)		1.4 x 10 ⁻¹⁵			[mg.m ⁻³]		
		SEDIMENT						
	Local PEC in surface water during emission episode (dissolved) Annual average local PEC in surface water (dissolved)		0.0158			[mg 1 ⁻¹]		
			0.0157			[mg	l ⁻¹]	
	fresh-water	PEC in sediment sion episode	0.27			[mg	kg wwt ⁻¹]	

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155 Version 2.0

Local PEC in seawater during emission episode (dissolved)	0.0194	[mg l ⁻¹]
Annual average local PEC in seawater (dissolved)	0.0162	[mg l ⁻¹]
Local PEC in marine sediment during emission episode	0.331	[mg kg wwt ⁻¹]
SOIL, GROUNDWATE	R	
Local PEC in agric. soil (total) averaged over 30 days	0.106	[mg kg wwt ⁻¹]
Local PEC in agric. soil (total) averaged over 180 days	0.347	[mg kg wwt ⁻¹]
Local PEC in grassland (total) averaged over 180 days	0.0139	[mg kg wwt ⁻¹]
Local PEC in pore water of agricultural soil	5.23 x 10 ⁻⁴	[mg l ⁻¹]
Local PEC in pore water of grassland	2.09 x 10 ⁻⁴	[mg l ⁻¹]
Local PEC in groundwater under agricultural soil	5.23 x 10 ⁻⁴	[mg I ⁻¹]

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Substance / User identity	
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	4. Personal care use
	Processes and activities covered by	SU20,SU21,SU22,
	the exposure scenario	PROC 10, PROC 11, PROC 19
2	Operational conditions and risk manage	
	Duration an frequency of use	
	Worker	
	All applicable PROCs	>4h
	Physical form of substance: under	solid
	conditions of use it is used as a liquid.	
	Concentration of substance in preparation or article	
	Other relevant operational conditions of use	The EU TGD A-Table A4.1 gives the releases of cosmetics to air and wastewater as 0 and 100% respectively. This seems reasonable, given that citrates are non-volatile and highly water soluble. It is also in agreement with Colipa's assessment of the fate of non-volatile components of cosmetics (Colipa 2008).
		The TGD defaults and REACH environmental release category (ERC8a) assume that if a substance is used widely across the EU, the fraction of the production volume used in the standard EU Region is 10%. For cosmetics, the fraction of the main local source (fmainsource) is 0.0005 (HERA, 2005, page 27). This is equivalent to saying that use in a region is evenly distributed. The number of days of use is 365 per year. Therefore, for 7500 tpa of citric acid in personal care products used widely across the EU, the estimated release of citric acid to a particular default-sized local waste water treatment plant is at most:
		7 500 000 kg/y x 0.1 x 0.0005 / 365 d/y = 1.03 kg/d
	Risk management measures:	
2.1	Control of worker exposure	
	Technical conditions and measures at process level (source) to prevent release	No risk management measures are possible for personal care use in respect of the environment.
	Technical conditions and measures to control dispersion from source towards the worker	No risk management measures are possible for personal care use in respect of the environment.
	Engineering controls:	No risk management measures are possible for personal care use in respect of the environment.
	Organisational measures to prevent/limit releases, dispersion and	No risk management measures are possible for personal care use in respect of the environment.
	exposure Conditions and measures related to personal protection, hygiene and health evaluation	No risk management measures are possible for personal care use in respect of the environment.
	Information on estimated exposure and	Downstream-user guidance
3	Environmental releases	Predicted Environmental Concentrations have been determined using EUSES 2.1.1. The EUSES program implements the environmental exposure models described in REACH Technical Guidance Chapter R16. Default model parameters

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155 Version 2.0

			largest sites in the EU relati Production volume in EU: 7 Regional tonnage: 750,000 Fraction of main local source Local tonnage: 1.03 tonnes Number of days: 365 The contribution of local considered using the approper Predicted Environmental Co- acid it has not been consider	onal production tonnages in the total tonnage as 1,500,000 tonnes	al concentration has been S 2.1.1. Table 9.33 shows the eady-biodegradability of citric a PEC. The low log Kow and s not a concern for citric acid.
Summary of	Predicted	Exposure		PEC	unit
Concentrations		•		-	
			AIR	Г	
			Annual average local	5.45 x 10 ⁻¹⁶	[mg.m ⁻³]
			PEC in air (total) WATER, SEDIMENT		
			Local PEC in surface		
			water during emission	2	. 1
			episode (dissolved)	1.59 x 10 ⁻²	[mg l ⁻¹]
			Annual average local		
			PEC in surface water	1.59 x 10 ⁻²	[mg l ⁻¹]
			(dissolved) Local PEC in fresh-water		
			sediment during		
			emission episode	2.71 x 10 ⁻¹	[mg kg wwt ⁻¹]
			Local PEC in seawater		
			during emission episode	1.48 x 10 ⁻³	[mg l ⁻¹]
			(dissolved)	1.70 A 10	[mg i]
			Annual average local		
			PEC in seawater (dissolved)	1.48 x 10 ⁻³	[mg l ⁻¹]
			Local PEC in marine		
			sediment during		1_
			emission episode	2.53 x 10 ⁻²	[mg kg wwt ⁻¹]
			SOIL, GROUNDWATE	R	
			Local PEC in agric. soil		
			(total) averaged over 30	3.02 x 10 ⁻²	[mg kg wwt ⁻¹]
			days Local PEC in agric. soil		
			(total) averaged over	9.89 x 10 ⁻³	[mg kg wwt ⁻¹]

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155 Version 2.0

	180 days		
	Local PEC in grassland		
	(total) averaged over	3.95 x 10 ⁻³	[mg kg wwt ⁻¹]
	180 days	3.93 X 10	[Ilig Kg wwt]
	Local PEC in pore water	1.49 x 10 ⁻⁴	[mg l ⁻¹]
	of agricultural soil	1.49 X 10	[IIIg I]
	Local PEC in pore water	5.97 x 10 ⁻⁵	[mg l ⁻¹]
	of grassland	3.77 X 10	[IIIg I]
	Local PEC in		
	groundwater under	1.49 x 10 ⁻⁴	[mg l ⁻¹]
	agricultural soil		
Other environmental releases	fate of a substance in the ST properties. For citric acid, Sir 12.6 % to water: 0.112 % to air: 0.0154 % to sludge: 87.3 % degraded. Sludge from WWTPs may be The dilution factor of 900 an fresh water and marine wate hydrodynamic conditions. There is no direct release biosludge from on-site wast	TP, based on the physic impleTreat predicts the formal e spread on agricultural and 1000 (in the receiving er respectively, as there to the terrestrial complete water treatment is due of municipal WWTP I	soil. water) have been applied for is no information on specific eartment on a local scale as isposed of via incineration or by some EU production sites,

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Substance / User identity			
	Registration number(s)	01-2119457026-42-0004		
	Substance identity	CAS#77-92-9; EC#201-069)-1	
1	Short title of the exposure scenario	5. Use of citric acid in clea		
•	Processes and activities covered by	SU3, SU21, SU22,	g products	
	the exposure scenario		, PROC 5, PROC 7, PROC	8a PROC 8h PROC 9
	ино охровано востано	PROC 10, PROC 11, PROC		04,11100 05,11100 0,
2	Operational conditions and risk manager			
	Duration an frequency of use			
	Worker			
	All applicable PROCs	>4h		
	Physical form of substance: under conditions of use it is used as a liquid.	May be liquid or solid.		
	Concentration of substance in preparation or article			
	Other relevant operational conditions of use	of citric acid in cleaning pro information in the public do Citric acid and citrates are aqueous solution. The mos via rinsing to drain in-use, liquors. Indeed, releases to citric acid/citrate will eventusince it does not allow for (extremely unlikely) during cleaning implement (e.g., consumer use can be estimated to release category (ERC8a). EU, the fraction of the products, the particular waste water treat the number of days of use in cleaning products used water a particular default-sized long 100,000,000 kg/y x 0.1 x 0. = (Amount of citrates used fraction in the region x fraction.)	ducts. Releases are thereformain. used in a variety of cleaning the likely release route will, the spillage, clean out or disconsus waste water can be assumulated by washed to drain. The rany of the substance to the process or to adsorb to loth) which may be landfilled use in cleaning products in mated. The TGD defaults assume that if a substance function volume used in the set fraction of the regional the theorem is 365 per year. Therefore, widely across the EU, the estical waste water treatment products of the regional than the set of the regional than the regional than the set of the regional than the regio	industrial, professional and and REACH environmental e is used widely across the standard EU Region is 10%. tonnage discharging to a ed as 0.0005 (HERA, 2005). for 100,000 tpa of citric acid timated release of citrates to lant is at most:
	Risk management measures:	LO admonties as valid.		
2.1	Control of worker exposure			
	Containment and local exhaust	Information type	Data field	Explanation
	ventilation	Containment plus good	Yes	General good hygiene
		work practice required		and housekeeping
		Local exhaust ventilation	No	
		required plus good work		
		' ' *		
		practise		

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Personal protective equipment (PPE)	Information type	Data field	Explanation
		Skin protection	Protective gloves	
		Eye protection	Safety glasses	
		Clothing	Working clothing worn.	
	Other risk management measures related to workers	N/A		
	Risk management measures related to	Information type	Data field	Explanation
	environmental emissions from industrial sites	Onsite pre-treatment of	Yes	Neutralisation
	inddothar citod	waste water		
		Resulting fraction of		On-site biological waste
		initially applied amount		treatment is expected to
		in waste water released		remove a high
		from site to the external		proportion of citric acid,
		sewage system		as the substance is
				highly biodegradable.
		Air emission abatement	No measured data	
		Resulting fraction of	No measured data	
		applied amount in waste		
		gas released to		
		environment		
		Onsite waste treatment		Secondary biological
			No measured data	treatment
		Fraction of initially		
		applied amount sent to		
		external waste		
		treatment. This is the		
		sum of direct losses		
		from processes to		
		waste, and the residues		
		from onsite waste water		
		and waste gas		
		treatment.	No measured data	
		Municipal or other type		
		of external waste water		
		treatment	None	None
		Effluent (of the waste		
		water treatment plant)	00000001/1	Default for a standard
		discharge rate	2000000 l/d	WWTP
		Recovery of sludge for		Dried sludge may be
		agriculture or	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	sold as an approved
		horticulture	Yes	agricultural fertiliser
		Onsite pre-treatment of	Yes	Neutralisation
		waste water		
2.2	Control of environmental exposure			

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

Duration, frequency and amount	Information type	Data field	Explanation
	Used amount of substance per day	200,000 kg/d	Generic information
	Duration of exposure per day at workplace [for one worker]	>4 hours (all PROCs)	For some applications/setting exposure times may be significantly less
	Frequency of exposure at workplace [for one worker]	Once per day	For some applications/settings with shorter duration exposures, multiple exposures may occur in a single day
	Annual amount used per site	10 kg/d	0.00005 (10% in region, plus 0.0005 fraction of main local source from HERA)
	Emission days per site	365 d/y	Default for ERC8
Information on estimated exposure an	d Downstream-user guidance		
Exposure estimation and reference to	-		

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

Dermal exposure estimates (based on ECETOC TRA model) for cleaning and maintenance	Process category	Description	Predicted exposure (µg/cm²/day)	Exposed skin surface area (cm²)	Dermal exposure (mg/kg/day) ^a
	PROC8a	Transfer from/to large vessels (non-dedicat	1000	960	13.7
	PROC8b	ed) Transfer from/to large vessels(dedic ated)	1000	480	6.9
	PROC9	Transfer to small containers	1000	480	6.9
	PROC7	Industrial spraying	100	1500	2.14
	PROC10	Roller application or brushing	2000	960	27.4
	PROC13	Dipping or pouring	2000	480	13.7
	(a) Calculated	assuming a defa	ult bodyweight of	70 kg for worke	rs

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Inhalation exposure estimates (based on ECETOC TRA model) for cleaning and maintenance products	Process category PROC8a	Description	on	Predicted exposure (µg/cm²/day)		osed skin ace area	Dermal exposure (mg/kg/day) ^a 0.07
		i Nocoa	from/to la vessels (non-ded ed)		0.003	0.3		0.07
		PROC8b	Transfer from/to la vessels (dedicate		0.012	0.1		0.014
		PROC9	Transfer small container		0.012	0.1		0.01
		PROC7	Spraying industrial settings a application	and	0.63	5		0.71
		PROC10	Roller application		0.063	0.5		0.07
		PROC13	Dipping of pouring	or	0.012	0.1		0.014
	Summary of long-term exposure	Routes of exp	osure	Cor	ncentrations		Justificati	on
	concentration to workers	Dermal local e	exposure	12			multiplied	TRA n for PROC10; l by a dermal ctor of 0.006.
		Dermal system exposure (in mg/kg bw/d		0.16	6		multiplied	TRA n for PROC10; I by a dermal ctor of 0.006.
		Inhalation exposure (in mg/m3)/8h workday Inhalation exposure (in mg/kg/d)/8h workday		5 0.71		ECETOC TRA prediction for PROC7		
						ECETOC prediction	TRA n for PROC7	
4	Operational conditions related to availab	le dilution capaci	ty and chara	acteris	stics of exposed	humai	ns	
	Occupational exposure	Information typ	-		a field		Explanati	on
	Operational conditions related to respiration and skin contact	Respiration vo under condition		10 r	n ³ /d		Default fo	r workers, light

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155 Version 2.0

		Area of skin contact with		ECETOC TRA default:
		the substance under	480 cm ²	PROC5:
		conditions of use	1500 cm ²	PROC7:
			960 cm ²	PROC8a:
			480 cm ²	PROC8b:
			480 cm ²	PROC9
			960 cm ²	PROC10
			1500 cm ²	PROC11
			480 cm ²	PROC13
			1980 cm ²	PROC19
		Body weight	70 kg	Default for workers
Operational conditions related to		Information type	Data field	Explanation
respiration, skin contact and ingesti	on	Skin contact area	960 cm2	ConsExpo default
for the general public		Mouth contact area	-	Not applicable – no oral
				exposure
		Respiration volume	26 m3	Default:
		under conditions of use		Light activity 26 m3/24 h
		Room size and	20m3; exchange per	ConsExpo defaults
		ventilation rate	hour 0.6 h-1	
		Body weight	65 kg	Default adult bodyweight
Predicted Exposure Concentrations	of		PEC	unit
Environmental releases				
		AIR		
		Annual average local	1.30 x 10 ⁻¹⁵	[mg.m ⁻³]
		PEC in air (total)		
		WATER, SEDIMENT		
		Local PEC in surface		
			2 40 40-2	5 113
· ·		water during emission	2.48 x 10 ⁻²	[mg l ⁻¹]
		episode (dissolved)	2.48 x 10 ⁻²	[mg l ⁻¹]
		episode (dissolved) Annual average local	2.48 x 10 ⁻²	
		episode (dissolved)		[mg l ⁻¹]
		episode (dissolved) Annual average local PEC in surface water (dissolved)	2.48 x 10 ⁻² 2.48 x 10 ⁻²	
		episode (dissolved) Annual average local PEC in surface water		[mg l ⁻¹]
		episode (dissolved) Annual average local PEC in surface water (dissolved) Local PEC in fresh-water sediment during	2.48 x 10 ⁻²	
		episode (dissolved) Annual average local PEC in surface water (dissolved) Local PEC in fresh-water sediment during emission episode		[mg l ⁻¹]
		episode (dissolved) Annual average local PEC in surface water (dissolved) Local PEC in fresh-water sediment during emission episode Local PEC in seawater	2.48 x 10 ⁻²	[mg l ⁻¹] [mg kg wwt ⁻¹]
		episode (dissolved) Annual average local PEC in surface water (dissolved) Local PEC in fresh-water sediment during emission episode Local PEC in seawater during emission episode	2.48 x 10 ⁻² 4.23 x 10 ⁻¹	[mg l ⁻¹]
		episode (dissolved) Annual average local PEC in surface water (dissolved) Local PEC in fresh-water sediment during emission episode Local PEC in seawater during emission episode (dissolved)	2.48 x 10 ⁻²	[mg l ⁻¹] [mg kg wwt ⁻¹]
		episode (dissolved) Annual average local PEC in surface water (dissolved) Local PEC in fresh-water sediment during emission episode Local PEC in seawater during emission episode (dissolved) Annual average local	2.48 x 10 ⁻² 4.23 x 10 ⁻¹	[mg l ⁻¹] [mg kg wwt ⁻¹] [mg l ⁻¹]
		episode (dissolved) Annual average local PEC in surface water (dissolved) Local PEC in fresh-water sediment during emission episode Local PEC in seawater during emission episode (dissolved) Annual average local PEC in seawater	2.48 x 10 ⁻² 4.23 x 10 ⁻¹ 2.37 x 10 ⁻³	[mg l ⁻¹] [mg kg wwt ⁻¹]
		episode (dissolved) Annual average local PEC in surface water (dissolved) Local PEC in fresh-water sediment during emission episode Local PEC in seawater during emission episode (dissolved) Annual average local PEC in seawater (dissolved)	2.48 x 10 ⁻² 4.23 x 10 ⁻¹	[mg l ⁻¹] [mg kg wwt ⁻¹] [mg l ⁻¹]
		episode (dissolved) Annual average local PEC in surface water (dissolved) Local PEC in fresh-water sediment during emission episode Local PEC in seawater during emission episode (dissolved) Annual average local PEC in seawater	2.48 x 10 ⁻² 4.23 x 10 ⁻¹ 2.37 x 10 ⁻³	[mg l ⁻¹] [mg kg wwt ⁻¹] [mg l ⁻¹]

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155 Version 2.0

emission episode		
SOIL, GROUNDWATE	R	
Local PEC in agric. soil		1
(total) averaged over 30	4.02 10-1	[mg kg wwt ⁻¹]
days	4.02 x 10 ⁻¹	
Local PEC in agric. soil		1
(total) averaged over	1 22 - 10-1	[mg kg wwt ⁻¹]
180 days	1.32 x 10 ⁻¹	
Local PEC in grassland		1-
(total) averaged over	5.27 x 10 ⁻²	[mg kg wwt ⁻¹]
180 days	5.27 X 10	
Local PEC in pore water	1.99 x 10 ⁻³	[mg l ⁻¹]
of agricultural soil	1.99 X 10	
Local PEC in pore water	7.95 x 10 ⁻⁴	[mg l ⁻¹]
of grassland	7.95 X 10	[8 -]
Local PEC in		1-
groundwater under	1.99 x 10 ⁻³	[mg l ⁻¹]
agricultural soil	1.99 X 1U	

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Substance / User identity	
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	6. Use in paper
	Processes and activities covered by	SU3, SU6
	the exposure scenario	PROC 5, PROC 8a
2	Operational conditions and risk manager	
	Duration an frequency of use	
	Worker	
	All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	solid
	Concentration of substance in preparation or article	
	Other relevant operational conditions of use	N/A
	Risk management measures:	
2.1	Control of worker exposure	Following the REACH descriptor system, the following product type is covered by this generic scenario: Paper and board dye, finishing and impregnation products: including bleaches and other processing aids (PC26).
	Technical conditions and measures at process level (source) to	N/A
	prevent release Technical conditions and measures to	AVA
	control dispersion from source	N/A
	towards the worker	
	Engineering controls:	N/A
	Organisational measures to prevent/limit releases, dispersion and exposure	N/A
	Conditions and measures related to	N/A
	personal protection, hygiene and	N/A
	health evaluation	
2.2	Control of environmental exposure	
	Frequency and duration of use	
	Waste water flow	N/A
	Dilution factor	
	Emission factor to waste water	N/A
	Release fraction	
	Conditions and measures related to	N/A
	external recovery of waste	

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Information on estimated exposure and Downstream-user guidance		
3	Exposure estimation and reference to its	s source:	
		N/A	
4	Guidance to DU to evaluate whether	ne works inside the boundaries set by the ES	
	Occupational exposure	N/A	
	Environmental emissions	Citric acid is used in the cleaning of papermaking machines and to prevent build up of deposits. It is added to the pulp slurry prior to bleaching to control paper staining by sequestering metal ions. Cleaning applications are covered under another exposure scenario; this document covers use of citrate as a processing aid in the paper-making industry.	
		This generic scenario makes use of the following documents:	
		OECD Emission Scenario Documents on Kraft, Non-Integrated and Recovered Pulp Mills.	
		This covers the use of citrate as a process aid in the paper-making industry. It is possible that a small amount of citrate is incorporated into the finished paper products. However, it is considered that the amount of citrate that ends up in articles and could be released (resulting in consumer exposure) is likely to be negligible.	
		The amount of citric acid believed to be used in this application is at most 1000 tpa. The industrial use per site is unknown. However, a default approach would be to consider 10 paper mills in a single region, operating over 300 days per year. The substance is not mixed into pulp, but is applied to machinery. A loss of 2% is a realistic maximum.	
		This gives a daily release of	
		100 t x 1000 kg/t x 0.02 / 300 d = 6.7 kg/d	
		For the environment, the amounts passing to waste are very likely to be less than those from the ES 1-5. Therefore there is no need to complete an exposure assessment at a local scale with full details of PEC values etc.	
		However, a regional release of 67 kg/d to waste water will be added to the model.	
		For human health worker exposure at paper mills will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.	

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Substance / User identity	
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	7. Use in construction
	Processes and activities covered by	SU3, SU21, SU22, SU2, SU10, SU19, PROC 2, PROC 4, PROC 5, PROC 7, PROC 8a,
	the exposure scenario	PROC 8b, PROC 10, PROC 11. PROC 13, PROC 14, PROC 19, PROC 21, PROC 24
2	Operational conditions and risk manage	ment measures
	Duration an frequency of use	
	Worker	
	All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	solid
	Concentration of substance in preparation or article	N/A
	Other relevant operational conditions of use	N/A
	Risk management measures:	
2.1	Control of worker exposure	Following the REACH descriptor system, the following product types are covered by this generic scenario: PC10 (Building and construction preparations not covered elsewhere).
		The following substances are used in construction materials: citric acid and trisodium citrate.
		Citrates can be used to retard the setting rate of cement and reduce the amount of water needed. They may therefore be added to concrete, mortar, plaster and render formulations. The concentration in these products is generally low (<1%).
	Technical conditions and measures at process level (source) to	N/A
	prevent release Conditions and measures related to	M/A
	personal protection, hygiene and	N/A
	health evaluation	
2.2	Control of environmental exposure	
	Frequency and duration of use	T.v.
	Use per site	N/A
	Duration of emission	
	Waste water flow	
	Dilution factor	
	Emission factor to waste water	N/A
	Release fraction	
	Environment factors not influenced by	N/A

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	risk management	
	Other given operational conditions	
	affecting environmental exposure	
	Technical conditions and measures at	No specific measures are considered.
	process level (source) to prevent	
	release	
	Technical onsite conditions and	N/A
	measures to reduce or limit	
	discharges, air emissions and releases	
	to soil	
	Organizational measures to	N/A
	prevent/limit release from site	
	Conditions and measures related to	N/A
	municipal sewage treatment plant	
	Conditions and measures related to	N/A
	external treatment of waste for	1021
	disposal	
	Conditions and measures related to	none
	external recovery of waste	
	Information on estimated exposure and	Downstream-user quidance
3	Exposure estimation and reference to its	-
	Occupational exposure:	N/A
	Dermal	
	Inhalation	
4		ne works inside the boundaries set by the ES
	Occupational exposure	N/A
	Environmental emissions	This document provides an environmental generic exposure scenario for substances used in construction materials. This generic scenario makes use of the following documents:
		EU Technical Guidance Document (TGD) emission scenario document. REACH Technical Guidance.
		The amount of citric acid believed to be used in this application is at most 1500 tpa. The industrial use per site is unknown, but should be considered as a widely dispersed use. In the worst case a release of the entire tonnage to the region could be included, i.e. 1500 tpa. Of this, part will be released to industrial soil (90%) and part to waste water (10%).
		A regional release of $150 \times 1000/365 = 411 \text{ kg/d}$ to waste water will be added to the model, and 3699 kg/d to industrial soil will be included.
		For human health worker exposure at construction sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Substance / User identity	
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	8. Use in polymers and plastics
'	Processes and activities covered by	SU3,SU11,SU12,
	the exposure scenario	PROC 3, PROC 5, PROC 8a, PROC 8b
2	Operational conditions and risk manager	
~	Duration an frequency of use	nent measures
	Physical form of substance: under	solid
	conditions of use it is used as a liquid.	
	Concentration of substance in	N/A
	preparation or article	Diagon also note that under saidic conditions (n.L7) sulfur diavide can be formed
	Other relevant operational conditions of use	Please also note that under acidic conditions (pH<7), sulfur dioxide can be formed. Please ensure compliance with the existing occupational exposure limit as recommended by SCOEL (2008) for sulfur dioxide of 0.5 ppm (TWA, 8h) respectively 1 ppm (STEL, 15 min).
		Polyolefin foams are used for a variety of applications such as automotive, construction, food packaging, sport and leisure, and many other industrial and consumer uses. They usually have a high strength to weight ratio and are manufactured in a variety of processes and in low density (25 - 250 kg/m3) or high density (250 - 700 kg/m3) versions, or even in densities as low as 16 kg/m3 for polystyrene. All current extrusion processes involve the following steps: melting, mixing with blowing agents, cooling of melt, expansion and degassing/aging. The steps in this process can be realized in different configurations of equipment, e.g., with long single-screw extruders, twin-screw extruders, or tandem extruder lines.
		Both citric acid (or citrate salt) and (bi)carbonate may be surface-treated with, for example, a fatty acid ester to make them compatible with the polyolefin. A concentrated master batch of the formulated foaming agent in polymer at loading levels of from about 5% to about 50% actives may then be prepared. The master batch is added to the polymer melt which is to be foamed such that the blowing agents are at 0.1 to 2.0% active levels in the final formulation [US 5,302,455 and refs. therein]. By-products of this reaction are mono-, di-, and/or trisodium citrate, in combination with other sodium salts, which will still be present within the foamed polymer. These residues are typically present at around 50 wt.% of the initial foaming agent
		formulation, which is equivalent to <1 wt.% of the total foamed polymer in most cases [RAPRA, 2004].
	Risk management measures:	
2.1	Control of worker exposure	
	Technical conditions and measures at process level (source) to	N/A
	prevent release	
	Technical conditions and measures to control dispersion from source towards the worker	N/A
	Engineering controls:	
	Organisational measures to	N/A
	prevent/limit releases, dispersion and	

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

Conditions and measures related to personal protection, hygiene and health evaluation			
personal protection, hygiene and health evaluation 2.2 Control of environmental exposure Use per site Duration of emission Waste water flow Dilution factor Release of citric acid Considered to be zero as the additive is destroyed during the conversion process. Thus, for 200 tpa of citrates used in plastics applications, assumed to be used at 1 sites across Europe, the local losses to water air and obtavate are: The REACH defaults for ERC6d are for the production on 300 days per year if it tonnage of the product is >5000 tpa [ECHA, 2009]. Citrate is present at <1% plastics applications (see Section 2.1.1), therefore, the total production volume approx. 10,000 tpa. Therefore, the maximum daily releases are as follows: Water: 20 tx 1000 kg/tx (0.0065) / 300 = 0.43 kg/d Air: 0 For the environment, the amounts passing to waste are very likely to be less the those from the ES 1-5. Therefore there is no need to complete an exposu assessment at a local scale with full details of PEC values etc. However, a regional release of 0.35 kg/d to waste water will be added to the mode and similarly 3.18 kg/d to the continental scale. Environment factors not influenced by risk management Other given operational conditions affecting environmental exposure Technical conditions and measures at process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Permal Inhalation Not relevant For human health worker exposure at construction sites will be to aqueou formulations for which no hazard has been identified. In addition, relevant exposures have been identified in addition, relevant exposures have been identified.		exposure	
Description of environmental exposure Duration of emission Duration of emission Waste water flow Dilution factor Dilution fact			
2.2 Control of environmental exposure Use per site Duration of emission Waste water flow Dilution factor Release of citric acid Losses from conversion, service life and disposal for chemical blowing agents a considered to be zero as the additive is destroyed during the conversion process. Thus, for 200 tpa of citrates used in plastics applications, assumed to be used at 1 sites across Europe, the local losses to water air acidid waste are: The REACH defaults for ERC6d are for the production on 300 days per year if it tonnage of the product is >5000 tpa (ECHA, 2009). Citrate is present at <1% plastics applications (see Section 2.1.1), therefore, the total production volume approx. 100,000 tpa. Therefore, the maximum daily releases are as follows: Water: 20 tx 1000 kg/st x (0.0055) / 300 = 0.43 kg/d Air: 0 For the environment, the amounts passing to waste are very likely to be less the those from the ES 1-5. Therefore there is no need to complete an exposus assessment at al coal scale with full details of PEC values etc. However, a regional release of 0.35 kg/d to waste water will be added to the mode and similarly 3.18 kg/d to the continental scale. Environment factors not influenced by risk management Other given operational conditions affecting environmental exposure Technical conditions and measures at process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure Dermal Inhalation Are Coupational exposure: Dermal Inhalation For human health worker exposure at construction sites will be to aqueou formulations for which no heazerd has been identified. In addition, relevant process level for life cycle stages with higher exposure species appreciated process process.			
Use per site Duration of emission Waste water flow Dilution factor Release of citric acid Considered to be zero as the additive is destroyed during the conversion process. Thus, for 200 tpa of citrates used in plastics applications, assumed to be used at sites across Europe, the local closses to water and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year if it tonnage of the product is > 5000 tpa [Cht.209]. Citrate is present at 1% plastics applications, assumed to be used at 1 sistes across Europe, the local closses to water and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year if it tonnage of the product is > 5000 tpa [Cht.209]. Citrate is present at 1% plastics applications (see Section 2.1.1), therefore, the total production volume approx. 100,000 tpa. Therefore, the maximum daily releases are as follows: Water: 20 tr. 1000 kg/tr x (0.0065) / 300 = 0.43 kg/d Air: 0 For the environment, the amounts passing to waste are very likely to be less the those from the ES 1-5. Therefore there is no need to complete an exposu assessment at a local scale with full details of PEC values etc. However, a regional release of 0.35 kg/d to waste water will be added to the mode and similarly 3.18 kg/d to the continental scale. Environment factors not influenced by risk management Other given operational conditions affecting environmental exposure Technical conditions and measures at process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation Not relevant Inhalation For human health worker exposure at construction sites will be to aqueot formulations for which no hazard has been identified. In addition, relevant known process.		health evaluation	
Use per site Duration of emission Waste water flow Dilution factor Release of citric acid Release of citric acid Considered to be zero as the additive is destroyed during the conversion process. Thus, for 200 tpa of citrates used in plastics applications, assumed to be used at 1 sistes across Europe, the local closses to water and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year if it tonnage of the product is > 5000 tpa [ECHA.209]. Citrate is present at 1% plastics applications, assumed to be used at 1 sistes across Europe, the local closses to water and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year if it tonnage of the product is > 5000 tpa [ECHA.209]. Citrate is present at 1% plastics applications (see Section 2.1.1), therefore, the total production volume approx. 100,000 tpa. Therefore, the maximum daily releases are as follows: Water: 20 tr. 1000 kg/m x (0.0065) / 300 = 0.43 kg/d Air: 0 For the environment, the amounts passing to waste are very likely to be less the those from the ES 1-5. Therefore there is no need to complete an exposu assessment at a local scale with full details of PEC values etc. However, a regional release of 0.35 kg/d to waste water will be added to the mode and similarly 3.18 kg/d to the continental scale. Environment factors not influenced by risk management Other given operational conditions affecting environmental exposure Technical conditions and measures at process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation For human health worker exposure at construction sites will be to aqueor formulations for which no hazard has been identified. In addition, relevant formulations for which no hazard has been identified.			
Use per site Duration of emission Waste water flow Dilution factor Release of citric acid Release of citric acid Considered to be zero as the additive is destroyed during the conversion process. Thus, for 200 tpa of citrates used in plastics applications, assumed to be used at 1 sistes across Europe, the local closses to water and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year if it tonnage of the product is > 5000 tpa [ECHA.209]. Citrate is present at 1% plastics applications, assumed to be used at 1 sistes across Europe, the local closses to water and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year if it tonnage of the product is > 5000 tpa [ECHA.209]. Citrate is present at 1% plastics applications (see Section 2.1.1), therefore, the total production volume approx. 100,000 tpa. Therefore, the maximum daily releases are as follows: Water: 20 tr. 1000 kg/m x (0.0065) / 300 = 0.43 kg/d Air: 0 For the environment, the amounts passing to waste are very likely to be less the those from the ES 1-5. Therefore there is no need to complete an exposu assessment at a local scale with full details of PEC values etc. However, a regional release of 0.35 kg/d to waste water will be added to the mode and similarly 3.18 kg/d to the continental scale. Environment factors not influenced by risk management Other given operational conditions affecting environmental exposure Technical conditions and measures at process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation For human health worker exposure at construction sites will be to aqueor formulations for which no hazard has been identified. In addition, relevant formulations for which no hazard has been identified.			
Use per site Duration of emission Waste water flow Dilution factor Release of citric acid Release of citric acid Considered to be zero as the additive is destroyed during the conversion process. Thus, for 200 tpa of citrates used in plastics applications, assumed to be used at 1 sistes across Europe, the local closses to water and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year if it tonnage of the product is > 5000 tpa [ECHA.209]. Citrate is present at 1% plastics applications, assumed to be used at 1 sistes across Europe, the local closses to water and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year if it tonnage of the product is > 5000 tpa [ECHA.209]. Citrate is present at 1% plastics applications (see Section 2.1.1), therefore, the total production volume approx. 100,000 tpa. Therefore, the maximum daily releases are as follows: Water: 20 tr. 1000 kg/m x (0.0065) / 300 = 0.43 kg/d Air: 0 For the environment, the amounts passing to waste are very likely to be less the those from the ES 1-5. Therefore there is no need to complete an exposu assessment at a local scale with full details of PEC values etc. However, a regional release of 0.35 kg/d to waste water will be added to the mode and similarly 3.18 kg/d to the continental scale. Environment factors not influenced by risk management Other given operational conditions affecting environmental exposure Technical conditions and measures at process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation For human health worker exposure at construction sites will be to aqueor formulations for which no hazard has been identified. In addition, relevant formulations for which no hazard has been identified.			
Use per site Duration of emission Waste water flow Dilution factor Release of citric acid Release of citric acid Considered to be zero as the additive is destroyed during the conversion process. Thus, for 200 tpa of citrates used in plastics applications, assumed to be used at 1 sistes across Europe, the local closses to water and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year if it tonnage of the product is > 5000 tpa [ECHA.209]. Citrate is present at 1% plastics applications, assumed to be used at 1 sistes across Europe, the local closses to water and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year if it tonnage of the product is > 5000 tpa [ECHA.209]. Citrate is present at 1% plastics applications (see Section 2.1.1), therefore, the total production volume approx. 100,000 tpa. Therefore, the maximum daily releases are as follows: Water: 20 tr. 1000 kg/m x (0.0065) / 300 = 0.43 kg/d Air: 0 For the environment, the amounts passing to waste are very likely to be less the those from the ES 1-5. Therefore there is no need to complete an exposu assessment at a local scale with full details of PEC values etc. However, a regional release of 0.35 kg/d to waste water will be added to the mode and similarly 3.18 kg/d to the continental scale. Environment factors not influenced by risk management Other given operational conditions affecting environmental exposure Technical conditions and measures at process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation For human health worker exposure at construction sites will be to aqueor formulations for which no hazard has been identified. In addition, relevant formulations for which no hazard has been identified.			
Use per site Duration of emission Waste water flow Dilution factor Release of citric acid Release of citric acid Considered to be zero as the additive is destroyed during the conversion process. Thus, for 200 tpa of citrates used in plastics applications, assumed to be used at 1 sistes across Europe, the local closses to water and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year if it tonnage of the product is > 5000 tpa [ECHA.209]. Citrate is present at 1% plastics applications, assumed to be used at 1 sistes across Europe, the local closses to water and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year if it tonnage of the product is > 5000 tpa [ECHA.209]. Citrate is present at 1% plastics applications (see Section 2.1.1), therefore, the total production volume approx. 100,000 tpa. Therefore, the maximum daily releases are as follows: Water: 20 tr. 1000 kg/m x (0.0065) / 300 = 0.43 kg/d Air: 0 For the environment, the amounts passing to waste are very likely to be less the those from the ES 1-5. Therefore there is no need to complete an exposu assessment at a local scale with full details of PEC values etc. However, a regional release of 0.35 kg/d to waste water will be added to the mode and similarly 3.18 kg/d to the continental scale. Environment factors not influenced by risk management Other given operational conditions affecting environmental exposure Technical conditions and measures at process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation For human health worker exposure at construction sites will be to aqueor formulations for which no hazard has been identified. In addition, relevant formulations for which no hazard has been identified.			
Duration of emission Waste water flow Dilution factor Release of citric acid Losses from conversion, service life and disposal for chemical blowing agents a considered to be zero as the additive is destroyed during the conversion process. Thus, for 200 top a citrates used in plastics applications, assumed to be used at sites across Europe, the local losses to water air and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year if it tonnage of the product is > 5000 tpa [ECH4, 2009]. Citrate is present at <1% plastics applications (see Section 2.1.1), therefore, the total production volume approx. 100,000 tpa. Therefore, the maximum daily releases are as follows: Water: 20 t x 1000 kg/x (0.0065) / 300 = 0.43 kg/d Air: 0 For the environment, the amounts passing to waste are very likely to be less the those from the ES 1-5. Therefore there is no need to complete an exposu assessment at a local scale with full details of PEC values etc. However, a regional release of 0.35 kg/d to waste water will be added to the mode and similarly 3.18 kg/d to the continental scale. Environment factors not influenced by risk management Other given operational conditions and measures at process level (source) to prevent release Conditions and measures at process level (source) to prevent release Conditions and measures and Downstream-user guidance 3 Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation Not relevant Inhalation For human health worker exposure at construction sites will be to aqueor formulations for which no hazard has been identified. In addition, relevant knipper exposures have been calculated for life cycle stages with higher exposure	2.2	Control of environmental exposure	
Waste water flow Dilution factor Release of citric acid Losses from conversion, service life and disposal for chemical blowing agents a considered to be zero as the additive is destroyed during the conversion process. Thus, for 200 tpa of citrates used in plastics applications, assumed to be used at 1 sites across Europe, the local losses to water air and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year lift to tonnage of the product is >5000 tpa [ECHA, 2009]. Citrate is present at <1% plastics applications (see Section 2.1.1), therefore, the total production volume approx. 100,000 tpa. Therefore, the maximum daily releases are as follows: Water: 20 tx 1000 kg/x (x).0065) / 300 = 0.43 kg/d Air: 0 For the environment, the amounts passing to waste are very likely to be less the those from the ES 1-5. Therefore there is no need to complete an exposu assessment at a local scale with full details of PEC values etc. However, a regional release of 0.35 kg/d to waste water will be added to the mode and similarly 3.18 kg/d to the continental scale. Environment factors not influenced by risk management Other given operational conditions affecting environmental exposure Technical conditions and measures at process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Sexposure estimation and reference to its source: Occupational exposure: Dermal Not relevant Inhalation For human health worker exposure at construction sites will be to aqueor formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposure		Use per site	N/A
Waste water flow Dilution factor Release of citric acid Losses from conversion, service life and disposal for chemical blowing agents a considered to be zero as the additive is destroyed during the conversion process. Thus, for 200 tpa of citrates used in plastics applications, assumed to be used at 1 sites across Europe, the local losses to water air and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year lift to tonnage of the product is >5000 tpa [ECHA, 2009]. Citrate is present at <1% plastics applications (see Section 2.1.1), therefore, the total production volume approx. 100,000 tpa. Therefore, the maximum daily releases are as follows: Water: 20 tx 1000 kg/x (x).0065) / 300 = 0.43 kg/d Air: 0 For the environment, the amounts passing to waste are very likely to be less the those from the ES 1-5. Therefore there is no need to complete an exposu assessment at a local scale with full details of PEC values etc. However, a regional release of 0.35 kg/d to waste water will be added to the mode and similarly 3.18 kg/d to the continental scale. Environment factors not influenced by risk management Other given operational conditions affecting environmental exposure Technical conditions and measures at process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Sexposure estimation and reference to its source: Occupational exposure: Dermal Not relevant Inhalation For human health worker exposure at construction sites will be to aqueor formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposure		Duration of emission	
Dilution factor Release of citric acid Losses from conversion, service life and disposal for chemical blowing agents a considered to be zero as the additive is destroyed during the conversion process. Thus, for 200 tpa of citrates used in plastics applications, assumed to be used at sites across Europe, the local losses to water air and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year if it tonnage of the product is >5000 tpa [ECHA, 2009]. Citrate is present at <1% plastics applications (see Section 2.1.1), therefore, the total production volume approx. 100,000 tpa. Therefore, the maximum daily releases are as follows: Water: 20 t × 1000 kg/x (0.0065) / 300 = 0.43 kg/d Air: 0 For the environment, the amounts passing to waste are very likely to be less the those from the ES 1-5. Therefore there is no need to complete an exposu assessment at a local scale with full details of PEC values etc. However, a regional release of 0.35 kg/d to waste water will be added to the mode and similarly 3.18 kg/d to the continental scale. Environment factors not influenced by risk management Other given operational conditions affecting environmental exposure Technical conditions and measures at process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation 4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES Occupational exposure For human health worker exposure at construction sites will be to aqueor formulations for which no hazard has been identified. In addition, releval exposure with higher exposure			
Release of citric acid Losses from conversion, service life and disposal for chemical blowing agents a considered to be zero as the additive is destroyed during the conversion process. Thus, for 200 tpa of citrates used in plastics applications, assumed to be used at sites across Europe, the local losses to water air and solid waste are: The REACH defaults for ERC6d are for the production a 300 days per year if it tonnage of the product is >5000 tpa [ECHA, 2009]. Citrate is present at <1% plastics applications (see Section 2.1.1), therefore, the total production volume approx. 100,000 tpa. Therefore, the maximum daily releases are as follows: Water: 20 t x 1000 kg/t x (0.0065) / 300 = 0.43 kg/d Air: 0 For the environment, the amounts passing to waste are very likely to be less the those from the ES 1-5. Therefore there is no need to complete an exposu assessment at a local scale with full details of PEC values etc. However, a regional release of 0.35 kg/d to waste water will be added to the mode and similarly 3.18 kg/d to the continental scale. Environment factors not influenced by risk management Other given operational conditions affecting environmental exposure Technical conditions and measures at process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Not relevant Inhalation Guidance to DU to evaluate whether he works inside the boundaries set by the ES Occupational exposure For human health worker exposure at construction sites will be to aqueou formulations for which no hazard has been identified. In addition, relevant exposure with higher exposure with higher exposure			
considered to be zero as the additive is destroyed during the conversion process. Thus, for 200 tpa of citrates used in plastics applications, assumed to be used at 1 sites across Europe, the local losses to water air and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year if it tonnage of the product is >5000 tpa [ECHA, 2009]. Citrate is present at <1% plastics applications (see Section 2.1.1), therefore, the total production volume approx. 100,000 tpa. Therefore, the number of the total production volume approx. 100,000 tpa. Therefore, the number of the total production volume approx. 100,000 tpa. Therefore, the number of the total production volume approx. 100,000 tpa. Therefore, the releases are as follows: Water: 20 t x 1000 kg/t x (0.0065) / 300 = 0.43 kg/d Air: 0 For the environment, the amounts passing to waste are very likely to be less that those from the ES 1-5. Therefore there is no need to complete an exposus assessment at a local scale with full details of PEC values etc. However, a regional release of 0.35 kg/d to waste water will be added to the mode and similarly 3.18 kg/d to the continental scale. Environment factors not influenced by risk management Other given operational conditions affecting environmental exposure Technical conditions and measures at process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation Not relevant Inhalation For human health worker exposure at construction sites will be to aqueou formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for lievycl		Dilution factor	
risk management Other given operational conditions affecting environmental exposure Technical conditions and measures at process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Not relevant Inhalation 4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES Occupational exposure For human health worker exposure at construction sites will be to aqueou formulations for which no hazard has been identified. In addition, releva exposures have been calculated for life cycle stages with higher exposure		Release of citric acid	considered to be zero as the additive is destroyed during the conversion process. Thus, for 200 tpa of citrates used in plastics applications, assumed to be used at 10 sites across Europe, the local losses to water air and solid waste are: The REACH defaults for ERC6d are for the production on 300 days per year if the tonnage of the product is >5000 tpa [ECHA, 2009]. Citrate is present at <1% in plastics applications (see Section 2.1.1), therefore, the total production volume is approx. $100,000$ tpa. Therefore, the maximum daily releases are as follows: Water: $20 \text{ t x } 1000 \text{ kg/t x } (0.0065) / 300 = 0.43 \text{ kg/d}$ Air: 0 For the environment, the amounts passing to waste are very likely to be less than those from the ES 1-5. Therefore there is no need to complete an exposure assessment at a local scale with full details of PEC values etc. However, a regional release of 0.35 kg/d to waste water will be added to the model,
Other given operational conditions affecting environmental exposure Technical conditions and measures at process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation 4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES Occupational exposure For human health worker exposure at construction sites will be to aqueou formulations for which no hazard has been identified. In addition, releval exposures have been calculated for life cycle stages with higher exposure		-	N/A
affecting environmental exposure Technical conditions and measures at process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation 4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES Occupational exposure For human health worker exposure at construction sites will be to aqueou formulations for which no hazard has been identified. In addition, releval exposures have been calculated for life cycle stages with higher exposure			N/A
Technical conditions and measures at process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation A Guidance to DU to evaluate whether he works inside the boundaries set by the ES Occupational exposure For human health worker exposure at construction sites will be to aqueou formulations for which no hazard has been identified. In addition, releval exposures have been calculated for life cycle stages with higher exposure			
process level (source) to prevent release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation Guidance to DU to evaluate whether he works inside the boundaries set by the ES Occupational exposure For human health worker exposure at construction sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposure			
release Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Not relevant Inhalation 4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES Occupational exposure For human health worker exposure at construction sites will be to aqueou formulations for which no hazard has been identified. In addition, releval exposures have been calculated for life cycle stages with higher exposure			N/A
Conditions and measures related to external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation A Guidance to DU to evaluate whether he works inside the boundaries set by the ES Occupational exposure For human health worker exposure at construction sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposure		process level (source) to prevent	
external recovery of waste Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation A Guidance to DU to evaluate whether he works inside the boundaries set by the ES Occupational exposure For human health worker exposure at construction sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposure		release	
Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation 4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES Occupational exposure For human health worker exposure at construction sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposure		Conditions and measures related to	none
Information on estimated exposure and Downstream-user guidance Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation Occupational exposure For human health worker exposure at construction sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposure		external recovery of waste	
Exposure estimation and reference to its source: Occupational exposure: Dermal Inhalation			Downstream-user quidance
Occupational exposure: Dermal Inhalation 4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES Occupational exposure For human health worker exposure at construction sites will be to aqueous formulations for which no hazard has been identified. In addition, relevative exposures have been calculated for life cycle stages with higher exposure	2		
Dermal Not relevant 4	٦	•	5 30UTUG.
Inhalation Guidance to DU to evaluate whether he works inside the boundaries set by the ES Occupational exposure For human health worker exposure at construction sites will be to aqueous formulations for which no hazard has been identified. In addition, relevative exposures have been calculated for life cycle stages with higher exposure		·	
4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES Occupational exposure For human health worker exposure at construction sites will be to aqueous formulations for which no hazard has been identified. In addition, relevation exposures have been calculated for life cycle stages with higher exposures		Dermal	Not relevant
Occupational exposure For human health worker exposure at construction sites will be to aqueous formulations for which no hazard has been identified. In addition, relevative exposures have been calculated for life cycle stages with higher exposures.		Inhalation	
Occupational exposure For human health worker exposure at construction sites will be to aqueous formulations for which no hazard has been identified. In addition, relevative exposures have been calculated for life cycle stages with higher exposures.	4	Guidance to DU to evaluate whether h	ne works inside the boundaries set by the ES
			For human health worker exposure at construction sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures.

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

Environmental emissio	ns N/A	
-----------------------	--------	--

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Substance / User identity		1
	Registration number(s)	01-2119457026-42-0004	-
	Substance identity	CAS#77-92-9; EC#201-069-1	
1	Short title of the exposure scenario	9. Use in the oil industry	
•	Processes and activities covered by	SU3, SU2	1
	the exposure scenario	PROC 3, PROC 4, PROC 5,	
2	Operational conditions and risk manager	·	
_	Duration an frequency of use	mont medaures	
	Physical form of substance: under conditions of use it is used as a liquid.	solid	-
	Concentration of substance in preparation or article	20-50%	
	Other relevant operational conditions of use	In the oil industry, citric acid is often used for oil-well acidizing to prevent the find hydroxide [APAC]. Oil well acidizing is the term used for the application of find 93-149°C) to remove tough wellbore scale [McGraw-Hill].	
		Oxidation reactions, which occur in wells injected with HCl, cause formation of ins The pumping operations are thus interrupted by these gels, and hence, citric acid preventing gel formation [APAC].	
		Oil producing well formations can become plugged with acid soluble minerals an production [Gewanter, Herman L. et al]. Production can be increased by forcing dissolve the minerals [Gewanter, Herman L. et al]. The acids readily dissolve the ir from the well casing and the formation [Gewanter, Herman L. et al]. However, wate acid in the formation, which allows for the re-precipitation of the iron to ferric hydromatical. Let al]. Certain chemicals must be added at this point to maintain it in a set al].	acid dovon and in and carl and carl xide above
	Risk management measures:		
2.1	Control of consumers exposure	Not relevant	
	Human factors not influenced by risk management	Not relevant	
	Other given operational conditions affecting consumers exposure	Not relevant	
	Conditions and measures related to information and behavioural advice to consumers	Not relevant	
	Conditions and measures related to personal protection, hygiene and health evaluation	Not relevant	
2.2	Control of environmental exposure		
	Frequency and duration of use		
	waste water Release	Control of the re-precipitation of iron and the pH, as the acid is spent, can be achieved by the sequestration by organic chelants and the reduction to soluble ferrous iron [Gewanter, Herman L. et al]. Citric acid is a useful organic chelant and is used for this purpose [Gewanter, Herman L. et al]. Other chelants may include gluconic acid, the tetrasodium salt of ethylenediaminetetraacetic acid (EDTA), and the trisodium salt of nitrilotriacetic acid (NTA) [Gewanter, Herman L. et al].	
	_	This is a widely dispersed use but in the worst case it can be envisaged that the	1

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

		entire tonnage could pass to surface marine water. This equates to
		100 t x 1000 kg/t /365 = 274 kg/d to the regional surface water
		900 t x 1000 kg/t /365 = 2740 kg/d to the continental surface water
	Environment factors not influenced by	None
	risk management	
	Conditions and measures related to	None
	external treatment of waste for	
	disposal	
	Conditions and measures related to	none
	external recovery of waste	
	Information on estimated exposure and	Downstream-user guidance
3	Exposure estimation and reference to its	s source:
	Human exposure:	For human health worker exposure at oil production sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.
4	Guidance to DU to evaluate whether h	ne works inside the boundaries set by the ES
	Consumer exposure	N/A
	Environmental emissions	N/A

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Substance / User identity				
	Registration number(s)	01-2119457026-42-0004			
	Substance identity	CAS#77-92-9; EC#201-069)-1		
1	Short title of the exposure scenario	10. Use in textiles			
	Processes and activities covered by	SU3,SU5			
	the exposure scenario	PROC8a,PROC8b, PROC1	IO, PROC13, PROC	22	
2	Operational conditions and risk manager	ment measures			
	Duration an frequency of use				
	Worker				
	All applicable PROCs	>4h			
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.			
	Concentration of substance in preparation or article				
	Other relevant operational conditions of use	No measured data are available for releases of citric acid to air and waste water from textile production sites. Releases are therefore estimated on the basis of information in the public domain. Potential exposure to humans and especially the environment is dependent on the intended function of the substance, as well as the substrates and processes used. Functional finishing agents and other chemically reactive substances are intended to be consumed during use, therefore the amount released is related to efficiency of the process. On the other hand, non-reacting substances (e.g. processing aids) are not consumed and will ultimately be lost to air or waste water, depending on their function and physicochemical properties. In virtually all cases, it is expected that citric acid or citrate salts, as process aids, will be lost to waste water. The annual tonnage of 300 t is considered to be used at 40% in the region. The largest site is estimated to use around 6 tpa. If all passed to waste water this is:			
	Disk management massures:	6 t x 1000 kg/t / 300 = 20 kg	,		
2.4	Risk management measures:	For human health worker	evnosure at tevtile	production sites will be to aqueous	
2.1	Control of worker exposure	formulations for which no	hazard has bee culated for life cyc	n identified. In addition, relevant cle stages with higher exposures.	
	Risk management measures for industrial site	Information type	Data field	Explanation	
	Industrial site	Onsite pre-treatment of	Yes	Neutralisation	
		waste water			
		Resulting fraction of		On-site biological waste	
		initially applied amount		treatment (where present) is	
		in waste water released		expected to remove a high	
		from site to the external		proportion of citric acid, as the	
		sewage system		substance is highly	
				biodegradable. However, on-site	
				biological waste treatment is not	
				assumed as it is not known that	
				this is always present.	

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155 Version 2.0

		Air emission abatement	No measured data	
		Resulting fraction of applied amount in waste gas released to environment	No waste gases	
		Onsite waste treatment	No measured data	Secondary biological treatment may be present but this is not assumed in the scenario
		Fraction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment.	No measured data	
		Municipal or other type of external waste water treatment	None	None
		Effluent (of the waste water treatment plant) discharge rate	2000000 I/d	Default for a standard WWTP
		Recovery of sludge for agriculture or horticulture	Yes	
	Personal protective equipment (PPE)	N/A		
	Other risk management measures related to workers	N/A		
2.2	Control of environmental exposure	•		
	Frequency and duration of use		-	
	Duration, frequency and amount			
	Information on estimated exposure and	Downstream-user guidance		
3	Exposure estimation and reference to its Releases to air		vith high water solul	bility, losses to air are considered to
3		As the citrates are solids w	vith high water solul	oility, losses to air are con

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155 Version 2.0

Releases to waste water	The most likely release discharge of spent treatment. Indeed, releas	Citric acid and citrates are used in textile and leather treatment in aqueous solution. The most likely release route will be to waste water via spillage, clean out and discharge of spent treatment baths and liquors recovered in handling fabrics after treatment. Indeed, releases to waste water can be assumed to be 100%, since all the citric acid/citrate may be washed to drain.		
Technical fate of substance and los from process/use to waste, w water and air		Data field 0 kg/kg	Explanation See text	
	Fraction of applied amount lost from process/use to waste water	1 kg/kg	See text	
Predicted Exposure Concentration	s of	PEC	unit	
Environmental releases	AIR			
	Annual average local PEC in air (total)	1.56 x 10 ⁻¹⁵	[mg.m ⁻³]	
	WATER, SEDIMENT			
	Local PEC in surface water during emission episode (dissolved)	2.92 x 10 ⁻²	[mg l ⁻¹]	
	Annual average local PEC in surface water (dissolved)	2.67 x 10 ⁻²	[mg l ⁻¹]	
	Local PEC in fresh-wate sediment during emission episode	4.98 x 10 ⁻¹	[mg kg wwt ⁻¹]	
	Local PEC in seawater during emission episode (dissolved)	1.01 x 10 ⁻¹	[mg l ⁻¹]	
	Annual average local PEC in seawater (dissolved)	8.35 x 10 ⁻²	[mg l ⁻¹]	
	Local PEC in marine sediment during emission episode	1.73	[mg kg wwt ⁻¹]	
	SOIL, GROUNDWAT	ER		
	Local PEC in agric. soil (total) averaged over 30 days	5.87 x 10 ⁻¹	[mg kg wwt ⁻¹]	
	Local PEC in agric. soil (total) averaged over 180 days	1.93 x 10 ⁻¹	[mg kg wwt ⁻¹]	

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155 Version 2.0

	Local PEC in grassland (total) averaged over 180 days	7.70 x 10 ⁻²	[mg kg wwt ⁻¹]
	Local PEC in pore water of agricultural soil	2.91x 10 ⁻³	[mg l ⁻¹]
	Local PEC in pore water of grassland	1.16 x 10 ⁻³	[mg l ⁻¹]
	Local PEC in groundwater under agricultural soil	2.91 x 10 ⁻³	[mg l ⁻¹]
Exposure concentration in sewage treatment plants (STP)	No measured data are available for the concentration of citric acid in set treatment plants (STP). The concentration of the citrate has been estimated to EUSES 2.1.1. The EUSES model uses the Simple Treat sewage treatment in to predict the fate of a substance in the STP, based on the physicochemical biodegradation properties. For citric acid, SimpleTreat predicts the following: 12.6 % to water: 0.112 % to air: 0.0154 % to sludge: 87.3 % degraded. Sludge from WWTPs may be spread on agricultural soil.		e has been estimated using eat sewage treatment model on the physicochemical and predicts the following:

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Substance / User identity	
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	11. Use in paints and coatings
	Processes and activities covered by	SU3, SU21, SU22, SU17, SU18, SU19
	the exposure scenario	PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 19, PROC 21, PROC
		24
2	Operational conditions and risk manager	ment measures
	Duration an frequency of use	
	Worker	
	All applicable PROCs	>4h
	Physical form of substance: under	Solid.
	conditions of use it is used as a liquid. Concentration of substance in	
	preparation or article	
	Other relevant operational conditions	N/A
	of use	
	Formulation of exposure scenario:	A point featow formulating 40000 top of fermulated woint sould need around 40000
2.1	Formulation of exposure scenario	A paint factory formulating 10000 tpa of formulated paint could need around 10000 x 0.001 = 10 tpa of citric acid. Paint formulation is a widespread activity and this
		estimate is consistent with a total market size of 300 tpa.
		It is taken that the regional tonnage is 40 tpa.
		Assuming a worst case of 2% handling loss this is a local release of 200 kg per year. Such a wastage rate is less than for scenarios considered earlier and there is no need to calculate local exposures. The releases will be added as regional and continental losses to waste water:
		Regional = 200 x (40/10) / 365 = 2.2 kg/d
		Continental 2.2 x (260/40) = 14.3 kg/d
	Use	The coating process used by both professionals and consumers is typically by brush or roller application. For releases to waste water during consumer use, the OECD Emission Scenario Document for coatings assumes that an estimated 1% of the volatile fraction of the coating will be lost as brush residues and then end up in the sewer. The same fraction (1%) of the volatile fraction is assumed to be lost during professional use, but this is properly disposed and does not end up in the sewer [OECD, 2007].
		Therefore the amount of citric acid in the application passing to waste is estimated to be widely dispersed:
		Regional wastewater:
		0.1 x 300 tpa x 1000 kg/t x 0.01 /365 = 0.82 kg/d
		Continental wastewater:
		0.9 x 300 tpa x 1000 kg/t x 0.01 /365 = 7.40 kg/d

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155 Version 2.0

	Therefore, for simplicity, for this application area, the totals are: Regional wastewater:
	+ 0.82 = 3.0 kg/d
	Continental wastewater:
	14.3 + 7.4 = 21.7 kg/d
	For human health worker exposure at paint production sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Substance / User identity	
	Registration number(s)	01-2119520510-57-0002
	Substance identity	CAS# 7775-14-6 ,EC#231-890-0
1	Short title of the exposure scenario	12. Use in photography
	Processes and activities covered by	SU20,SU21,SU22
	the exposure scenario	PROC5, PROC 13
2	Operational conditions and risk manage	ment measures
	Duration an frequency of use	
	Worker	
	All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.
	Concentration of substance in preparation or article	
	Other relevant operational conditions of use	N/A
	Formulation of exposure scenario:	
2.1	Exposure scenario	Citric acid is one of a range of complexing agents used in photography to control the effects of calcium and magnesium hardness, and to keep iron soluble in solution as part of redox processes.
		Due to the rapid growth of digital photography, use of chemicals in film processing is now limited almost entirely to a small number of professional providers. The chemicals used are collected by photochemical companies in order to recover silver and disposal to drain does not take place.
		Citrate may also be used as a stop bath in professional or consumer settings as part of the process for the manual development of photographic film. Releases to the environment from this application are insignificant compared to those from considered in other exposure scenarios (cleaning products for example).
		Therefore this scenario need not be considered further in respect of the environment.
	human health	For human health, the processes applied during both professional and consumer uses are: PROC 9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC 5 Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) PROC 13 Treatment of articles by dipping and pouring

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

Printing date:6/5/2011

Revision date: 6/5/2011		

	Substance / User identity	
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	13. Use in paints and coatings
	Processes and activities covered by	SU3
	the exposure scenario	PROC 1, PROC 2, PROC 4, PROC 8a
2	Operational conditions and risk manager	ment measures
	Duration an frequency of use	
	Worker	
	All applicable PROCs	>4h
	Physical form of substance: under	Solid.
	conditions of use it is used as a liquid. Concentration of substance in	
	preparation or article	
	relevant operational conditions of use	Following the REACH descriptor system [ECHA, 2009] the following sector of use is covered by this scenario: SU3 Industrial uses
		The relevant product category is PC21 Laboratory chemicals
		Citric acid may be used at low levels within laboratories. Exposures will take place but under highly controlled conditions. Therefore this scenario need not be considered further for human health or the environment.

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Substance / User identity	
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	14. Use in water treatment
	Processes and activities covered by	SU3, SU14, SU15, SU16, SU17,
	the exposure scenario	PROC 1, PROC 2, PROC 3, PROC 4, PROC 7, PROC 8a, PROC 8b, PROC 9,
		PROC 10, PROC 13, PROC 17, PROC 18, PROC 20, PROC 23, PROC xyz ¹
2	Operational conditions and risk manage	ment measures
	Duration an frequency of use	
	Worker	
	All applicable PROCs	>4h
	Physical form of substance: under	Solid.
	conditions of use it is used as a liquid.	Golid.
	Concentration of substance in preparation or article	
	relevant operational conditions of use	This scenario covers use in smaller-scale circulating water treatment in industrial settings, which typically use high substance concentration at low discharges and would usually have a waste water treatment plant (WWTP) in place. The degradability of citric acid in power station cooling systems makes in not suitable for such purposes.
	Formulation of exposure scenario:	
2.1	Industrial cooling systems	Industrial cooling systems can be categorized by their design and by using water as coolants. The exchange of heat between process medium and coolant is enhanced by heat exchangers. From the heat exchangers the coolant transports the heat into the environment.
		Usage of water treatments containing citrates would be continuous for the correct functioning of the cooling water system. Re-loading may be needed more or less frequently, for open and closed cooling water systems respectively, to refresh the system.
		The worst-case for the local environment is to assume treatment of a large industrial plant, open cooling system, which requires the use of large volumes of a high concentration product on a continuous basis and involves the direct release of blow down effluent to the river or receiving water.
	In open recirculating systems	In open recirculating systems, alkaline conditions (pH of 8-9), in combination with organic complexing agents are effective against corrosion and scaling. Most currently used corrosion programmes are based on phosphates, and zinc is added if water conditions require this.
		Typical concentrations of scale control agents (polyphosphates, phosphonates, polyacrylates, copolymers and ter-polymers) range from 2 to 20 mg/l, as active compound. Hardness stabilisers prevent the formation of crystals and are used in recirculating systems, but rarely or never in once-through systems. Citrates may be used to enhance the performance of the other additives.
		In most downstream uses treatment chemicals are applied in water-based processes. The final concentration in the water used in scale inhibition is typically from less than 1 to 10 ppm. Depending on the exact nature of the process, the complexing agents may remain present in the aqueous effluent and the discharge streams. These streams will be treated on the user's site, discharged to sewer

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	systems or discharged to waterways (wide dispersive use).
	Given the low volatility and the high water solubility of the substances, direct releases to air and soil can be considered negligible.
Wastewater	In the UK, the capacity of 50% of installed base cooling towers is in the range of 22.7 m³ and 227 m³ (OECD, 2004). The water circulation rate of a typical open cooling system (with capacity of 100 m³), for an industrial plant, is assumed to be 350 m³/h (3.5 times the capacity). The blowdown of open cooling systems is related to the rate of evaporation (1% of the circulation rate) and the concentration cycle, which is the ratio (typically 3) of the maximum concentration of dissolved solids in the recirculating water to the concentration in the make up water (OECD, 2004). For the purpose of this calculation, a scaling inhibitor product with an active content of citrate at 25% is assumed. Therefore, for a blowdown of 1.75 m³/h from an open cooling system; the estimated release of citrates to water is
	0.25 x 20 mg/l x 1.75 m ³ /h x 1000 l/m ³ x 24 h/d x 10-6 kg/mg = 0.44 kg/day.
	This is lower than ES considered above and there is therefore no need to develop the scenario further.
	In the nature of the use it must be assumed that all the citric acid used in water treatment could pass to waste water. Therefore:
	Regional wastewater:
	x 1000 tpa x 1000 kg/t /365 = 274 kg/d
	Continental wastewater:
	0.9 x 1000 tpa x 1000 kg/t x /365 = 2470 kg/d
human health	For human health worker exposure at industrial sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Out-1/11	
	Substance / User identity	04 04404
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	15. Use in metal surface treatment
	Processes and activities covered by	SU3, SU14, SU15, SU16, SU17, SU21,SU22
	the exposure scenario	PROC 2, PROC 3, PROC 4, PROC 7, PROC 8a, PROC 8b, PROC 9, PROC 10,
		PROC 13, PROC 17, PROC 18, PROC 23
2	Operational conditions and risk manage	ment measures
	Duration an frequency of use	
	Worker	
	All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.
	Concentration of substance in preparation or article	
	relevant operational conditions of use	Citric acid may be used as a complexing agent during metal surface treatment operations. This includes cleaning, brightening and passivation of fabricated stainless steel components, and other metal components, cleaning of circuit boards prior to soldering, and metal cleaning or chemical polishing for the surface treatment of aluminium, copper and other metals. The following applications should be taken as representative rather than the sole example of where and why citric acid or citrates may be used in the treatment of metal surfaces. Some industries using citric acid include fasteners, medical devices, semi-conductors, automotive and aerospace.
	Passivation	Citric acid may be used in stainless steel passivation to remove iron from the surface of the stainless steel and prevent later corrosion. After thorough cleaning, the stainless steel part is immersed in a passivating acid bath. Any one of three approaches can be used: nitric acid passivation, nitric acid with sodium dichromate passivation and citric acid passivation. Which approach to use depends on the grade of stainless steel and prescribed acceptance criteria. When citric acid passivation is used, typical solutions range from 4 to 10% citric acid by weight.
	Electroless plating	Plating describes the coating of surfaces with metals, either through an electrolysis or electroless plating processes. Electroless plating is also known as 'autocatalytic' plating; deposition of the metal starts on metal nuclei such as palladium and continues autocatalytically. Electroless plating is favoured over electrolysis for most component production (EA 2009).
		There are usually three stages in the electroless plating process: de-smearing, activation and electroless copper plating. The plating solution has a copper content of $2-5$ g/l, with sodium hydroxide ($15-20$ g/l), complexing agents ($10-15$ g/l) or tartrates ($5-10$ g/l) and reducing agents, such as formaldehyde ($3-5$ g/l). The process solution lifetime is limited by the build-up of reaction products and is proportional to the rate of throughput of components (EA 2009). Citrate may be used as a complexing agent.
		Electroless plating involves the large-scale use of water in both providing the medium for the process itself and for the subsequent rinsing and washing of components. There is a degree of recycling of rinse water through use to top-up the plating tanks, but there is ultimately loss through carry-over on components. Spent fluids can only be topped up a limited number of times before the media needs replacing. Water-soluble waste is discharged in waste water for basic on-site

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

		treatment (settling and pH adjustment) before discharge to municipal treatment works, controlled by local discharge consent agreements (EA 2009).
	Exposure scenario:	
2.1	Environment exposure	The use of citrate in metal-surface treatment is estimated as approx. 1000 tpa. Therefore, environmental releases are not dissimilar to those discussed in the cleaning scenario (ES5) but on a much smaller scale. Therefore, it is not considered necessary to further assess environmental exposure.
	human health	For workers, exposures are not expected to be greater than those discussed in other industrial use scenarios. The basic risk management measures discussed for these scenarios are considered sufficient to ensure safe use. Human health exposure is not discussed further.

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Substance / User identity	
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	16. Use in agriculture
	Processes and activities covered by the exposure scenario	SU1, SU3, SU21, SU22 PROC 3, PROC 5, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 14, PROC 15, PROC 19
2	Operational conditions and risk manage	ment measures
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.
	Concentration of substance in preparation or article	
	relevant operational conditions of use	This scenario covers use in smaller-scale circulating water treatment in industrial settings, which typically use high substance concentration at low discharges and would usually have a waste water treatment plant (WWTP) in place. The degradability of citric acid in power station cooling systems makes in not suitable for such purposes.
	Formulation of exposure scenario:	
	Wastewater	The amount of citric acid believed to be used in this application is at most 1500 tpa. The use per site is unknown, but this should be considered as a widely dispersed use. In the worst case a release of the entire tonnage to the region could be included, i.e. 1500 tpa. Of this, part will be released to agricultural soil (90%) and part to waste water (10%).
		A regional release of $150 \times 1000/365 = 411 \text{ kg/d}$ to waste water will be added to the model, and 3699 kg/d to soil will be included.
	human health	For human health worker exposure will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

Revision	Revision date: 6/5/2011				

	Substance / User identity					
	Registration number(s)	01-2119457026-42-0004				
	Substance identity	CAS#77-92-9; EC#201-069-1				
1	Short title of the exposure scenario	17. Use in medical devices				
	Processes and activities covered by	SU3, SU20, SU22				
	the exposure scenario	PROC 1				
2	Operational conditions and risk manager	Operational conditions and risk management measures				
	Duration an frequency of use					
	Worker					
	All applicable PROCs	>4h				
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.				
	Concentration of substance in preparation or article					
	relevant operational conditions of use	Citrates may be used in medical devices, for example, citrate is added to human blood to prevent coagulation. The whole blood collection process is a closed process as sterility must be maintained. Procedures are carried out by trained personnel in a controlled environment. Therefore, exposures from this use are expected to be minimal and the scenario is not considered further for human health or the environment.				

According to Regulation (EU) No. 1907/2006, Annex II, Amended by REGULATION (EU) No 453/2010

Citric acid

SDS Record Number: CSSS-TCO-010-100155

Version 2.0

	Substance / User ide	Substance / User identity							
	Registration number	(s)	01-2119	9457026-42-0	004				
	Substance identity		CAS#77	7-92-9; EC#20	01-069-1				
1	Short title of the expo	18、Re	18、Regional exposure concentrations						
	Processes and activities covered by		y N/A	N/A					
	the exposure scenari								
2	Regional exposure	Regional exposure concentrations							
		Predicted Exposure Concentration	regional ons	al Measured regional exposure concentrations		Explanation / source of measured data			
		value	unit	value	unit				
	Freshwater	1.52 x 10 ⁻²	mg/l	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1			
	Marine water	1.41 ⁻³	mg/l	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1			
	Freshwater sediments	3.32 x 10 ⁻¹	mg/kg d.w.	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1			
	Marine sediments	2.60 x 10 ⁻²	mg/l	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1			
	Agricultural soil	3.19 x 10 ⁻³	mg/kg wwt	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1			
	Grassland	7.47 x 10 ⁻¹²	mg/kg wwt	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1			
	Air	1.24 x 10 ⁻¹⁹	(mg/m ³)	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1			



COMPANY INFORMATION DISTRIBUTOR						
name	BRENNTAG N.V.	BRENNTAG Nederland B.V.				
address	Nijverheidslaan 38 8540 Deerlijk	Donker Duyvisweg 44 3316 BM Dordrecht				
country	Belgium	The Netherlands				
phone number	+32 (0)56 77 69 44	+31 (0)78 65 44 944				
fax number	+32 (0)56 77 57 11	+31 (0)78 65 44 919				
website	www.brenntag.be	www.brenntag.nl				
e-mail	info@brenntag.be	info@brenntag.nl				
activities	Distribution and e	Distribution and export of chemicals and raw materials				
VAT number	BE0405317567	NL001375945B01				
recall procedure available		Yes				
emergency number (24/365)	+32 (0)56 77 69 44	+31 (0)78 6544 944				
QUALITY SYSTEMS						
ISO 9001	Yes	Yes				
ISO 14001	Yes	Yes				
ISO 22000	Yes	Yes				
FSSC 22000	Yes	Yes				
GMP+ -feed	Yes	Yes				
OHSAS18001	-	Yes				
ESAD	Yes	Yes				
other	-	AEO				