



6,00
mmSPECIAL
THICKNESS

- (GB) „C“ PROFIL GUIDE FOR CANTILEVER GATE
- (D) „C“ PROFIL FÜR FREITRAGENDE SCHIEBETÖRE
- (F) GUIDE À PROFIL EN « C » POUR PORTAIL AUTOPORTANT
- (E) GUÍA CON PERFIL "C" PARA PUERTA VOLADIZA
- (P) GUIA DE PERFIL "C" PARA PORTÃO CANTILEVER
- (I) GUIDA CON PROFILO A "C" PER CANCELLO AUTOPORTANTE
- (DK) "C" PROFILVANGE TIL FRITTBÆRENDE PORT
- (NL) "C" PROFIEL GELEIDER VOOR VRIJDRAGENDE SCHUIFPOORT
- (N) "C"-PROFILSKINNE FOR FRITTBÆRENDE PORTX
- (S) "C" GEJDPROFIL FÖR FRIBÄRANDE GRIND
- (FIN) "C" -PROFILLIÖHJAIN ULOKEKANNETTEISEEN PORTTIIN
- (PL) SZYNA DO BRAM SAMONOŚNYCH
- (SK) NOSNÝ „C“ PROFIL PRE POSUVNÚ SAMONOSNÚ BRÁNU
- (EE) "C"-PROFILI JUHIK KONSOOLVÄRAVA JAOKS
- (LT) „C“ FORMOS PROFILIUOTAS KREIPTUVAS GEMBINIAMS VARTAMS
- (LV) "C" VEIDA PROFILS KONSOLVEIDA VÄRTIEM

- (CZ) ŠÍNA „C“ PROFIL PRO POSUVNOU SAMONOSNOU BRÁNU
- (RO) GHIDAJ CU PROFIL „C“ PENTRU POARTA AUTOPORTANTĂ ÎN CONSOLĂ
- (HR) VODILICA „C“ PROFILA ZA KLIZNA DVORIŠNA VRATA
- (RUS) НАПРАВЛЯЮЩИЙ РЕЛЬС / ПРОФИЛЬ «С» ДЛЯ ОТКАТНЫХ САМОНЕСУЩИХ ВОРОТ
- (SLO) "C" VODILO ZA SAMONOSNA DRŠNA VRATA
- (TR) KONSOL BAHÇE KAPISI İÇİN "C" PROFIL KIZAĞI
- (AR) للبوابة المدعومة "C" دعامة خفيفة جانبية
- (CHN) 悬臂门"C"型导轨
- (MAL) PANDU PROFIL "C" UNTUK PINTU PAGAR JULUR
- (H) C-VEZETŐSÍN TOLÓKAPUHOZ
- (IL) קורה בפרופיל "C" לשער קונסולי
- (BG) "C"-ОБРАЗНА РЕЛСА ЗА КОНЗОЛНА ВРТА
- (KO) 캔틸레버 게이트용 "C"자형 프로파일 가이드
- (SRB) VODICA „C“ PROFILA ZA SAMONOSIVU KAPIJU

Art.	CARRIAGE	SURFACE FINISH	L/1pc	1pc			CODE
			mm	kg	pcs	kg	
STAGE LB 6	SPEED L	UNGALVANIZED	6000	130,2	6	781,2	1700179
STAGE LB 3	SPEED L	UNGALVANIZED	3000	65,1	6	390,6	1700178
STAGE LB 2	SPEED L	UNGALVANIZED	2000	43,4	6	260,4	1700218
STAGE LB 1	SPEED L	UNGALVANIZED	1000	21,7	6	130,2	1720046
STAGE LZ 6	SPEED L	GALVANIZED	6000	130,2	6	781,2	1700180
STAGE LZ 3	SPEED L	GALVANIZED	3000	65,1	6	390,6	1700019
STAGE LZ 2	SPEED L	GALVANIZED	2000	43,4	6	260,4	1700220
STAGE LZ 1	SPEED L	GALVANIZED	1000	21,7	6	130,2	1720052

24
months24 MONTHS
TESTED
& PROVEN- 37°C
TESTED
& PROVEN+ 50°C
TESTED
& PROVEN