

## Product information

# 98 20 65

- Ergonomically optimised dual component handle for fatigue reduced work and optimum transmission of force
- Handle design prevents rolling
- Chrome vanadium molybdenum steel

## Screwdrivers for slotted screws

IEC 60900 DIN EN 60900



⚡ 1000 V ⚡

### General

|               |   |
|---------------|---|
| Article No.   | 98 20 65                                      |
| EAN           | 4003773026419                                 |
| point         | burnished                                     |
| Handles       | insulating multi-component handle, VDE-tested |
| Weight        | 105 g   |
| Dimensions    | 262 x 35 x 32 mm                              |
| Standard      | DIN EN 60900 IEC 60900                        |
| Reach-konform | no  |
| RohS-konform  | no  |

### Technical details

|                               |        |
|-------------------------------|--------|
| Blade length                  | 150 mm |
| Length of non-insulated blade | 15 mm  |
| Handle length                 | 112 mm |
| Blade width                   | 6.5 mm |
| Blade thickness               | 1.2 mm |
| VDE tested                    | yes    |

### Classification

|                |            |
|----------------|------------|
| eCl@ss 5.1.4   | 21040401   |
| ETIM 5.0       | EC000158   |
| ETIM 6.0       | EC000158   |
| proficl@ss 6.0 | AAA817c008 |
| UNSPSC 13.1    | 27111701   |

*technical change and errors excepted*