
FRANKLY AMSTERDAM





ALL STAR

Manufacturing Pile surface Material Carpet weight Carpet thickness Roll width Backing Fire classification Colors Delivery time Advantages

Installation

Flatwoven Loop pile 100% P.P. ± 1.650 g/m² ± 5 mm 4 meters Gel backing. For 8801 and 8808 Precoat Latex Cfl-s1 / Efl for color 8801 and 8808 11 standard 1 - 6 weeks ± suitable for indoor and outdoor use

- + suitable for residential and contract
- + available as wall-to-wall, carpet and stair runner

+ waterproof and UV proof

- + easy cleaning, even with bleach
- + castor proof

Please reference our digital contract brochure. Rubber underlayment is recommended for all wall-to-wall installations and area rugs. This flat woven carpet allows you to move around the space without any worries. Its water and UV-resistance makes it perfect for both indoor and outdoor applications, and it's suitable for residential and commercial installations.

Due to the different production dyelots, slight variation in color tone may occur. A small deviation from the sample swatches are not considered flaws.

Rugs with a folded padded edge will have felted padding at the bottom, therefor they can only be used indoors and can not be used for stair runners. Please calculate a 10 cm margin around all edges for a rug with folded padded edge. Maximum rug width for this finish is 380 cm.



Classification EN 1307:2014 and EN 14041:2004



CARE INSTRUCTIONS

- We advise you to **vacuum** the carpet once or twice a week for domestic applications and light use areas. For commercial applications and heavier traffic use, daily vacuuming is advised to reduce the presence and buildup of loose dirt particles.

- For flat weave carpets use a suction only vacuum to prevent distortion or pilling of the carpet surface. Do not use the brush or beater bar.

- While vacuuming, the starting point should be varied each time to make sure that the carpet is not always brushed in the same direction.

- Wet stains need to be removed immediately. Absorb the stain using a strong absorbing paper (like kitchen paper) or clean towel.

- **High traffic area stains** from castor wheels, luggage and service trollies may result in rubber transfer markings. Remove rubber stains and markings from the fibres using an approved gel type solvent. The treated area must be thoroughly rinsed out

- Light stains can safely be treated with JAMES cleaning agents, which have been successfully tested on our products. Please follow the instructions of the JAMES staindisc delivered with the James starter kit. Treating stains within 24 hours increases the possibility of successful stain removal, nevertheless, complete removal can never be guaranteed. The usage of a cleaning agent that is not tested on our products cannot be guaranteed for safe cleaning.

- When **cleaning with bleach**, gently rub a water diluted bleach solution on the stain and let it sit for a few minutes. Don't let the bleach dry. Avoid soaking the carpet with bleach. Wipe off with water and allow to dry before use.

- In case of **heavy staining** or transferred dirt, we advise you to always have your rug cleaned by a specialist in rug cleaning.

- To avoid the carpet getting moldy while using **outdoor**, hang or lay down the rug in sunlight on a clean surface to dry.

- When you **store** the outdoor carpet (during cold or rainy seasons) it must be cleaned and dried properly first. Roll up the dry and clean carpet on a tube, wrap it in plastic and secure it with tape. Never fold the carpet while storing it.

WARRANTY

- Frankly Amsterdam guarantees its carpets for 2 years of normal use.

- All our products are made with care. In case a **manufacturing defect** escaped our attention, please inform us within 14 days after delivery and leave the product unused.

- Small differences or **irregularities** in color, weft or size may occur. This is to be accepted when within normal commercial tolerances.

- Frankly Amsterdam will not accept any complaint if shading is concerned.

