


SAFETY DATA SHEET



ARCUS HOBBY COLORS

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : E001 Enamel Thinner

EC number : 919-857-5

CAS number : -

Product description : THINNER

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

☒ Uses in coatings - Consumer use. Apply this product only as specified on the label and in the safety data sheet.
Uses in Coatings - Industrial use. Thinner.
Uses in Coatings - Professional use. Thinner.

1.3 Details of the supplier of the safety data sheet

Manufacturer or Distributor

ARCUS HOBBY COLORS

P.O. Box 121

Vinogradnaya 47

Ukraine

Telephone +2560688938808

e-mail address of person responsible for this SDS : ARCUS HOBBY COLORS, e-mail: arcus.trade@gmail.com

1.4 Emergency telephone number

Telephone number : 112
(24h)

Supplier or Manufacturer

Telephone number : ARCUS HOBBY COLORS
+2560688938808 (GMT +2) Mon-Fri 8-16

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : UVCB

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

STOT SE 3, H336

Asp. Tox. 1, H304

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended

2.2 Other hazards

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.1 Substances : UVCB

| Product/ingredient name | Identifiers | % | <u>Classification</u> Regulation (EC) No. 1272/2008 [CLP] | Notes |
|---|-------------------------|-----|--|-------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | EC: 919-857-5 CAS: - | 100 | Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066 See Section 16 for the full text of the H statements declared above. | H,P |

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC.

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Show this safety data sheet or label to the doctor if possible.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of lukewarm water, keeping eyelids open. Continue to rinse for at least 15 minutes. Get medical attention if symptoms occur.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention

| | |
|---------------------|--|
| Skin contact | : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. |
| Ingestion | : Aspiration hazard if swallowed. Can enter lungs and cause damage. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Remove to fresh air and keep at rest in a position comfortable for breathing. Do NOT induce vomiting. |

4.2 Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1 Extinguishing media

| | |
|---------------------------------------|---|
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. Recommended: Alcohol resistant foam, CO ₂ , powders or water spray/mist. |
| Unsuitable extinguishing media | : Do not use a direct water jet that could spread the fire. |

5.2 Special hazards arising from the substance or mixture

| | |
|--|--|
| Hazards from the substance or mixture | : Flammable liquid and vapor. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard. |
| Hazardous combustion products | : When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc. |

5.3 Advice for firefighters

| | |
|---|---|
| Special protective actions for fire-fighters | : Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. Do not release runoff from fire to drains or watercourses. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |

SECTION 6: Accidental release measures

| | |
|--|--|
| 6.1 Personal precautions, protective equipment and emergency procedures | : Shut off all ignition sources. No flares, smoking or flames in hazard area. Provide adequate ventilation. Avoid breathing vapor or mist. Avoid direct skin contact with product. See Section 8 for information on appropriate personal protective equipment. |
| 6.2 Environmental precautions | : Do not allow to enter drains, water courses or soil. |
| 6.3 Methods and materials for containment and cleaning up | : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with a detergent. Avoid using solvents. |
| 6.4 Reference to other sections | : See Section 1 for emergency contact information. See Section 13 for additional waste treatment information. |

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- : Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. Isolate from sources of heat, sparks and open flame. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. No sparking tools should be used.
Skin contact with the product and exposure to spray mist and vapor should be avoided. Avoid contact with skin and eyes. Avoid inhalation of dust from sanding. Wear appropriate respirator when ventilation is inadequate. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

- : Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store and use away from heat, sparks, open flame or any other ignition source. No smoking. Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Recommended storage temperature is +5°C ...+25°C. Store in accordance with local regulations.

7.3 Specific end use(s)

- : See Appendices:
As scaling result (ECETOC TRA Tool) following use conditions represent safe use of the product when product is used according to the product specific instructions.

Uses in coatings - Consumer use.

Solvent rich, high solid, waterborne paints.

Unless otherwise stated. Covers use up to 6 days per year
Covers use up to 1 time per day.

For each use event, covers use amounts up to 10 kg Paint.

Covers use under typical household ventilation.

Covers use in room size of 20 m³

For each use event, covers use amounts up to 8 hours per event

Removers (paint-, glue-, wall paper-, sealant-remover)

Unless otherwise stated. Covers use up to 6 days per year

Covers use up to 1 time per day.

Covers use up to 7,5 kg Removers (paint-, glue-, wall paper-, sealant-remover)

Covers use under typical household ventilation.

Covers use in room size of 20 m³

For each use event, covers use amounts up to 8 hours per event

Fillers and putty

Unless otherwise stated. Covers use up to 12 days per year

Covers use up to 3 kg Fillers and putty

Covers use in room size of 20 m³

For each use event, covers use amounts up to 4 hours per event

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof ventilation equipment. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn (see Personal protection). Comply with the health and safety at work laws.

Individual protection measures

- Eye/face protection** : Use safety eyewear designed to protect against splash of liquids (EN166).
- Hand protection** : Wear protective gloves. Gloves should be replaced regularly and if there is any sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.
Recommended glove material (EN374):
< 1 hour (breakthrough time): nitrile rubber
> 8 hours (breakthrough time): fluor rubber, laminated foil
Not recommended: PVC or natural rubber (latex) gloves
- Skin protection** : Wear suitable protective clothing. This product is classified as flammable. If necessary, personnel should wear antistatic clothing made of natural fibers or of high-temperature-resistant synthetic fibers.
- Respiratory protection** : If ventilation is inadequate, use respirator that will protect against organic vapor and dust/mist. During spray-application use respirators with combination filter A/P3 (EN405:2001). Wear a half mask or full face respirator with gas and vapor filter A and dust filter P2 during sanding (EN140:1998, EN405:2001). During continuous and long-term work the use of motor-driven or air-fed respirators is recommended (EN12941:1998). Be sure to use an approved/certified respirator or equivalent. Check that mask fits tightly and change filter regularly.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Clear.
- Odor** : Strong.
- Odor threshold** : Not relevant for the hazard assessment of the product.
- pH** : Not relevant for the hazard assessment of the product.
- Melting point/freezing point** : <-15°C
- Initial boiling point and boiling range** : 150 to 200°C
- Flash point** : Closed cup: 36°C
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not applicable. Product is a liquid.

| | |
|--|--|
| Upper/lower flammability or explosive limits | : Lower: 0.6% Upper: 7% |
| Vapor pressure | : 0.3 kPa |
| Vapor density | : >3 [Air = 1] |
| Density | : 0.8 g/cm ³ |
| Solubility(ies) | : insoluble in water. |
| Partition coefficient: n-octanol/water | : Not available. |
| Auto-ignition temperature | : 250°C |
| Decomposition temperature | : Not relevant for the hazard assessment of the product. |
| Viscosity | : Not relevant for the hazard assessment of the product. |
| Explosive properties | : No explosive ingredients present. |
| Oxidizing properties | : No oxidizing ingredients present. |

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

Molecular weight : 146 g/mole

No additional information.

SECTION 10: Stability and reactivity

- | | |
|--|--|
| 10.1 Reactivity | : See Section 10.5. |
| 10.2 Chemical stability | : Stable under recommended storage and handling conditions (see Section 7). |
| 10.3 Possibility of hazardous reactions | : May present an explosion hazard when material is suspended in air in confined areas or equipment and subjected to spark, heat or flame. |
| 10.4 Conditions to avoid | : Avoid extreme heat and freezing. Avoid all possible sources of ignition (spark or flame). |
| 10.5 Incompatible materials | : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents strong acids strong alkalis |
| 10.6 Hazardous decomposition products | : When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc. |

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There is no testdata available on the product itself.

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting.

Acute toxicity

Not classified.

Sensitization

Not classified.

Mutagenicity

Not classified.

Carcinogenicity

Not classified.

Reproductive toxicity

Not classified.

Teratogenicity

Not classified.

Specific target organ toxicity (single exposure)

May cause drowsiness or dizziness.

| Product/ingredient name | Category | Route of exposure | Target organs |
|---|------------|-------------------|------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | Category 3 | - | Narcotic effects |

Specific target organ toxicity (repeated exposure)

Not classified.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not applicable.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

Ecological testing has not been conducted on this product.

The product is not classified as environmentally hazardous according to Regulation (EC) 1272/2008.

Do not allow to enter drains, water courses or soil.

12.1 Toxicity : No specific data.

Not available.

12.2 Persistence and degradability

: No specific data.

12.3 Bioaccumulative potential : No specific data.

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

| Product/ingredient name | PBT | P | B | T | vPvB | vP | vB |
|---|-----|-----|-----|----|------|-----|-----|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | No | N/A | N/A | No | N/A | N/A | N/A |

12.6 Endocrine disrupting properties : Not applicable.

12.7 Other adverse effects : Not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : Remove as much product as possible from the tools before cleaning. Liquid residue and cleaning liquids are hazardous waste and must not be emptied into drains or sewage system, but handled in accordance with national regulations. Product residues should be left at special companies which have permission for gathering this kind of wastes.

European waste catalogue (EWC)

| Waste code | Waste designation |
|------------|---|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances |

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging


Methods of disposal : Empty packaging should be recycled or disposed of in accordance with national regulations.


Special precautions : None.


SECTION 14: Transport information

| | ADR/RID | IMDG | IATA |
|--|--|--|--|
| 14.1 UN number or ID number | UN1268 | UN1268 | UN1268 |
| 14.2 UN proper shipping name | PETROLEUM DISTILLATES, N.O.S. (hydrocarbons) | PETROLEUM DISTILLATES, N.O.S. (hydrocarbons) | Petroleum distillates, n.o.s. (hydrocarbons) |
| 14.3 Transport hazard class(es) | 3 | 3 | 3 |
| 14.4 Packing group | III | III | III |
| 14.5 Environmental hazards | No. | No. | No. |

Additional information

ADR/RID :  **Hazard identification number** 30
Limited quantity 5 L
Special provisions 363, 664
Tunnel code (D/E)

IMDG :  **Emergency schedules** F-E, S-E
Special provisions 223, 363, 955

IATA :  **Quantity limitation** Passenger and Cargo Aircraft: 60 L.. Packaging instructions: 355. Cargo Aircraft Only: 220 L.. Packaging instructions: 366. Limited Quantities - Passenger Aircraft: 10 L.. Packaging instructions: Y344.
Special provisions A3

- 14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
- 14.7 Maritime transport in bulk according to IMO instruments** : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Other EU regulations

Europe inventory : This material is listed or exempted.

Persistent Organic Pollutants

Not listed.

VOC max value (g/l) : 100

15.2 Chemical Safety Assessment : Complete.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification

Justification

| | |
|--------------------|-----------------|
| Flam. Liq. 3, H226 | Expert judgment |
| STOT SE 3, H336 | Expert judgment |
| Asp. Tox. 1, H304 | Expert judgment |

Full text of abbreviated H statements : H226 Flammable liquid and vapor.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.
EUH066 Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS] : Asp. Tox. 1 ASPIRATION HAZARD - Category 1
Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3
STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

Date of issue/ Date of revision : 5/24/2022

Date of previous issue : 1/25/2018

Version : 3

Notice to reader

This Safety Data Sheet is prepared in accordance with Annex II (EU) No 878/2020 to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Annex to the extended Safety Data Sheet (eSDS)

Identification of the substance or mixture

Product definition : UVCB
Code : 0061050
Product name : E001 Enamel Thinner

Section 1 - Title

Short title of the exposure scenario : Thinner

List of use descriptors : **Identified use name:** Thinner.
Process Category: PROC05, PROC08a, PROC08b
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC04
Market sector by type of chemical product: Not applicable.
Article category related to subsequent service life: Not applicable.

Environmental contributing scenarios : ERC4

Health Contributing scenarios : PROC5, PROC8a, PROC8b

| | |
|--|--|
| Processes and activities covered by the exposure scenario | : Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities. |
|--|--|

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1: ERC4

This substance is not classified for environmental hazards nor is a PBT/vPvB, an exposure assessment is not required.

Contributing scenario controlling worker exposure for 2: PROC5, PROC8a, PROC8b

| | |
|--|--|
| Concentration of substance in mixture or article | : Covers percentage substance in the product up to 100 %. |
| Physical state | : Liquid, vapor pressure 0.5 - 10 kPa at Standard Temperature and Pressure |
| Amounts used | : No limit. |
| Frequency and duration of use/exposure | : Covers daily exposures up to 8 hours |
| Other conditions affecting workers exposure | : Assumes use at not more than 20°C above ambient temperature. Assumes a good basic standard of occupational hygiene has been implemented |
| Conditions and measures related to personal protection, hygiene and health evaluation | |
| Advice on general occupational hygiene | : Assumes a good basic standard of occupational hygiene has been implemented |
| Personal protection | : See Section 8 of the safety data sheet (personal protective equipment). |
| Respiratory protection | : See Section 8 of the safety data sheet (personal protective equipment). |

Annex to the extended Safety Data Sheet (eSDS)

Identification of the substance or mixture

Product definition : UVCB
Code : 0061050
Product name : E001 Enamel Thinner

Section 1 - Title

Short title of the exposure scenario : Uses in Coatings

List of use descriptors : **Identified use name:** Thinner.
Process Category: PROC05, PROC08a
Substance supplied to that use in form of: As such
Sector of end use: SU22
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08a, ERC08d
Market sector by type of chemical product: Not applicable.

Environmental contributing scenarios : ERC8a, ERC8d

Health Contributing scenarios : PROC5, PROC8a

Processes and activities covered by the exposure scenario : Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities.

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1: ERC8a, ERC8d

This substance is not classified for environmental hazards nor is a PBT/vPvB, an exposure assessment is not required.

Contributing scenario controlling worker exposure for 2: PROC5, PROC8a

Concentration of substance in mixture or article : Covers percentage substance in the product up to 100 %.

Physical state : Liquid, vapor pressure 0.5 - 10 kPa at Standard Temperature and Pressure

Amounts used : No limit.

Frequency and duration of use/exposure : Covers daily exposures up to 8 hours

Other conditions affecting workers exposure : Assumes use at not more than 20°C above ambient temperature.
Assumes a good basic standard of occupational hygiene has been implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Advice on general occupational hygiene : Assumes a good basic standard of occupational hygiene has been implemented

Personal protection : See Section 8 of the safety data sheet (personal protective equipment).

Respiratory protection : See Section 8 of the safety data sheet (personal protective equipment).