PRODUCT INFO



COMMUTER-BAG TWO URBAN

Bike briefcase with flap closure and QL3.1 mounting system























QL3/QL3.1mounting	components	(incl.)
-------------------	------------	---------

dimensions	height cm/in	width cm/in.	depth cm/in.	vol. L/cu.in.	weight g/oz.
bag	31/12.2	40/15.7	14/5.5	20/1221	1040/36.7
laptop compartment	27/10.6	40/15.7	3/1.2		

Top QL3.1 mounting

protruding hooks

SPECIFICATIONS:

- + Modern bike briefcase with flap
- + Ideal for biking to the office, city, university etc.
- + Sturdy soft-touch PU-laminated Cordura blend
- + Featuring QL3.1 mounting system
- + Mounting components are fixed to rack
- + Single handed mounting and release of bag
- + Flat mounting elements ensure smooth uncluttered back of bag
- + Height and inclindation of bag can be adjusted individually
- + Lower hook of mounting set rotatable
- + Main compartment closed with metallic buckles, flap adjustable in height
- + Zippered outer pocket (not waterproof)
- + Organizer with laptop sleeve, pen slot and key strap
- + Removable shoulder strap fixed with snaphook
- + Shoulder strap microfiber pad
- + Two strong lateral 3M Scotchlite reflectors

Contents: Commuter-Bag Two Urban with QL3.1 mounting system

Attention: Remove or stow away shoulder strap prior to biking

Optional accessories: QL3.1 mounting brakets for racks with diameter 11 to 14 mm (No. E190), QL3.1 mounting set (e.g. for a second bike),

Attention: Maximum load per pannier is 9kg / 20 lbs. We recommend weighing each loaded pannier to confirm that the maximum allowance of the pannier fixation is not exceeded. This practice is advised for both rear and front panniers. CAUTION: The maximum weight capacity of every carrier model is different. Please observe the maximum weight allowance of the carrier fitted to your bicycle. Note: Sometimes the maximum capacity of the panniers fixing system can exceed the maximum capacity of the carrier. DO NOT exceed the maximum capacity of the carrier! Note, that the use of panniers will significantly influence the handling properties of your bicycle.

Note: For reaching protection standard IP53 (5=dust protected, 3=protected against splash water coming 60° to the vertical) the roll closure must be entirely closed.

 $\textbf{ORTLIEB Sportartikel GmbH} \cdot \textbf{Rainstrasse} \ 6 \cdot 91560 \cdot \textbf{Heilsbronn}, \textbf{Germany} \cdot \textbf{T} + 49\ 9872\ 800 \cdot 0 \cdot \textbf{F} + 49\ 9872\ 800 \cdot 266 \cdot \textbf{E} \ \text{info@ortlieb.com} \cdot \textbf{www.ortlieb.com}$



08_2019