

- Ready Mixed Primer
- Application on porous and non-porous bases
- Quick-drying
- Indoor and outdoor use

capa Primer Top

SILANE AND QUARTZ RESIN FOR POROUS AND NON-POROUS SUPPORTS



DESCRIPTION

Ready-to-use adhesion primer, silane and quartz resin based, with excellent adhesion on porous and non-porous bases. Ideal for indoor and outdoor applications, prior to the application of all types of cement mortars and plasters.

APPLICATIONS

As a bonding primer, it can be used on absorbent and non-absorbent bases in addition to:

Tiles, cement mortars, rendering and prefabricated gypsum boards, anhydrite, plastic, brick, fibre cement, concrete, metal, natural or artificial stone masonry.

It acts as an adhesion layer to join plaster and cement plasters, as well as cement and lime based plasters, on porous and non-porous bases.

ADVANTAGES

Capa Primer Top guarantees a rough adhesion surface and a reduction in the base's absorption, allowing correct adherence on the following bases:

- Tiles
- Cement mortars
- Rendering and prefabricated gypsum boards
- Anhydrite
- Plastic
- Brick
- Fibre cement
- Concrete
- Metal

The product's main advantages are:

- Excellent adhesion
- Low VOC emission (Volatile Organic Compounds)
- Neutral smell
- Quick drying

INSTRUCTIONS FOR USE



- 1 The base must be clean, dry, stable, free of oils, grease and dirt.
- 2 The product can be applied by brush, roller (long hair, hard hair) or gravity spray gun.
- 3 The approximate consumption will be 0.125 - 0.175 kg/l. depending on the roughness and final nature of the base.

PRECAUTIONS AND RECOMMENDATIONS

- The product is supplied ready for use, but must be homogenised before being put into service.
- Do not apply the product at temperatures below 5°C or above 35°C.
- Do not add water or any other solid or liquid compound.
- The tools should be cleaned with water immediately after use, before the product has hardened.
- In case of gravity gun application, a uniform film needs to be formed on the final application base.
- Do not apply on wet or flooded bases.
- Use it within 1 year from the date of packaging and store in an open, dry place in its original closed container, protected from moisture.

capa Primer Top

SILANE AND QUARTZ RESIN FOR POROUS AND NON-POROUS SUPPORTS

PRESENTATION

Capa Primer Top is sold in 5 kg cans, 200 kg pallets (40 units).

TECHNICAL CHARACTERISTICS

Appearance	Viscous liquid
Colour	bluish
pH	$8,0 \pm 0,5$
Density	$1,43 \pm 0,1$ kg/l.

NOTE

Recommendations for use are based on our knowledge and experience. The technical data have been obtained under normal laboratory conditions, and may vary depending on working conditions. Since the conditions of application are not controllable by us, the information on this sheet does not imply the company's responsibility.