

KS-7090

DATENBLATT DATASHEET



KSE-LIGHTS
be tough • be safe • be different

LICHT LIGHT

Name // Name	KS-7090
Art. -Nr. // Art. No.	KS-7090
max. Lumen // max. lumens	216 lm
max. Distanz // max. distance	100 m
Anz. Schaltstufen // no. of modes	2
Optiken // optics	Reflektor // reflector
Optik #1 // optic #1	6000 Kelvin
Leuchtmittel // light source	LEDs

SCHALTSTUFEN LIGHT MODES

Arbeitsmodus // working mode	KS-7090
Lumen // lumens	100 lm
Distanz // distance	50 m
Leuchtzeit // luminous time	12 h
Powermodus // power mode	KS-7090
Lumen // lumens	216 lm
Distanz // distance	100 m
Leuchtzeit // luminous time	5 h

SICHERHEIT SAFETY

Zertifikate // certificates	KS-7090
ATEX	Ja // yes
IECEX	Ja // yes

Geräteklasse // equipment class	II 1G Ex ia IIC T4 Ga IP67
zulässige Temp. // allowed temp.	-20 °C < Ta < +40 °C

GENERELLES GENERAL

Generelles // general	KS-7090
Schutzklasse // protection class	IP67
Gehäusematerial // housing material	Kunststoff // plastic
Gehäusefarbe // color of housing	schwarz & gelb // black & yellow
Gewicht // weight	130 g (ohne Batterien // without batteries)
Garantie // warranty	2 Jahre // 2 years

Akkumulator // battery	3x AAA
------------------------	--------

Zolltarifnummern // customs tariff numbers	8513 1000
Ursprungsland // country of origin	China // China
Produktmaße // product dimensions	47mm x 79mm x 61mm
Maße Verpackung // packing dimensions	75mm x 98mm x 69mm

Lieferumfang // scope of delivery	KS-7090
Lieferumfang // scope of delivery	Stirnband // headband
Lieferumfang // scope of delivery	Anleitung // manual
Lieferumfang // scope of delivery	ohne Batterien // without batteries

15.03.2022

Erstellt durch KSE-LIGHTS
Erstelldatum
Irrtümer vorbehalten

Rückfragen // questions? -> +49 (0) 23 33 - 982 47 30

www.kse-lights.com
www.shop.kse-lights.com
[KSE-Instagram](#)
[KSE-Facebook](#)