



16000DCT Dual Clutch Transmission Fluid

Documentversie: 19 okt. 2025

Omschrijving

This Special Gearbox Fluid is a specially developed product for the wet clutch 'Double Shift Gearboxes' used in cars with a DCT transmission. MPM Dual Clutch Transmission Fluid meets the extreme requirements of high-tech Double Shift Gearboxes, featuring special additives for wet clutches.

Toepassingshandleiding

Volgens de specificaties van

BMW DCTF-1 / DCTF-2 / MTF LT-5
Citroën 9734.S2
Ford M2C218-A1 / M2C936-A
MB 236.21 / 236.22 / 236.25 / 239.21 / 239.22
Mitsubishi Dia-Queen SSTF-1
Nissan DCT fluid
Nissan GTR R35
Peugeot 9734.S2
Renault DC4 / DW5 / DW6
VW G 009 317 / 052 182 / 052 513 / 055 529 / 055 549
Volvo 1161838 / 1161839

Verpakkingseenheden

ART. NR.	VOLUME	AANTAL PER STUK	AANTAL PER PALLET
16001DCT	1 L	6	450
16004DCT	4 L	4	112
16020DCT	20 L	1	30
16060DCT	60 L	1	6
16205DCT	205 L	1	2
16999DCT	1000 L	1	-

Standaardanalyses

TEST	WAARDE		METHODE
Density bij 15°C	0.848	kg/l	ISO 12185
Colour	YellowBrown		
Viscosity	10W		
Kinematic Viscosity bij 40°C	36.48	mm ² /s	ISO 3104
Kinematic Viscosity bij 100°C	7.55	mm ² /s	ISO 3104
Viscosity Index	182		ISO 2909
Flashpoint	220	°C	EN ISO 2592
Pourpoint	-45	°C	ISO 3016

Deze waarden zijn typerend voor de huidige productie. Er kan variatie in de waarden optreden.