

SUPERIOR LC 900 series

Build-in manual bio-fireplace



EU CLASS
NORM



ECO & SAFE
BEST FOR YOU



100%
ORIGINAL

by BIOPASJA

VBSB LC 900



SAFE CONTROL

A thoughtfully designed safety chamber offers peace of mind by providing thermal insulation and ensuring any spilled bioethanol remains safely outside the combustion area. Handy indicators make bioethanol measurement a breeze.

ECO HEATER

Experience cleaner, more mesmerizing flames with our unique V-shaped tank and catalyst insert. Adjust the flames effortlessly with a safety-first cold handle.

Warranty

All Bio-fireplaces undergo a thorough quality control process, which includes a leak test to ensure their safety and performance.

Manufactured and tested according European Standard EU norm EN 16647 Predicate to test report no. 3515 A1 21

Note: All calculations and figures presented are based on controlled testing and should be considered as theoretical estimates. Actual

Discover a Fireplace that Offers Six Unique Configurations in one unit.

Introducing Biopasja's **SUPERIOR** Series: The Peak of Bio-fireplace Innovation. Immerse yourself in an exceptional world of luxury and adaptability with the **SUPERIOR** Bio-fireplace from Biopasja. It's not just a fireplace; it's a versatile design element that effortlessly blends with your interior preferences.

Left-Sided Precision: Designed for those who demand both functionality and exquisite aesthetics. Built with premium 2mm steel and a sleek black powder-coated finish, it offers easy installation, crystal-clear viewing through 10mm Optiwhite glass, and a choice of Artflame 700 burner or Dimplex vapor unit. Elevate your space with optional features like a log set tray and a 6mm black reflecting glass. Enjoy the perfect blend of style and warmth with this exceptional bio-fireplace.

MODEL	LEFT CORNER
Dimensions without profile edges in mm (L x D* x H) D+ 10 mm upper heat deflector edge - *D: 310mm (D+10) + 18 mm surrounding mounting edges - *D: 328mm	900x300x494 + 10 mm + 18mm
Burner options: A - Artflame 700 Black B - Dimplex water vapor unit	A & B
A - Artflame burner tank capacity B - Dimplex water reservoir	A - 2,8L B - 1,3L
(ARTFLAME) Flame control	Manual stainless cold handle
(ARTFLAME) Amount of ethanol combusted at maximum opening /hour	0.46 L/h
(ARTFLAME) Maximum heat at maximum opening/hour kW/h or BTU/h	2,7 kW/h or 9100 BTU/h
(ARTFLAME) Net weight without bioethanol	14,0 kg
(ARTFLAME) Required air venting grid, in cm ² (100cm ² x 2,7 kW)	270 cm ²
(ARTFLAME) Operating airflow rate, factor 99.4 Nm ³ /h / 0.1L/h	45,7 Nm ³ /h/0,46L/h*
Minimal room size m ³ (desired temp. increase with 5°C) & heating area capacity 0,1kW per 1m ² for well-insulated space	54 m ³ & 27m ²

* Nm³ stands for m³ of gas in normal conditions (101235 Pa) The value includes the moisture content of ambient air 50% relative humidity Rh

- Superior bio-fireplace made of DC01, 2mm steel, powder coated rough black (RAL9005).
- Upper heat deflector edge profile + 10mm front (28mm)
- Surrounding mounting edge profile + 18mm front.
- Glass holder Easy-simple slider Pro U04.
- Transparent tempered Optiwhite glass 10mm.
- BURNER: Artflame 700 burner or Dimplex vapor unit.
- OPTIONAL log set tray.
- OPTIONAL vertical 6mm reflecting stove painted wall glass panel.
- Cut out for support vertical reflecting glass wall panel.

