



## Hot water tank with coil 200 L

Rakentaa PW-300-A2-001

MODEL	PW-300-A2-001
TANK VOLUME	300 L
Inner tank Materials	Stainless steel 304
Material of Outer Casing	Galvanized steel sheets
Inner tank Thickness	1,5 mm
Heat insulation thickness	50 mm
Heat Insulation materials	PVC foamed cotton
Inlet Pipe Qty	1 (Cold Water Inlet) + 1 (Heat pump circulation Inlet)
Diameter of Inlet Pipe	DN20 (Cold Water Inlet) / DN25 (Heat pump circulation Inlet)
Outlet Pipe Qty	1 (Hot water Outlet) + 1 (Heat pump circulation Outlet)
Diameter of Outlet Pipe	DN20 (Hot water Outlet) / DN25 (Heat pump circulation Outlet)
Safety valve	1 pc. / DN20
Exhaust air port	-
Water Re-filling port	-
End-Terminal Return Water Pipe	1 pc. / DN20
Temperature measurement port	3 pcs / DN10
Magnesium rod mouth	1 pc. / DN20
Anode	Magnesium
Drainage Hole	1 pc. / DN20
Built-in Heat Coil	Stainless steel 304 $\varnothing$ 25*30m
Type of Built-in heat coil	Corrugated Tube
Thickness of Corrugated tube	0,33 mm
Heat coil area	4,3 m <sup>2</sup>
Built-in Auxiliary E-heater	Stainless steel 304 / 3KW
Gross weight	96 kgs
Dimension	$\varnothing$ 560 mm x 1860 mm
Packing Dimension	63 cm x 63 cm x 195 cm

