



## Yuasa Technical Data Sheet

### Yuasa YBX3027 - YBX3000 SMF Batteries

\* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

#### Performance

Voltage	12V
Capacity (20-hour)	62Ah
Cold Cranking Amps (EN1)	550A

#### Dimensions

Length	243mm
Width	175mm
Height	190mm

#### Weights & Measures

Mean Weight with Acid	16kg
-----------------------	------



#### Container Features

Case Type	L2 DIN
Hold Down	B13B14
State of Charge Indicator	✓
Handles	✓
End Venting	✓
Lid Type	SMF Double Lid


#### Technology

Flame Arrestor	✓
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✓
Recommended Charge Rate	4A
Performance Marking	W3-C2-V2-E1

#### Terminal Type

##### T1


Standard DIN Post



Positive Terminal


Negative Terminal

#### Cell Assembly Layout



#### Battery Hold-down

B3/B4 (B3 with Hold-Down adaptor)



Data Sheet generated on 02/12/2020 - E&OE