



Strip Heater Solutions

*Cafeterias • Buffets • Supermarkets & Delis
Restaurants & Cafés • Clubs & Bars*



GRAL-48 pg. 4



GRAH-42D with 6" spacer and optional non-adjustable tubular stands pg. 6



GRAHL-96D with optional *Designer* color and non-adjustable tubular stands pg. 7



GRAML-60D with optional non-adjustable tubular stands pg. 12



GRNH-48 with standard angle brackets and optional *Designer* color (sneeze guards as shown not available) pg. 16



GRAIHL-48 (requires Remote Control Enclosure) pg. 18



GR2AHL-84 with optional *Designer* color and sneeze guards pg. 22



UGA-24D in Gloss finish Radiant Red pg. 27



UGAH-36D with 3" spacer pg. 27




Ordering Instructions

**GRA-72,
GRAH-72 or
GRAM-72**



**GRA-72D,
GRAH-72D or
GRAM-72D**



**GRAL-72,
GRAHL-72 or
GRAML-72**



**GRAL-72D,
GRAHL-72D or
GRAML-72D**



GRAIH-60



GRAIH-60D




GRAIHL-60



GRAIHL-60D




**UGA-36 or
UGAH-36**



**UGA-36D or
UGAH-36D**



**UGAL-36 or
UGAHL-36**



**UGAL-36D or
UGAHL-36D**



Glo-Ray® Infrared Metal-Sheathed Strip Heaters: (pages 3-13)

1. Choose a length
2. Single or dual warmer
3. Standard, high or max watt
4. Lights or no lights
5. Voltage: 120, 208, 240 or 120/208, 120/240 for units with lights
6. Choose control option, remote installation recommended (required on some GRAM models)*

GRN4L-36



GRN4-36

Glo-Ray® Narrow Halogen Strip Heaters: (page 14-15)

1. Choose a length
2. Voltage: 120
3. Includes remote control enclosure

**GRN-24
GRNH-24
GRNM-24**



Glo-Ray® Narrow Infrared Strip Heaters: (page 16-17)

1. Choose a length
2. Standard, high or max watt
3. Voltage: 120, 208, 240
4. Choose control option, remote installation is recommended*

Glo-Ray® Infra-Black® Strip Heaters: (pages 18-20)

1. Choose a length
2. Single or dual warmer
3. Lights or no lights
4. Voltage: 120, 208, 240 or 120/208, 120/240 for units with lights
5. Choose control option, remote installation is recommended*

Glo-Ray® Designer Infrared Strip Heaters: (pages 21-25)

1. Choose a length
2. Single or dual warmer
3. Standard or high watt
4. Lights or no lights
5. Voltage: 120, 208, 240 or 120/208, 120/240 for units with lights
6. Choose control option, remote installation only*
7. Choose inset panel and corner cap color

**GR2A-36
or GR2AH-36**



**GR2A-36D
or GR2AH-36D**



**GR2AL-36
or GR2AHL-36**



**GR2AL-36D
or GR2AHL-36D**



Typical Conduit Connection

Glo-Ray® strip heaters come standard with right angle attached 3' conduit and 42" leads on back of unit (Narrow Strip Heater standard with 6" leads, no conduit, GR2A models exit posts only)

* Multiple Strip Heaters may be connected to one RMB2 if the combined current draw of the warmers are less than the rating for the RMB2.


Glo-Ray® Infrared Strip Heaters

Safely hold the temperature of your product without drying out or further cooking food with Hatco's Glo-Ray® Infrared Strip Heaters. The end result is hot, fresh food that's ready-to-serve. The continuous aluminum housing and heavy-duty mountings ensure the durability and quality of Hatco products. Heavy-duty stainless steel housings are available (see next page).

Toggle Switch: Max. 15 amps
Infinite Switch: Max. 12.2 amps

- Ensures maximum flavor, safety and holding time
- Even heat distribution – no “cold spots”
- Sturdy extruded aluminum housings that do not sag, from 18" to 144" (12")
- Reflector does not blacken, maintaining a consistent heat pattern
- Heavy-duty insulation minimizes heat loss
- All units single phase only
- Standard and high watt models available
- Optional sneeze guards (excludes stainless steel models)
- Available in stainless steel housing 18" to 96"
- Available with lights (shatter resistant incandescent lights or optional Halogen lights - excludes stainless steel models)

- Pre-focused heat pattern bathes entire holding surface
- Additional reflector styles and lower wattage elements available, consult factory for more information



GRAH-36 High watt, toggle controlled with 2-S hooks, 2-6" chains (optional cord and plug attached)

ALUMINUM STRIP HEATERS WITH CONDUIT (Standard Watt)

Model	Width	Voltage Single Phase	Watts	Ship Weight
Standard Watt				
GRA-18	18"	120, 208 or 240	250	7 lbs.
GRA-24	24"	120, 208 or 240	350	7 lbs.
GRA-30	30"	120, 208 or 240	450	8 lbs.
GRA-36	36"	120, 208 or 240	575	9 lbs.
GRA-42	42"	120, 208 or 240	675	11 lbs.
GRA-48	48"	120, 208 or 240	800	11 lbs.
GRA-54	54"	120, 208 or 240	925	13 lbs.
GRA-60	60"	120, 208 or 240	1050	14 lbs.
GRA-66	66"	120, 208 or 240	1160	16 lbs.
GRA-72	72"	120, 208 or 240	1275	17 lbs.
GRA-84*	84"	120, 208 or 240	1500	21 lbs.
GRA-96*	96"	120, 208 or 240	1725	23 lbs.
GRA-108	108"	120, 208 or 240	1850	24 lbs.
GRA-120	120"	120, 208 or 240	2100	26 lbs.
GRA-132	132"	120, 208 or 240	2320	30 lbs.
GRA-144	144"	120, 208 or 240	2550	33 lbs.

* Does not include RMB (see page 31 and 32).

▼ When using an infinite control with 120V Models, additional switch(es) and tandem (end-to-end) elements are required, cord not available.

▲ 120V Models require additional switches and tandem (end-to-end) elements.

All Aluminum Strip Heater Models Feature:

Toggle Switch (Max. 15 Amps) Location: Chef's left side (unless otherwise specified).


Leads: 3' conduit with leads – server's right. NEMA 5-15P cord available on 120V Models 72" or less with C-leg, T-leg stand or chain-hook mount. GRAH-66 and GRAH-72 require NEMA 5-20P cord for Canada.

Dimensions: 18"-144"W x 6"D x 2½"H.

OPTIONS AND ACCESSORIES – PAGE 5

RECOMMENDED MOUNTING HEIGHTS – PAGE 29

ONE YEAR ON-SITE PARTS AND LABOR WARRANTY, PLUS ONE ADDITIONAL YEAR PARTS-ONLY WARRANTY ON ALL GLO-RAY® METAL-SHEATHED HEATING ELEMENTS.



ALUMINUM STRIP HEATERS WITH CONDUIT (High Watt)

Model	Width	Voltage Single Phase	Watts	Ship Weight
High Watt				
GRAH-18	18"	120, 208 or 240	350	7 lbs.
GRAH-24	24"	120, 208 or 240	500	8 lbs.
GRAH-30	30"	120, 208 or 240	660	8 lbs.
GRAH-36	36"	120, 208 or 240	800	11 lbs.
GRAH-42	42"	120, 208 or 240	950	12 lbs.
GRAH-48	48"	120, 208 or 240	1100	13 lbs.
GRAH-54	54"	120, 208 or 240	1250	14 lbs.
GRAH-60	60"	120, 208 or 240	1400	16 lbs.
GRAH-66*	66"	120, 208 or 240	1560	17 lbs.
GRAH-72*	72"	120, 208 or 240	1725	18 lbs.
GRAH-84*	84"	120, 208 or 240	2050	19 lbs.
GRAH-96*	96"	120, 208 or 240	2400	21 lbs.
GRAH-108	108"	120, 208 or 240	2500	23 lbs.
GRAH-120	120"	120, 208 or 240	2800	26 lbs.
GRAH-132	132"	120, 208 or 240	3120	31 lbs.
GRAH-144	144"	120, 208 or 240	3450	48 lbs.

ALUMINUM STRIP HEATERS WITH S HOOKS, CHAINS AND CORD AND PLUG ATTACHED



Model	Order No.	Width	Voltage Single Phase	Watts	Ship Weight
Standard Watt - Toggle Controlled with S Hooks and Chain, Cord and Plug attached					
GRA-24	GRA24120TCCS	24"	120	350	7 lbs.
GRA-36	GRA36120TCCS	36"	120	575	9 lbs.
GRA-48	GRA48120TCCS	48"	120	800	11 lbs.
GRA-60	GRA60120TCCS	60"	120	1050	14 lbs.
High Watt - Toggle Controlled with S Hooks and Chain, Cord and Plug attached					
GRAH-18	AH18120TCCS	18"	120	350	6 lbs.
GRAH-24	AH24120TCCS	24"	120	500	7 lbs.
GRAH-30	AH30120TCCS	30"	120	660	8 lbs.
GRAH-36	AH36120TCCS	36"	120	800	9 lbs.
GRAH-42	AH42120TCCS	42"	120	950	10 lbs.
GRAH-48	AH48120TCCS	48"	120	1100	11 lbs.
GRAH-60	AH60120TCCS	60"	120	1400	14 lbs.
GRAH-72*	AH72120TCCS.1	72"	120	1725	17 lbs.
High Watt - Infinite Controlled with S Hooks and Chain, Cord and Plug attached					
GRAH-24	AH24120ICCS	24"	120	500	7 lbs.
GRAH-36	AH36120ICCS	36"	120	800	9 lbs.
GRAH-48	AH48120ICCS	48"	120	1100	11 lbs.
GRAH-60	AH60120ICCS	60"	120	1400	14 lbs.


* Not available for Canada.



Strip Heater Solutions



GRAHL-36 with optional sneeze guards and adjustable tubular stands



- A** Stainless steel or sturdy aluminum housings that do not sag, from 18" up to 12' in 6" increments. Stainless units available in single units without lights, up to 96" in width
- B** Shatter-resistant incandescent lights (standard on GRAL/GRAHL), optional halogen bulb available
- C** Heavy-duty insulation minimizes heat loss
- D** Standard brackets are provided
- E** Aluminized reflector retains full heat intensity and directs more heat towards the edges of the holding surface
- F** Metal-sheathed heating element is guaranteed against burnout and breakage for two years
- G** Protective wire guard supports heating element without affecting heat distribution

ALUMINUM STRIP HEATERS WITH LIGHTS

Model	Bulbs	Width	Voltage Single Phase	Watts	Ship Weight
Standard Watt					
GRAL-18	2	18"	120, 120/208 or 120/240	370	9 lbs.
GRAL-24	2	24"	120, 120/208 or 120/240	470	10 lbs.
GRAL-30	2	30"	120, 120/208 or 120/240	570	12 lbs.
GRAL-36	3	36"	120, 120/208 or 120/240	755	13 lbs.
GRAL-42	3	42"	120, 120/208 or 120/240	855	15 lbs.
GRAL-48	4	48"	120, 120/208 or 120/240	1040	17 lbs.
GRAL-54	4	54"	120, 120/208 or 120/240	1165	19 lbs.
GRAL-60	5	60"	120, 120/208 or 120/240	1350	21 lbs.
GRAL-66	5	66"	120, 120/208 or 120/240	1460	22 lbs.
GRAL-72	6	72"	120, 120/208 or 120/240	1635	24 lbs.
GRAL-84	7	84"	120, 120/208 or 120/240	1920	28 lbs.
GRAL-96	8	96"	120, 120/208 or 120/240	2205	32 lbs.
GRAL-108	9	108"	120, 120/208 or 120/240	2390	36 lbs.
GRAL-120	10	120"	120, 120/208 or 120/240	2700	40 lbs.
GRAL-132	11	132"	120, 120/208 or 120/240	2980	44 lbs.
GRAL-144	12	144"	120, 120/208 or 120/240	3270	48 lbs.
High Watt					
GRAHL-18	2	18"	120, 120/208 or 120/240	470	9 lbs.
GRAHL-24	2	24"	120, 120/208 or 120/240	620	10 lbs.
GRAHL-30	2	30"	120, 120/208 or 120/240	780	12 lbs.
GRAHL-36	3	36"	120, 120/208 or 120/240	980	13 lbs.
GRAHL-42	3	42"	120, 120/208 or 120/240	1130	16 lbs.
GRAHL-48	4	48"	120, 120/208 or 120/240	1340	17 lbs.
GRAHL-54	4	54"	120, 120/208 or 120/240	1490	19 lbs.
GRAHL-60	5	60"	120, 120/208 or 120/240	1700	21 lbs.
GRAHL-66	5	66"	120, 120/208 or 120/240	1860	22 lbs.
GRAHL-72	6	72"	120, 120/208 or 120/240	2085	34 lbs.
GRAHL-84	7	84"	120, 120/208 or 120/240	2470	28 lbs.
GRAHL-96	8	96"	120, 120/208 or 120/240	2880	33 lbs.
GRAHL-108	9	108"	120, 120/208 or 120/240	3040	36 lbs.
GRAHL-120	10	120"	120, 120/208 or 120/240	3400	40 lbs.
GRAHL-132	11	132"	120, 120/208 or 120/240	3780	44 lbs.
GRAHL-144	12	144"	120, 120/208 or 120/240	4170	48 lbs.

* Does not include RMB (see page 31 and 32).

▼ When using an infinite control with 120V Models, additional switch(es) and tandem (end-to-end) elements are required, cord not available.

▲ 120V Models require additional switches and tandem (end-to-end) elements.

All Aluminum Strip Heater Models with Lights Feature:

Toggle Switch (Max. 15 Amps) Location: Chef's left side – light side (unless otherwise specified).

Leads: 3' conduit with leads – server's right. NEMA 5-15P cord available on 120V Models 72" or less with C-leg, T-leg stand or hook-chain mount. GRAHL-54, GRAHL-60, GRAL-66 & GRAL-72 require NEMA 5-20P cord for Canada. GRAHL-66 & GRAHL-72 require NEMA 5-20P cord - not available for Canada.

Dimensions: 18"-144"W x 9"D x 2½"H.

OPTIONS AND ACCESSORIES – PAGE 5

RECOMMENDED MOUNTING HEIGHTS – PAGE 29

STAINLESS STEEL STRIP HEATERS

Model	Width	Voltage Single Phase	Watts	Ship Weight
Standard Watt				
GR-18	18"	120, 208 or 240	250	7 lbs.
GR-24	24"	120, 208 or 240	350	7 lbs.
GR-36	36"	120, 208 or 240	575	10 lbs.
GR-48	48"	120, 208 or 240	800	12 lbs.
GR-60	60"	120, 208 or 240	1050	15 lbs.
GR-72	72"	120, 208 or 240	1275	19 lbs.
GR-96*	96"	120, 208 or 240	1725	24 lbs.
High Watt				
GRH-18	18"	120, 208 or 240	350	7 lbs.
GRH-24	24"	120, 208 or 240	500	7 lbs.
GRH-36	36"	120, 208 or 240	800	10 lbs.
GRH-48	48"	120, 208 or 240	1100	12 lbs.
GRH-60	60"	120, 208 or 240	1400	15 lbs.
GRH-72*	72"	120, 208 or 240	1725	19 lbs.
GRH-96	96"	208 or 240	2400	24 lbs.

*Does not include RMB (see page 4 and 4).

•Infinite not available in 120V.

All Stainless Steel Strip Heater Models Feature:

Toggle Switch (max. 15 Amps) Location: Chef's left side.


Leads: 3' conduit with leads – server's right. NEMA 5-15P cord available on 120 volt models 72" or less with C-leg, T-leg stand or chain-hook mount. GRH-72 requires NEMA 5-20P cord for Canada.

Dimensions: 18"-96"W x 6"D x 2¼"H.

Contact factory for stainless marine applications.

ONE YEAR ON-SITE PARTS AND LABOR WARRANTY, PLUS ONE ADDITIONAL YEAR PARTS-ONLY WARRANTY ON ALL GLO-RAY® METAL-SHEATHED HEATING ELEMENTS.

STAINLESS STEEL MODELS ARE NOT AVAILABLE WITH LIGHTS, SNEEZE GUARDS OR AS DUAL OR TANDEM UNITS.





GRAHL-48
with optional
sneeze guard

OPTIONS (available at time of purchase only)

Designer Colors, Aluminum Models 18"-144" – Non-standard colors are non-returnable – Clear Anodized Standard –

COLOR-6 6" Housing for GRA and GRAH Models

COLOR-9 9" Housing for GRAL and GRAHL Models

RED Warm Red	GRAY Gray Granite	NAVY Navy Blue	COPPER Antique Copper
BLACK Black	WHITE White Granite	GREEN Hunter Green	

Gloss Finishes, Aluminum Models 18"-144" – Non-standard colors are non-returnable – Clear Anodized Standard –

GLOSS-6 6" Housing for GRA and GRAH Models (select color)

GLOSS-9 9" Housing for GRAL and GRAHL Models (select color)

RRED Radiant Red	GGRAY Glossy Gray	BBLACK Bold Black
GGOLD Gleaming Gold	BBLUE Brilliant Blue	

IND. LGT Indicator Light (Remote Control only on all Tandem Element units)

Leads (extended beyond standard 3' Conduit – must specify Lead length) –

LEADS5 1'-5' Extended Electrical Leads

LEADS10 6'-10' Extended Electrical Leads

LEADS15 11'-15' Extended Electrical Leads

LEADS20 16'-20' Extended Electrical Leads

9.375BP1 9¾" Sneeze Guard – one side (Aluminum Models only)

9.375BP2 9¾" Sneeze Guard – two sides (Aluminum Models only)

14BP1 14" Sneeze Guard – one side (Aluminum Models only)

14BP2 14" Sneeze Guard – two sides (Aluminum Models only)

HAL Halogen Bulb in lieu of standard Display Light (60 Watt – Aluminum Models only)

NO BULB No Bulb Option (GRAL, GRAHL Models only)

LIGHTS-ADD'L Extra Lamps – installed (max. two per ft. less one – one per foot is standard). Must be ordered with Remote Switches only (Aluminum Models only)

3 ANEAL REFL Bright Annealed Reflector for Lights (Aluminum Models only)

NO CONTROL No Control included (GRA, GRAH, GRAL, GRAHL, GR, GRH Models only) Requires selection of RMB2-xx Control

See page 31

BLT INF Infinite Control Built-In in lieu of Toggle (max. 12.2 Amps). Remote installation recommended

REM INF Remote Infinite Switches in lieu of Toggle (max. 12.2 Amps)

REM TOG Remote Toggle Switches (max. 15 Amps)

RMB Remote Box (available in Designer Colors or Gloss Finishes) – Non-standard colors are non-returnable –

See page 31 and 32

ATL Adjustable Tubular Stands 10"-14" (not available in Designer Colors). Not available with Cord

NTL-10, 12 Non-Adjustable Tubular Stands (specify 10" or 12" clearance). Not available with Cord

NTL-14, 16 Non-Adjustable Tubular Stands (specify 14" or 16" clearance). Not available with Cord

NTL-PAINT Designer Color or Gloss Finish for Non-Adjustable Tubular Stands – Non-standard colors are non-returnable –

CL-LOW C-Leg Stands standard watt – 10" clearance (for Models up to 72" wide). Only available with Cord

CL-HIGH C-Leg Stands high watt – 13½" clearance (for Models up to 72" wide). Only available with Cord

TL-10 T-Leg Stands 10" clearance (for standard watt Models only up to 72" wide). Only available with Cord

TL-13 T-Leg Stands 13½" clearance (for Models up to 72" wide). Only available with Cord

TL-16 T-Leg Stands 16" clearance (for Models up to 72" wide). Only available with Cord

TL-18 T-Leg Stands 18" clearance (for Models up to 72" wide). Only available with Cord

CAP Attached 6' Cord and Plug Set (120V only) on Models up to 72" wide requires standard Chain Mount Kit (two S Hooks with two 6" Lengths of Chain) or add optional C-Leg Stands or T-Leg Stands (see specific Model for plug configuration)

CHAIN-HOOK Two S Hooks with two 6" Lengths of Chain

ACCESSORIES (available for purchase at any time)

ADJ-ANGLE Adjustable Angle Brackets (see page 30 for illustration – GRA, GRAH Models only)

GR-ANGLE Adjustable Angle Brackets (see page 30 for illustration – GR Models only)

CHAIN 1 Chain Suspension

Chef LED 120V Adjustable Bulb – GRAL, GRAHL Models only, all voltages –

Please contact your local representative or the factory for the most up-to-date listing of installations and applicable Models –

CLED-2700-120 Emulates incandescent	CLED-3000-120 Emulates halogen	CLED-4000-120 Emulates fluorescent
--	---------------------------------------	---

COLORS AND FINISHES – PAGE 33



**CLED-2700, -3000
or -4000**

Glo-Ray® Dual Infrared Strip Heaters

Create a deeper holding area with Glo-Ray® Aluminum Dual Infrared Strip Heaters mounted side-by-side, keeping hot food at optimum serving temperatures. The pre-focused heat pattern directs heat from a metal-sheathed element across the entire holding surface. The continuous aluminum housing and heavy-duty mountings ensure the durability and quality of Hatco products.

Toggle Switch: Max. 15 amps
Infinite Switch: Max. 12.2 amps

- Ensures maximum flavor, safety and holding time
- Provides even heat distribution – no “cold spots”
- Sturdy extruded aluminum housings that do not sag, from 18" to 144" (12')
- Reflector does not blacken, maintaining a consistent heat pattern
- Protective wire guard supports heating element without affecting heat distribution
- 3" or 6" spacer available
- Heavy-duty insulation minimizes heat loss
- Additional reflector styles and lower wattage elements available, consult factory for more information



ALUMINUM DUAL STRIP HEATERS

Model	Width	Voltage	Watts	Ship Weight
		Single Phase		
Standard Watt				
GRA-18D	18"	120, 208 or 240	500	14 lbs.
GRA-24D	24"	120, 208 or 240	700	16 lbs.
GRA-30D	30"	120, 208 or 240	900	18 lbs.
GRA-36D	36"	120, 208 or 240	1150	19 lbs.
GRA-42D	42"	120, 208 or 240	1350	23 lbs.
GRA-48D	48"	120, 208 or 240	1600	27 lbs.
GRA-54D	54"	120, 208 or 240	1850	30 lbs.
GRA-60D	60"	120, 208 or 240	2100	35 lbs.
GRA-66D	66"	120, 208 or 240	2320	36 lbs.
GRA-72D	72"	120, 208 or 240	2550	40 lbs.
GRA-84D▼	84"	120, 208 or 240	3000	50 lbs.
GRA-96D▼	96"	120, 208 or 240	3450	52 lbs.
GRA-108D	108"	120, 208 or 240	3700	59 lbs.
GRA-120D	120"	120, 208 or 240	4200	66 lbs.
GRA-132D	132"	120, 208 or 240	4640	73 lbs.
GRA-144D	144"	120, 208 or 240	5100	80 lbs.
High Watt				
GRAH-18D	18"	120, 208 or 240	700	14 lbs.
GRAH-24D	24"	120, 208 or 240	1000	16 lbs.
GRAH-30D	30"	120, 208 or 240	1320	18 lbs.
GRAH-36D	36"	120, 208 or 240	1600	19 lbs.
GRAH-42D	42"	120, 208 or 240	1900	23 lbs.
GRAH-48D	48"	120, 208 or 240	2200	27 lbs.
GRAH-54D	54"	120, 208 or 240	2500	30 lbs.
GRAH-60D	60"	120, 208 or 240	2800	35 lbs.
GRAH-66D▼	66"	120, 208 or 240	3120	36 lbs.
GRAH-72D▼	72"	120, 208 or 240	3450	40 lbs.
GRAH-84D▲	84"	120, 208 or 240	4100	50 lbs.
GRAH-96D▲	96"	120, 208 or 240	4800	52 lbs.
GRAH-108D	108"	120, 208 or 240	5000	59 lbs.
GRAH-120D	120"	120, 208 or 240	5600	66 lbs.
GRAH-132D	132"	208 or 240	6240	73 lbs.
GRAH-144D	144"	208 or 240	6900	80 lbs.

* Does not include RMB (see page 31 and 32).

▲ 120V Models require additional switches and tandem (end-to-end) elements.

▼ When using an infinite control with 120V Models, additional switch(es) and tandem (end-to-end) elements are required.

All Aluminum Dual Strip Heater Models Feature:

Toggle Switch (Max. 15 Amps) Location: Chef's left side (unless otherwise specified).

Leads: 3' conduit with leads – server's right.

Dimensions: with 3" Spacer (standard): 18"-144"W x 15"D x 2½"H.


with 6" Spacer: 18"-144"W x 18"D x 2½"H.

OPTIONS AND ACCESSORIES – PAGE 6

RECOMMENDED MOUNTING HEIGHTS – PAGE 29


NOTE: 120V models may require additional switches.

ONE YEAR ON-SITE PARTS AND LABOR WARRANTY, PLUS ONE ADDITIONAL YEAR PARTS-ONLY WARRANTY ON ALL GLO-RAY® METAL-SHEATHED HEATING ELEMENTS.



Glo-Ray® Dual Infrared Strip Heaters *continued*

- A** Shown with optional lights (shatter-resistant incandescent lights or halogen bulbs available)
- B** Sturdy extruded aluminum housings that do not sag, from 18" up to 144" (12')
- C** Reflector does not blacken, maintaining a consistent heat pattern
- D** Standard hanger tab is provided for under shelf or chain installation
- E** Heavy-duty insulation minimizes heat loss
- F** Metal-sheathed heating element is guaranteed against burnout and breakage for two years
- G** Protective wire guard supports heating element without affecting heat distribution



Toggle Switch: Max. 15 amps

Infinite Switch: Max. 12.2 amps

ALUMINUM DUAL STRIP HEATERS WITH LIGHTS

Model	Bulbs	Width	Voltage Single Phase	Watts	Ship Weight
Standard Watt					
GRAL-18D	2	18"	120, 120/208 or 120/240	620	14 lbs.
GRAL-24D	2	24"	120, 120/208 or 120/240	820	16 lbs.
GRAL-30D	2	30"	120, 120/208 or 120/240	1020	19 lbs.
GRAL-36D	3	36"	120, 120/208 or 120/240	1330	22 lbs.
GRAL-42D	3	42"	120, 120/208 or 120/240	1530	25 lbs.
GRAL-48D	4	48"	120, 120/208 or 120/240	1840	29 lbs.
GRAL-54D	4	54"	120, 120/208 or 120/240	2090	33 lbs.
GRAL-60D	5	60"	120, 120/208 or 120/240	2400	37 lbs.
GRAL-66D	5	66"	120, 120/208 or 120/240	2620	39 lbs.
GRAL-72D	6	72"	120, 120/208 or 120/240	2910	42 lbs.
GRAL-84D▼	7	84"	120, 120/208 or 120/240	3420	47 lbs.
GRAL-96D▼	8	96"	120, 120/208 or 120/240	3930	56 lbs.
GRAL-108D	9	108"	120, 120/208 or 120/240	4240	64 lbs.
GRAL-120D	10	120"	120, 120/208 or 120/240	4800	72 lbs.
GRAL-132D	11	132"	120, 120/208 or 120/240	5300	79 lbs.
GRAL-144D	12	144"	120, 120/208 or 120/240	5820	86 lbs.
High Watt					
GRAHL-18D	2	18"	120, 120/208 or 120/240	820	14 lbs.
GRAHL-24D	2	24"	120, 120/208 or 120/240	1120	16 lbs.
GRAHL-30D	2	30"	120, 120/208 or 120/240	1440	19 lbs.
GRAHL-36D	3	36"	120, 120/208 or 120/240	1780	22 lbs.
GRAHL-42D	3	42"	120, 120/208 or 120/240	2080	25 lbs.
GRAHL-48D	4	48"	120, 120/208 or 120/240	2440	29 lbs.
GRAHL-54D	4	54"	120, 120/208 or 120/240	2740	33 lbs.
GRAHL-60D	5	60"	120, 120/208 or 120/240	3100	37 lbs.
GRAHL-66D▼	5	66"	120, 120/208 or 120/240	3420	39 lbs.
GRAHL-72D▼	6	72"	120, 120/208 or 120/240	3810	42 lbs.
GRAHL-84D▲	7	84"	120, 120/208 or 120/240	4520	47 lbs.
GRAHL-96D▲	8	96"	120, 120/208 or 120/240	5280	56 lbs.
GRAHL-108D▲	9	108"	120, 120/208 or 120/240	5540	64 lbs.
GRAHL-120D▲	10	120"	120, 120/208 or 120/240	6200	72 lbs.
GRAHL-132D▲	11	132"	120/208 or 120/240	6900	79 lbs.
GRAHL-144D▲	12	144"	120/208 or 120/240	7620	86 lbs.

* Does not include RMB (see page 31 and 32).

▼ When using an infinite control with 120V Models, additional switch(es) and tandem (end-to-end) elements required.

▲ 120V Models require additional switches (remote only) and tandem (end-to-end) elements.

▶ Available with RMB or remote switch only.

All Aluminum Dual Strip Heater Models with Lights Feature:

Toggle Switch (Max. 15 Amps) Location: Chef's left side (unless otherwise specified).


Leads: 3' conduit with leads – server's right.

Dimensions: with 3" Spacer (standard): 15"D x 2½"H.
with 6" Spacer: 18"D x 2½"H.

OPTIONS AND ACCESSORIES – PAGE 7

RECOMMENDED MOUNTING HEIGHTS – PAGE 29

ONE YEAR ON-SITE PARTS AND LABOR WARRANTY, PLUS ONE ADDITIONAL YEAR PARTS-ONLY WARRANTY ON ALL GLO-RAY® METAL-SHEATHED HEATING ELEMENTS.





A series of **GRAH-60D** models

OPTIONS (available at time of purchase only)

Designer Colors, Aluminum Models 18"-144" – Non-standard colors are non-returnable – Clear Anodized Standard –

Designer Colors, Aluminum models 15-18 are standard colors and are returnable. Great Anodized Standard							
COLOR-15, -18 15" and 18" Housings for GRA, GRAH, GRAL and GRAHL Dual Models							
RED	Warm Red	GRAY	Gray Granite	NAVY	Navy Blue	COPPER	Antique Copper
BLACK	Black	WHITE	White Granite	GREEN	Hunter Green		

Gloss Finishes, Aluminum Models 18"-144" – Non-standard colors are non-returnable – Clear Anodized Standard –

GLOSS-15, -18						15" and 18" Housings for GRA, GRAH, GRAL and GRAHL Dual Models					
RRED		Radiant Red		GGRAY		Glossy Gray		BBLACK		Bold Black	
GGOLD		Gleaming Gold		BBLUE		Brilliant Blue					

IND. LGT Indicator Light (remote only)

Leads (extended beyond standard 3' Conduit – must specify Lead length) –

LEADS5	1'-5' Extended Electrical Leads
LEADS10	6'-10' Extended Electrical Leads
LEADS15	11'-15' Extended Electrical Leads
LEADS20	16'-20' Extended Electrical Leads

9.375BP1 9 $\frac{3}{8}$ " Sneeze Guard – one side

9.375BP2 9 $\frac{3}{8}$ " Sneeze Guard – two sides

14BP1 14" Sneeze Guard – one side

14BP2 14" Sneeze Guard – two sides

HAL Halogen Bulb in lieu of standard Display Light (60 Watt)

NO BULB No Bulb Option (GRAL-xxD, GRAHL-xxD Models only)

LIGHTS-ADD'L Extra Lamps – installed (max. two per ft. less one – one per foot is standard)

3 ANEAL REFL Bright Annealed Reflector for Lights with 3" Spacer

6 ANEAL REFL Bright Annealed Reflector for Lights with 6" Spacer

NO CONTROL No Control included (GRA, GRAH, GRAL, GRAHL-xxD Models only). Requires selection of RMB2-xx Control

See page 31

REM INF Remote Infinite Switches (max. 12.2 Amps)

REM TOG Remote Toggle Switches (max. 15 Amps)

RMB Remote Box (available in *Designer Colors* or *Gloss Finishes*) – Non-standard colors are non-returnable –

See page 31 and 32

ATL-D Adjustable Tubular Stands 10"-14" (not available in *Designer Colors*)

NTL-10-D, 12-D Non-Adjustable Tubular Stands (specify 10" or 12" clearance)

NTL-14-D, 16-D Non-Adjustable Tubular Stands (specify 14" or 16" clearance)

NTL-PAINT-D *Designer Color* or *Gloss Finish* for Non-Adjustable Tubular Stands – Non-standard colors are non-returnable –

ACCESSORIES (available for purchase at any time)

ADJ ANGLE-D Adjustable Angle Brackets (see page 30 for illustration)

CHAIN 1 Chain Suspension (see page 30 for illustration)

Chef LED 120V Adjustable Bulb – GRAL-xxD Models only, all voltages –

Please contact your local representative or the factory for the most up to date listing of installations and applicable Models –

CLED-2700-120 Emulates incandescent **CLED-3000-120** Emulates halogen **CLED-4000-120** Emulates fluorescent

COLORS AND FINISHES – PAGE 33



**CLED-2700, -3000
or -4000**

Glo-Ray® Max Watt Infrared Strip Heaters

Safely hold the temperature of your product without drying out or further cooking food with Hatco's Glo-Ray® Max Watt Infrared Strip Heaters. The end result is hot, fresh food that's ready-to-serve. The continuous aluminum housing and heavy-duty mountings ensure the durability and quality of Hatco products.

- Features 25% greater wattage output than Glo-Ray high watt by comparison with single units varying in watts from 450 to 4150 watts; and units with lights varying from 570 to 4870 watts
- Sturdy extruded aluminum housings that do not sag, from 18" to 72" in 6" increments and 84" to 144" in 12" increments
- Protective wire guards under heating element
- Heavy-duty insulation minimizes heat loss
- Available options include an electronic infinite control with relay in a remote control enclosure
- Shatter-resistant incandescent lights (standard on GRAML models) enhance product display while safeguarding food products from bulb breakage. An optional halogen bulb may be used in lieu of incandescents
- Additional reflector styles available, consult factory for more information



GRAM-36



GRAML-36 with shatter-resistant incandescent lights and standard angle brackets

ALUMINUM MAX WATT INFRARED STRIP HEATERS

Model	Width	Voltage Single Phase	Watts	Ship Weight*
Max Watt				
GRAM-18	18"	120, 208 or 240	450	6 lbs.
GRAM-24	24"	120, 208 or 240	650	7 lbs.
GRAM-30	30"	120, 208 or 240	825	8 lbs.
GRAM-36	36"	120, 208 or 240	1000	9 lbs.
GRAM-42	42"	120, 208 or 240	1175	10 lbs.
GRAM-48	48"	120, 208 or 240	1300	11 lbs.
GRAM-54	54"	120, 208 or 240	1500	13 lbs.
GRAM-60	60"	120, 208 or 240	1700	14 lbs.
GRAM-66 [▲]	66"	120, 208 or 240	1875	16 lbs.
GRAM-72 [▲]	72"	120, 208 or 240	2075	17 lbs.
GRAM-84 [▲]	84"	120, 208 or 240	2400	19 lbs.
GRAM-96 [▲]	96"	120, 208 or 240	2675	21 lbs.
GRAM-108 [▶]	108"	208 or 240	3000	23 lbs.
GRAM-120 [▶]	120"	208 or 240	3400	26 lbs.
GRAM-132 [▶]	132"	208 or 240	3750	30 lbs.
GRAM-144 [▶]	144"	208 or 240	4150	33 lbs.

* Includes Remote Control Enclosure with toggle switch(es) and indicator light(s) or attached Control Enclosure with toggle switch(es) except as noted.

▶ Available with Remote Control Enclosure only.

▲ Add 2-8 lbs. depending on RMB.

▼ Electronic infinite control with 120V Models requires additional switch(es) and tandem (end-to-end) elements, cord not available.

▲ 120V Models require additional switches and tandem (end-to-end) elements.

▶ 120V Models available with RMB (GRAM-66, -72, -84, -96 only).

All Aluminum Max Watt Infrared Strip Heater Models Feature:

Includes: Angle brackets and attached or Remote Control Enclosure

Voltage: 120, 208 or 240, single phase only.

Leads: 3' conduit with leads – server's right.

Dimensions: 18"-144"W x 6"D x 2½"H.

ALUMINUM MAX WATT INFRARED STRIP HEATERS WITH LIGHTS

Model	Bulbs	Width	Voltage Single Phase	Watts	Ship Weight*
Max Watt					
GRAML-18	2	18"	120, 120/208 or 120/240	570	9 lbs.
GRAML-24	2	24"	120, 120/208 or 120/240	770	10 lbs.
GRAML-30	2	30"	120, 120/208 or 120/240	945	11 lbs.
GRAML-36	3	36"	120, 120/208 or 120/240	1180	13 lbs.
GRAML-42	3	42"	120, 120/208 or 120/240	1355	15 lbs.
GRAML-48	4	48"	120, 120/208 or 120/240	1540	17 lbs.
GRAML-54	4	54"	120, 120/208 or 120/240	1740	19 lbs.
GRAML-60 [▲]	5	60"	120, 120/208 or 120/240	2000	21 lbs.
GRAML-66 [▲]	5	66"	120, 120/208 or 120/240	2175	22 lbs.
GRAML-72 [▲]	6	72"	120, 120/208 or 120/240	2435	24 lbs.
GRAML-84 [▲]	7	84"	120, 120/208 or 120/240	2820	28 lbs.
GRAML-96 [▲]	8	96"	120, 120/208 or 120/240	3155	32 lbs.
GRAML-108 [▶]	9	108"	120/208 or 120/240	3540	36 lbs.
GRAML-120 [▶]	10	120"	120/208 or 120/240	4000	40 lbs.
GRAML-132 [▶]	11	132"	120/208 or 120/240	4410	44 lbs.
GRAML-144 [▶]	12	144"	120/208 or 120/240	4870	48 lbs.

* Includes Remote Control Enclosure with toggle switch(es) and indicator light(s) or Attached Control Enclosure with toggle switch(es) except as noted.

▶ Available with Remote Control Enclosure only.

▲ Add 2-8 lbs. depending on RMB.

▼ Electronic infinite control with 120V Models requires additional switch(es) and tandem (end-to-end) elements, cord not available.

▲ 120V Models require additional switch(es) and tandem (end-to-end) elements.

▶ 120V Models available with RMB (GRAML-60, -66, -72, -84 only).

All Aluminum Max Watt Infrared Strip Heater Models with Lights Feature:

Includes: Angle brackets and attached or Remote Control Enclosure


Voltage: 120, 120/208 or 120/240, single phase only.

Leads: 3' conduit with leads – server's right.

Dimensions: 18"-144"W x 9"D x 2½"H.

OPTIONS AND ACCESSORIES – PAGE 9

RECOMMENDED MOUNTING HEIGHTS – PAGE 29



ONE YEAR ON-SITE PARTS AND LABOR WARRANTY, PLUS ONE ADDITIONAL YEAR PARTS-ONLY WARRANTY ON ALL GLO-RAY® METAL-SHEATHED HEATING ELEMENTS.



GRAML-48
with standard
angle brackets

OPTIONS (available at time of purchase only)

Designer Colors, Aluminum Models 18"-144" – Non-standard colors are non-returnable –

COLOR-6	6" Housing for GRAM Models				
COLOR-9	9" Housing for GRAML Models				
RMB-COLOR	Remote Control Housing in Designer Colors				
RED	Warm Red	GRAY	Gray Granite	NAVY	Navy Blue
BLACK	Black	WHITE	White Granite	GREEN	Hunter Green
				COPPER	Antique Copper

Gloss Finishes, Aluminum Models 18"-144" – Non-standard colors are non-returnable –

GLOSS-6	6" Housing for GRAM Models				
GLOSS-9	9" Housing for GRAML Models				
RMB-GLOSS	Remote Control Housing in Gloss Finishes				
RRED	Radiant Red	GGRAY	Glossy Gray	BBLACK	Bold Black
GGOLD	Gleaming Gold	BBLUE	Brilliant Blue		

Leads (extended beyond standard 3' Conduit – must specify Lead length) –

HTLEADS5	1'-5' Extended Electrical Leads
HTLEADS10	6'-10' Extended Electrical Leads
HTLEADS15	11'-15' Extended Electrical Leads
HTLEADS20	16'-20' Extended Electrical Leads
3 ANEAL REFL	Bright Annealed Reflector for Lights with 3" Spacer
RMB-GRAM-INF	Remote Control Enclosure with Toggle Control Switch, Electronic Infinite Control, Relay and Indicator Light in lieu of standard Remote Control Box
NTL-14, -16	Non-Adjustable Tubular Stands (specify 14" or 16" clearance)
NTL-18, -20	Non-Adjustable Tubular Stands (specify 18" or 20" clearance)
NTL-22, -24	Non-Adjustable Tubular Stands (specify 22" or 24" clearance)
NTL-PAINT	Designer Color or Gloss Finish for Non-Adjustable Tubular Stands (one pair) – Non-standard colors are non-returnable –
CAP	Attached 6' Cord and Plug Set (120V only) on Models up to 48" requires standard Chain Mount Kit (two S Hooks with two 6" Lengths of Chain)
CHAIN-HOOK	Two S Hooks with two 6" Lengths of Chain
HAL	Halogen Bulb in lieu of Incandescent Display Light (60 Watt)
NO BULB	No Bulb Option (GRAML Models only)

ACCESSORIES (available for purchase at any time)

CHAIN 1	Chain Suspension
----------------	------------------

COLORS AND FINISHES – PAGE 33

Glo-Ray® Max Watt Dual Infrared Strip Heaters

Create a deeper holding area with Glo-Ray® Max Watt Dual Aluminum Infrared Strip Heaters mounted side-by-side, keeping hot food at optimum serving temperatures. The pre-focused heat pattern directs heat from a metal-sheathed element, bathing the entire holding surface. The continuous aluminum housing and heavy-duty mountings ensure the durability and quality of Hatco products.

- Features 25% greater wattage output than Glo-Ray high watt by comparison with dual units varying in wattage from 900 to 8300 watts; and units with lights varying from 1020 to 9020 watts
- Sturdy extruded aluminum housings that do not sag, from 18" to 72" in 6" increments and 84" to 144" in 12" increments
- Reinforced wire guard provides operator safety without affecting heat distribution
- 3" or 6" spacer available
- Heavy-duty insulation minimizes heat loss
- Shatter-resistant incandescent lights (standard on GRAML models) enhance product display while safeguarding food products from bulb breakage. An optional halogen bulb may be used in lieu of incandescents
- Additional reflector styles available, consult factory for more information



GRAM-36D
with 3" spacer

ALUMINUM MAX WATT DUAL STRIP HEATERS

Model	Width	Voltage Single Phase	Watts	Ship Weight*
Max Watt				
GRAM-18D	18"	120, 208 or 240	900	14 lbs.
GRAM-24D	24"	120, 208 or 240	1300	16 lbs.
GRAM-30D	30"	120, 208 or 240	1650	18 lbs.
GRAM-36D	36"	120, 208 or 240	2000	21 lbs.
GRAM-42D	42"	120, 208 or 240	2350	24 lbs.
GRAM-48D	48"	120, 208 or 240	2600	27 lbs.
GRAM-54D	54"	120, 208 or 240	3000	30 lbs.
GRAM-60D	60"	120, 208 or 240	3400	34 lbs.
GRAM-66D [▲]	66"	120, 208 or 240	3750	37 lbs.
GRAM-72D [▲]	72"	120, 208 or 240	4150	41 lbs.
GRAM-84D [▲]	84"	120, 208 or 240	4800	44 lbs.
GRAM-96D ^{▼▲}	96"	120, 208 or 240	5350	52 lbs.
GRAM-108D	108"	208 or 240	6000	59 lbs.
GRAM-120D	120"	208 or 240	6800	66 lbs.
GRAM-132D	132"	208 or 240	7500	73 lbs.
GRAM-144D	144"	208 or 240	8300	80 lbs.

* Includes Remote Control enclosure with toggle switch(es) and indicator light(s).

♦ Add 2-8 lbs. depending on RMB.

▲ 120V Models require additional switches and tandem (end-to-end) elements.

▼ When using an infinite control with 120V Models, additional switch(es) and tandem (end-to-end) elements are required.

All Aluminum Max Watt Dual Strip Heater Models Feature:

Includes: Angle brackets and Remote Control Enclosure.

Voltage: 120, 208 or 240, single phase only.


Leads: 3' conduit with leads – server's right.

Dimensions: with 3" Spacer (standard): 18"-144"W x 15"D x 2½"H.

with 6" Spacer: 18"-144"W x 18"D x 2½"H.

OPTIONS AND ACCESSORIES – PAGE 13


RECOMMENDED MOUNTING HEIGHTS – PAGE 29



ONE YEAR ON-SITE PARTS AND LABOR WARRANTY, PLUS ONE ADDITIONAL YEAR PARTS-ONLY WARRANTY ON ALL GLO-RAY® METAL-SHEATHED HEATING ELEMENTS.



Strip Heater Solutions



GRAML-72D with 3" spacer and lights and optional Black *Designer* color, includes Remote Control enclosure

ALUMINUM MAX WATT DUAL STRIP HEATERS WITH LIGHTS

Model	Bulbs	Width	Voltage Single Phase	Watts	Ship Weight [◇]
Max Watt					
GRAML-18D	2	18"	120, 120/208 or 120/240	1020	14 lbs.
GRAML-24D	2	24"	120, 120/208 or 120/240	1420	16 lbs.
GRAML-30D	2	30"	120, 120/208 or 120/240	1770	19 lbs.
GRAML-36D	3	36"	120, 120/208 or 120/240	2180	22 lbs.
GRAML-42D	3	42"	120, 120/208 or 120/240	2530	25 lbs.
GRAML-48D	4	48"	120, 120/208 or 120/240	2840	29 lbs.
GRAML-54D	4	54"	120/208 or 120/240	3240	34 lbs.
GRAML-60D	5	60"	120/208 or 120/240	3700	37 lbs.
GRAML-66D [▲]	5	66"	120/208 or 120/240	4050	40 lbs.
GRAML-72D [▲]	6	72"	120/208 or 120/240	4510	42 lbs.
GRAML-84D [▲]	7	84"	120/208 or 120/240	5220	47 lbs.
GRAML-96D ^{▼▲}	8	96"	120/208 or 120/240	5830	56 lbs.
GRAML-108D [▼]	9	108"	120/208 or 120/240	6540	64 lbs.
GRAML-120D [▼]	10	120"	120/208 or 120/240	7400	72 lbs.
GRAML-132D [▼]	11	132"	120/208 or 120/240	8160	79 lbs.
GRAML-144D [▼]	12	144"	120/208 or 120/240	9020	86 lbs.

* Includes Remote Control Enclosure with toggle switch(es) and indicator light(s).

► Available with Remote Control Enclosure, RMB-GRAM-INF only, see page 13.

◇ Add 2-8 lbs. depending on RMB.

▲ 120V Models require additional switches and tandem (end-to-end) elements.

▼ When using an infinite control with 120V Models, additional switch(es) and tandem (end-to-end) elements are required.

Note: Other control options available, consult factory.

All Aluminum Max Watt Dual Strip Heater with Models with Lights Feature:

Includes: Angle brackets and Remote Control Enclosure.

Voltage: 120, 120/208 or 120/240, single phase only.

Leads: 3' conduit with leads – server's right.

Dimensions: with 3" Spacer (standard): 15"D x 2½"H.

with 6" Spacer: 18"D x 2½"H.

OPTIONS AND ACCESSORIES – PAGE 13

RECOMMENDED MOUNTING HEIGHTS – PAGE 29



ONE YEAR ON-SITE PARTS AND LABOR WARRANTY, PLUS ONE
ADDITIONAL YEAR PARTS-ONLY WARRANTY ON ALL GLO-RAY®
METAL-SHEATHED HEATING ELEMENTS.

GRAML-60D with optional
non-adjustable tubular stands



OPTIONS (available at time of purchase only)

Designer Colors, Aluminum Models 18"-144" – Non-standard colors are non-returnable –

COLOR-15, -18 15" and 18" Housings for GRAM and GRAML Dual Models

RMB-COLOR Remote Control Housing in Designer Colors

RED Warm Red
BLACK Black

GRAY Gray Granite
WHITE White Granite

NAVY Navy Blue
GREEN Hunter Green

COPPER Antique Copper

Gloss Finishes, Aluminum Models 18"-144" – Non-standard colors are non-returnable –

GLOSS-15, -18 15" and 18" Housings for GRAM and GRAML Dual Models

RMB-GLOSS Remote Control Housing in Gloss Finishes

RR Radiant Red
GG Gleaming Gold

GG Glossy Gray
BB Brilliant Blue

BB Bold Black

Leads (extended beyond standard 3' Conduit – must specify Lead length) –

HTLEADS5 1'-5' Extended Electrical Leads

HTLEADS10 6'-10' Extended Electrical Leads

HTLEADS15 11'-15' Extended Electrical Leads

HTLEADS20 16'-20' Extended Electrical Leads

RMB-GRAM-INF Remote Control Enclosure with Toggle Control Switch, Electronic Infinite Control, Relay and Indicator Light in lieu of standard Remote Control Box

3 ANEAL REFL Bright Annealed Reflector for Lights with 3" Spacer

6 ANEAL REFL Bright Annealed Reflector for Lights with 6" Spacer

NTL-18-D, -20 -D Non-Adjustable Tubular Stands (specify 18" or 20" clearance)

NTL-22-D, -24-D Non-Adjustable Tubular Stands (specify 22" or 24" clearance)

NTL-PAINT-D Designer Color or Gloss Finish for Non-Adjustable Tubular Stands – Non-standard colors are non-returnable –

HAL Halogen Bulb in lieu of Incandescent Display Light (60 Watt)

NO BULB No Bulb Option (GRAML-xxD Models only)

COLORS AND FINISHES – PAGE 33



Strip Heater Solutions

Glo-Ray® Narrow Halogen Strip Heaters

Hatco Glo-Ray® Narrow Halogen Strip Heaters are great for use in tight spaces and keep the focus on food items being displayed. Even the most delicate dishes hold that just-prepared look.

- Sleek, slim design with just 2½" height and 4" depth
- Halogen heat source is controlled by a dimmer switch, allowing maximum flexibility
- Xenon bulbs, controlled by a toggle switch, light food product when no extra heat is desired
- Available in widths from 18" to 72" for GRN4 models and 24" to 72" for GRN4L models

Remote Control Enclosures



For GRN4 models:
One dimmer and one toggle switch



For GRN4L models:
One dimmer and two toggle switches

GRN4L-36 in Designer Black (standard) alternates Halogen heat with Xenon lights - Angle brackets standard (not shown)



GRN4-36 in Designer Black (standard) using Halogen heat - Angle brackets standard (not shown)

NARROW HALOGEN STRIP HEATERS

Model	No. of Elements	Width	Watts	Ship Weight [□]
GRN4-18	2	18"	400	8 lbs.
GRN4-24	2	24"	400	8 lbs.
GRN4-30	2	30"	400	10 lbs.
GRN4-36	3	36"	600	11 lbs.
GRN4-42	3	42"	600	12 lbs.
GRN4-48	3	48"	600	12 lbs.
GRN4-54	4	54"	800	15 lbs.
GRN4-60	4	60"	800	15 lbs.
GRN4-66	5	66"	1000	17 lbs.
GRN4-72	5	72"	1000	18 lbs.

[□] Includes Remote Control Enclosures with dimmer and toggle(s).

All Narrow Halogen Strip Heater Models Feature:

Voltage: 120, single phase only.

Leads: 6" leads.

Models Shipped with: 3' conduit with leads, angle brackets and Remote Control Enclosure with switch(es).

Dimensions: 18" to 72"W x 4"D x 2½"H.

NARROW HALOGEN STRIP HEATERS WITH XENON LIGHTS

Model	No. of Elements	No. of Bulbs	Width	Watts	Ship Weight [□]
GRN4L-24	2	1	24"	450	9 lbs.
GRN4L-30	2	1	30"	450	10 lbs.
GRN4L-36	3	2	36"	700	13 lbs.
GRN4L-42	3	2	42"	700	14 lbs.
GRN4L-48	3	2	48"	700	14 lbs.
GRN4L-54	4	3	54"	950	17 lbs.
GRN4L-60	4	3	60"	950	18 lbs.
GRN4L-66	5	4	66"	1200	21 lbs.
GRN4L-72	5	4	72"	1200	21 lbs.

[□] Includes Remote Control Enclosures with dimmer and toggle(s).

All Narrow Halogen Strip Heater Models with Xenon Lights Feature:


Voltage: 120, single phase only.

Leads: 6" leads.


Models Shipped with: 3' conduit with leads, angle brackets and remote control enclosure with switch(es).

Dimensions: 24" to 72"W x 4"D x 2½"H.

OPTIONS AND ACCESSORIES – PAGE 14
RECOMMENDED MOUNTING HEIGHTS – PAGE 29



- A** Powdercoated steel continuous housing in a variety of colors
- B** Heavy-duty insulation minimizes heat loss
- C** Aluminized reflector retains full heat intensity and directs more heat towards the edges of the holding surface
- D** Ceramic glass shields provide a safety barrier for the xenon and halogen bulbs
- E** Xenon bulbs light food when no extra heat is needed





GRN4L-54 with optional
non-adjustable tubular stands
above a GR2S-42

OPTIONS (available at time of purchase only)

Designer Colors – Non-standard colors are non-returnable – Black Standard –

RED	Warm Red	GRAY	Gray Granite	NAVY	Navy Blue	COPPER	Antique Copper
BLACK	Black	WHITE	White Granite	GREEN	Hunter Green		

Gloss Finishes – Non-standard colors are non-returnable –

SWHITE	Smooth White	GGOLD	Gleaming Gold	GGRAY	Glossy Gray	BBLACK	Bold Black
---------------	--------------	--------------	---------------	--------------	-------------	---------------	------------

Stainless Steel – Non-standard colors are non-returnable –

SS	Stainless Steel
-----------	-----------------

Gloss Finishes* – Non-standard colors are non-returnable –

RRED*	Radiant Red	BBLUE*	Brilliant Blue
--------------	-------------	---------------	----------------

Plated Finishes* – Non-standard colors are non-returnable –

BBRASS1*	Bright Brass	BCOPPER1*	Bright Copper	ANICKEL1*	Antique Nickel
BNICKEL1*	Bright Nickel	ABRASS1*	Antique Brass	ABRONZE1*	Antique Bronze

Leads (must specify Lead length) –

LEADS5 1'-5' Extended Electrical Leads

LEADS10 6'-10' Extended Electrical Leads

LEADS15 11'-15' Extended Electrical Leads

LEADS20 16'-20' Extended Electrical Leads

NTL-10, 12 Non-Adjustable Tubular Stands (specify 10" or 12" clearance)

NTL-14, 16 Non-Adjustable Tubular Stands (specify 14" or 16" clearance)

NTL-PAINT Designer Color or Gloss Finish for Non-Adjustable Tubular Stands – Non-standard colors are non-returnable –

Control Box Bezel – Designer Colors – Non-standard colors are non-returnable –

RED	Warm Red	GRAY	Gray Granite	NAVY	Navy Blue	COPPER	Antique Copper
BLACK	Black	WHITE	White Granite	GREEN	Hunter Green		

* Special process required and extended lead times.

COLORS AND FINISHES – PAGE 33

Glo-Ray® Narrow Infrared Strip Heaters

Hatco Glo-Ray® Narrow Infrared Strip Heaters keep all hot foods at optimum serving temperatures longer, while the slim design fits ideally in buffet areas. Even the most delicate dishes hold that "just-prepared" look. The entire holding surface is heated evenly with no "cold" spots.

- Slim design that's 2" high and 4" deep
- Available in widths from 18"-72"
- Pre-focused heat pattern maintains serving temperatures longer without continuing to cook the food
- Optional remote control enclosure available in *Designer* colors

Toggle Switch: Max. 15 amps
Infinite Switch: Max. 12.2 amps



GRN-24 in standard
Designer Black with
standard angle brackets

NARROW STRIP HEATERS

Model*	Width	Voltage (Single Phase)	Watts	Ship Weight
Standard Watt				
GRN-18	18"	120, 208 or 240	250	6 lbs.
GRN-24	24"	120, 208 or 240	350	7 lbs.
GRN-30	30"	120, 208 or 240	450	8 lbs.
GRN-36	36"	120, 208 or 240	575	9 lbs.
GRN-42	42"	120, 208 or 240	675	10 lbs.
GRN-48	48"	120, 208 or 240	800	11 lbs.
GRN-54	54"	120, 208 or 240	925	13 lbs.
GRN-60	60"	120, 208 or 240	1050	14 lbs.
GRN-66	66"	120, 208 or 240	1160	16 lbs.
GRN-72	72"	120, 208 or 240	1275	17 lbs.

High Watt

GRNH-18	18"	120, 208 or 240	350	6 lbs.
GRNH-24	24"	120, 208 or 240	500	7 lbs.
GRNH-30	30"	120, 208 or 240	660	8 lbs.
GRNH-36	36"	120, 208 or 240	800	9 lbs.
GRNH-42	42"	120, 208 or 240	950	10 lbs.
GRNH-48	48"	120, 208 or 240	1100	11 lbs.
GRNH-54	54"	120, 208 or 240	1250	13 lbs.
GRNH-60	60"	120, 208 or 240	1400	14 lbs.
GRNH-66[†]	66"	120, 208 or 240	1560	16 lbs.
GRNH-72[‡]	72"	120, 208 or 240	1725	17 lbs.

* Does not include RMB (see page 31 and 32).

* Units not available with Infinite Switch in 120V. RMB2-1R or RMB2-2R series remote control box required.

All Narrow Strip Heater Models Feature:

Toggle Switch (Max. 15 Amps) with Indicator Light Location: Chef's left side (unless otherwise specified).


Designer Color Angle Brackets: To match unit color and provide 1½" clearance between Strip Heater and overshef. Non-standard colors are non-returnable.

Leads: 6" leads – server's right.

Dimensions: 18"-72"W x 4"D x 2"H.


RECOMMENDED MOUNTING HEIGHTS – PAGE 29

COLORS AND FINISHES – PAGE 33



- A** Sturdy housing in stainless steel or one of seven *Designer* colors
- B** Heavy-duty insulation minimizes heat loss
- C** Aluminized reflector retains full heat intensity and directs more heat towards edges of holding surface
- D** Protective wire guard supports heating element without affecting heat distribution

ONE YEAR ON-SITE PARTS AND LABOR WARRANTY, PLUS ONE
ADDITIONAL YEAR PARTS-ONLY WARRANTY ON ALL GLO-RAY®
METAL-SHEATHED HEATING ELEMENTS.



OPTIONS (available at time of purchase only)

Designer Colors, Models 18"-72" – Non-standard colors are non-returnable – Black Standard –

Models 10 - 12	Non-Standard Colors are Non-Returnable	Black Standard
RED Warm Red	GRAY Gray Granite	NAVY Navy Blue
BLACK Black	WHITE White Granite	GREEN Hunter Green
		COPPER Antique Copper

Stainless Steel – Non-standard colors are non-returnable –

SS Stainless Steel

Leads (must specify Lead length) –

LEADS5	1'-5'	Extended	Electrical Leads
LEADS10	6'-10'	Extended	Electrical Leads
LEADS15	11'-15'	Extended	Electrical Leads
LEADS20	16'-20'	Extended	Electrical Leads

LEADS20	10 - 20 Extended Electrical Leads
NO CONTROL	No Control included (requires selection of RMB2-xx Control)

See page 31

RMB Remote Box (available in *Designer Colors* or *Gloss Finishes*) – Non-standard colors are non-returnable –

See page 31 and 32

TABS Stainless Steel Hanger Tabs in lieu of Angle Brackets

CAP Attached 6' Cord and Plug Set (120V only) on Models up to 72" with standard Chain Mount Kit (two S Hooks with two 6" Lengths of Chain) and Hanger Tabs (max. 1800 Watt)

CHAIN-HOOK Two S Hooks with two 6" Lengths of Chain

CHAIN LOCK	Two S-locks with two S-locks or Chain
NTL-10, 12	Non-Adjustable Tubular Stands (specify 10" or 12" clearance and power location)

NTL-13, 12	Non-Adjustable Tubular Stands (specify 13" or 12" clearance and power location)
NTL-14, 16	Non-Adjustable Tubular Stands (specify 14" or 16" clearance and power location)

NTL-PAINT *Designer Color for Non-Adjustable Tubular Stands – Non-standard colors are non-returnable –*

Glo-Ray® Narrow Max Watt Infrared Strip Heaters

Glo-Ray® Narrow Max Watt Infrared Strip Heaters keep all hot foods at optimum serving temperatures longer, while the slim design fits ideally in buffet areas. The entire holding surface is heated evenly with no “cold” spots.

- Slim design that's 2" high and 4" deep
- Available in widths from 18"-72"
- Pre-focused heat pattern maintains serving temperatures longer without continuing to cook the food
- Available in stainless steel only



GRNM-24 in standard stainless steel with standard angle brackets

NARROW MAX WATT INFRARED STRIP HEATERS

Model*	Width	Voltage	Watts	Ship Weight
		Single Phase		
GRNM-18	18"	120, 208 or 240	450	6 lbs.
GRNM-24	24"	120, 208 or 240	650	7 lbs.
GRNM-30	30"	120, 208 or 240	825	8 lbs.
GRNM-36	36"	120, 208 or 240	1000	9 lbs.
GRNM-42	42"	120, 208 or 240	1175	10 lbs.
GRNM-48	48"	120, 208 or 240	1300	11 lbs.
GRNM-54[‡]	54"	120, 208 or 240	1500	13 lbs.
GRNM-60[‡]	60"	120, 208 or 240	1700	14 lbs.
GRNM-66[‡]*[×]	66"	120, 208 or 240	1875	16 lbs.
GRNM-72[‡]*[×]	72"	120, 208 or 240	2075	17 lbs.

* Does not include RMB (see page 31 and 32).

[‡] Units not available with Infinite Switch in 120V. RMB2-1R or RMB2-2R series remote control box required.

[×] RMB2-1R or RMB2-2R series Remote Control Box required.

All Narrow Max Watt Infrared Strip Heater Models Feature:

Angle Brackets: Provides 1½" clearance between Strip Heater and overshelf.

Leads: 6" leads – server's right.

Dimensions: 18"-72"W x 4"D x 2"H.

RECOMMENDED MOUNTING HEIGHTS – PAGE 29

OPTIONS (available at time of purchase only)

Leads (extended beyond standard 6" Leads – must specify Lead length) –

HTLEADS5 1'-5' Extended Electrical Leads

HTLEADS10 6'-10' Extended Electrical Leads

HTLEADS15 11'-15' Extended Electrical Leads

HTLEADS20 16'-20' Extended Electrical Leads

NO CONTROL No Control included (requires selection of RMB2-xx Control)

See page 31

RMB Requires Remote Box (not available with Built-In Controls)

See page 31 and 32

TABS Stainless Steel Hanger Tabs in lieu of Angle Brackets

CHAIN-HOOK Two S Hooks with two 6" Lengths of Chain

NTL-14, 16 Non-Adjustable Tubular Stands (specify 14" or 16" clearance and power location)



ONE YEAR ON-SITE PARTS AND LABOR WARRANTY, PLUS ONE ADDITIONAL YEAR PARTS-ONLY WARRANTY ON ALL GLO-RAY® METAL-SHEATHED HEATING ELEMENTS.



Strip Heater Solutions

Glo-Ray® High Watt Infra-Black® Strip Heaters

For foodwarming at a close range to food product, the Glo-Ray® Infra-Black® heat technology is ideal, emitting a solid panel of uniform heat. Sturdy continuous single or dual extruded aluminum housings assure quality, durability and a variety of widths, depths, mounting arrangements and colors will fit your operation.


Toggle Switch: Max. 15 amps
Infinite Switch: Max. 12.2 amps

GRAIH-36 with optional wire guard (requires Remote Control Enclosure)



- Provides ideal amount of heat for limited space operations, mounted 4" to 10" above target surface for singles and 8" to 14" for duals
- Metal-sheathed heating elements guaranteed against burnout and breakage for two years
- Infra-Black emitter provides even heat distribution – eliminating hot spots
- Sturdy aluminum housings that do not sag, from 18" to 72" in 6" increments
- Heavy-duty insulation keeps the exterior housing cool
- Optional wire guard available to protect user from incidental contact with heated surface
- Optional 3" or 6" spacer available on dual models with or without lights (see next page)

GRAIH-36 with optional TCBI control box and wire guard



ALUMINUM STRIP HEATERS – HIGH WATT INFRA-BLACK

Model®	Width	Voltage		Watts	Ship Weight*
		Single Phase			
GRAIH-18	18"	120, 208 or 240	350	6 lbs.	
GRAIH-24	24"	120, 208 or 240	500	11 lbs.	
GRAIH-30	30"	120, 208 or 240	660	13 lbs.	
GRAIH-36	36"	120, 208 or 240	800	15 lbs.	
GRAIH-42	42"	120, 208 or 240	950	17 lbs.	
GRAIH-48	48"	120, 208 or 240	1100	21 lbs.	
GRAIH-54	54"	120, 208 or 240	1250	24 lbs.	
GRAIH-60	60"	120, 208 or 240	1400	27 lbs.	
GRAIH-66♦	66"	120, 208 or 240	1560	30 lbs.	
GRAIH-72♦	72"	120, 208 or 240	1725	33 lbs.	

ALUMINUM STRIP HEATERS – HIGH WATT INFRA-BLACK WITH LIGHTS

Model	No. of Bulbs	Width	Voltage Single Phase	Watts	Ship Weight*
GRAIHL-18	2	18"	120, 120/208 or 120/240	470	12 lbs.
GRAIHL-24	2	24"	120, 120/208 or 120/240	620	15 lbs.
GRAIHL-30	2	30"	120, 120/208 or 120/240	780	17 lbs.
GRAIHL-36	3	36"	120, 120/208 or 120/240	980	20 lbs.
GRAIHL-42	3	42"	120, 120/208 or 120/240	1130	23 lbs.
GRAIHL-48	4	48"	120, 120/208 or 120/240	1340	26 lbs.
GRAIHL-54	4	54"	120, 120/208 or 120/240	1490	29 lbs.
GRAIHL-60	5	60"	120, 120/208 or 120/240	1700	33 lbs.
GRAIHL-66*	5	66"	120, 120/208 or 120/240	1860	34 lbs.
GRAIHL-72* ^Δ	6	72"	120, 120/208 or 120/240	2085	36 lbs.

* Does not include RMB or TCBI. Must choose either RMB (see page 31 and 32) or TCBI (see OPTIONS on page 18).

* Does not include RMB.

* Infinite not available in 120V.

^ 120V Models available with remote control only.

All Infra-Black Aluminum Strip Heater Models Feature:

Leads: 3' conduit with leads – server's right. 6" leads when supplied with TCBI – exit side of control box.

Dimensions: GRAIH: 18"-72"W x 6"D x 2½"H.


GRAIHL: 18"-72"W x 9"D x 2½"H.

TCBI Control Enclosure Dimensions (not including Switches): 8"W x 3"D x 2½"H.

Control Enclosure location: Chef's left side – light side (unless otherwise specified).


OPTIONS AND ACCESSORIES – PAGE 18

RECOMMENDED MOUNTING HEIGHTS – PAGE 29



- A** Thermostatically controlled to regulate heat and provide consistent temperature. (Optional remote infinite control available)
- B** Heavy-duty insulation minimizes heat loss
- C** Provides ideal amount of heat for limited space operations, effectively holding product
- D** Optional protective reinforced wire guard supports heating element without affecting heat distribution
- E** Infra-Black emitter provides even heat distribution, eliminating hot spots for close applications

ONE YEAR ON-SITE PARTS AND LABOR WARRANTY, PLUS ONE ADDITIONAL YEAR PARTS-ONLY WARRANTY ON ALL GLO-RAY® METAL-SHEATHED HEATING ELEMENTS.



Glo-Ray® High Watt Dual Infra-Black® Strip Heaters

Toggle Switch: Max. 15 amps
Infinite Switch: Max. 12.2 amps



GRAIH-60D 120V
models available with
remote control only



GRAIHL-24D in
optional Radiant Red
Gloss Finish

DUAL ALUMINUM STRIP HEATERS – HIGH WATT INFRA-BLACK

Model ^o	Width	Voltage	Watts	Ship Weight [*]
		Single Phase		
GRAIH-18D	18"	120, 208 or 240	700	13 lbs.
GRAIH-24D	24"	120, 208 or 240	1000	19 lbs.
GRAIH-30D	30"	120, 208 or 240	1320	21 lbs.
GRAIH-36D	36"	120, 208 or 240	1600	24 lbs.
GRAIH-42D^Δ	42"	120, 208 or 240	1900	27 lbs.
GRAIH-48D^Δ	48"	120, 208 or 240	2200	32 lbs.
GRAIH-54D^Δ	54"	120, 208 or 240	2500	35 lbs.
GRAIH-60D^Δ	60"	120, 208 or 240	2800	39 lbs.
GRAIH-66D^Δ*	66"	120, 208 or 240	3120	42 lbs.
GRAIH-72D^Δ*	72"	120, 240	3450	46 lbs.

DUAL ALUMINUM STRIP HEATERS – HIGH WATT INFRA-BLACK WITH LIGHTS

Model ^o	No. of Bulbs	Width	Voltage	Watts	Ship Weight [*]
			Single Phase		
GRAIHL-18D	2	18"	120, 120/208 or 120/240	820	18 lbs.
GRAIHL-24D	2	24"	120, 120/208 or 120/240	1120	21 lbs.
GRAIHL-30D	2	30"	120, 120/208 or 120/240	1440	23 lbs.
GRAIHL-36D	3	36"	120, 120/208 or 120/240	1780	27 lbs.
GRAIHL-42D^Δ	3	42"	120, 120/208 or 120/240	2080	30 lbs.
GRAIHL-48D^Δ	4	48"	120, 120/208 or 120/240	2440	35 lbs.
GRAIHL-54D^Δ	4	54"	120, 120/208 or 120/240	2740	38 lbs.
GRAIHL-60D^Δ	5	60"	120, 120/208 or 120/240	3100	42 lbs.
GRAIHL-66D^Δ*	5	66"	120, 120/240	3420	44 lbs.

^o Does not include RMB or TCBI. Must choose either RMB (see page 19 and 19) or TCBI (see OPTIONS on page 19).

^Δ Does not include RMB.

^Δ 120V Models available with remote control only.

^{*} Infinite not available in 120V.

All Dual Infra-Black Aluminum Strip Heater Models Feature:

Leads: 3' conduit with leads – server's right. 6" leads when supplied with TCBI – exit side of control box.

Dimensions: GRAIH-xxD with 3" Spacer: 18"-72"W x 15"D x 2½"H.

GRAIHL-xxD with 3" Spacer: 18"-66"W x 15"D x 2½"H.

GRAIH-xxD with 6" Spacer: 18"-72"W x 18"D x 2½"H.


GRAIHL-xxD with 6" Spacer: 18"-66"W x 18"D x 2½"H.

TCBI Control Enclosure Dimensions (not including Switches): 8"W x 3"D x 2½"H.

Control Enclosure location: Chef's left side – light side (unless otherwise specified).

OPTIONS AND ACCESSORIES – PAGE 19

RECOMMENDED MOUNTING HEIGHTS – PAGE 29



ONE YEAR ON-SITE PARTS AND LABOR WARRANTY, PLUS ONE
 ADDITIONAL YEAR PARTS-ONLY WARRANTY ON ALL GLO-RAY®
 METAL-SHEATHED HEATING ELEMENTS.



GRAIH-72 with optional wire guard (requires Remote Control Enclosure)

OPTIONS (available at time of purchase only)

Designer Colors – Non-standard colors are non-returnable –

COLOR-6, -9 6" Housing for GRAIH Models and 9" Housing for GRAIHL Models

COLOR-15, -18 15" and 18" Housings for GRAIH and GRAIHL Dual Models

RED	Warm Red	GRAY	Gray Granite	NAVY	Navy Blue	COPPER	Antique Copper
BLACK	Black	WHITE	White Granite	GREEN	Hunter Green		

Gloss Finishes – Non-standard colors are non-returnable –

GLOSS-6, -9 6" Housing for GRAIH Models and 9" Housing for GRAIHL Models

GLOSS-15, -18 15" and 18" Housings for GRAIH and GRAIHL Dual Models

RRED	Radiant Red	GGRAY	Glossy Gray	BBLACK	Bold Black
GGOLD	Gleaming Gold	BBLUE	Brilliant Blue		

AIH18WG -AIH72WG Element Wire Guard (Dual Models require two sets)

HAL Halogen Bulb in lieu of standard Display Light (60 Watt)

NO CONTROL No Control included (GRAIH, GRAIHL-xx, GRAIH, GRAIHL-xxD Models only). Requires selection of RMB2-xx Control

See page 31

RMB Remote Box (available in *Designer Colors* or *Gloss Finishes*) – Non-standard colors are non-returnable –

See page 31 and 32

TCBI Thermostatic Control Box with Indicator Lights

AIH4NTL 4" Non-Adjustable Tubular Stands

AIH6NTL 6" Non-Adjustable Tubular Stands

AIH8NTL 8" Non-Adjustable Tubular Stands (Dual Models require two pair)

AIH10NTL 10" Non-Adjustable Tubular Stands (Dual Models require two pair)

AIH12NTL-D 12" Non-Adjustable Tubular Stands

AIH14NTL-D 14" Non-Adjustable Tubular Stands

NTL-PAINT *Designer Color* or *Gloss Finish* for Non-Adjustable Tubular Stands – Non-standard colors are non-returnable –

NTL-PAINT-D *Designer Color* or *Gloss Finish* for Non-Adjustable Tubular Stands – Non-standard colors are non-returnable –

ACCESSORIES (available for purchase at any time)

ADJ ANGLE Adjustable Angle Brackets (Dual Models require two pair). See page 30 for illustration

ADJ ANGLE-D Adjustable Angle Brackets (see page 30 for illustration)

CHAIN 1 Chain Suspension (see page 30 for illustration)

Chef LED 120V Adjustable Bulb – GRAIHL Models only, all voltages –

Please contact your local representative or the factory for the most up to date listing of installations and applicable models –

CLED-2700-120 Emulates incandescent **CLED-3000-120** Emulates halogen **CLED-4000-120** Emulates fluorescent

COLORS AND FINISHES – PAGE 33



**CLED-2700, -3000
or -4000**

Glo-Ray® Designer Infrared Strip Heaters

Hatco Glo-Ray® Designer Infrared Strip Heaters safely keep all hot foods at optimum serving temperatures longer. This modern design is ideal for front-of-the-house use. Units are offered in continuous housings, up to 7', are available in *Designer* colors to match most décors and include 14" *Designer* non-adjustable stands.

Toggle Switch: Max. 15 amps
Infinite Switch: Max. 12.2 amps

- Pre-focused heat maintains safe serving temperatures longer without continuing to cook the food
- Available in widths from 21½" to 87½"
- Available in a variety of models, configurations, colors and accessories to provide unlimited flexibility
- Black corner caps and inset panels standard

- Optional coated shatter-resistant incandescent or halogen lights enhance product displays while safeguarding food from bulb breakage
- Optional sneeze guards
- Additional reflector styles and lower wattage elements available, consult factory for more information



GR2AH-36 with *Designer* non-adjustable stands and optional *Designer* color inset panels



GR2AHL-36 with optional overhead mounts and *Designer* color inset panels

DESIGNER INFRARED ALUMINUM STRIP HEATERS

Model* [©]	Width	Watts	Ship Weight*
Standard Watt			
GR2A-18	21½"	250	28 lbs.
GR2A-24	27½"	350	32 lbs.
GR2A-30	33½"	450	35 lbs.
GR2A-36	39½"	575	37 lbs.
GR2A-42	45½"	675	53 lbs.
GR2A-48	51½"	800	64 lbs.
GR2A-54	57½"	925	74 lbs.
GR2A-60	63½"	1050	82 lbs.
GR2A-66	69½"	1160	91 lbs.
GR2A-72	75½"	1275	100 lbs.
GR2A-84 [▼]	87½"	1500	120 lbs.
High Watt			
GR2AH-18	21½"	350	28 lbs.
GR2AH-24	27½"	500	32 lbs.
GR2AH-30	33½"	660	35 lbs.
GR2AH-36	39½"	800	37 lbs.
GR2AH-42	45½"	950	53 lbs.
GR2AH-48	51½"	1100	64 lbs.
GR2AH-54	57½"	1250	74 lbs.
GR2AH-60	63½"	1400	82 lbs.
GR2AH-66 [▼]	69½"	1560	91 lbs.
GR2AH-72 [▼]	75½"	1725	100 lbs.
GR2AH-84 [▲]	87½"	2050	120 lbs.

* When no color is specified, color inset panels and corner caps will be Black.

° Does not include RMB. Must choose RMB (see page 31 and 32).

* Does not include RMB.

▼ When using an infinite control with 120V Models, additional switch(es) and tandem (end-to-end) elements required.

▲ 120V Models require additional switches and tandem (end-to-end) elements.

All Designer Infrared Aluminum Strip Heater Models Feature:

Voltage: 120, 208 or 240, single phase only.


Switch Location: Remote only (see page 31 and 32).

Leads: 5' leads through ½" conduit in leg cavity.

Dimensions without Stands: 21½"-87½"W x 9"D x 3½"H.

OPTIONS AND ACCESSORIES – PAGE 21

RECOMMENDED MOUNTING HEIGHTS – PAGE 29



ONE YEAR ON-SITE PARTS AND LABOR WARRANTY, PLUS ONE ADDITIONAL YEAR PARTS-ONLY WARRANTY ON ALL GLO-RAY® METAL-SHEATHED HEATING ELEMENTS.



Glo-Ray® Designer Infrared Strip Heaters with Lights



GR2AHL-24 with Designer non-adjustable stands optional sneeze guards and Designer color inset panels

DESIGNER ALUMINUM STRIP HEATERS WITH LIGHTS

Model [©]	No. of Bulbs	Width	Watts	Ship Weight*
Standard Watt				
GR2AL-18	2	21½"	370	28 lbs.
GR2AL-24	2	27½"	470	32 lbs.
GR2AL-30	2	33½"	570	35 lbs.
GR2AL-36	3	39½"	755	37 lbs.
GR2AL-42	3	45½"	855	53 lbs.
GR2AL-48	4	51½"	1040	64 lbs.
GR2AL-54	4	57½"	1165	74 lbs.
GR2AL-60	5	63½"	1350	83 lbs.
GR2AL-66	5	69½"	1460	93 lbs.
GR2AL-72	6	75½"	1635	101 lbs.
GR2AL-84 [†]	7	87½"	1920	123 lbs.
High Watt				
GR2AHL-18	2	21½"	470	28 lbs.
GR2AHL-24	2	27½"	620	32 lbs.
GR2AHL-30	2	33½"	780	35 lbs.
GR2AHL-36	3	39½"	980	37 lbs.
GR2AHL-42	3	45½"	1130	53 lbs.
GR2AHL-48	4	51½"	1340	64 lbs.
GR2AHL-54	4	57½"	1490	74 lbs.
GR2AHL-60	5	63½"	1700	83 lbs.
GR2AHL-66 [†]	5	69½"	1860	93 lbs.
GR2AHL-72 [†]	6	75½"	2085	101 lbs.
GR2AHL-84 [†]	7	87½"	2470	123 lbs.

* When no color is specified, color inset panels and corner caps will be Black.

© Does not include RMB. Must choose RMB (see page 31 and 32).

† Does not include RMB.

† When using an infinite control with 120V Models, additional switch(es) and tandem (end-to-end) elements required.

† 120V Models require additional switches and tandem (end-to-end) elements.

All Designer Aluminum Strip Heater Models with Lights Feature:

Voltage: 120, 120/208 or 120/240, single phase only.


Switch Location: Remote only (see page 31 and 32).

Leads: 5' leads through ½" conduit in leg cavity.

Dimensions without Stands: 21½"-87½"W x 12"D x 3½"H.

OPTIONS AND ACCESSORIES – PAGE 22

RECOMMENDED MOUNTING HEIGHTS – PAGE 29



A Choice of seven Designer color inset panels and attractive styling for front-of-the-house applications

B Heavy-duty insulation minimizes heat loss

C Decorative post concealing the power wiring available for counter or overhead mounting

D Accent color corners available in Dark Gray or Black (standard)

E Sturdy aluminium extrusion construction; available in clear anodized aluminum finish or one of seven Designer colors for housings (shown in optional Designer Black)

F Long life metal-sheathed heating element with two year warranty

G Aluminized Reflectors won't discolor, so heat can be reflected and directed to the food product being held

H Protective wire guard supports heating element without affecting heat distribution

GR2AHL-XX



ONE YEAR ON-SITE PARTS AND LABOR WARRANTY, PLUS ONE ADDITIONAL YEAR PARTS-ONLY WARRANTY ON ALL GLO-RAY® METAL-SHEATHED HEATING ELEMENTS.



GR2AHL-84 with standard *Designer* non-adjustable stands and optional *Designer* color and sneeze guards

OPTIONS (available at time of purchase only)

Designer Colors, Aluminum Models 21½" - 87½" (includes Stands) – Non-standard colors are non-returnable –

COLOR-6	9" Housing for GR2A and GR2AH Models							
COLOR-9	12" Housing for GR2AL and GR2AHL Models							
RED	Warm Red	GRAY	Gray Granite	NAVY	Navy Blue	COPPER	Antique Copper	
BLACK	Black	WHITE	White Granite	GREEN	Hunter Green			

Designer Inset Panel Colors – Non-standard colors are non-returnable – Black Standard –

RED	Warm Red	GRAY	Gray Granite	NAVY	Navy Blue	COPPER	Antique Copper	
BLACK	Black	WHITE	White Granite	GREEN	Hunter Green			

Designer Corner Caps – Black Standard –

BLACK	Black Corner Caps	DKGRAY	Dark Gray Corner Caps					
--------------	-------------------	---------------	-----------------------	--	--	--	--	--

NO CONTROL No Control included (GR2A, GR2AH, GR2AL, GR2AHL Models only). Requires selection of RMB2-xx Control **See page 31**

RMB Must choose Remote Control Enclosure (RMB not included) **See page 31 and 32**

Designer Remote Control Enclosures – Non-standard colors are non-returnable –

RMB-COLOR	Remote Control Housing in <i>Designer</i> Color							
RED	Warm Red	GRAY	Gray Granite	NAVY	Navy Blue	COPPER	Antique Copper	
BLACK	Black	WHITE	White Granite	GREEN	Hunter Green			

7.5BP1 7½" Sneeze Guard – one side

7.5BP2 7½" Sneeze Guard – two sides

14BP1 14" Sneeze Guard – one side

14BP2 14" Sneeze Guard – two sides

NTL2-10, 12, 16 *Designer* Color for Non-Adjustable Stands to match unit color: 10", 12" or 16" in lieu of 14" standard Stands – Non-standard colors are non-returnable –

NTH2-4 *Designer* Color for 4" Overhead Mounts to match unit color in lieu of 14" standard Legs – Non-standard colors are non-returnable –

HAL Halogen Bulb in lieu of standard Display Light (60 Watt)

NO BULB No Bulb Option (GR2AL, GR2AHL Models only)

LIGHTS-ADD'L Extra Lamps – installed (max. two per ft. less one – one per foot is standard)

Leads (must specify Lead length) –

LEADS5 1'-5' Extended Electrical Leads

LEADS10 6'-10' Extended Electrical Leads

LEADS15 11'-15' Extended Electrical Leads

LEADS20 16'-20' Extended Electrical Leads

ACCESSORIES (available for purchase at any time)

Chef LED 120V Adjustable Bulb – GR2AL, GR2AHL Models only, all voltages –

Please contact your local representative or the factory for the most up to date listing of installations and applicable models –

CLED-2700-120 Emulates incandescent **CLED-3000-120** Emulates halogen **CLED-4000-120** Emulates fluorescent

COLORS AND FINISHES – PAGE 33



**CLED-2700, -3000
or -4000**



Strip Heater Solutions

Glo-Ray® Designer Dual Infrared Strip Heaters

Glo-Ray® Designer Aluminum Dual Infrared Strip Heaters allow side-by-side mounting of two warmers to provide a deeper holding area, keeping hot food at optimum serving temperatures. These modern front-of-the-house warmers have 3" spacers standard with optional 6" spacers. Units are available in *Designer* colors to match most décors.

Toggle Switch: Max. 15 amps
Infinite Switch: Max. 12.2 amps

- Sturdy continuous aluminum housings eliminate sagging
- Pre-focused heat pattern directs heat from a tubular element to bathe the entire holding surface, holding food safely
- Available in widths from 21½" to 87½"
- Variety of models, configurations, colors and accessories provide unlimited flexibility – non-standard colors are non-returnable



GR2AH-24D with standard *Designer* non-adjustable stands, optional sneeze guards and optional *Designer* color inset panels

- Optional sneeze guards that meet food safety standards can be ordered for display areas and buffet lines
- Optional shatter-resistant incandescent lights available
- Black corner caps and inset panels standard
- Additional reflector styles and lower wattage elements available, consult factory for more information



GR2AHL-48D with standard *Designer* non-adjustable stands and optional *Designer* color inset panels

DESIGNER ALUMINUM DUAL STRIP HEATERS

Model* [©]	Width	Watts	Ship Weight*
Standard Watt			
GR2A-18D	21½"	500	44 lbs.
GR2A-24D	27½"	700	48 lbs.
GR2A-30D	33½"	900	52 lbs.
GR2A-36D	39½"	1150	57 lbs.
GR2A-42D	45½"	1350	66 lbs.
GR2A-48D	51½"	1600	77 lbs.
GR2A-54D	57½"	1850	88 lbs.
GR2A-60D	63½"	2100	97 lbs.
GR2A-66D	69½"	2320	107 lbs.
GR2A-72D	75½"	2550	117 lbs.
GR2A-84D*	87½"	3000	138 lbs.

High Watt			
GR2AH-18D	21½"	700	44 lbs.
GR2AH-24D	27½"	1000	48 lbs.
GR2AH-30D	33½"	1320	52 lbs.
GR2AH-36D	39½"	1600	57 lbs.
GR2AH-42D	45½"	1900	66 lbs.
GR2AH-48D	51½"	2200	77 lbs.
GR2AH-54D	57½"	2500	88 lbs.
GR2AH-60D	63½"	2800	97 lbs.
GR2AH-66D*	69½"	3120	107 lbs.
GR2AH-72D*	75½"	3450	117 lbs.
GR2AH-84D*	87½"	4100	138 lbs.

* When no color is specified, color inset panels and corner caps will be Black.

© Does not include RMB. Must choose RMB (see page 31 and 32).

* Does not include RMB.

■ 120V Models with infinite controls not available.

* 120V Models not available.

All Designer Aluminum Dual Strip Heater Models Feature:

Voltage: Models without Lights: 120, 208 or 240, single phase only.

Switch Location: Remote only (see page 31 and 32).

Leads: 5' leads through ½" conduit in leg cavity.

Dimensions: with 3" Spacer (standard): 21½"-87½"W x 18"D x 3½"H.

with 6" Spacer: 21½"-87½"W x 21"D x 3½"H.

OPTIONS AND ACCESSORIES – PAGE 24

RECOMMENDED MOUNTING HEIGHTS – PAGE 29

DESIGNER ALUMINUM DUAL STRIP HEATERS WITH LIGHTS

Model* [©]	No. of Bulbs	Width	Watts	Ship Weight*
Standard Watt				
GR2AL-18D	2	21½"	620	44 lbs.
GR2AL-24D	2	27½"	820	48 lbs.
GR2AL-30D	2	33½"	1020	53 lbs.
GR2AL-36D	3	39½"	1330	58 lbs.
GR2AL-42D	3	45½"	1530	67 lbs.
GR2AL-48D	4	51½"	1840	79 lbs.
GR2AL-54D	4	57½"	2090	91 lbs.
GR2AL-60D	5	63½"	2400	100 lbs.
GR2AL-66D	5	69½"	2620	110 lbs.
GR2AL-72D	6	75½"	2910	120 lbs.
GR2AL-84D*	7	87½"	3420	141 lbs.

High Watt				
GR2AHL-18D	2	21½"	820	44 lbs.
GR2AHL-24D	2	27½"	1120	48 lbs.
GR2AHL-30D	2	33½"	1440	53 lbs.
GR2AHL-36D	3	39½"	1780	58 lbs.
GR2AHL-42D	3	45½"	2080	67 lbs.
GR2AHL-48D	4	51½"	2440	79 lbs.
GR2AHL-54D	4	57½"	2740	91 lbs.
GR2AHL-60D	5	63½"	3100	100 lbs.
GR2AHL-66D*	5	69½"	3420	110 lbs.
GR2AHL-72D*	6	75½"	3810	120 lbs.
GR2AHL-84D*	7	87½"	4520	141 lbs.

* When no color is specified, color inset panels and corner caps will be Black.

© Does not include RMB. Must choose RMB (see page 31 and 32).

* Does not include RMB.

■ 120V Models with infinite controls not available.

* 120V Models not available.

All Designer Aluminum Dual Strip Heater Models with Lights Feature:


Voltage: Models with Lights: 120, 120/208 or 120/240, single phase only.

Switch Location: Remote only (see page 31 and 32).

Leads: 5' leads through ½" conduit in leg cavity.

Dimensions: with 3" Spacer (standard): 21½"-87½"W x 18"D x 3½"H.

with 6" Spacer: 21½"-87½"W x 21"D x 3½"H.



GR2AHL-30D



OPTIONS (available at time of purchase only)

Designer Colors, Aluminum Models 21½" - 87½" (includes Stands) – Non-standard colors are non-returnable –

COLOR-15, -18 15" and 18" Housings for GR2A, GR2AH, GR2AL and GR2AHL Dual Models

RED	Warm Red	GRAY	Gray Granite	NAVY	Navy Blue	COPPER	Antique Copper
BLACK	Black	WHITE	White Granite	GREEN	Hunter Green		

Designer Inset Panel Colors – Non-standard colors are non-returnable – Black Standard –

RED	Warm Red	GRAY	Gray Granite	NAVY	Navy Blue	COPPER	Antique Copper
BLACK	Black	WHITE	White Granite	GREEN	Hunter Green		

Designer Corner Caps – Black Standard –

BLACK	Black Corner Caps	DKGRAY	Dark Gray Corner Caps
--------------	-------------------	---------------	-----------------------

NO CONTROLS No Control included (GR2A, GR2AH, GR2AL, GR2AHL-xxD Models only). Requires selection of RMB2-xx Control

See page 31

RMB Remote Box (available in *Designer Colors* or *Gloss Finishes*) – Non-standard colors are non-returnable – (must choose Remote Control Enclosure - RMB not included)

See page 31 and 32

Designer Remote Control Enclosures – Non-standard colors are non-returnable –

RMB-COLOR Remote Control Housing in *Designer Color*

RED	Warm Red	GRAY	Gray Granite	NAVY	Navy Blue	COPPER	Antique Copper
BLACK	Black	WHITE	White Granite	GREEN	Hunter Green		

7.5BP1 7½" Sneeze Guard – one side

7.5BP2 7½" Sneeze Guard – two sides

14BP1 14" Sneeze Guard – one side

14BP2 14" Sneeze Guard – two sides

NTL2-10, 12, 16 *Designer Color* for Non-Adjustable Stands: 10", 12" or 16" in lieu of 14" standard Stands – Non-standard colors are non-returnable –

NTH2-4 *Designer Color* for 4" Overhead Mounts in lieu of 14" standard Stands – Non-standard colors are non-returnable –

HAL Halogen Bulb in lieu of standard Display Light (60 Watt)

NO BULB No Bulb Option (GR2AL-xxD, GR2AHL-xxD Models only)

LIGHTS-ADD'L Extra Lamps – installed (max. two per ft. less one – one per foot is standard)

Leads (must specify Lead length) –

LEADS5 1'-5' Extended Electrical Leads

LEADS10 6'-10' Extended Electrical Leads

LEADS15 11'-15' Extended Electrical Leads

LEADS20 16'-20' Extended Electrical Leads

ACCESSORIES (available for purchase at any time)

Chef LED 120V Adjustable Bulb – GR2AL-xxD Models only, all voltages –

Please contact your local representative or the factory for the most up to date listing of installations and applicable models –

CLED-2700-120	Emulates incandescent	CLED-3000-120	Emulates halogen	CLED-4000-120	Emulates fluorescent
----------------------	-----------------------	----------------------	------------------	----------------------	----------------------

COLORS AND FINISHES – PAGE 33



**CLED-2700, -3000
or -4000**



Strip Heater Solutions


Ultra-Glo® Ceramic Infrared Strip Heaters

Hatco Ultra-Glo® Ceramic Strip Heaters provide the ultimate holding power. Increased heights improve working clearances and the heat zone blankets the entire holding area. All models include adjustable angle brackets for mounting. Available with or without lights, with attached or remote control box enclosure (recommended).



UGAH-18 optional gloss finish and requires remote control box (not shown)

- Pre-focused pyramidal heat pattern concentrates the heat at the edges where heat loss is greatest
- Increased height that the ceramic heat source affords improves operational working clearances, giving the chef and server an improved ergonomic environment in which to work
- Adaptable to many locations and configurations, including back- or front-of-the-house use, open kitchen concepts or buffet lines
- Available in widths from 18" to 72" in 6" increments
- Optional coated shatter-resistant incandescent or halogen bulbs enhance product display while safeguarding food from bulb breakage



- A** Sturdy aluminum housings that do not sag
- B** Adjustable standard mounting bracket (allows 3 different mounting heights and allows for conduit connection to end of the unit)
- C** Heavy-duty insulation surrounds heating element to keep exterior housing cooler and minimize heat loss
- D** Dual aluminized steel reflector keeps housing cooler, focuses more heat towards the food
- E** Shape of element focuses heat on the food
- F** Protective wire guards under heating element

ALUMINUM CERAMIC STRIP HEATERS

Model	Width	Voltage Single Phase	Watts	Ship Weight*
Standard Watt				
UGA-18	18"	120, 208 or 240	490	9 lbs.
UGA-24	24"	120, 208 or 240	675	10 lbs.
UGA-30	30"	120, 208 or 240	750	11 lbs.
UGA-36	36"	120, 208 or 240	980	12 lbs.
UGA-42	42"	120, 208 or 240	1120	13 lbs.
UGA-48	48"	120, 208 or 240	1470	14 lbs.
UGA-54	54"	208 or 240	1470	16 lbs.
UGA-60	60"	208 or 240	1960	17 lbs.
UGA-66	66"	208 or 240	1960	19 lbs.
UGA-72	72"	208 or 240	1960	20 lbs.
High Watt				
UGAH-18	18"	120, 208 or 240	675	9 lbs.
UGAH-24	24"	120, 208 or 240	750	10 lbs.
UGAH-30	30"	120, 208 or 240	1125	11 lbs.
UGAH-36	36"	120, 208 or 240	1350	12 lbs.
UGAH-42	42"	120, 208 or 240	1500	13 lbs.
UGAH-48	48"	208 or 240	2025	14 lbs.
UGAH-54	54"	208 or 240	2250	16 lbs.
UGAH-60	60"	208 or 240	2700	17 lbs.
UGAH-66	66"	208 or 240	2700	19 lbs.
UGAH-72	72"	208 or 240	3000	20 lbs.

ALUMINUM CERAMIC STRIP HEATERS WITH LIGHTS

Model	No. of Bulbs	Width	Voltage Single Phase	Watts	Ship Weight*
Standard Watt					
UGAL-18	1	18"	120, 120/208 or 120/240	550	12 lbs.
UGAL-24	2	24"	120, 120/208 or 120/240	795	13 lbs.
UGAL-30	2	30"	120, 120/208 or 120/240	870	15 lbs.
UGAL-36	3	36"	120, 120/208 or 120/240	1160	17 lbs.
UGAL-42	3	42"	120, 120/208 or 120/240	1300	18 lbs.
UGAL-48	4	48"	120, 120/208 or 120/240	1710	20 lbs.
UGAL-54	4	54"	120/208 or 120/240	1710	22 lbs.
UGAL-60	5	60"	120/208 or 120/240	2260	23 lbs.
UGAL-66	5	66"	120/208 or 120/240	2260	25 lbs.
UGAL-72	6	72"	120/208 or 120/240	2320	27 lbs.
High Watt					
UGAHL-18	1	18"	120, 120/208 or 120/240	735	12 lbs.
UGAHL-24	2	24"	120, 120/208 or 120/240	870	13 lbs.
UGAHL-30	2	30"	120, 120/208 or 120/240	1245	15 lbs.
UGAHL-36	3	36"	120, 120/208 or 120/240	1530	17 lbs.
UGAHL-42	3	42"	120, 120/208 or 120/240	1680	18 lbs.
UGAHL-48	4	48"	120/208 or 120/240	2265	20 lbs.
UGAHL-54	4	54"	120/208 or 120/240	2490	22 lbs.
UGAHL-60	5	60"	120/208 or 120/240	3000	23 lbs.
UGAHL-66	5	66"	120/208 or 120/240	3000	25 lbs.
UGAHL-72	6	72"	120/208 or 120/240	3360	27 lbs.

*Does not include Remote Control Enclosure.

*Includes either Attached Control or Remote Control Enclosure with toggle switch(es) and indicator light(s).

All Aluminum Ceramic Strip Heater Models Feature:

Models Shipped with: Angle brackets and leads (3' conduit whip).

Dimensions with Attached Control Box, Toggle and Indicator Light:


18"-72"W x 9 1/8"D x 2 1/2"H.

Dimensions with Remote Control Enclosure, Toggle and Indicator Light:

18"-72"W x 6"D x 2 1/2"H.

OPTIONS AND REMOTE BOXES – PAGE 28

RECOMMENDED MOUNTING HEIGHTS – PAGE 29




ALL CERAMIC HEATING ELEMENTS WARRANTED
AGAINST BURNOUT FOR ONE YEAR.

Ultra-Glo® Ceramic Dual Infrared Strip Heaters

Hatco Ultra-Glo® Ceramic Strip Heaters provide the ultimate holding power. Increased height improves working clearances and the heat zone blankets the entire holding area. All models include adjustable angle brackets for mounting. Dual mounted strip heaters accommodate wider food holding areas.

- Increased height improves operational working clearances, giving chef and server an improved ergonomic environment in which to work
- Adaptable to any location and configuration, including back- or front-of-the-house use, open kitchen concepts or buffet lines
- Pre-focused heat pattern provides an increased pyramidal dimension, concentrating heat at the edges where heat loss is the greatest

- Available in widths from 18" to 72"
- Remote control enclosure with toggle switch, indicator light and wiring for convenient control placement
- Sturdy extruded aluminum housings eliminate sagging



UGAHL-60D with optional gloss finish and lights in a 3" spacer. Remote control enclosure required (not shown)

ALUMINUM DUAL CERAMIC STRIP HEATERS

Model	Width	Voltage		Watts	Ship Weight*
		Single Phase			
Standard Watt					
UGA-18D	18"	120, 208 or 240	980	17 lbs.	
UGA-24D	24"	120, 208 or 240	1350	19 lbs.	
UGA-30D	30"	120, 208 or 240	1500	21 lbs.	
UGA-36D	36"	208 or 240	1960	24 lbs.	
UGA-42D	42"	208 or 240	2240	27 lbs.	
UGA-48D	48"	208 or 240	2940	30 lbs.	
UGA-54D	54"	208 or 240	2940	33 lbs.	
UGA-60D	60"	208 or 240	3920	37 lbs.	
UGA-66D	66"	208 or 240	3920	40 lbs.	
UGA-72D	72"	208 or 240	3920	44 lbs.	
High Watt					
UGAH-18D	18"	120, 208 or 240	1350	17 lbs.	
UGAH-24D	24"	120, 208 or 240	1500	19 lbs.	
UGAH-30D	30"	208 or 240	2250	21 lbs.	
UGAH-36D	36"	208 or 240	2700	24 lbs.	
UGAH-42D	42"	208 or 240	3000	27 lbs.	
UGAH-48D	48"	208 or 240	4050	30 lbs.	
UGAH-54D	54"	208 or 240	4500	33 lbs.	
UGAH-60D	60"	208 or 240	5400	37 lbs.	
UGAH-66D	66"	208 or 240	5400	40 lbs.	
UGAH-72D	72"	208 or 240	6000	44 lbs.	


ALUMINUM DUAL CERAMIC STRIP HEATERS WITH LIGHTS

Model	No. of Bulbs	Width	Voltage Single Phase	Watts	Ship Weight*
Standard Watt					
UGAL-18D	1	18"	120, 120/208 or 120/240	1040	17 lbs.
UGAL-24D	2	24"	120, 120/208 or 120/240	1470	19 lbs.
UGAL-30D	2	30"	120, 120/208 or 120/240	1620	21 lbs.
UGAL-36D	3	36"	120/208 or 120/240	2140	24 lbs.
UGAL-42D	3	42"	120/208 or 120/240	2420	27 lbs.
UGAL-48D	4	48"	120/208 or 120/240	3180	30 lbs.
UGAL-54D	4	54"	120/208 or 120/240	3180	33 lbs.
UGAL-60D	5	60"	120/208 or 120/240	4220	37 lbs.
UGAL-66D	5	66"	120/208 or 120/240	4220	40 lbs.
UGAL-72D	6	72"	120/208 or 120/240	4280	44 lbs.
High Watt					
UGAHL-18D	1	18"	120, 120/208 or 120/240	1410	17 lbs.
UGAHL-24D	2	24"	120, 120/208 or 120/240	1620	19 lbs.
UGAHL-30D	2	30"	120/208 or 120/240	2370	21 lbs.
UGAHL-36D	3	36"	120/208 or 120/240	2880	24 lbs.
UGAHL-42D	3	42"	120/208 or 120/240	3180	27 lbs.
UGAHL-48D	4	48"	120/208 or 120/240	4290	30 lbs.
UGAHL-54D	4	54"	120/208 or 120/240	4790	33 lbs.
UGAHL-60D	5	60"	120/208 or 120/240	5700	37 lbs.
UGAHL-66D	5	66"	120/208 or 120/240	5700	40 lbs.
UGAHL-72D	6	72"	120/208 or 120/240	6360	44 lbs.

*Does not include RMB.

*Includes either Attached Control or Remote Control Enclosure with toggle switch(es) and indicator light(s).

ALL CERAMIC HEATING ELEMENTS WARRANTED AGAINST BURNOUT FOR ONE YEAR.



All Aluminum Ceramic Dual Strip Heater Models Feature:

Models Shipped with: Angle brackets and leads (3' conduit whip).

Dimensions with Attached Control Box, Toggle and Indicator Light: 18" - 72"W x 18 7/8" or 21 7/8"D x 2 1/2"H.

Dimensions with Remote Control Enclosure, Toggle and Indicator Light: 18" - 72"W x 15" or 18"D x 2 1/2"H.

OPTIONS AND REMOTE BOXES – PAGE 28
RECOMMENDED MOUNTING HEIGHTS – PAGE 29



Strip Heater Solutions



UGAH-36D with 3" spacer,
remote control enclosure
recommended (not shown)

OPTIONS (available at time of purchase only)

Designer Colors, Aluminum Models 18"-72" – Non-standard colors are non-returnable –

COLOR-6	6" Housing for Single UGA and UGAH Models, 18"- 72" (select color)			
COLOR-9	9" Housing for Single UGAL and UGAHL Models, 18"- 72" (select color)			
COLOR-15, -18	15" and 18" Housings for Dual UGA, UGAH, UGAL, UGAHL Models, 18"- 72" (select color)			
RED	Warm Red	GRAY	Gray Granite	NAVY Navy Blue
BLACK	Black	WHITE	White Granite	COPPER Antique Copper
		GREEN	Hunter Green	

Gloss Finishes, Aluminum Models 18"- 72" – Non-standard colors are non-returnable –

GLOSS-6	6" Housing for Single UGA and UGAH Models, 18"- 72" (select finish)			
GLOSS-9	9" Housing for Single UGAL and UGAHL Models, 18"- 72" (select finish)			
GLOSS-15, -18	15" and 18" Housings for Dual UGA, UGAH, UGAL, UGAHL Models, 18"- 72" (select finish)			
RRED	Radiant Red	GGRAY	Glossy Gray	BBLACK Bold Black
GGOLD	Gleaming Gold	BBLUE	Brilliant Blue	

Designer Colors for Remote Control Enclosures – Non-standard colors are non-returnable –

RMB-COLOR	Remote Control Housing in Designer Color			
RED	Warm Red	GRAY	Gray Granite	NAVY Navy Blue
BLACK	Black	WHITE	White Granite	COPPER Antique Copper
		GREEN	Hunter Green	

Gloss Finishes for Remote Control Enclosures – Non-standard colors are non-returnable –

RMB-GLOSS	Remote Control Housing in Gloss Finish			
RRED	Radiant Red	GGRAY	Glossy Gray	BBLACK Bold Black
GGOLD	Gleaming Gold	BBLUE	Brilliant Blue	

HAL

Halogen Bulb in lieu of standard Display Light (60 Watt)

LIGHTS ADD'L

Extra Lamps – installed (max. two per ft. less one – one per ft. is standard). Not available for Dual Models

UGA-NTL-14, -16

Non-Adjustable Tubular Stands (specify 14" or 16" clearance)

UGA-NTL-18, -20

Non-Adjustable Tubular Stands (specify 18" or 20" clearance)

UGA-NTL-22

Non-Adjustable Tubular Stands (for 22" clearance)

UGA-NTL-18-D, -20 -D

Non-Adjustable Tubular Stands (specify 18" or 20" clearance)

UGA-NTL-22-D, -24-D, -26-D

Non-Adjustable Tubular Stands (specify 22", 24" or 26" clearance)

NTL-PAINT

Designer Color or Gloss Finish for Non-Adjustable Tubular Stands – Non-standard colors are non-returnable –

NTL-PAINT-D

Designer Color or Gloss Finish for Non-Adjustable Tubular Stands – Non-standard colors are non-returnable –

Leads (must specify Lead length) –

HT-LEADS5	1'-5'	Extended Electrical Leads
HT-LEADS10	6'-10'	Extended Electrical Leads
HT-LEADS15	11'-15'	Extended Electrical Leads
HT-LEADS20	16'-20'	Extended Electrical Leads

RMB-UGA

Remote Control Enclosure with Toggle Control and Indicator in lieu of attached Control Box (Designer Colors and Gloss Finishes available)

RMB-UGA-INF

Remote Control Enclosure with Toggle Switch, Electronic Infinite Control, Relay and Indicator Light in lieu of attached Control Box (Designer Colors and Gloss Finishes available)

COLORS AND FINISHES – PAGE 33

RMB-UGA-INF



Details Of Strip Heater Recommended Range Above Target* and Strip Heater Spacing Requirements - Based on 24" Strip Heaters

GLO-RAY® INFRARED

Singles

(GRA, GRAL, GRAH, GRAHL GRN)

Singles Designer

(GR2A, GR2AH, GR2AL, GR2AHL)

Combustibles: 13½" high watt or 10" standard watt below, 1" above and 3" to back wall.

Non-combustibles: 1" above, 10" below for high watt with infinite or indicator lamp and 8" below for high watt toggle or standard watt. Must be installed in a pass-through area. Units with remote switches may be installed against a non-combustible back wall, flush to an overshelf and 8"

to a surface below. Maximum 10" setback from the front of an overshelf. Models with cords must be installed 3" below an overshelf and 11" high watt or 10" standard watt over a surface below.

Duals (GRA-D, GRAH-D, GRAL-D, GRAHL-D)

Duals Designer (GR2A-D, GR2AH-D, GR2AL-D, GR2AHL-D)

May not be installed in combustible surroundings. Non-combustibles: 1" above, 10" below. Must be installed in a pass-through area. Units with remote switches may be installed 3" from a non-combustible back wall, 8" from surface below and flush to an overshelf. Maximum 10" setback from the front of an overshelf.

Singles Max-Watt (GRAM, GRAML, GRNM)

Do not use in combustible surroundings. Non-combustibles: 1" above, 12" to surface and 3" from back wall. Cord connected: 3" below an overshelf, 12" from surface below. Max. 10" setback from front of an overshelf.

Duals Max-Watt (GRAM-D, GRAML-D)

May not be installed in combustible surroundings. Non-combustibles: units may be installed 3" from a non-combustible back wall, 1" below an overshelf, 15" to surface below. Maximum 10" setback from the front of an overshelf.

ULTRA-GLO®

Singles and Duals

(UGA, UGA-D, UGAH, UGAH-D, UGAL, UGAL-D, UGAHL, UGAHL-D)

May not be installed in combustible surroundings. Non-combustibles: 1" above, 17" high watt or 14" standard watt from a surface below and 3" from a back wall.

Dual Mounting Do not mount warmers side by side (dual mounting) with less than a 3" space between units.

GLO-RAY® INFRA-BLACK®





Singles (GRAIH, GRAIHL, GRAIHL-D, GRAIH-D)

May not be installed in combustible surroundings. Non-combustibles: 1" above and 4" below. Must be installed in a pass-through area. Units with remote switches may be installed 3" from a non-combustible back wall and flush to an overshelf. Maximum 10" setback from the front of an overshelf.

GLO-RAY® NARROW HALOGEN

Singles (GRN4, GRN4L)

Combustibles: Minimum of 10" above surface and 2" from a back wall. Non-Combustibles: 7" above and 2" from a back wall.




DEPTH OF HEAT PATTERN AT RECOMMENDED ELEMENT HEIGHT

* Recommended single unit application without base heat, based on ideal conditions. Based on a 24" Strip Heater. Individual applications may vary, consult factory.



Glo-Ray® Mounting Arrangements



PERMANENT - FOR HARD WIRED INSTALLATION

Designer Non-Adjustable Stands

(GR2A series only)
Sturdy stands conceal all hook-up wiring. Available in *Designer* colors.

Non-Adjustable Tubular Stands

Sturdy stands conceal all hook-up wiring. Available in *Designer* colors. Duals require two pair. Specify power location.

Adjustable Tubular Stands


Sturdy tubular stands conceal all hook-up wiring. Duals require two pair (not available on Max Watt or Ultra-Glo models). Specify power location.

Angle Brackets

Special adjustable angle brackets fit 6" or 9" housings for mounting Glo-Ray under a shelf. Provides 1"-2" space between Glo-Ray and oversheaf. Duals require two pair. (standard on Max Watt or Ultra-Glo models).

Chain Suspension

Chains attach to tabs provided with warmers and are available in various lengths to suit the location (not available on Max Watt or Ultra-Glo models).



PORTABLE - FOR CORD AND PLUG INSTALLATION

C-Leg Stands

Attractive chrome plated legs allow easy relocation of the warmer. For models 72" or less in width (not available on Max Watt or Ultra-Glo models). Requires attached cord and plug.

T-Leg Stands

Provide rigid stability and allow for more pass-through area below unit. For models 72" or less in width (not available on Max Watt or Ultra-Glo models). Requires attached cord and plug.

STATIONARY - FOR CORD AND PLUG INSTALLATION

Chain Hook

Chains attach to tabs provided with warmers. 6" chain with S-Hooks for units with cord and plug only.

Remote Control Enclosures

- 1 Find the volt and current (amp) rating for the Strip Heater(s) the RMB2 will be controlling. This is the total current of all circuits on the warmer(s).
- 2 If the current rating is under 20 amps, then select an RMB2-1R, if the current rating is between 20 and 40 amps, select the RMB2-2R. The RMB2-2R has two 20 amp outputs.
- 3 Select the current (amp) rating of the RMB2 that is just above the total current rating of the warmer(s) it will control. The RMB2 will need to be connected to a branch circuit breaker suitable for its current rating.
- 4 Select the voltage rating for the RMB2 based on the highest voltage rating of the warmer(s). For example, if the warmer(s) is rated 120/208 volts, select a 208 volt RMB2 control.

- Easy to specify, install and service
- Compatible with most Strip Heaters (GR, GRA, GRAH, GRAIH, GR2A, GR2AH, GRN and GRNH series)
- Total amperage of light and heat combined cannot exceed max amp rating of the control box
- Maximum of 8 amps total allowed on the light circuit
- Multiple Strip Heaters may be connected to one RMB2 if the combined current draw of the warmers is less than the rating of the RMB2. All warmers will be controlled with same set-point



RMB2-2R
with two relays



RMB2-1R
with one relay

REMOTE CONTROL ENCLOSURES (RMB)

Model	Description	Voltage
1 Toggle 1 Infinite 1 Relay, 1 Indicator		
RMB2-1R	12 Max. Amps	120, 208, 240
	16 Max. Amps	120, 208, 240
	20 Max. Amps	120, 208, 240
1 Toggle 1 Infinite 2 Relays, 1 Indicator		
RMB2-2R	24 Max. Amps	120, 208, 240
	32 Max. Amps	120, 208, 240
	40 Max. Amps	120, 208, 240

All Remote Control Enclosure Models Feature:

Ship Weight: 6-8 lbs. depending on components.

Dimensions: RMB2-1R: 11"W x 4½"D x 5½"H.

RMB2-2R: 14"W x 4½"D x 5½"H.

Cutout Dimensions: RMB2-1R: 10⅞" W x 4¾" H.

RMB2-2R: 13⅞" W x 4¾" H.



Strip Heater Solutions

Remote Control Enclosures

Hatco Remote Control Enclosures are built in accordance with UL standards for toggle or infinite switches, indicator lights and wiring, ready for installation when purchased with Glo-Ray® Strip Heaters. When Remote Control Enclosures are used, no more than one RMB per strip heater and no more than one strip heater per RMB.

- Built for toggle or infinite switches, indicator lights and wiring
- One RMB per strip heater
- Consult RMB configurator for specific details at www.hatcocorp.com

RMB-7L with toggle switch and infinite control



RMB-16E with infinite controls, toggle switches and optional *Designer* color



RMB-14E with infinite controls



RMB-3F with toggle switch and indicator light

RMB-7D with toggle switches and optional *Designer* color



REMOTE CONTROL ENCLOSURES (RMB)

Model	Description	Voltage	Width
RMB-3A, -3B, -3C	1 Infinite	120, 208, 240	5½"
RMB-3D	1 Toggle	120, 208, 240	5½"
RMB-3E	2 Toggle	120, 208, 240	5½"
RMB-3F, -3G, -3H	1 Toggle, 1 Indicator	120, 208, 240	5½"
RMB-7A, -7B, -7C	2 Infinite	120, 208, 240	9"
RMB-7D	3 Toggle	120, 208, 240	9"
RMB-7E	4 Toggle	120, 208, 240	9"
RMB-7F, -7G, -7H	1 Infinite, 1 Indicator	120, 208, 240	9"
RMB-7I, -7J, -7K	2 Toggle, 2 Indicator	120, 208, 240	9"
RMB-7L, -7M, -7N	1 Toggle, 1 Infinite	120, 208, 240	9"
RMB-7O, -7P, -7Q	1 Toggle, 1 Infinite, 1 Indicator	120, 208, 240	9"
RMB-14A, -14B, -14C	3 Infinite	120, 208, 240	14"
RMB-14D, -14E, -14F	4 Infinite	120, 208, 240	14"
RMB-14G	5 Toggle	120, 208, 240	14"
RMB-14H	6 Toggle	120, 208, 240	14"
RMB-14I, -14J, -14K	3 Toggle, 3 Indicator	120, 208, 240	14"
RMB-14L, -14M, -14N	2 Infinite, 2 Indicator	120, 208, 240	14"
RMB-14O, -14P, -14Q	2 Toggle, 2 Infinite	120, 208, 240	14"
RMB-14R, -14S, -14T	1 Toggle, 1 Infinite w/Relay, 1 Indicator	120, 208, 240	14"
RMB-14V, -14W, -14Y	1 Toggle, 2 Infinite	120, 208, 240	14"
RMB-14AA, -14AB	Master Toggle, 1 Electronic Infinite w/Relay	120, 208, 240	14"
RMB-14AF, -14AG, -14AH	3 Toggle, 2 Indicator	120, 208, 240	14"
RMB-14AI, -14AJ, -14AK	1 Toggle, 3 Infinite	120, 208, 240	14"
RMB-14AL, -14AM, -14AN	1 Toggle, 2 Infinite, 2 Indicator	120, 208, 240	14"
RMB-14AO, -14AP, -14AQ	1 Toggle, 2 Infinite, 3 Indicator	120, 208, 240	14"
RMB-14AR, -14AS, -14AT	1 Infinite w/Relay, 1 Indicator	120, 208, 240	14"
RMB-16B, -16C, -16D	1 Toggle, 4 Infinite	120, 208, 240	16"
RMB-16E, -16F, -16G	3 Toggle, 2 Infinite	120, 208, 240	16"
RMB-20D, -20E, -20F	3 Toggle, 2 Infinite	120, 208, 240	20"
RMB-20G, -20H, -20I	2 Toggle, 4 Infinite	120, 208, 240	20"
RMB-20J, -20K, -20L	3 Toggle, 4 Infinite, 4 Indicator	120, 208, 240	20"
RMB-20M, -20N, -20P	3 Toggle, 2 Infinite, 2 Indicator	120, 208, 240	20"
RMB-20R, -20S, -20T	2 Toggle, 4 Infinite, 4 Indicator	120, 208, 240	20"
RMB-20AA, -20AB, -20AC	2 Toggle, 2 Infinite, 2 Indicator	120, 208, 240	20"
RMB-20AF, -20AG, -20AH	4 Infinite, 4 Indicator	208, 240, 120	20"
RMB-20AN, -20AO, -20AP	4 Toggle, 4 Indicator	120, 208, 240	20"

All Remote Control Enclosure Models Feature:

Ship Weight: 2-8 lbs. depending on components.

Max. Allowable Amperage per Switch: Toggle 15.0; Infinite 12.2

Dimensions (not including Switches): 5½", 9", 14", 16" or 20"W x 3"D x 2½"H.

Toggle Switch: Max. 15 amps
Infinite Switch: Max. 12.2 amps

NOTE: See our RMB picker on the Hatco website, www.hatcocorp.com

OPTIONS (available at time of purchase only)

Designer Colors – Non-standard colors are non-returnable –

RMB-COLOR	Remote Control Housing in Designer Color					
	RED	Warm Red	GRAY	Gray Granite	NAVY	Navy Blue
	BLACK	Black	WHITE	White Granite	GREEN	Hunter Green
					COPPER	Antique Copper

Gloss Finishes – Non-standard colors are non-returnable –

RMB-GLOSS	Remote Control Housing in Gloss Finish		
	RRED	Radiant Red	GGRAY
	GGOLD	Gleaming Gold	BBLUE
			BBLACK
			Bold Black

COLORS AND FINISHES – PAGE 33



GRA-36D

Paint Chip Sample Colors


DESIGNER COLORS



Warm Red



Black

Gray
GraniteWhite
GraniteNavy
BlueHunter
GreenAntique
Copper

GLOSS FINISHES

Smooth
WhiteGleaming
GoldGlossy
GrayBold
BlackRadiant
RedBrilliant
Blue

PLATED FINISHES

Bright
BrassBright
NickelBright
CopperAntique
NickelAntique
BrassAntique
Bronze

Colors are a representation and may not exactly match our colors.
Consult factory for possible color matching options on these colors.
Non-standard colors are non-returnable.

To order a Hatco Paint Chip & Stone Sample Colors Sheet, visit www.hatcocorp.com / Order Literature / Sales Literature / Sell Sheets.

Sturgeon Bay, WI 54235 U.S.A. Telephone: (800) 558-0607 or (414) 671-6350 www.hatcocorp.com



Scan with web-enabled
mobile device to visit
www.hatcocorp.com



Hatco Corporation

P.O. Box 340500 | Milwaukee WI 53234-0500 USA
800-558-0607 | 414-671-6350 | Fax: 800-543-7521
www.hatcocorp.com | equipsales@hatcocorp.com