# KM-1301SAH-E

STACKABLE ICE CUBER

KM-1301SAH-E 10/30/17 Item # 13055

### W x D x H 122 x 69.5 x 69.5 cm

Shipping Dimensions 131.5 x 83.8 x 85.1 cm

KM-1301SAH-E Air-Cooled 1 Phase Shown on optional bin: B900















## **Features**

AIA#:

- Individual crescent cube
- Stainless steel evaporator
- ► CycleSaver™ design CycleSave



- Up to 505 kg of ice production per 24 hours
- Stackable for 1010 kg per 24 hours ice production in the same floor space
- Durable stainless steel exterior
- Protected by H-Guard Plus H-GUARD Antimicrobial Agent
- ullet EverCheck $^{ ext{TM}}$  alert system evercheck
- · Removable air filters
- R-404A Refrigerant

#### **Available on Bins:**

B-800 B-1150SS B-1500SS *Top kit may be required.*B-900 B-1300SS B-1650SS *See Bin Spec Sheets.* 


#### Warranty:

Call factory for warranty information.

			ICE PROI	DUCTION	WATER USAGE		ELECTRICAL*							
	Condenser	Model	Air / Water Temp kg per 24 hours 21°/10°C   32°/21°C		Potable Liters per 45 kg 32°/21°C	Liters per 45 kg	per 45 kg	Max. Fuse Size or HACR Circuit Breaker	Amperage	Voltage	Circuit Wires (including ground)	Heat Rejection BTU/hr.	Charge Amount	Net / Ship Weight (kg.)
ı	Air	KM-1301SAH-E	505	455	59.0	N/A	5.1	20A	11.8A	220-240V/50/1	3	19,000	1620g	125 / 143 kg

<sup>\*</sup>If neutral is not available transformer kit (HS-5030) is required. Refer to instruction manual for installation and electrical requirements.

#### **KM Cube Dimensions\***



\* approximate size in millimeters, image not to scale Printed in the U.S.A.

#### **Operating Limits**

• Ambient Temp Range 7 - 38°C

• Water Temp Range 7 - 32°C

• Water Pressure 0.7 - 8 kg/cm<sup>2</sup>

• Voltage Range 198 - 254V

#### **Service**

- Panels easily removed and all components accessible for service.
- Allow 15 cm clearance at rear, sides, and top for proper air circulation and ease of maintenance/ service.

#### **Plumbing**

- Icemaker Water Supply Line: Min. 10 mm Nominal OD Copper Water Tubing or Equivalent
- Icemaker Drain Line: Min.18 mm Nominal OD Hard Pipe or Equivalent

#### Water Filter

Please refer to water filter spec sheet for recommended configurations.


Hoshizaki reserves the right to change specifications without notice.





KM-1301SAH-E 10/30/17 Item # 13055

> mm [inches]


**FRONT VIEW** 







AIR-COOLED



**AIR-COOLED**