

GASTRONORM SLIDE BAR TROLLEYS

www.tournus.com

Fully welded construction:

The panels are connected by 5 welded spacers.

This design ensures maximum rigidity to the trolleys which boast a non-deformable structure, even under a heavy load: the trolleys can withstand up to 250 kg maximum and 20 kg per level.

The slide bars are continuous welded on an automatic welding bench. The weld seam is performed over the whole length of the bar slide without filler metal. This production process ensures even welds. And above all, exceptionnal resistance to wrenching.





The trolleys are made of stainless steel ensuring their robustness and good corrosion resistance so therefore a long life expectancy.

The L-shaped slide bars mean containers can be inserted easily. The runner stops stabilise the racks and plates during movements.

The trolleys are fitted with 4 stainless steel swivel castors with polyamide cover and stainless steel axle and ball. The ball bearing guarantees the rolling quality and optimum resistance with time. 2 castors have brakes for the immobilization of the trolley. The wheel treads and protective bumpers are non marking.



A broad range for all uses:

5 heights:

- **760 mm with top panel:** to go under tables
- 900 mm with top panel: same height as tables
- 1490 mm: to go into cold rooms, height: 1520 mm
- 1645 mm: to go into cold rooms, height: 1670 mm or 1720 mm
- 1785 mm: to go into cold rooms, height: 1800 mm and over, bigger space between slide bars.

Also available:

- **GN trolleys delivered flat packed:** more compact for transport and storage
- **GN stackable trolleys**: more compact for storage when empty
- Options: washable and disposal covers
- Special realization: trolley with bar closing for stability of the containers durant transport



25 avenue Jean Moulin - CS2005 71700 TOURNUS - FRANCE

RC Mâcon B 383 567 104 Code APE 295 E SAS Capital 16 355 625€ CONTACT


Tel: + 33 (0)3 85 27 42 65 E-mail: export@tournus.com



GASTRONORM SLIDE BAR TROLLEYS

TECHNICAL SPECIFICATIONS

www.tournus.com



Construction:

- Welded stainless steel.
- Square tube of 25x25 mm, 1.2 mm thick
- One intermediate spacer on trolleys with 17 and 20 levels and GN 2/1 trolleys with 15 levels

Slide bars:

- Made of bright polished sheet : 1.2 mm thick
- Continuous argon welded without filler metal
- L-shaped with runner stops at each end

Descriptions	Levels	L (mm)	H (mm)	e (mm)	B (mm)	A (mm)	B (mm)
GN 1/1 bar slide trolley							
804 201	6	638	760	81	304	332	304
804 203	8	638	900	81	304	332	304
804 206	15	638	1490	81	304	332	304
804 207	17	638	1650	81	304	332	304
804 209	20	638	1785	77	304	332	304
GN 2/1 bar slide trolley							
804 231	6	758	760	81	509	537	509
804 233	8	758	900	81	509	537	509
804 236	15	758	1490	81	509	537	509
804 237	17	758	1650	81	509	537	509
804 239	20	758	1785	77	509	537	509
GN 1/1 bar slide trolley (flat packed)							
804 216	15	638	1490	81	304	332	304
804 217	17	638	1650	81	304	332	304
804 219	20	638	1785	77	304	332	304
GN 2/1 bar slide trolley (flat packed)							
804 246	15	758	1490	81	509	537	509
804 247	17	758	1650	81	509	537	509
804 249	20	758	1785	77	509	537	509
GN 1/1 stackable trolley							
804 229	20	638	1758	77	304	332	304
GN 2/1 stackable trolley							
804 259	20	758	1785	77	509	537	509

Castors:

- 4 swivel castors, 2 with braked
- Ø 125 mm with round bumpers
- Polyamide cover, stainless steel axles and ball bearings
- Rubber mark-proof tread

Options:

Bar of closing for transport

25 avenue Jean Moulin - CS2005 71700 TOURNUS - FRANCE

RC Mâcon B 383 567 104 Code APE 295 E SAS Capital 16 355 625€ **CONTACT**

Tel: + 33 (0)3 85 27 42 65 E-mail: export@tournus.com