

Product data sheet — Gas deep fat fryer Prag

MKN-Nr.:
2060301

Deep-fat fryer according to DIN 18856. Special appliance for use in commercial kitchens. For deep frying, frying of starch and albuminous products in a fat bath.



Technical highlights

Material:

Casing and cover are made completely of CNS (material No. 1.4301) / AISI 304.
Visible surfaces with polished and satin finish, 320 grit.

Bendings:

Cover bent downwards 50 mm at the front and on the sides, bent upwards 25 mm at the rear. Designed as a drip edge at the front on the bottom side. 50 mm cover projection closed to the appliance body. With tightly welded drain channels on the side – rounded (R30) at the rear.

Body:

Buckling resistant, self-supporting, closed construction with side walls, rear wall and bottom.

Control panel:

Control panel with profile to protect the control elements, can be taken off at the front for simple and cost-efficient service access. Ergonomically shaped knobs for a easy identification of the position.

Effective area:

Deep-frying basin of CNS/stainless steel, drawn deep with 20 mm collection rim welded seamlessly and tightly into the cover plate.

Installation:

Equipped for installation of appliance feet which are adjustable in height (optional) or for installation on a plinth provided by customer.

Type of energy:

Appliance is completely tubed internally in accordance with gas requirements for the gas connection provided by customer.

Special feature:

Heating:

Heating by atmospheric linear burners, thermoelectrically protected. Piezo ignition for the ignition burners to start up the main burner.



Master of Performance

Subject to change without notice!
29.05.2013

Product data sheet — Gas deep fat fryer Prag

MKN-Nr.:
2060301

Deep-fat fryer for deep frying, frying of starch and albuminous products in a fat bath.

Current drawings you will find here:

www.mkn.eu

► service & support

► spare parts database & download

Further features

- connection, sealing by special clip bars flush mounted to the cover (optional)
- bottom section closed at the front by one hinged door
- impressed filling marks (min./max.) in the basin to control the fat filling
- deep cold zone under the heating elements to hold suspended particles with precisely fitting fat clarifier
- bottom of the basin with outlet inclination and welded drain valve installed vertically downwards
- with integrated heat exchanger and a detachable waste gas stack behind the basin for transportation purposes
- thermostatic temperature control with thermoelectric safety device, safety temperature limiter and temperature display for fat – Gas shut off valve installed in appliance for maintenance purposes

Technical data

Dimensions (LxWxH*) (mm):	600 x 850 x 700
Effective area:	1
Dim.: effect. area (LxWxH) (mm):	400 x 395 x 165
Diameter (mm):	
Nominal capacity (L):	28
Nominal fill quantity (L):	
Connected load (electrical) (kW):	
Voltage ¹ (V):	
Recommended fuses (A):	
Frequency range (Hz):	50/60
Rated heat load (kW):	16
Standard gas pressure – natural gas ² (mbar):	20
Standard gas pressure – liquid gas ² (mbar):	30 (DE), 50 (EU)
Gas connection:	DN 20 (3/4")
Heat-up time (Min.):	
Vapour pressure (bar):	
Refrigeration capacity (kW):	
Net weight (kg):	85
Gross weight ³ (kg):	86
Heat emission latent (W):	11200
Heat emission sensitive (W):	1440
Type of protection:	

* Carcass height plus optional appliance feet with a height of 150 mm or 200 mm

Product safety

- CE mark

Installation requirements

- gas connection provided by customer

Option / accessories

MKN-No.:	Description:
813001	fat drain-off receptacle (15 liter)

¹ special voltages on request

³ seaworthy packing on request

² further types of gas on request



Subject to change without notice!
29.05.2013