



## EURONORM RACKING TROLLEYS



804 159

804 155

Stainless steel 25 x 25 frame construction. Argon welded tray runners with tray runner stops at each end.

4 swivel wheels Ø 125 mm, with polyamide cover (2 braked). Annular bumpers. The 9 tier trolleys include an upper shelf. Max load : 20 Kg per tier and 250 Kg per trolley.

Euronorm trolleys	Opening (mm)	e* (mm)	Overall dim. l x W x h (mm)	Number of tiers	Reference
400 x 600 mm	400	70	725 x 540 x 900	9	<u>804 155</u>
400 x 600 mm	400	125	725 x 540 x 1785	12	<u>804 156</u>
400 x 600 mm	400	94	725 x 540 x 1785	16	<u>804 157</u>
600 x 400 mm (1)	600	94	525 x 732 x 1785	16	<u>804 158</u>
400 x 600 mm	400	75	725 x 540 x 1785	20	<u>804 159</u>
600 x 400 mm (1)	600	75	525 x 732 x 1785	20	<u>804 160</u>
400 x 800 mm	400	75	925 x 540 x 1785	20	<u>804 161</u>
600 x 800 mm (1)	600	94	925 x 732 x 1785	16	<u>804 162</u>
600 x 800 mm (1)	600	75	925 x 732 x 1785	20	<u>804 163</u>

(\*) e : vertical space between tray runners.  
(1) 600 mm opening trolleys do not accept ABS trays.

### Extra-cost for euronorm trolleys

Description	Reference
Extra-cost for 4 stainless steel wheels	<u>702 181</u>
Washable polyamide cover (for trolleys 400 x 600 mm, with 400 opening - except 9 tier model).	<u>229 519</u>

THE TOURNUS ASSET

- Hygiene certified
- Sturdy trolleys
- Stainless steel wheels
- Rolling quality

## STORAGE TROLLEYS

Stainless steel 25 x 25 frame construction. Argon welded tray runners with runner stops at each end. 4 swivel wheels Ø 125 mm, with galvanized steel wheel cover, non protruding, designed for heavy loads, freezing environment (-40°C) and proving chambers.



814 322

Euronorm storage trolleys	Opening (mm)	e* (mm)	Overall dim. l x W x h (mm)	Number of tiers	Reference
600 x 800 mm	600	75	855 x 662 x 1775	20	<u>814 321</u>
800 x 600 mm	800	75	655 x 862 x 1775	20	<u>814 322</u>
1000 x 700 mm	1000	75	755 x 1062 x 1775	20	<u>814 323</u>
1000 x 800 mm	1000	75	855 x 1062 x 1775	20	<u>814 324</u>

**With removable shelf**

600 x 800 mm	600	75	855 x 662 x 1775	20	<u>824 321</u>
800 x 600 mm	800	75	655 x 862 x 1775	20	<u>824 322</u>
1000 x 700 mm	1000	75	755 x 1062 x 1775	20	<u>824 323</u>
1000 x 800 mm	1000	75	855 x 1062 x 1775	20	<u>824 324</u>

### Extra-cost for storage trolleys

Description	Reference
Extra-cost for 2 wheels - wheels with galvanized cover with brakes	<u>702 140</u>
Extra-cost for 4 wheels with stainless steel cover	<u>702 141</u>
Extra-cost for 4 swivel with stainless steel cover - 2 braked	<u>702 142</u>

Removable shelf

## TROLLEYS FOR DOUGH CONTAINERS



804 165

Trolleys for round and rectangular dough containers.

Welded stainless steel construction.

Maximum load per level: 25 kg. Weight: 13 kg.

▪ **Tube structure** : uprights and spacers made of 25 x 25 mm section stainless steel tube, thickness 1,2 mm. 2 lower spacers made of 25 x 25 mm section stainless steel tube, thickness 1,2 mm.

▪ **Slide bars** : 7 levels of sliders made of stainless steel bent tube, Ø 12 mm, with spacing of 183 mm. Fitted into uprights and continuous argon welds with no added metal.

▪ **Wheels** : 4 swivel wheels Ø 125 mm with polyamide cover, 2 with brake.

Trolley for containers	Opening (mm)	Overall dim. l x W x h (mm)	Reference
8 tier	195	660 x 470 x 1810	<u>804 165</u>

## FLOUR CONTAINERS



Stainless steel construction. 4 swivel wheels Ø 100 mm with galvanized steel cover.



907 005

Description	Overall dim. l x W x h (mm)	Reference
120 litre flour container + stainless steel lid	605 x 395 x 725	<u>907 005</u>
120 litre flour container with dividing panel + s/ steel lid	605 x 395 x 725	<u>806 150</u>

## TROLLEYS FOR UTENSILS



906 440

801 331

801 310

- **Hook trolley**: Stainless steel construction. 4 swivel wheels Ø 100 mm with galvanized steel cover. 12 bars for utensils.
- **Accessories holder trolley**: Stainless steel construction. 4 swivel wheels Ø 100 mm with galvanized steel cover. 1 container GN 1/1, depth 40 mm removable, 3 bars for utensils with 1 hook.
- **Chef's trolley**: Stainless steel construction. 4 swivel wheels Ø 125 mm with polyamide cover, stainless steel axle and ball bearings. Sliding frame 7 GN 2/1 levels, 1 polyethylene worktop, 1 support for 6 poly. GN 1/6 depth 100 mm, pans provided, 1 lateral box for knives, 1 bar for accessories.

Description	Overall dim. l x W x h (mm)	Reference
Hook trolley	660 x 640 x 1755	<u>906 440</u>
Holder trolley	560 x 365 x 1600	<u>801 310</u>
Chef's trolley	590 x 690 x 1750	<u>801 331</u>