

EQUIPMENT OVERVIEW AND TECHNICAL DATA

CafeRomatica coffee machines

					
Pre-brewing system	x	x	x	x	x
AROMATICA System	x	x	x	x	x
Aroma Balance System	x (3 profile)	x (3 profile)	x (3 profile)	x (3 profile)	x (3 profile)
Choice of coffee strength	x (5-stage)	x (5-stage)	x (5-stage)	x (5-stage)	x (5-stage)
2-cup function for espresso/coffee	x	x	x	x	x
Factory setting of the recipes can be changed	x	x	x	x	x
Individual programme "My Coffee"	x (18)	x (10)	x (10)	x (10)	x (5)
Professional 15-bar pump pressure	x	x	x	x	x
Digital text/symbol dialogue display	x (TFT, Touch)	x (TFT, colour)	x (TFT, colour)	x (TFT, colour)	x (TFT, colour)
Cup lighting	x (2-colour)	x (2-colour)	x (2-colour)	x (2-colour)	x
Cup holder actively heated	x	x			
Automatic descaling display	x	x	x	x	x
Integrated descaling programme	x	x	x	x	x
Cleaning programme	x	x	x	x	x
OneTouch SPUMATORE (Cappuccino at the push of a button)	x (Duo)	x (Duo)	x (Duo)	x (Duo)	x
Automatic washing-up device for OneTouch-SPUMATORE	x	x	x	x	x
Manual SPUMATORE					
Adjustable coffee temperature	x (3-level)	x (3-level)	x (3-level)	x (3-level)	x (3-level)
Height-adjustable coffee spout	x (16.5 cm)	x (14.0 cm)	x (14.0 cm)	x (14.0 cm)	x (14.0 cm)
CLARIS fresh water filter	x	x	x	x	x
Control indicator for filter change	x	x	x	x	x
Extra quiet - noise-reduced operation	x	x	x	x	x
Adjustable coffee quantity (approx. 20 ml - ca. max. 240 ml)	x	x	x	x	x
Quiet conical grinding mill (hardened steel)	x	x	x	x	x
Individually adjustable grinding degree	x	x	x	x	x
Powder compartment for pre-ground coffee (1 serving)	x	x	x	x	x
Individually adjustable water hardness (4-stage)	x	x	x	x	x
Removable water tank, volume approx.	3.5 l	1.8 l	1.8 l	1.8 l	2.2 l
Hot water function for instant drinks/tea	x (3-level)	x (3-level)	x (3-level)	x (3-level)	x (3-level)
Compact dimensions (W x H x D), cm approx.	30 x 42 x 48	24 x 33 x 48	24 x 33 x 48	24 x 33 x 48	24 x 34 x 46
Colour (front / controls)	Black / Chrome	Stainless steel/chrome	Aluminium-silver/chrome	Matte black/chrome	Inmold black/chrome
Brewing unit removable for cleaning	x	x	x	x	x
Stainless steel Thermo-Milk Cooler, 0.5 l	optional	optional	optional	optional	x
Milk container, plastic, transparent, 1.0 l	x	optional	optional	optional	optional
Bean container, content approx.	600 g	250 g	250 g	250 g	250 g
Movable rear wheels	x	x	x	x	x
Cord storage	x	x	x	x	x
ECO mode / 0-Watt switch	x	x	x	x	x
Voltage	230 v	230 v	230 v	230 v	230 v
Max. Power consumption	2700 w	1465 w	1465 w	1465 w	1455 w
Weight incl. packaging	16.4 kg	11.0 kg	11.0 kg	11.0 kg	11.0 kg
Article no.	300 001 030	300 800 859	300 800 842	300 800 841	300 700 788
EAN-Code	42 600 8346 030 6	42 600 8346 859 3	42 600 8346 842 5	42 600 8346 841 8	42 600 8346 788 6
	NICR 1030	NICR 859	NICR 842	NICR 841	NICR 788



CafeRomatica 778



CafeRomatica 768



CafeRomatica 758



CafeRomatica 680



CafeRomatica 670



CafeRomatica 660



CafeRomatica 530



CafeRomatica 520

x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
x (3 profile)	x (3 profile)	x (1 profile)	x (3 profile)	x (3 profile)	x (3 profile)		
x (5-stage)	x (5-stage)	x (3-level)	x (5-stage)	x (5-stage)	x (5-stage)	x (3-level)	x (3-level)
x	x	x	x	x	x	x	x
x	x	x	x	x	x		
x (1)	x (1)	x (1)	x (5)	x (5)	x (1)		
x	x	x	x	x	x	x	x
x (TFT, colour)	x (TFT, colour)	x (TFT, colour)	x (TFT, colour)	x (TFT, colour)	x (TFT, colour)	- / x	- / x
x	x		x	x			
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
2.2 l	2.2 l	2.2 l	2.2 l	2.2 l	2.2 l	2.2 l	2.2 l
x (3-level)	x (3-level)	x (3-level)	x (3-level)	x (3-level)	x (3-level)	x (3-level)	x (3-level)
24 x 34 x 46	24 x 34 x 46	24 x 34 x 46	24 x 34 x 46	24 x 34 x 46	24 x 34 x 46	24 x 34 x 46	24 x 34 x 46
Inmold white/chrome	Inmold silver/chrome	Black / Chrome	Inmold black/chrome	Inmold silver/chrome	Matte black/chrome	Silver/chrome	Matte black/chrome
x	x	x	x	x	x	x	x
optional	optional	optional	optional	optional	optional	optional	optional
optional	optional	optional	x	x	optional	optional	optional
250 g	250 g	250 g	250 g	250 g	250 g	250 g	250 g
x	x		x	x		x	
x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x
230 v	230 v	230 v	230 v	230 v	230 v	230 v	230 v
1455 w	1455 w	1455 w	1455 w	1455 w	1455 w	1455 w	1455 w
11.0 kg	11.0 kg	11.0 kg	10.0 kg	10.0 kg	10.0 kg	10.0 kg	10.0 kg
300 700 778	300 700 768	300 700 758	300 600 680	300 600 670	300 600 660	300 500 530	300 500 520
42 600 8346 778 7	42 600 8346 768 8	42 600 8346 758 9	42 600 8346 680 3	42 600 8346 670 4	42 600 8346 660 5	42 600 8346 530 1	42 600 8346 520 2
NICR 778	NICR 768	NICR 758	NICR 680	NICR 670	NICR 660	NICR 530	NICR 520