

BCDv 1003



 GERMAN
ENGINEERING

LIEBHERR

Forced Air Display Coolers



Display Cooler	BCDv 1003	HFC free
Total gross/net capacity cu.ft. (l)	3.0 / 2.7 (85 / 77)	
Exterior dimensions in inches (w/d/h)	19 5/8 20 13/16 32 3/16	
in mm (w/d/h)	497 / 528 / 816	
Interior dimensions in inches (w/d/h)	16 15/16 14 3/16 21 7/16	
in mm (w/d/h)	430 / 340 / 544	
Energy consumption in 24 hours	1.326 kWh	
Ambient temperature in °F (°C)	+50°F to +95°F (+10°C to 35°C)	
Refrigerant	R 600a	
Sound rating *	53 dB	
Connection rating	2.5 A	
Frequency/voltage	60Hz / 115 V ~	
Cooling system	Dynamic	
Defrost	Automatic	
Temperature range in °F (°C)	+36°F to +59°F (+2°C to +15°C)	
External cabinet finish	Steel	
Door/lid material	Double-glazed door	
Internal liner material	Plastic white	
Type of control	Mechanic control system	
Interior light	LED ceiling lighting	
Adjustable shelves	2	
Shelf material	Grid shelves plastic coated	
Shelf load weight in lbs (kg)	66 (30)	
Usable shelf area in inches (mm)	13 7/16 x 16 15/16 (340 x 430)	
Handle	Recessed grip	
Lock	Fitted	
Self-closing door	Yes	
Door hinges	Right interchangeable	
Insulation in inches (mm)	1.33 (34)	
Gross/net weight in lbs (kg)	83.8 / 79.4 (38 / 36)	
Accessories		
Scanner rail	7450756	

* Noise level – sound power re 1pW – according to IEC 60704-2-14.

Subject to modification. For up-to-date information, visit home.liebherr.com