

BLANCO COOK GRIDDLES



Model	Griddle, flat			Griddle, ribbed	
Basic unit equipment	<ul style="list-style-type: none"> - All-round seamlessly welded griddle surface with rounded corners for optimal cleaning and hygiene - Trough depth 30 mm - 15 mm-thick griddle for optimal temperature storage - Extremely powerful up to +250 °C - Even, full-surface heat distribution through tubular heating elements - Unheated resting zone (70 mm) on operator side - Drain opening, including Teflon grease drain plug - Large, removable grease catch tray, capacity 1.6 litres - Continuous temperature adjustment with rotary knobs - 2 indicator lights to display operating mode and heating phase - Height-adjustable rotating feet - Mains connection cable (1.5 m) 				
Temp. range	+80 °C to +250 °C				
Protection type	IP X4				
Accessories	See Page 19				
Material	<ul style="list-style-type: none"> - Stainless steel (AISI 304) with micro-polished surface - Grilling surface made of tempered, corrosion-resistant chrome steel (material 1.2316) 				
Model	BC GF 3500	BC GF 4200	BC GF 8400	BC GR 3500	BC GR 4200
Model	Griddle with straight, flat surface/grilling surface			Griddle with straight, ribbed surface/grilling surface	
			2 separately adjustable heating zones		
Exterior dimensions (W x D x H):	400 x 620 x 240 mm		800 x 620 x 240 mm	400 x 620 x 240 mm	
Usable area (W x D)	304 x 506 mm (of which 304 x 435 mm heated)		704 x 506 mm (of which 704 x 435 mm is heated)	304 x 506 mm (of which 304 x 435 mm heated)	
Plugs	Schuko plug	16 A CEE plug	16 A CEE plug	Schuko plug	16 A CEE plug
Connected load	220–240 V, 50–60 Hz 1N PE, 16 A	400 V, 50–60 Hz 3N PE, 16 A	400 V, 50–60 Hz 3N PE, 16 A	220–240 V, 50–60 Hz 1N PE, 16 A	400 V, 50–60 Hz 3N PE, 16 A
Heat emission	Sensitive Normal operation	1155	1386	2772	1155
		Latent	1400	1680	3360
Output	3.5 kW	4.2 kW	8.4 kW (2 x 4.2 kW per heating zone)	3.5 kW	4.2 kW
Weight	34 kg		69 kg	31 kg	
Order no.	574 203	574 204	574 205	574 206	574 207