





Model	Front cooking station BC FS 2	Front cooking station BC FS 3	Front cooking station BC FS 4		
Model	» Mobile front cooking station with placement shelf for table-top cooking units				
Basic equipment	 Extraction bridge with flame arrestor grease filters (correspond to Class A, DIN 18869-5) Electronic control with filter change indicator 3 power steps for need-oriented extraction Air nozzles for fume-guiding air stream along the unit placement niche (on three sides) Mains connection cable (approx. 4 m) Removable placement shelf with max. load of approx. 150 kg Free usable space below the device placement shelf 				
Height of underframe	» 900 mm				
Protection type	» IP X4 with fan removed				
Castor model	» Solid synthetic castors, 75 mm dia, 6 steering castors, 2 of which have brakes				
Material	» Stainless steel (AISI 304)				

Model	BC FS 2	BC FS 3	BC FS 3 BHG	BC FS 4
Equipment	see basic equipment	see basic equip- ment	see basic equipment, lighting, closed sneeze guard and railing	see basic equipment
Number of cooking units with max. dimensions (L x W x H)	for 2 table-top cooking units » 400 x 650 x 300 mm	for 3 table-top cooking units » 400 x 650 x 300 mm		for 4 table-top cooking units » 400 x 650 x 300 mm
Placement niche dim. (L x W x H)	806 x 648 x 300 mm	1211 x 648 x 300 mm		1616 x 648 x 300 mm
Free usable space below placement shelf (L x W x H)	830 x 648 x 575 mm	1235 x 648 x 575 mm		1640 x 648 x 575 mm
Socket outlets (max. power consumption)	2 x 230 V Schuko socket outlets, 2 x 400 V CEE socket outlets (max. 10 kW)	3 x 230 V Schuko socket outlets, 3 x 400 V CEE socket outlets (max. 20 kW)		4 x 230 V Schuko socket outlets, 4 x 400 V CEE socket outlets (max. 20 kW)
Plugs	16 A CEE plug	32 A CEE plug		32 A CEE plug
Connected load	400 V, 50/60 Hz, 3N PE	400 V, 50/60 Hz, 3N PE		400 V, 50/60 Hz, 3N PE
Output	10.8 kW	20.8 kW		20.8 kW
Exterior dim. (L x W x H)	1538 x 750 x 1361 mm	1943 x 750 x 1361 mm		2348 x 750 x 1361 mm
Order No.	573 973	573 974	573 975	573 976