



F60/100 - IMC Vulture 725 In-tabling Food Waste Disposer - 1 Phase - W 338 mm - 1.1 kW Reliable, efficient, safe and easy to operate, the compact 725 Waste Disposer allows operators to quickly and effectively remove waste, to create a safer and cleaner kitchen.

- Fast and efficient disposal of up to 400kg of food waste per hour.
- Handles up to 850 covers per sitting ideal for medium-size kitchens.
- For medium waste (plate waste, vegetables and peelings, meat and fish scraps).
- Compact design allows hopper to be tablemounted, for quick and easy loading.
- Manually reversible motor to extend operational life.
- Suitable for medium kitchens with single-phase power supply.

## **Specifications**

Packed Weight Kg

Packed Height cm

Packed Width cm

Packed Depth cm

43.45

104

63

48

Summary		Power and Performance	
3rand	IMC	Total Power kW	1.1
Range	Vulture	НР	1.5
Series	700 Series	IP Rating	IP55
Power Type	Electric		
Unit Type	Welded into tabling		
Available in UK Only	No		
UK Warranty	2 Years Parts and Labour Warranty		
Export Warranty	Contact your local dealer		
Mounting	In-tabling		
GTIN	5056105199526		
Key Specifications		Capacity	
Operator Safety	Interlocks	Type of Waste	Medium waste
Airbreak	No	Covers Per Sitting	850
		Capacity Kg per Hour	400
Weights and Dimensions		Supply Connections	
Unit Height (External) mm	733	Requires Installation	Yes
Unit Width (External) mm	340	Requires Electrical Supply	Yes
Unit Depth (External) mm	472	UK 3 Pin Plug	No
Net Weight Kg	39.5	Requires Hardwiring	Yes
		<b>Electrical Supply Rating Watts</b>	1100
		Single Phase Amps	7.4
		Single Phase Voltage	230
		Water Supplied From	Storage cistern
		Water Connection Pressure Bar	0.4
		Drain Connection	2" BSP threaded flange, connected to 54mm piping;
		Water Connection	15mm



## **Available Options**

MAG CUTLERY SAVER

**VS167** 700/800/904/904X MAGNETIC CUTLERY SAVER

WATER FLOW CONTROL

**VS355** 725 WATER FLOW CONTROL

## **Technical Picture**





