



Product Code: MBCT250W

Floorless Modular Blast Chiller with 900mm door width



Features & Benefits

- MBCT models are supplied floorless for blast chilling application only
- 250kg chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature of up to 90°C for chilling
- Freezing capacity from 70° to -18°C in less than 240 minutes within specifications
- All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase+neutral)
- Intuitive easy touch control panel - Just press and go with easy to use colour coding to indicate cycle status.
- Foster Circulair air circulation system ensures uniform chilling whilst protecting the food surface
- Operator-friendly fans cut-out whenever door is opened
- HACCP software is available as an option in 3 formats for data retrieval and management

Shelving		Base Fittings		Doors			
Additional S/S Trayslides	Standard	Remote Refrigeration System	Standard	Solid	Standard		
Trolley - Gastronorm - 1/1 (Not Supplied)	Option	Electrical & Service Data		Left Hand Hinged Door	Option		
Trolley - Gastronorm - 2/1 (Not Supplied)	Option	400/50/3	Standard	Product Extras			
Trolley Capacity - 890x1040x1890	Standard	Finish		Hold Facility	Option		
Refrigeration		White lam ext and door & white control panel		Standard			
R404a - Industry Standard	Standard	White lam int & ext, 304 s/s door and white control panel		Option			
Less Condensing Unit	Standard	304 s/s		Option			
Specification							
Blast Chiller	Standard						
Width	1550						
Depth	2330						
Height	2350						
Weight (Unpacked, kg)	790						
Weight (Packed, kg)	790						
Chilling Capacity (Kgs)	250						
Gross Volume (Ltr)	250						
RS485 connection for HACCP data logging	Option						

Footnotes

- MBC models are supplied floorless for blast chilling application only.
- Control panel sprayed white
- Anti Condensation heater to control panel recommended where products are installed in an ambient below 15oC e.g. Prep rooms
- Condensing Unit: All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase + neutral).



Energy



Quality



Value



Design



Hygiene



After Care