



Catalogue :

OTHER REFRIGERATION

Chapter :

REFRIGERATED DISPLAYS

Article :

ERM-250 NL BOTTLE COOLER 230V 50/60Hz 1N

Code:

19020854

<u>DIMENSIONS AND WEIGHTS</u>		<u>Net dimensions</u>	<u>Packed</u>
Length	mm	925,00	575,00
Depth	mm	520,00	970,00
Height	mm	900,00	1.025,00
Weight	kg	80,00	83,00
Volume	m3	0,43	0,57
<u>ELECTRICITY</u>		50/60Hz	
	Power		0,34 kW
Connections	230 V. 1+N+T	2X1,5+T - 4 A	
	230 V. III+T	3X10+T - 63 A	
	400 V. III+N+T	4X2,5MM2+T	
<u>GAS</u>	Not necessary		
<u>WATER</u>	Not necessary		
<u>STEAM</u>	Not necessary		
<u>AIR</u>	Not necessary		
			R-134a
	Refrigeration power		0,345
	Climat class	4	
<u>SOUND LEVEL</u>			< 65,00 db
<u>CERTIFICATES</u>	SGS-2103-0906-1		
<u>INSTALLATION - CONNECTIONS</u>			Ø
	► ELECTRICITY	SI	

DESCRIPTION

REFRIGERATED WALL DISPLAYS, ERM-250

SPECIFICATIONS

Sanitary epoxy coated galvanized steel inside.
Two outside finish options: Either satin stainless steel (Inox version) or black plastic covered galvanized steel (black version).
40 kg/m3 injected polyurethane isolation.
Copper piping and aluminium flaps evaporator.
Hermetically sealed copper serpentine ventilated compressor.
Double glazed doors with anti-mist protection (low E) with inner air chamber and handle.
Fitted with a lock.
Digital display for electronic control of temperature.
ON/OFF power switch.
Top horizontal lightning.
Fitted with two plastic covered steel grid shelves.
Working temperature: +4 °C, +8 °C (Room temperature: 32 °C).

Doors: 2
Capacity: 214 L
Bottle capacity: 77
Electric power: 400 W
Coolant: R-134a
Dimensions: 925x520x900 mm





Catalogue :
OTHER REFRIGERATION

Chapter :
REFRIGERATED DISPLAYS

Article :
ERM-250 NL BOTTLE COOLER 230V 50/60Hz 1N

Code :
19020854

SCHEMA - DIMENSIONS

